sammic

DYNAMIC PREPARATION

P/N 31143

VEGETABLE PREPARATION MACHINES & COMBI MODELS

Combi CK-401

2 IN 1: VEGETABLE PREPARATION MACHINE AND CUTTER

It consists of a variable speed motor block with a large capacity hopper and a 5 qt. food processor bowl complete with a hub with serrated blades.

· User-friendly, waterproof led-lit control panel.
· Hopper, lid and bowl easily detachable for interchanging or cleaning.
· Automatic hopper detection.

As vegetable preparation machine:
· Machine and discs specially designed to obtain the perfect cut.
· Adjustable speed (5 positions).
· Ergonomic design.
· Central blade to slice open larger food products: maximum efficiency.
· Lateral shootout: needs less counter space and allows a more natural workflow (left to right).
· High profile ejection disc for larger outuput.

As food processor:
· Adjustable speed (10 positions), programmable by time and pulse switch.
· 5 qt. stainless steel food processor bowl.
· Polycarbonate lid complete with scraper that allows consistent and homogeneous mixing and avoids product overheating.
· Optional flat blade set for raw meat and fibrous products.

DEFAULT EQUIPMENT
· Variable speed motor block.
· Large capacity hopper.
· Food processor bowl complete with hub with serrated blades.

OPTIONAL EQUIPMENT
· Long vegetable attachment.
· Automatic hopper.
· Discs, grids, disc holder device.
· Stand-trolley.
· Hub with flat blades.
· Hub with perforated blades.

TECHNICAL SPECIFICATIONS

Loading: 1500 W

As vegetable preparation machine
Hourly production: 200 Kg - 650 Kg
Inlet opening dimensions: 286 cm2
Disc diameter: 205 mm
Speeds as veg. slicer (positions): 5 (365 rpm - 1000 rpm)
External dimensions: 389 mm x 400 mm x 767 mm
Net weight: 30 Kg

As cutter
Boiler capacity: 5 l
Speeds as cutter (positions): 10 (365 rpm - 3000 rpm)
External dimensions:283 mm x 390 mm x 468 mm
Net weight: 23 Kg.

AENOR Empresa Registrada ER-0437/1/96 · IQNet · UNE-EN ISO 9001

SAMMIC, S.L. (Sociedad Unipersonal)
Basarte, 1 - 20720 AZKOITIA - www.sammic.com

European Directives:
2006/42/CE, 2006/95/CE, 2004/108/CE

Norms:
EN 60 335-1, CEI 335-2-64, UNE-EN 55014-1, UNE-EN 55014-2, UNE-EN 61000-3-2, UNE-EN 61000-3-3, NSF/ANSI Standard 8.