DYNAMIC PREPARATION

PORTABLE LIQUIDISERS & BEATERS

Motor unit TR/BM-250

COMPACT MODEL FOR DISCONTINUOUS USE. SUITABLE BOTH FOR MIXING AND LIQUIDIZING PRODUCTS

Variable speed motor unit. Shafts in option.

· Suitable for food-processing in containers of up to 15-litre / 16-qt. capacity.
· Variable speed.
· Ergonomic design.
· Easy to use and clean.
· NSF-International certified appliance (complying with Hygiene, Cleaning and Food Material regulations).
· Manufactured from durable top quality materials.

· Available shafts:

· Liquidiser arm: suitable for pureeing (vegetables, potatoes, soups, etc.) or preparing creams (onion, pepper, tomato, confectioner´s, etc.) and all sorts of sauces.
· Beater arm for whipping cream or preparing meringue, chantilly, mayonnaise and Genoese sauce, omelettes, pancake batter, soufflés, etc.

· Easily detachable shafts with no need of tools.
· Wholly stainless arms.

DEFAULT EQUIPMENT
· Adjustable speed motor unit.

OPTIONAL EQUIPMENT
· Beater arm BB-250.
· Liquidiser arm BS.

TECHNICAL SPECIFICATIONS

Loading: 250 W
Maximum recipient capacity: 15 lCompatible liquidising arm: BS

Revolving arm: BB-250
Fixed arm: n

Speed (in liquid) : 1500 rpm - 9000 rpm

Length

·Liquidising arm length: 290 mm
·Revolving arm length: 300 mm
·Total length: 550 mm
·Total length (with revolving arm): 560 mm

Net weight: 1,9 Kg - 2,3 Kg

AENOR ER Empresa Registrada ER-0437/1/96 · IQNet · UNE-EN ISO 9001

SAMMIC, S.L. (Sociedad Unipersonal)
Basarte, 1 - 20720 AZKOITIA - www.sammic.com

CEI 60335-2-64:02+EN 60335-2-64:2000, UNE-EN 60335-1:97; UNE-EN 55014-1:2002+A1:02, UNE-EN 61000-3-2:01; UNE-EN 61000-3-3:97+A1.02+C:99, UNE-

2006/95/EC, 2004/108/EC, NSF/ANSI Standard 8.