

```

#
# /etc/pam.d/common-auth - authentication settings common to all services
#
# This file is included from other service-specific PAM config files,
# and should contain a list of the authentication modules that define
# the central authentication scheme for use on the system
# (e.g., /etc/shadow, LDAP, Kerberos, etc.). The default is to use the
# traditional Unix authentication mechanisms.
#
# As of pam 1.0.1-6, this file is managed by pam-auth-update by default.
# To take advantage of this, it is recommended that you configure any
# local modules either before or after the default block, and use
# pam-auth-update to manage selection of other modules. See
# pam-auth-update(8) for details.

# here are the per-package modules (the "Primary" block)
auth      [success=1 default=ignore]      pam_unix.so nullok
# here's the fallback if no module succeeds
auth      requisite                       pam_deny.so
# prime the stack with a positive return value if there isn't one already;
# this avoids us returning an error just because nothing sets a success code
# since the modules above will each just jump around
auth      required                       pam_permit.so
# and here are more per-package modules (the "Additional" block)
# end of pam-auth-update config

```

```

GNU nano 8.4                               /etc/security/faillock.conf *
no_log_info
#
# Only track failed user authentication attempts for local users
# in /etc/passwd and ignore centralized (AD, IdM, LDAP, etc.) users.
# The `faillock` command will also no longer track user failed
# authentication attempts. Enabling this option will prevent a
# double-lockout scenario where a user is locked out locally and
# in the centralized mechanism.
# Enabled if option is present.
local_users_only
#
# Deny access if the number of consecutive authentication failures
# for this user during the recent interval exceeds n tries.
# The default is 3.
deny = 3
#
# The length of the interval during which the consecutive
# authentication failures must happen for the user account
# lock out is <replaceable>n</replaceable> seconds.
# The default is 900 (15 minutes).
fail_interval = 180
#
# The access will be re-enabled after n seconds after the lock out.
# The value 0 has the same meaning as value `never` - the access
# will not be re-enabled without resetting the faillock
# entries by the `faillock` command.
# The default is 600 (10 minutes).
unlock_time = 180
#
# Root account can become locked as well as regular accounts.
# Enabled if option is present.
even_deny_root
#
# This option implies the `even_deny_root` option.
# Allow access after n seconds to root account after the
# account is locked. In case the option is not specified
# the value is the same as of the `unlock_time` option.
root_unlock_time = 900
#
# If a group name is specified with this option, members
# of the group will be handled by this module the same as
# the root account (the options `even_deny_root` and
# `root_unlock_time` will apply to them.
# By default, the option is not set.
_admin_group = <admin_group_name>

```

```
GNU nano 8.4 /etc/pam.d/common-auth
```

```
#
auth required pam_faillock.so preauth
# /etc/pam.d/common-auth - authentication settings common to all services
#
# This file is included from other service-specific PAM config files,
# and should contain a list of the authentication modules that define
# the central authentication scheme for use on the system
# (e.g., /etc/shadow, LDAP, Kerberos, etc.). The default is to use the
# traditional Unix authentication mechanisms.
#
# As of pam 1.0.1-6, this file is managed by pam-auth-update by default.
# To take advantage of this, it is recommended that you configure any
# local modules either before or after the default block, and use
# pam-auth-update to manage selection of other modules. See
# pam-auth-update(8) for details.

# here are the per-package modules (the "Primary" block)
auth [success=1 default=ignore] pam_unix.so nullok
auth [default=die] pam_faillock.so authfail
auth sufficient pam_faillock.so authsucc
# here's the fallback if no module succeeds
auth requisite pam_deny.so
# prime the stack with a positive return value if there isn't one already;
# this avoids us returning an error just because nothing sets a success code
# since the modules above will each just jump around
auth required pam_permit.so
# and here are more per-package modules (the "Additional" block)
# end of pam-auth-update config
```

```
GNU nano 8.4 /etc/pam.d/common-account
```

```
#
account required pam_faillock.so
# /etc/pam.d/common-account - authorization settings common to all services
#
# This file is included from other service-specific PAM config files,
# and should contain a list of the authorization modules that define
# the central access policy for use on the system. The default is to
# only deny service to users whose accounts are expired in /etc/shadow.
#
# As of pam 1.0.1-6, this file is managed by pam-auth-update by default.
# To take advantage of this, it is recommended that you configure any
# local modules either before or after the default block, and use
# pam-auth-update to manage selection of other modules. See
# pam-auth-update(8) for details.
#

# here are the per-package modules (the "Primary" block)
account [success=1 new_authtok_reqd=done default=ignore] pam_unix.so
# here's the fallback if no module succeeds
account requisite pam_deny.so
# prime the stack with a positive return value if there isn't one already;
# this avoids us returning an error just because nothing sets a success code
# since the modules above will each just jump around
account required pam_permit.so
# and here are more per-package modules (the "Additional" block)
# end of pam-auth-update config
```

```
root@lew-mdudchenko:~# faillock --user student1
```

```
student1:
```

When	Type	Source	Valid
2026-04-28 18:16:43	TTY	/dev/tty1	V
2026-04-28 18:16:55	TTY	/dev/tty1	V
2026-04-28 18:17:10	TTY	/dev/tty1	V

```
root@lew-mdudchenko:~# _
```

```

root@lew-mdudchenko:~# faillock --user student1
student1:
When                Type  Source                                Valid
2026-04-28 18:16:43 TTY    /dev/tty1                            V
2026-04-28 18:16:55 TTY    /dev/tty1                            V
2026-04-28 18:17:10 TTY    /dev/tty1                            V
root@lew-mdudchenko:~# faillock --user student1 --reset
root@lew-mdudchenko:~# faillock --user student1
student1:
When                Type  Source                                Valid
root@lew-mdudchenko:~#

```

```

root@lew-mdudchenko:/home/mark_markk# ls -l /etc/pam.d/
razem 76
-rw-r--r-- 1 root root 384 2025-04-19 chfn
-rw-r--r-- 1 root root 92 2025-04-19 chpasswd
-rw-r--r-- 1 root root 581 2025-04-19 chsh
-rw-r--r-- 1 root root 1208 04-14 16:05 common-account
-rw-r--r-- 1 root root 1214 04-14 16:05 common-auth
-rw-r--r-- 1 root root 1633 04-28 15:58 common-password
-rw-r--r-- 1 root root 1620 04-28 15:40 common-password.bak
-rw-r--r-- 1 root root 1259 04-14 16:05 common-session
-rw-r--r-- 1 root root 1221 04-14 16:05 common-session-noninteractive
-rw-r--r-- 1 root root 606 2025-04-03 cron
-rw-r--r-- 1 root root 3974 2025-05-10 login
-rw-r--r-- 1 root root 92 2025-04-19 newusers
-rw-r--r-- 1 root root 520 2025-06-29 other
-rw-r--r-- 1 root root 92 2025-04-19 passwd
-rw-r--r-- 1 root root 143 2025-05-10 runuser
-rw-r--r-- 1 root root 138 2025-05-10 runuser-l
-rw-r--r-- 1 root root 2118 04-05 01:29 sshd
-rw-r--r-- 1 root root 2259 2025-05-10 su
-rw-r--r-- 1 root root 137 2025-05-10 su-l
root@lew-mdudchenko:/home/mark_markk#

```

```

# here are the per-package modules (the "Primary" block)
password [success=1 default=ignore] pam_unix.so obscure yescrypt \ remember=5
# here's the fallback if no module succeeds
password requisite pam_deny.so
# prime the stack with a positive return value if there isn't one already;
# this avoids us returning an error just because nothing sets a success code
# since the modules above will each just jump around
password required pam_permit.so
# and here are more per-package modules (the "Additional" block)
# end of pam-auth-update config

```

```

# here are the per-package modules (the "Primary" block)
password [success=1 default=ignore] pam_unix.so obscure des \ remember=5
# here's the fallback if no module succeeds
password requisite pam_deny.so
# prime the stack with a positive return value if there isn't one already;
# this avoids us returning an error just because nothing sets a success code
# since the modules above will each just jump around
password required pam_permit.so
# and here are more per-package modules (the "Additional" block)
# end of pam-auth-update config

```

```
# here are the per-package modules (the "Primary" block)
password [success=1 default=ignore] pam_unix.so obscure des
# here's the fallback if no module succeeds
password requisite pam_deny.so
# prime the stack with a positive return value if there isn't one already;
# this avoids us returning an error just because nothing sets a success code
# since the modules above will each just jump around
password required pam_permit.so
# and here are more per-package modules (the "Additional" block)
# end of pam-auth-update config

root@lew-mdudchenko:/home/mark_markk# passwd mark_m
Nowe hasło:
Proszę ponownie wpisać nowe hasło:
passwd: hasło zostało zmienione
root@lew-mdudchenko:/home/mark_markk# grep "mark_m" /etc/shadow | cut -d: -f2 >> /home/mark_markk/hasla.txt
root@lew-mdudchenko:/home/mark_markk# cat hasla.txt
$y$j9T$i5bA4wHp0I9jBKnfHH1s1$oDVkF.eaWi71GVWjgX3obo0y5V8SSWund3FbyI0h7k6 YESCRYPT
$y$j9T$i5bA4wHp0I9jBKnfHH1s1$oDVkF.eaWi71GVWjgX3obo0y5V8SSWund3FbyI0h7k6
xmdx017nsFPBI
root@lew-mdudchenko:/home/mark_markk#
```

```
# here are the per-package modules (the "Primary" block)
password [success=1 default=ignore] pam_unix.so obscure md5
# here's the fallback if no module succeeds
password requisite pam_deny.so
# prime the stack with a positive return value if there isn't one already;
# this avoids us returning an error just because nothing sets a success code
# since the modules above will each just jump around
password required pam_permit.so
# and here are more per-package modules (the "Additional" block)
# end of pam-auth-update config

root@lew-mdudchenko:/home/mark_markk# passwd mark_m
Nowe hasło:
Proszę ponownie wpisać nowe hasło:
passwd: hasło zostało zmienione
root@lew-mdudchenko:/home/mark_markk# grep "mark_m" /etc/shadow | cut -d: -f2 >> /home/mark_markk/hasla.txt
root@lew-mdudchenko:/home/mark_markk# cat hasla.txt
$y$j9T$i5bA4wHp0I9jBKnfHH1s1$oDVkF.eaWi71GVWjgX3obo0y5V8SSWund3FbyI0h7k6 YESCRYPT
$y$j9T$i5bA4wHp0I9jBKnfHH1s1$oDVkF.eaWi71GVWjgX3obo0y5V8SSWund3FbyI0h7k6
xmdx017nsFPBI
$1$gzC0oJpo$90FFUtHGLKBSqyR2WLiCD/
root@lew-mdudchenko:/home/mark_markk#
```

```
# here are the per-package modules (the "Primary" block)
password [success=1 default=ignore] pam_unix.so obscure sha256
# here's the fallback if no module succeeds
password requisite pam_deny.so
# prime the stack with a positive return value if there isn't one already;
# this avoids us returning an error just because nothing sets a success code
# since the modules above will each just jump around
password required pam_permit.so
# and here are more per-package modules (the "Additional" block)
# end of pam-auth-update config
```

```
root@lew-mdudchenko:/home/mark_markk# passwd mark_m
Nowe hasło:
Proszę ponownie wpisać nowe hasło:
passwd: hasło zostało zmienione
root@lew-mdudchenko:/home/mark_markk# cat hasla.txt
$y$j9T$i5bA4wHp0I9jBKnfHH1s1$oDVkF.eaWi71GvWjgX3obo0y5V8SSWund3FbyI0h7k6 YESCRYPT
$y$j9T$i5bA4wHp0I9jBKnfHH1s1$oDVkF.eaWi71GvWjgX3obo0y5V8SSWund3FbyI0h7k6
xmdx017nsFPBI
$1$gz00jpo$90FFUtHGLKBSqyR2WLiCD/
root@lew-mdudchenko:/home/mark_markk# grep "mark_m" /etc/shadow | cut -d: -f2 >> /home/mark_markk/hasla.txt
root@lew-mdudchenko:/home/mark_markk# cat hasla.txt
$y$j9T$i5bA4wHp0I9jBKnfHH1s1$oDVkF.eaWi71GvWjgX3obo0y5V8SSWund3FbyI0h7k6 YESCRYPT
$y$j9T$i5bA4wHp0I9jBKnfHH1s1$oDVkF.eaWi71GvWjgX3obo0y5V8SSWund3FbyI0h7k6
xmdx017nsFPBI
$1$gz00jpo$90FFUtHGLKBSqyR2WLiCD/
$5$PbNxJ/00bPGst.At$Nui4zyBVSEecidVHG7ASjMLRd90ZsWAX2A9S0j18UY0
root@lew-mdudchenko:/home/mark_markk#
```

```
# here are the per-package modules (the "Primary" block)
password [success=1 default=ignore] pam_unix.so obscure sha512
# here's the fallback if no module succeeds
password requisite pam_deny.so
# prime the stack with a positive return value if there isn't one already;
# this avoids us returning an error just because nothing sets a success code
# since the modules above will each just jump around
password required pam_permit.so
# and here are more per-package modules (the "Additional" block)
# end of pam-auth-update config
```

```
root@lew-mdudchenko:/home/mark_markk# passwd mark_m
Nowe hasło:
Proszę ponownie wpisać nowe hasło:
passwd: hasło zostało zmienione
root@lew-mdudchenko:/home/mark_markk# grep "mark_m" /etc/shadow | cut -d: -f2 >> /home/mark_markk/hasla.txt
root@lew-mdudchenko:/home/mark_markk# cat hasla.txt
$y$j9T$i5bA4wHp0I9jBKnfHH1s1$oDVkF.eaWi71GvWjgX3obo0y5V8SSWund3FbyI0h7k6 YESCRYPT
$y$j9T$i5bA4wHp0I9jBKnfHH1s1$oDVkF.eaWi71GvWjgX3obo0y5V8SSWund3FbyI0h7k6
xmdx017nsFPBI
$1$gz00jpo$90FFUtHGLKBSqyR2WLiCD/
$5$PbNxJ/00bPGst.At$Nui4zyBVSEecidVHG7ASjMLRd90ZsWAX2A9S0j18UY0
$6$uu.hxA.keszJtiIm$XT0GoQcJH/I28BT3m27HReIej1FUKPuMt/NZ0fB9skpqfiwqHjiyFDKuxyL06DA3gWI/Q/bqwXKF5hDsSQtG60
root@lew-mdudchenko:/home/mark_markk#
```

```

#
# Password aging controls:
#
# PASS_MAX_DAYS    Maximum number of days a password may be used.
# PASS_MIN_DAYS    Minimum number of days allowed between password changes.
# PASS_WARN_AGE    Number of days warning given before a password expires.
#
PASS_MAX_DAYS    15
PASS_MIN_DAYS     2
PASS_WARN_AGE     5_

```

```

student:$y$9T$0JJIUf29k/2Q4n9TXyKWB.$gmQV2mhwA0CkgM.tKTP.8ewBt2MCn5B9Sa1yDug6y1/:20557:0:99999:7:::
mark_m:$6$uu.hxA.keszJtiIm$XT0GoQcJH/I28BT3m27HRelej1FUKPuMT/N20fB9skpqfiwqHjiyFDKuxyL06DA3gWI/Q/bqwXKF5hDsSQtG60:20571:0:99999:7:::
student1:$y$9T$GsoaHQgAVHTgXVh2tu/k.0$Q6ufSt/CDVjJs.E0hG88G1j0lIRhsCBDjQYsMmoIit8:20571:2:15:5:::

```

```

root@lew-mdudchenko:~# apt install libpam-pwquality
Instalowane:
  libpam-pwquality

Instalowane zależności:
  cracklib-runtime libcrack2 libpwquality-common libpwquality1

Podsumowanie:
 Aktualizowanych: 0, Instalowanych: 5, Usuowanych: 0, Nieaktualizowanych: 0
 Do pobrania: 266 kB
 Wymagane miejsce: 1 402 kB / 7 447 MB dostępnych

Kontynuować? [T/n] y
Pobr:1 http://ftp.pl.debian.org/debian trixie/main amd64 libcrack2 amd64 2.9.6-5.2+b1 [44,4 kB]
Pobr:2 http://ftp.pl.debian.org/debian trixie/main amd64 cracklib-runtime amd64 2.9.6-5.2+b1 [143 kB]
Pobr:3 http://ftp.pl.debian.org/debian trixie/main amd64 libpwquality-common all 1.4.5-5 [51,9 kB]
Pobr:4 http://ftp.pl.debian.org/debian trixie/main amd64 libpwquality1 amd64 1.4.5-5 [13,2 kB]
Pobr:5 http://ftp.pl.debian.org/debian trixie/main amd64 libpam-pwquality amd64 1.4.5-5 [13,1 kB]
Pobrano 266 kB w 10s (27,2 kB/s)
Wybieranie wcześniej niewybranego pakietu libcrack2:amd64.
(Odczytywanie bazy danych ... 37118 plików i katalogów obecnie zainstalowanych.)
Przygotowywanie do rozpakowania pakietu .../libcrack2_2.9.6-5.2+b1_amd64.deb ...
Rozpakowywanie pakietu libcrack2:amd64 (2.9.6-5.2+b1) ...
Wybieranie wcześniej niewybranego pakietu cracklib-runtime.
Przygotowywanie do rozpakowania pakietu .../cracklib-runtime_2.9.6-5.2+b1_amd64.deb ...
Rozpakowywanie pakietu cracklib-runtime (2.9.6-5.2+b1) ...
Wybieranie wcześniej niewybranego pakietu libpwquality-common.
Przygotowywanie do rozpakowania pakietu .../libpwquality-common_1.4.5-5_all.deb ...
Rozpakowywanie pakietu libpwquality-common (1.4.5-5) ...
Wybieranie wcześniej niewybranego pakietu libpwquality1:amd64.
Przygotowywanie do rozpakowania pakietu .../libpwquality1_1.4.5-5_amd64.deb ...
Rozpakowywanie pakietu libpwquality1:amd64 (1.4.5-5) ...
Wybieranie wcześniej niewybranego pakietu libpam-pwquality:amd64.
Przygotowywanie do rozpakowania pakietu .../libpam-pwquality_1.4.5-5_amd64.deb ...
Rozpakowywanie pakietu libpam-pwquality:amd64 (1.4.5-5) ...
Konfigurowanie pakietu libpwquality-common (1.4.5-5) ...
Konfigurowanie pakietu libcrack2:amd64 (2.9.6-5.2+b1) ...
Konfigurowanie pakietu cracklib-runtime (2.9.6-5.2+b1) ...
skipping line: 1
Konfigurowanie pakietu libpwquality1:amd64 (1.4.5-5) ...
Konfigurowanie pakietu libpam-pwquality:amd64 (1.4.5-5) ...
Przetwarzanie wyzwalaczy pakietu libc-bin (2.41-12+deb13u2)...
Przetwarzanie wyzwalaczy pakietu man-db (2.13.1-1)...
root@lew-mdudchenko:~#

```

```

# here are the per-package modules (the "Primary" block)
password    requisite                                pam_pwquality.so retry=3
password    [success=1 default=ignore]              pam_unix.so obscure use_authtok try_first_pass yescrypt remember=3
# here's the fallback if no module succeeds
password    requisite                                pam_deny.so
# prime the stack with a positive return value if there isn't one already;
# this avoids us returning an error just because nothing sets a success code
# since the modules above will each just jump around
password    required                                  pam_permit.so
# and here are more per-package modules (the "Additional" block)
# end of pam-auth-update config

```

```
student1@lew-mdudchenko:~$ passwd student1
Zmianianie hasła dla student1.
Obecne hasło:
Należy poczekać dłużej na zmianę hasła.
passwd: Błąd podczas modyfikowania tokenu uwierzytelniania
passwd: password unchanged
student1@lew-mdudchenko:~$ _
```

```
lew-mdudchenko login: student1
Password:
Linux lew-mdudchenko 6.12.74+deb13+1-amd64 #1 SMP PREEMPT_DYNAMIC Debian 6.12.74-2 (2026-03-08) x86_64

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
student1@lew-mdudchenko:~$ passwd student1
Zmianianie hasła dla student1.
Obecne hasło:
Nowe hasło:
BŁĘDNE HASŁO: Hasło jest takie same jak poprzednie
Nowe hasło: _
```

```
# here are the per-package modules (the "Primary" block)
password      requisite                                pam_pwquality.so retry=2 difok=4 minlen=10 ucredit=-1 lcredit=-2 orncredit=-1
password      [success=1 default=ignore]                    pam_unix.so obscure use_authok try_first_pass yescrypt remember=3
# here's the fallback if no module succeeds
```

```
lew-mdudchenko login: student1
Password:
Linux lew-mdudchenko 6.12.74+deb13+1-amd64 #1 SMP PREEMPT_DYNAMIC Debian 6.12.74-2 (2026-03-08) x86_64

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
student1@lew-mdudchenko:~$ passwd student1
Zmianianie hasła dla student1.
Obecne hasło:
Nowe hasło:
BŁĘDNE HASŁO: Hasło jest krótsze niż 10 znaków
Nowe hasło:
```

```
Nowe hasło:
BŁĘDNE HASŁO: Hasło jest krótsze niż 10 znaków
Nowe hasło:
BŁĘDNE HASŁO: Hasło zawiera mniej niż 1 wielkich liter
passwd: Wykorzystano maksymalną liczbę prób dla usługi
passwd: password unchanged
student1@lew-mdudchenko:~$
```