

Check sg in RDS:

The screenshot shows a SQL IDE interface. The top menu bar includes File, View, Data, SQL, Macros, Workspace, Tools, and Help. The top status bar displays 'User=admin, URL=jdbc:mysql://databases:3306'. The left sidebar shows a tree view of databases: mp, tabases, information_schema, mysql, and mysqldb. Under 'TABLE', the 'emp' table is selected. The main editor area shows a list of SQL statements, with 'Statement 1' and 'Statement 2' tabs. The statements are as follows:

```
24 INSERT INTO emp VALUES ('7566','JONES','MANAGER','7839','1981-04-02','2975.00',NULL,'20');
25 INSERT INTO emp VALUES ('7654','MARTIN','SALESMAN','7698','1981-09-28','1250.00','1400.00','30');
26 INSERT INTO emp VALUES ('7698','BLAKE','MANAGER','7839','1981-05-01','2850.00',NULL,'30');
27 INSERT INTO emp VALUES ('7782','CLARK','MANAGER','7839','1981-06-09','2450.00',NULL,'10');
28 INSERT INTO emp VALUES ('7788','SCOTT','ANALYST','7566','1982-12-09','3000.00',NULL,'20');
29 INSERT INTO emp VALUES ('7839','KING','PRESIDENT',NULL,'1981-11-17','5000.00',NULL,'10');
30 INSERT INTO emp VALUES ('7844','TURNER','SALESMAN','7698','1981-09-08','1500.00','0.00','30');
31 INSERT INTO emp VALUES ('7876','ADAMS','CLERK','7788','1983-01-12','1100.00',NULL,'20');
32 INSERT INTO emp VALUES ('7900','JAMES','CLERK','7698','1981-12-03','950.00',NULL,'30');
33 INSERT INTO emp VALUES ('7902','FORD','ANALYST','7566','1981-12-03','3000.00',NULL,'20');
34 INSERT INTO emp VALUES ('7934','MILLER','CLERK','7782','1982-01-23','1300.00',NULL,'10');
35
36 INSERT INTO dept VALUES ('10','ACCOUNTING','NEW YORK');
37 INSERT INTO dept VALUES ('20','RESEARCH','DALLAS');
38 INSERT INTO dept VALUES ('30','SALES','CHICAGO');
39 INSERT INTO dept VALUES ('40','OPERATIONS','BOSTON');
40
41
42
```

At the bottom, there is a 'Messages' tab.

Loop over tables using list comprehension python and print tables in mysql db using databricks

```
09:36 AM (4s) 3

#tabs=["emp","dept","orders"]
data="jdbc:mysql://database-1.c5i60sy0s0pm.us-east-1.rds.amazonaws.com:3306/mysqlpdb"
qry="(SELECT table_name FROM information_schema.tables WHERE table_schema = 'mysqlpdb') aaa"
all=spark.read.format("jdbc").option("url",data).option("user","admin").option("password","Mounis10909").option("dbtable",qry).load()
type(all)
print(all)
tabs = [t[0] for t in all.collect()]
print("t[0]---",t[0])
print("t---",t)

print("tabs---",tabs)
for t in tabs:
    print("table:--",t)
    data="jdbc:mysql://database-1.c5i60sy0s0pm.us-east-1.rds.amazonaws.com:3306/mysqlpdb"
    df=spark.read.format("jdbc").option("url",data).option("user","admin").option("password","Mounis10909").option("dbtable",t).load()
    df.show(4)
    #df.write.format("jdbc").option("url",mshost).option("user","myuser").option("password","Mypassword.1").option("dbtable",t+"_mysql123").save()

(4) Spark Jobs

all: pyspark.sql.dataframe.DataFrame = [TABLE_NAME: string]
df: pyspark.sql.dataframe.DataFrame = [empno: decimal(4,0), ename: string ... 7 more fields]

DataFrame [TABLE_NAME: string]
t[0]--- m
t--- myemp
tabs--- ['dept', 'emp', 'myemp']
table:-- dept
+-----+-----+-----+
|deptno|  dname|   loc|
+-----+-----+-----+
|    10|ACCOUNTING|NEW YORK|
|    20| RESEARCH| DALLAS|
```