

AWS:

RDS: create RDS db instance free tier.

Check sg in RDS:

Inbound rules (3)

Search

Manage tags Edit inbound rules

< 1 > ⚙

Group rule ID	IP version	Type	Protocol	Port range	Source
b9ac8ee6465	-	All traffic	All	All	59.122.122.122/32
176ef7de41f	IPv4	MySQL/Aurora	TCP	3306	0.0.0.0/0
411ea93b853	IPv4	Redshift	TCP	5439	0.0.0.0/0

```
View Data SQL Macros Workspace Tools Help
User=admin, URL=jdbc:mysql://databases-xxxxx.us-east-1.amazonaws.com:3306

Statement 1 Statement 2
24 INSERT INTO emp VALUES ('7566','JONES','MANAGER','7839','1981-04-02','2975.00',NULL,'20');
25 INSERT INTO emp VALUES ('7654','MARTIN','SALESMAN','7698','1981-09-28','1250.00','1400.00','30');
26 INSERT INTO emp VALUES ('7698','BLAKE','MANAGER','7839','1981-05-01','2850.00',NULL,'30');
27 INSERT INTO emp VALUES ('7782','CLARK','MANAGER','7839','1981-06-09','2450.00',NULL,'10');
28 INSERT INTO emp VALUES ('7788','SCOTT','ANALYST','7566','1982-12-09','3000.00',NULL,'20');
29 INSERT INTO emp VALUES ('7839','KING','PRESIDENT',NULL,'1981-11-17','5000.00',NULL,'10');
30 INSERT INTO emp VALUES ('7844','TURNER','SALESMAN','7698','1981-09-08','1500.00','0.00','30');
31 INSERT INTO emp VALUES ('7876','ADAMS','CLERK','7788','1983-01-12','1100.00',NULL,'20');
32 INSERT INTO emp VALUES ('7900','JAMES','CLERK','7698','1981-12-03','950.00',NULL,'30');
33 INSERT INTO emp VALUES ('7902','FORD','ANALYST','7566','1981-12-03','3000.00',NULL,'20');
34 INSERT INTO emp VALUES ('7934','MILLER','CLERK','7782','1982-01-23','1300.00',NULL,'10');
35
36 INSERT INTO dept VALUES ('10','ACCOUNTING','NEW YORK');
37 INSERT INTO dept VALUES ('20','RESEARCH','DALLAS');
38 INSERT INTO dept VALUES ('30','SALES','CHICAGO');
39 INSERT INTO dept VALUES ('40','OPERATIONS','BOSTON');
40
41
42
Messages
```

Loop over tables using list comprehension python and print tables in mysql db using databricks

```
#tabs=["emp", "dept", "orders"]
data="jdbc:mysql://database-1.c[REDACTED].us-east-1.rds.amazonaws.com:3306/mysqlpdb"
qry="(SELECT table_name FROM information_schema.tables WHERE table_schema = 'mysqlpdb') aaa"
all=spark.read.format("jdbc").option("url",data).option("user","admin").option("password","[REDACTED]909").option("dbtable",qry).load()
type(all)
print(all)
tabs = [t[0] for t in all.collect()]
print("t[0]---",t[0])
print("t---",t)

print("tabs---",tabs)
for t in tabs:
    print("table:--",t)
    data="jdbc:mysql://database-1.c[REDACTED].us-east-1.rds.amazonaws.com:3306/mysqlpdb"
    df=spark.read.format("jdbc").option("url",data).option("user","admin").option("password","Mou[REDACTED]909").option("dbtable",t).load()
    df.show(4)
    #df.write.format("jdbc").option("url",mshost).option("user","myuser").option("password","Mypassword.1").option("dbtable",t+"_mysql123").save()
```

▶ (4) Spark Jobs

▶ all: pyspark.sql.dataframe.DataFrame = [TABLE_NAME: string]

▶ df: pyspark.sql.dataframe.DataFrame = [empno: decimal(4,0), ename: string ... 7 more fields]

DataFrame[TABLE_NAME: string]

t[0]--- m

t--- myemp

tabs--- ['dept', 'emp', 'myemp']

table:-- dept

deptno	dname	loc
10	ACCOUNTING	NEW YORK
20	RESEARCH	DALLAS