

Results

Chart

	#	CUSTOMER_ID	A	CUSTOMER_NAME	A	EMAIL
1		1		John Doe		johndoe@gmail.com
2		2		Jane Smith		janesmith@yahoo.com

Query Details

Query duration

Rows

Query ID

Show more

CUSTOMER

Masking udf:

```
CREATE OR REPLACE function Mask_email(email String)
returns String
Language sql
as
$$
CASE WHEN POSITION('@' IN email) > 0 THEN
LEFT(EMAIL,3) || '*****' || SUBSTRING(email, POSITION('@' IN EMAIL), LENGTH(email))
ELSE email
END
$$;

select Mask_email(email) from Customers;
```

Same can be used in procedure to mask email

```
create or replace procedure mask_emails()  
returns string  
Language sql  
as  
$$  
Begin
```

```
Create or replace temporary table temp_customers as  
select customer_id,  
       Mask_email(email) as masked_email from Customers;
```

```
--update original table with masked emails
```

```
update customers  
set email=temp_customers.masked_email  
from temp_customers  
where customers.customer_id = temp_customers.customer_id;
```

```
RETURN 'Customer emails masked successfully.';
```

```
End;  
$$;
```

```
CALL mask_emails();
```

```
select * from customers
```

Results				Chart		Query Details	
#	CUSTOMER_ID	CUSTOMER_NAME	EMAIL			Query ID	01ba8717-030c-5cb2-0...
1	1	John Doe	joh*****@gmail.com			Query duration	122m
2	2	Jane Smith	jan*****@yahoo.com			Rows	
						End time	Feb 20, 5:15 PM
						Scan	1.5KB (100%)
						Role	ACCOUNTADMIN
						Warehouse	SAMPLE_WI