

cloning

- zero copy cloning helps in cloning data by using pointers , but it does not create physical data instead it use pointers
- changes to clone does not affect others

```
CREATE OR REPLACE TABLE sales (  
  sale_id INTEGER,  
  sale_date DATE,  
  amount DECIMAL(10, 2)  
);  
INSERT INTO sales (sale_id, sale_date, amount) VALUES  
(1, '2023-07-01', 100.00),  
(2, '2023-07-02', 200.00),  
(3, '2023-07-03', 300.00);
```

```
CREATE TABLE sales_clone CLONE sales;
```

```
select * from sales_clone;
```

```
INSERT INTO sales_clone (sale_id, sale_date, amount) VALUES  
(4, '2023-07-04', 400.00);
```

```
select * from sales;  
select * from sales_clone;
```

Creating clone:

<

Query - 01ba447c-030c-39d2-000b-6e670001f01a

SAMPLE_WH

SPP0878

Query Details

Query Profile

Query Telemetry

Details

Status

Success

Duration

984ms

Driver Status

Supported

Start Time

2/8/2025, 9:04:48 PM

Query ID

01ba447c-030c-39d2-000b-6e670001f01a

Client Driver

Go 1.1.5

End Time

2/8/2025, 9:04:49 PM

Query Tag

—

Session ID

3217613404635142

Warehouse Size

X-Small

Attributed Compute Credits

—

Parameterized query hash

f132cdc4dcb7eb86e3797d776891147

SQL Text

INSERT INTO sales (sale_id, sale_date, amount) VALUES

Clone:

```
select * from sales;
select * from sales_clone;

CREATE TABLE sales_clone_at_time CLONE sales AT
(statement => '01ba447c-030c-39d2-000b-6e670001f01a');
```

--2/8/2025, 9:04:48 PM

CREATE TABLE sales_clone_at_time12 CLONE sales AT
(TIMESTAMP => '2025-02-08 12:00:00');

Clone production db:

CREATE DATABASE dev_db CLONE production_db;

CREATE DATABASE backup_db CLONE production_db;

UPDATE production_db.sales SET amount = amount * 1.1;

DROP DATABASE production_db;

Recreate dropped database:

CREATE DATABASE production_db CLONE backup_db;