

Power BI Vibes

Client Guide - v0.1.1

Build useful Power BI tools with ChatGPT, GitHub, and privacy-safe development data.

You explain the job and the business meaning. ChatGPT handles most repository and Power BI implementation work. Local Power BI validation is reported separately so a committed file is never mistaken for a Desktop-tested result.

The core boundary

- Create and maintain the project in a private GitHub repository.
- Use approved real samples, scrubbed templates, schema-only reports, or deterministic synthetic data according to your sharing rules.
- Keep operational data, restricted screenshots, credentials, and unsafe logs out of shared repositories unless explicitly permitted.
- Treat structural validation, Power BI Desktop rendering, and production refresh as separate checks.

Bootstrap prompt

```
I want to build a Power BI tool.
```

```
Use this framework:
```

```
https://github.com/dudechilling/Power-Bi-Vibes
```

```
My private project repository is:
```

```
<PASTE YOUR PRIVATE GITHUB REPOSITORY URL>
```

```
Read BOOTSTRAP.md in Power-Bi-Vibes and follow it. Do not ask me to share operational data that I am not permitted to share.
```


5. Pull safely to your computer

Use a short local path to reduce Power BI path-length problems:

```
git clone <YOUR-PRIVATE-REPOSITORY-URL> C:\PBI\<PROJECT-NAME>
```

Before pulling newer changes into a copy that has been opened or saved in Power BI Desktop, inspect the working tree:

```
cd C:\PBI\<PROJECT-NAME>
git status --short --branch
```

If the working tree is clean, `git pull --ff-only` is appropriate. If files are modified, stop and give the status output to ChatGPT. Desktop saves can modify tracked PBIP/PBIR/TMDL source, so the framework preserves those edits in a rescue branch before resolving local/remote divergence.

6. Power BI Desktop prerequisites

PBIP/PBIR requirements can change by Desktop version. Before the first local open, ChatGPT should check current Microsoft guidance for the exact format it created and tell you whether a specific Desktop version or preview feature is required.

7. Production-data smoke test

After synthetic QA passes, switch the named source parameter/connection to the approved operational source locally. First refresh may require credentials or a data-source privacy choice. Test refresh, relationships, totals, interactions, and performance at real data volume. Keep synthetic and production paths separable rather than unnecessarily combining them in a Power Query chain.

