

# Automating Deployments Using Docker Stack

A docker-compose alternative for swarm cluster

## We'll cover the following



- Docker stack implementation
- Docker stack commands

In this lesson, we will automate all the steps we took to create and deploy our app using services.

Clone the project using `git clone https://github.com/venky8283/Docker.git`  
Type `git checkout fc0a9af7f7fb2c8d61e4777befdbf451568cf578` to get the exact code used in this lesson.

We did the same thing while working with docker-compose. In docker-compose, we created a docker-compose file and automated all the steps in it.

We will modify the same docker-compose file to run with docker-swarm because Compose and Docker stack are similar on some level.

Let's list all the steps we need to automate as follows:

- Pull the Flask\_app v3.0 image from Docker Hub
- Increase the number of replicas of the Flask app to three
- Create a database service
- Establish communication between services using the network
- Create a visualizer service to monitor the swarm

## Docker stack implementation #

Docker stack is a bundle of services. When you want to deploy a set of services to a

machine, instead of creating each service separately, Docker stack allows users to deploy the full-stack of the services at once.

Let's see changes in our docker-compose file below.

```
version: '3.8'
services:
  web:
    # Path to dockerfile.
    # '.' represents the current directory in which
    # docker-compose.yml is present.
    image: venky8283/flask_app:3.0

    # Mapping of container port to host

    ports:
      - "5000:5000"
    # Mount volume
    volumes:
      - "./:/code"

    networks:
      - app

    deploy:
      replicas: 3

  database:

    # image to fetch from docker hub
    image: mysql/mysql-server:5.7

    # Environment variables for startup script
    # container will use these variables
    # to start the container with these defined variables.
    env_file:
      - ./env

    # Mount init.sql file to automatically run
    # and create tables for us.
    # everything in docker-entrypoint-initdb.d folder
    # is executed as soon as container is up and running.
    volumes:
      - "./db/init.sql:/docker-entrypoint-initdb.d/init.sql"

    deploy:
      replicas: 2

    networks:
      - app

  viz:

    # Visualizer image for swarm cluster.

    image: dockersamples/visualizer

    # Mapping container ports to host port

    ports:
```

```

- "8080:8080"

# Mounting docker socket to container.

volumes:

- "/var/run/docker.sock:/var/run/docker.sock"

networks:
- app

networks:
  app:

```

- **Line 1:** It is good practice to lock the exact version of Compose we are using.
- **Line 7:** We removed the build keyword and added an image location for the app. 'Build' is not supported in the swarm.
- **Line 17-21:** We added a deploy keyword to inform Docker swarm to maintain three instances of our app service. Also, we mentioned in which network our service will be located in.
- **Line 41-45:** We defined the deployment of database containers along with the network information.
- **Line 47-65:** We Defined the visualizer service. We have defined the image to be pulled from Docker Hub, ports mapping, mounted a Docker socket to sync events and the network to be used by the service.
- **Line 71-73:** We told the Docker swarm to create a network named app so that it can be used by the services.

Docker service also provides in-depth configuration for deployment at CPU level, but we will not make our docker-compose file more complex.

Since our docker-compose file is ready, let's deploy the services on the swarm manager node below.

Type `docker stack deploy <stack name> --compose-file=<location of docker-compose.yml file> .`

```
$ docker stack deploy login_app --compose-file=docker-compose.yml
```

```
$ docker stack deploy login_app --compose-file=docker-compose.yml
Creating network login_app_app
Creating service login_app_web
Creating service login_app_database
Creating service login_app_viz
```

This will deploy a stack of all services on swarm manager with just one command.

Now, verify the services using `docker service ls`.

```
$ docker service ls
```

ID	NAME	MODE	REPLICAS
	IMAGE	PORTS	
iv1nkq62i6fx	login_app_database	replicated	2/2
	mysql/mysql-server:5.7		
yo7o89dr5s9b	login_app_viz	replicated	1/1
	dockersamples/visualizer:latest	*:8080->8080/tcp	
rpuagx2yj9zg	login_app_web	replicated	3/3
	venky8283/flask_app:3.0	*:5000->5000/tcp	

## Docker stack commands #

Docker stack has few commands to manage stack on the swarm node. Type `docker stack --help` to list them.

```
$ docker stack --help
```

Usage: docker stack [OPTIONS] COMMAND

Manage Docker stacks

Options:

- orchestrator string Orchestrator to use (swarm|kubernetes|all)

Commands:

- deploy Deploy a new stack or update an existing stack
- ls List stacks
- ps List the tasks in the stack
- rm Remove one or more stacks
- services List the services in the stack

Run 'docker stack COMMAND --help' for more information on a command.

- `deploy`: We used this one to deploy our stack. We can update the docker-compose file and redeploy stack

- **ls**: This provides a short overview of stack

```
docker stack ls
```

NAME	SERVICES	ORCHESTRATOR
login_app	3	Swarm

- **ps**: Lists down all the containers created by the stack

```
$ docker stack ps login_app
```

ID	NAME	IMAGE	N
ODE	DESIRED STATE	CURRENT STATE	ERROR
PORTS			
zn1c6ro9f1ld	login_app_viz.1	dockersamples/visualizer:latest	d
ocker-desktop	Running	Running 9 minutes ago	
sjh64hceb9jh	login_app_database.1	mysql/mysql-server:5.7	d
ocker-desktop	Running	Running 9 minutes ago	
ew7zdtczb2su	login_app_web.1	venky8283/flask_app:3.0	d
ocker-desktop	Running	Running 10 minutes ago	
luo5j6vj1jhv	login_app_database.2	mysql/mysql-server:5.7	d
ocker-desktop	Running	Running 9 minutes ago	
ug3v9p7fy7a9	login_app_web.2	venky8283/flask_app:3.0	d
ocker-desktop	Running	Running 10 minutes ago	
9v3q0hfmirxc	login_app_web.3	venky8283/flask_app:3.0	d
ocker-desktop	Running	Running 10 minutes ago	

- **services**: Lists all the services in the stack

```
$ docker stack services login_app
```

ID	NAME	MODE	REPLICAS
IMAGE	PORTS		
iv1nkq62i6fx	login_app_database	replicated	2/2
	mysql/mysql-server:5.7		
rpuagx2yj9zg	login_app_web	replicated	3/3
	venky8283/flask_app:3.0		*:5000->5000/tcp
yo7o89dr5s9b	login_app_viz	replicated	1/1
	dockersamples/visualizer:latest		*:8080->8080/tcp

- **rm**: Removes stack from the swarm nodes, including network

```
$ docker stack rm login_app
```

Removing service login\_app\_database

Removing service login\_app\_viz

Removing service login\_app\_web

Removing network login\_app\_app

---

I guess that's enough to get started with stack. You can always explore more as long as you understand the fundamentals.

In the next lesson, we will review all the commands we have used in this section and look at a cheat sheet with us in case we forget some of them.