


Relational Learning between Multiple Pulmonary Nodules via Deep Set Attention Transformers

Jiancheng Yang, Haoran Deng,
Xiaoyang Huang, Bingbing Ni, Yi Xu

April 2020

Causes of Multiple Lung Nodules



verywell

Illustration by Jessica Olah, Verywell

<https://www.verywellhealth.com/multiple-lung-nodules-causes-and-diagnosis-2249390>

Challenges:

1/ Diagnosis of multiple pulmonary nodules is **complex**

2/ Previous methods use **solitary**-nodule approaches for **multiple** pulmonary nodules, *i.e.*, ignore the relations


Solutions:

Relational learning between multiple nodules via **Set Attention Transformers**



We propose **Set Attention Transformers (SATs)**, inspired from our previous study, **Point Attention Transformers** for point clouds:


- **Permutation-equivariant** for sets
- **Relational learning** between set elements
- **Parameter-efficient**
- **Group Shuffle Attention**




Check our CVPR'19 study on point clouds

Modeling Point Clouds with Self-Attention and Gumbel Subset Sampling.

Jiancheng Yang, Qiang Zhang, Bingbing Ni, Linguo Li, Jinxian Liu, Mengdie Zhou, Qi Tian



We use a parameter-efficient 3D DenseNet for representation backbone, adapted from our previous study:




Check our Cancer Research study on tumor invasiveness

3D Deep Learning from CT Scans Predicts Tumor Invasiveness
of Subcentimeter Pulmonary Adenocarcinomas.

Wei Zhao*, Jiancheng Yang*, Yingli Sun, *et al.* (*equal contribution).

Combining 3D DenseNet backbone with the proposed **Set Attention Transformers (SATs)**, we proposed end-to-end **NoduleSATs**:







Experiments: Lung Nodule Detection

Dataset	Method	Average FROC (CPM)
LUNA16 [10]	2D-CNN [11]	0.790
	3D-CNN [12]	0.908 ²
	3D DenseNet	0.884
	NoduleSAT	0.916
Tianchi VAL	3D DenseNet	0.677
	NoduleSAT	0.716


1/ LUNA16 False Positive Reduction: 888 subjects with 1186 nodules, totally 754,975 candidates, 10-fold cross validation.

2/ Tianchi Lung Nodule Detection: 800 subjects with 1,224 nodules, 5,531 candidates on the training set, 1,515 candidates on the validation set.





(a) Nodule Count Distribution



(b) Model Performance

LIDC-IDRI: one of the largest public available lung cancer screening databases

Patients in LIDC-IDRI dataset have 1 - 23 nodules

527 malignant + 656 benign + 992 undefined-label



- We propose a **Set Attention Transformer (SAT)**, to explicitly learn relational information between multiple pulmonary nodules from a same subject.
- Integrated with a 3D DenseNet, the proposed end-to-end trainable **NoduleSAT** encourages the model to learn top-down **inter-nodule relations** from bottom-up nodule-level representations.
- We empirically prove the benefit of relation learning between multiple pulmonary nodules.





Thanks for Listening

饮水思源 爱国荣校

