

pass the run-on peak discharge (design flood) of a magnitude that has an annual exceedance probability of one percent or less (one hundred-year flood peak discharge or greater). (C) Sufficient erosion protection and freeboard (one foot minimum) are to be provided for all drainage control features to preclude failure of those features during passage of the design flood. (v) Submit engineering plans and specifications for any containment barrier equalling or exceeding as storage capacity of ten acre-feet to the department's dam safety section for review under RCW 90.03.350. (b) Leachate systems. Monofill owners or operators shall: (i) Install a department-approved leachate collection system sized according to water balance calculations or using other accepted engineering methods; (ii) Install a leachate collection system to prevent no more than one foot of leachate developing at the topographical low point of the active area; and (iii) Install a leachate treatment system to meet requirements of WAC 173-306-200 (3)(c)(ii)(B) through (E). (c) Liner and final cap design. Ash monofill owners or operators shall comply with the requirements of WAC 173-306-450. (d) Liner construction and inspection. Ash monofill owners or operators shall: (i) Comply with the requirements of WAC 173-306-450. (ii) Employ an independent third party as defined in WAC 173-306-100 to inspect the liners during construction and installation for uniformity, damage and imperfections (e.g., holes, cracks, thin spots, foreign materials) and quality of construction; and immediately after construction and installations to inspect: (A) Synthetic liners and covers for tight seams and joints and the absence of tears, punctures or blisters; and (B) Soil-based and admixed liners and covers for imperfections (e.g., lenses, cracks, channels, root holes) or structural nonuniformities that may affect liner permeability. (e) Filling requirements for ash cells. Monofill owners or operators shall design and fill ash monofills in phases or cells, as defined in WAC 173-306-100. Only one cell may be open and in use at one time; each cell must be graded and covered with a flexible high density polyethylene liner or other material of equivalent mechanical strength and chemical resistance during the interim period before reaching final elevation. The liner must be 60 mils and have the ability to withstand weather conditions. The owner or operator shall provide, as part of the interim cover, a method of detecting and/or monitoring/inspecting the integrity and any possible failure of the interim cover. (f) Fugitive dust controls. Monofill owners and operators shall: (i) Employ tire washing for all ash-carrying vehicles as they leave the site or any equivalent method to prevent the trackout of ash onto the site and the public right of way. Contaminated wash-waters must be disposed of according to WAC 173-306-200 (3)(c); (ii) Orient the major axis of the active area of the monofill with respect to the prevailing wind directions so as to minimize the effect of wind upon dispersion of special incinerator ash unless engineering designs can provide equivalent protection; and (iii) Provide for paved approach and exit roads outside the active area with traffic separation and traffic control on-site and at the site entrance. Certified on 10/25/2019 Page 23