

Groverize Monotone Local Search.


David Ponnarovsky

April 24, 2023

1 Introduction.

We follow the study of [Fom+15], who relate between the parametrized complexity to the general average case complexity. Crudely put, they shown that for particular wide range of NP hard problems, a solution which run exponentially at some complexity parameter, for example the tree-width of a graph, can be used to derive a batter than bruteforce solution for the general problem. We continue their work by plugin the Grover search [Gro96] routine instead the original sampling process.

$$\begin{aligned} \sum_{k' \leq k} \frac{1}{\sqrt{p(k')}} \cdot c^{k'-t} N^{\mathcal{O}(1)} &\leq \max_{k' \leq k} \left(\frac{\binom{n-|X|}{t}}{\binom{k'}{t}} \right)^{\frac{1}{2}} \cdot c^{k'-t} N^{\mathcal{O}(1)} = \\ &\left(\max_{k' \leq k} \frac{\binom{n-|X|}{t}}{\binom{k'}{t}} \cdot c^{2(k'-t)} \right)^{\frac{1}{2}} N^{\mathcal{O}(1)} = \left(\max_{k \leq n-|X|} \frac{\binom{n-|X|}{t}}{\binom{k}{t}} \right)^{\frac{1}{2}} \cdot c^{2(k-t)} N^{\mathcal{O}(1)} \leq \\ &\Rightarrow \left(2 - \frac{1}{c^2} \right)^{\frac{n-|X|}{2}} N^{\mathcal{O}(1)} \end{aligned}$$



References

- [Gro96] Lov K. Grover. *A fast quantum mechanical algorithm for database search*. 1996. arXiv: [quant-ph/9605043](#) [[quant-ph](#)].
- [Fom+15] Fedor V. Fomin et al. *Exact Algorithms via Monotone Local Search*. 2015. arXiv: [1512.01621](#) [[cs.DS](#)].