

Magic States Distillation Using Quantum LDPC Codes.

David Ponarovsky

March 30, 2024

1 Current Status.

1. Section 5 - Correct. In any CSS code, one can find a large subspace $\Lambda \subset C_X$ with a dimension that is linear in n and this subspace also satisfies the required relation for distillation. Specifically, for any $x \in \Lambda$, $y, z \in C_X$, it holds that $xy = 0$ and $xyz = 0$.
2. Sections 6 and 7 - Incorrect. Initially, I believed that assuming the code is LDPC, one could encode the state C_Z^\perp in constant depth. However, this idea turned out to be incorrect both in calculation and in contrast to the fact that synthesizing the ground state of the Toric code requires $\Omega(\log n)$ depth.

2 Candidate For Triorthogonal LDPC Code.

Claim 2.1. Consider the ring $\mathbb{F}_q[x]$ where q is a prime number. Let $\Delta = 4^c$ where $c \geq 3$. Then we have:

$$\sum_{x \in [\Delta]} x^i =_{\Delta} \{0, \Delta/2\}$$

Proof. By induction on c .

1. Base. For $c = 3$ we compute the summation bruteforcely.
2. Assumption. Assume the correctness of the claim for $c - 1$.
3. Step. Denote by $B_j(\Delta)$ the bucket $\Delta \cdot j + 1, \Delta \cdot j + 2, \dots, \Delta \cdot (j + 1) - 1$. Observe that:

$$\sum_{x \in B_{j+1}(\Delta)} x^i =_{\Delta} \sum_{x \in B_{j+1}(\Delta)} (x - \Delta)^i =_{\Delta} \sum_{x \in B_j(\Delta)} x^i$$

On the other hand, by the induction assumption, there is some integer a for which:

$$\sum_{x \in B_1(\Delta/4)} x^i = \Delta/8 \cdot a$$

Thus the summation over Δ elements equals to:

$$\sum_{x \in [\Delta]} x^i = \sum_{j \in [4]} \sum_{x \in B_j(\Delta/4)} x^i = \Delta/8 \cdot a \cdot 4 = \Delta \cdot a/2$$

□

Definition 2.1. Let $G = (L, R, E)$ be a bipartite graph, and let Δ be an integer. Define G' to be the graph: $G' = (\Delta \times L, R, E')$ defined as follows:

$$E' = \{ \{(i, v), u\} : i \in [\Delta], \{u, v\} \in E \}$$

In addition, we define the equivalence relation $u \sim v$ for $u, v \in \Delta \times L$ to hold if the first coordinates of u and v are equal.

Let G' be a graph constructed as described above. Consider the code C over the \mathbb{F}_q alphabet, defined as all the assignments of symbols from \mathbb{F}_q to the $\Delta \times L$ vertices. Such any vertex on the right side of G sees a polynomial of degree at most d on its local view, in addition the x 's value of bit in $\Delta \times L$ is the same module Δ for all the checks. To clarify, if one checks, treat $u \in \Delta \times L$ as the value of the polynomial at coordinate z , and treat the other check as the value of the polynomial at coordinate z' , then $z =_{\Delta} z'$.

Claim 2.2. C is a good LDPC code. (If G is expander graph).

Proof. We obtain a lower bound on the code dimension by subtracting restrictions. So,

$$\dim C = \Delta \cdot |L| - |R| \cdot (1 - \rho) \cdot q$$

Now, assume trough contradiction that there is $x \in C$ at weight $|x| < \gamma n$ denote by $S' \subset \Delta \times L$ the set of vertices setted to a non-trivial symbol. And observes that in the original graph G , S' induce a set of vertices S by taking the delegations of the equivalence classes.

Since G is a (n, m, γ, α) expander, and $|S| < |S'| < \gamma n$, it followees that $|\Gamma(S)| > \alpha|S| \Rightarrow$

$$\begin{aligned} |S|/|\Gamma(S)| &< \frac{1}{\alpha} \\ \Rightarrow |S'|/|\Gamma(S)| &< \frac{\Delta}{\alpha} \end{aligned}$$

So there is a check that sees a local view at weight less than $\frac{\Delta}{\alpha}$ bits. (Otherwise, $|S'| > |\Gamma(S)| \cdot \frac{\Delta}{\alpha}$). So, if $\frac{\Delta}{\alpha}$ is lower than C_0 distance we get a contradiction. \square

Claim 2.3. Let h_1, h_2, h_3 be arbitrary checks of C , not necessarily different. Then:

$$\begin{aligned} h_1 h_2 &=_{\Delta} 0 \\ h_1 h_2 h_3 &=_{\Delta} 0 \end{aligned}$$

Proof. Complete it. \square

Consider the Tanner **Graph**, such that the graph G is bipartite, and every two checks overlap on the i th bucket, Δ -size, bits. So for any two checks, we have that

$$\begin{aligned} \sum_{x=i \cdot \Delta}^{(i+1)\Delta} x^j &=_{\Delta} \sum_{x'=(i-1) \cdot \Delta}^{i\Delta} (x' + \Delta)^j \\ &=_{\Delta} \sum_{x=(i-1) \cdot \Delta}^{i\Delta} x'^j = \sum_{x \in \mathbb{F}_{\Delta}} x^j \\ &= \sum_{x \in \mathbb{F}_{\Delta}} (x + a\Delta)^i (x + b\Delta)^j = \sum_{x \in \mathbb{F}_{\Delta}} x^{i+j} \end{aligned}$$

So it's left to show that if we take the bipartite graph to be an expander graph then we have a good code.

Let G be a bipartite graph $G = (L, R, E)$ that is a (n, m, γ, α) expander. This means that for any subset $S \subset V(G)$ with $|S| < \gamma n$, the size of the group of neighbors of S is at least $|\Gamma(S)| > \alpha|S|$. Consider the graph $G' = (\Delta \times L, R, E')$ defined as follows:

$$E' = \{\{(i, v), u\} : i \in [\Delta], \{u, v\} \in E\}$$

Thus for any $S \subset \Delta \times L$ if $|S|/\Delta < \gamma n$ we have that: $|\Gamma'(S)| < \Gamma(|S|/\Delta)$.

Therefore, if S is the set of vertices associated with the non-trivial symbols induced by the assignment of a codeword on the vertices, then if $|S| < \gamma n$, we have:

$$\frac{|S|}{|\Gamma'(S)|} \leq \frac{|S|}{\Gamma(|S|/\Delta)} \leq \frac{\Delta}{\alpha}$$

So there is a check that sees on his local view less than Δ/α non-trival bits $< d(C_0)$.

3 Hyprproduct Code of two Triorthogonal Codes.

Suppose that H is a parity check matrix such that $h_i h_j = \Delta \in \{\Delta, \Delta/2\}$ for any two rows. Is that true that the same property holds for the following check matrix?

$$H' \leftarrow [H \otimes I | I \otimes H]$$

$$H'_i H'_j = (H \otimes I)_i (H \otimes I)_j + (I \otimes H)_i (I \otimes H)_j$$

Denote $i = (i_1, i_2)$ and $j = (j_1, j_2)$. So:

$$(H \otimes I)_i (H \otimes I)_j = \delta_{i_2, j_2} H_{i_1} H_{j_1}$$

and

$$(I \otimes H)_i (I \otimes H)_j = \delta_{i_1, j_1} H_{i_2} H_{j_2}$$

4 The problem with the above.

The code that is obtained by the polynomial tanner is (almost) self dual code, module Δ the multiplication $x \cdot x$ belongs to $\{0, \Delta/2\}$. While what we actually want to have is $x \cdot x = 1$. An idea how to correct that, sets the checks such only two of them don't commute. After taking the Hyprproduct code, they will turned to $\Theta(\sqrt{n})$ that don't commute. So if we have a perfect $\Theta(\sqrt{n})$ T states, we can cancel their phase before the encoding.

Let B be the bucket which matches $\{2, 3, \dots, \Delta - 1\}$. On that bucket, the multiplication of the checks corresponds to $\sum_{x \in \mathbb{F}_\Delta} x^i - 1^i$, which is $\in \{-1, \Delta/2 - 1\}$. On the otherhand, the codeword ξ that corresponds to the constant function $f(x) = 1$ in every bucket gives $\xi \cdot \xi = \Delta - 1$.

So $\xi' = \xi \otimes I$ padding with zeros, is a codeword of the Hyprproduct code, such that $\xi' \cdot \xi' = 1$.

5 Good Codes With Large Λ .

Claim 5.1. *Let v_1, v_2, \dots, v_k vectors in \mathbb{F}_2^n , then there are $u_1, u_2, \dots, u_{k'}$ for $k' > k/2$. Such $\text{span}\{u_1, u_2, \dots, u_{k'}\} \subset \text{span}\{v_1, v_2, \dots, v_k\}$ and for any i, j it holds that $u_i u_j = 0$.*

```

1 Let  $J \leftarrow \emptyset$ 
2 for  $i \in [k/2]$  do
3    $J \leftarrow J \cup \{v_{2i-1}, v_{2i}\}$ 
4   for  $S \subset J$  do
5     Compute the vector  $m_S$ 
6     define as  $m_{S,j} = u_j \sum_{w \in S} w$ 
7   end
8   Pick  $S$  such  $m_S = 0$  and set
9      $u_i \leftarrow \sum_{w \in S} w$ 
9   Choose randomly  $w \in S$  and set
10   $J \leftarrow J/w$ 
10 end
: Find commuted vectors  $u_1, u_2, \dots, u_{k'}$ 

```

```

1 Let  $J \leftarrow \emptyset$ 
2 for  $i \in [k/3]$  do
3    $J \leftarrow J \cup \{v_{3i-2}, v_{3i-1}, v_{3i}\}$ 
4   for  $S \subset J$  do
5     Compute the vector  $m_S$ 
6     define as
7        $m_{S,j,j'} = u_{j'} u_j \sum_{w \in S} w$ 
7   end
8   Pick  $S$  such  $m_S = 0$  and set
9      $u_i \leftarrow \sum_{w \in S} w$ 
9   Choose randomly  $w \in S$  and set
10   $J \leftarrow J/w$ 
10 end
: Find commuted vectors  $u_1, u_2, \dots, u_{k'}$ 

```

Proof. Consider Algorithm 1a, We are going to prove that at line number (8) the alg always finds a subset S that satisfies the equality. Assume not. On one hand, the number of possible values that m_S can have is $2^i - 1$. On the other hand, since J contains $i + 1$ vectors on the i th iteration, it follows that the number of subsets is $2^{i+1} - 1 \geq 2^i$.

Therefore, there must be at least two different subsets S and S' such that $u_S = u_{S'}$. However, this means that

$$\begin{aligned} m_{S \Delta S', j} &= u_j \sum_{w \in S \Delta S'} w = u_j \left(\sum_{w \in S \Delta S'} w + 2 \sum_{w \in S \cap S'} w \right) \\ &= m_{S, j} + m_{S', j} = 0 \end{aligned}$$

Thus, $m_{S \Delta S'} = 0$. Additionally, it is clear that the rank does not decrease, as for u_i , there exists one v_j such that only u_i is supported by v_j . \square

Claim 5.2. Let v_1, v_2, \dots, v_k vectors in \mathbb{F}_2^n and m be an integer $m < k$, then there are $u_1, u_2, \dots, u_{k'}$ for $k' > k/2 - m$. Such $\text{span}\{u_1, u_2, \dots, u_{k'}\} \subset \text{span}\{v_{m+1}, v_{m+2}, \dots, v_k\}$, for any i, j it holds that $u_i u_j = 0$ and for any $i \in [k']$, $j \leq m$ it holds that $u_i v_j = 0$.

Proof. Modify the Algorithm 1a as follows, Initialize u_1, \dots, u_m to be v_1, \dots, v_m and $J = \{v_{m+1}, \dots, v_{2m+2}\}$. Notice that in the i th iteration, for the counting argument to work in the proof of Claim 5.1, we have to ensure that:

$$\begin{aligned} |J| &\geq m + i + 1, \text{ So } m + i + 1 \leq k - m - i \\ \Rightarrow i &\leq k/2 - m - \frac{1}{2} \end{aligned}$$

In the end, $u_{m+1}, u_{m+2}, \dots, u_{k'}$ will satisfy the equations. \square

Claim 5.3. Let v_1, v_2, \dots, v_k vectors in \mathbb{F}_2^n , then there are $u_1, u_2, \dots, u_{k'}$ for $k' > k/4$. Such $\text{span}\{u_1, u_2, \dots, u_{k'}\} \subset \text{span}\{v_1, v_2, \dots, v_k\}$. And for any i, j $\sum u_{i,k} u_{j,k} =_4 0$.

Proof. Use the Algorithm 1a twice. However, in the second iteration, define $m_{S,j}$ to be the product of module 4. Note that $m_{S,j}$ must be either $4n$ or $4n + 2$. Thus, we can follow the proof of Claim 5.1. \square

Claim 5.4. [COMMENT] Complete for the above the version, which handle triples. number of options is $(2^i)^2 = 2^{2i}$ and therefore we have the correctness if $|J| > 2i + 1$.

Claim 5.5. Consider the Left-Right (Δ, n) -Complex Γ . $\dim C_X / C_Z^\perp \cap C_Z / C_X^\perp$ is linear in n .

Proof. The rates of both C_X / C_Z^\perp and C_Z^\perp / C_X^\perp are $(2\rho - 1)^2$, where ρ can be any number in the range $(0, 1)$ [LZ22]. Consider choosing ρ such that the rates of the quotient spaces are strictly greater than $\frac{1}{2} + \alpha$. This implies that the rate of their intersection is greater than 2α . \square

Corollary 5.1. Fix the rate of the small codes C_A and C_B to $\rho = \frac{1}{2} + \alpha$. There is a subspace $\Lambda \subset C_X / C_Z^\perp$ at rate $\frac{1}{4} \cdot 2\alpha$ such that for any $x \in \Lambda$ and $y, z \in C_Z^\perp \cup \Lambda$ it holds that:

1. $xy =_4 0$
2. $xyz =_4 \sum_i x_i y_i z_i =_4 0$

Claim 5.6. Consider C, Λ and C', Λ' defined in ?? Denote by $\bar{\Lambda}$ the subspace C/Λ . Then:

$$d(C'/\bar{\Lambda}') \geq d(C/\bar{\Lambda})$$

Proof. The way we perform Guess elimination is critical. We want to make sure that we do not add an Λ row to a $\bar{\Lambda}$ row. [COMMENT] Continue, Easy. Just need to perform the row reduction when rows of Λ at bottom, and then rotate the matrix \curvearrowright

$$\begin{bmatrix} A & B \\ C & D \end{bmatrix} \curvearrowright \begin{bmatrix} D & C \\ B & A \end{bmatrix}$$

\square

Claim 5.7 (Not Formal). *It is easy to see that by using concatenation again, one can obtain the code $\dim \Lambda' \leftarrow \frac{1}{2} \dim \Lambda'$. For any $x \in \text{gen } \Lambda'$, $|x|_4 = 1$, and for any $x \in C'/\Lambda'$, we have $|x|_4 = 0$.*

Proof. [COMMENT] We will do it by iterating the generators of C after performing rows reduction to the generator matrix. Now we will concatenate the i coordinate to complete the weight of the i th row to satisfy the requirements. \square

6 Compute $|C_Z^\perp\rangle$ In Constant Depth. [COMMENT] Wrong Section.

Let C_0 be a Δ -length error linear binary code, Γ a Δ -regular bipartite graph, and let C_Z be the Tanner code defined by C_0 and Γ . We are about to prove that the uniform superposition over C_Z^\perp codewords can be computed with constant probability at a depth dependent only on Δ , in particular independent of the C_Z^\perp -length. For this, we are going to use Proposition 10 in [MN98], which states that both the encoder and the decoder of any stabilizer m -length code can be implemented by a circuit at depth $\Theta(\log m)$ with $\Theta(m^2)$ ancillae.

Claim 6.1. *Let G be a Δ -regular bipartite graph, and denote by C_Z^\perp the dual-tanner code $\mathcal{T}(G, C_0^\perp)^\perp$. Then there is a circuit that with constant probability computes the state $|C_Z^\perp\rangle$ at $\Theta(\log \Delta)$ depth, and $\Theta(\Delta^2)n$ ancillary qubits.*

Proof. Let E_v and D_v be the encoder and the decoder of C_0 over the local view of vertex v . By [MN98] we have that both have depth $\Theta(\log \Delta)$ and require Δ^2 ancillae. Since Γ is bipartite, we can decompose V into V^- and V^+ such that the local views of any two vertices in V^\pm are disjoint. Therefore, for any two different vertices $v, u \in V^\pm$, the encoders E_v and E_u act on disjoint subsets of qubits, each corresponding to the local view of either v or u . Consider the following algorithm:

- 1 Initialize $2n$ qubits.
- 2 Call the left and right segments L and R .
- 3 Apply E_v in parallel on L for any $v \in V^+$.
- 4 Apply E_v in parallel on R for any $v \in V^-$.
- 5 XOR R into L by applying CNOT from the i th bit of R to the i th bit of L .
- 6 Apply D_v in parallel on R for any $v \in V^-$.
- 7 Apply H^k on L . And measure.
- 8 Accept if the result in C_Z

Algorithm 1: Compute $|C_Z^\perp\rangle$

For any $v \in V$, let $|z_v\rangle$ be the superposition of codewords in C_0 supported by the local view of v . Similarly, for any subset of vertices $W \subset V$, let $|z_W\rangle$ be the uniform superposition over the subspace spanned by the generators supported by the vertices in W . In other words:

$$|z_W\rangle = \left| \sum_{v \in W} z_v \right\rangle$$

Using the notation, applying the encoders E_v, E_u for any pair of vertices with disjoint local view become:

$$\begin{aligned} E_v \cup E_u |0\rangle^n &= E_v |0 + z_u\rangle = E_v |0_{/u's \text{ view}}\rangle \otimes |z_u\rangle \\ &= |z_v\rangle |z_u\rangle = |z_u + z_v\rangle = |z_{\{u,v\}}\rangle \end{aligned}$$

So applying all the encoders E_v at once over the positive vertices results in:

$$(\cup_{v \in V^+} E_v) |0\rangle^n = (\cup_{v \in V^+ / v_0} E_v) |z_{v_0} + 0\rangle = |z_{V^+}\rangle$$

Thus the whole computation sum up into:

$$\begin{aligned}
(\cup_{v \in V+} E_v) \otimes (\cup_{v \in V+} E_v) & \quad |0\rangle^n \otimes |0\rangle^n \mapsto \\
\text{CNOT} \sum_{z \in A} \sum_{z' \in B} & \quad |z_{V+}\rangle |z_{V-}\rangle \mapsto \\
I \otimes H^k \sum_{z \in A} \sum_{z' \in B} & \quad |z + z'\rangle |z'\rangle \mapsto \\
\sum_{z \in A} \sum_{z' \in B} & \quad |z + z'\rangle (-1)^{wz'} |w\rangle \mapsto
\end{aligned}$$

So if $w \in C_Z$ then clearly $z'w = 0$. The probability for that to occur is

$$\Pr[w \in C_Z] = \frac{|C_Z|}{\mathbb{F}_2^n} = 2^{(\rho-1)n}$$

□

7 Distillate $|\Lambda + C_Z^\perp\rangle$ Into Magic.

Let $|f\rangle$ be a codeword in C_X , and let \hat{X}_g be the indicator that equals 1 if f has support on generator g , and 0 otherwise. Observe that applying T^\otimes on $|f\rangle$ yields the state:

$$\begin{aligned}
T^{\otimes n} |f\rangle &= T^{\otimes n} \left| \sum_g \hat{X}_g g \right\rangle = \exp \left(i\pi/4 \sum_g \hat{X}_g |g| - 2 \cdot i\pi/4 \sum_{g,h} \hat{X}_g \hat{X}_h |g \cdot h| \right. \\
&\quad \left. + 4 \cdot i\pi/4 \sum_{g,h} \hat{X}_g \hat{X}_h \hat{X}_l |g \cdot h \cdot l| - 8 \cdot i\pi/4 \cdot \text{integers} \right) |f\rangle \\
&= \exp \left(i\pi/4 \sum_g \hat{X}_g |g| - 2 \cdot \pi/4 \sum_{g,h} \hat{X}_g \hat{X}_h |g \cdot h| + 4 \cdot i\pi/4 \sum_{g,h} \hat{X}_g \hat{X}_h \hat{X}_l |g \cdot h \cdot l| \right) |f\rangle
\end{aligned}$$

So in our case:

$$\begin{aligned}
T^{\otimes n} |f\rangle &= \\
&= \exp \left(i\pi/4 \sum_{g \in \text{gen } \Lambda} \hat{X}_g \right. \\
&\quad \left. - 2 \cdot \pi/4 \sum_{g,h \in \text{gen } C_Z^\perp} \hat{X}_g \hat{X}_h |g \cdot h| \right. \\
&\quad \left. + 4 \cdot i\pi/4 \sum_{g,h \in \text{gen } C_Z^\perp} \hat{X}_g \hat{X}_h \hat{X}_l |g \cdot h \cdot l| \right) |f\rangle
\end{aligned}$$

So eventually, we have a product of gates when non-Clifford gates are applied on only on generators of C_Z^\perp .

$$T^n |f\rangle = \prod_{g \in \text{gen } \Lambda} T_g \prod_{g,h \in \text{gen } C_Z^\perp} \{CS_{g,h}|CZ_{g,h}|I\} \prod_{g,h,l \in \text{gen } C_Z^\perp} \{CCZ_{g,h,l}|I\} |f\rangle$$

Decompose $f = f_1 + f_2$, where f_1 is supported only on C_X/C_Z^\perp and f_2 is supported only on C_Z^\perp . By using commuting relations, the above can be turned into.

$$\begin{aligned}
T^n |f\rangle &= \prod_{g \in \text{gen } \Lambda} T_g X_{f_1} \\
&\quad \prod_{g,h \in \text{gen } C_Z^\perp} \{CS_{g,h}|CZ_{g,h}|I\} \prod_{g,h,l \in \text{gen } C_Z^\perp} \{CCZ_{g,h,l}|I\} |f_2\rangle
\end{aligned}$$

Denote by M_1, M_2 the gates:

$$M_1 = \prod_{g \in \text{gen } \Lambda, h} \{CZ_{g,h}|I\}$$

$$M_2 = \prod_{g,h \in \text{gen } C_Z^\perp} \{CS_{g,h}|CZ_{g,h}|I\} \prod_{g,h,l \in \text{gen } C_Z^\perp} \{CCZ_{g,h,l}|I\}$$

And then we get that

$$\prod_{g \in \text{gen } \Lambda} T_g |f\rangle = M_1^\dagger T^n M_2^\dagger |f\rangle$$

$$\prod_{g \in \text{gen } \Lambda} T_g |f\rangle = M_1^\dagger T^n E_L[M_2^\dagger] |L[f]\rangle$$

Claim 7.1. Let $v \in V^-$, and let g_1 be the generator supported by v , which matches an assignment of a codeword in $C_A \otimes C_B$ on the local view of v . Denote by U_{v,g_1} the control-gate which, depending on the control bit $(v, 1)$, turns on g_1 over the edges associated with the local view of v in the graph G . Then, the depth of U_{v,g_1} depend only on Δ .

Claim 7.2. Let (v, g_1) and (u, g_2) be control wires for two different generators in the graph G . Then U_{v,g_1} and U_{u,g_2} **[COMMENT]** There must be a claim about the relationship between two different generators intersection, But I don't sure exactly why.

Definition 7.1. We say that a quantum circuit \mathcal{C} is well error spreading if the light cone define by any T .

Claim 7.3. The state:

$$\sum_{z \in C_Z^\perp} \exp\left(-2 \cdot \pi/4 \sum_{g,h \in \text{gen } C_Z^\perp} \hat{X}_g \hat{X}_h |g \cdot h| \right. \\ \left. + 4 \cdot i\pi/4 \sum_{g,h \in \text{gen } C_Z^\perp} \hat{X}_g \hat{X}_h \hat{X}_l |g \cdot h \cdot l|\right) |z\rangle$$

Can be computed such that any

Proof. Denote by U_v the gate which turn on all the generators supported on v . As any of them is just of a code word of $C_A \otimes C_B$, namely turning on generator require touching at most constant number of qubits combing \square

Claim 7.4. The state $(M_2^\dagger \otimes I) |C_Z^\perp + \Lambda\rangle |0\rangle$ can be computed, such that the light cone depth of any non-clifford gate is bounded by constant.

Proof.

$$\begin{aligned}
(I \otimes H_X) C X_{n \rightarrow n} (E \otimes E) I \otimes L[M_2^\dagger] & \prod_{\substack{J \in \{\text{gen } \Lambda, g \in J \\ \text{gen } C_Z^\perp\}}} \prod (I + X_{L[g]}) & |0\rangle |0\rangle \\
= (I \otimes H_X) C X_{n \rightarrow n} \sum_{\substack{z \in C_Z^\perp \\ x \in \Lambda}} e^{\varphi(z)} & |x\rangle |z\rangle \\
= \sum_{\substack{z \in C_Z^\perp \\ x \in \Lambda}} e^{\varphi(z)} & |x+z\rangle |0\rangle \\
= \sum_{\substack{z \in C_Z^\perp \\ x \in \Lambda}} (M_2^\dagger \otimes I) & |x+z\rangle |0\rangle \\
= (M_2^\dagger \otimes I) & |C_Z^\perp + \Lambda\rangle |0\rangle
\end{aligned}$$

□

Denote by $p \in [0, 1]$ the error rate of input magic states, and let $|A\rangle$ be an ancilla initialized to a one-qubit magic state. This $|A\rangle$ can be used to compute the T gate, with a probability of Z error occurring with a probability of p [BH12].

Claim 7.5. *There are constant numbers ζ_Δ, ξ_Δ , and a circuit \mathcal{C} such that:*

1. *In the no-noise setting, The circuit compute the state*

$$\mathcal{C} |0\rangle^{\Theta(n)} \otimes |A\rangle^{\Theta(n)} \rightarrow \prod_{g \in \text{gen } \Lambda} T_g |C_Z^\perp + \Lambda\rangle$$

2. *Otherwise, the circuit computes the state*

$$\mathcal{C} |0\rangle^{\Theta(n)} \otimes |A\rangle^{\Theta(n)} \rightarrow Z^e \prod_{g \in \text{gen } \Lambda} T_g |C_Z^\perp + \Lambda\rangle$$

, where the probability that $e_i = 1$ is less than $\zeta_\Delta \cdot p$. Additionally, for any i , there are at most ξ_Δ indices j such that e_i and e_j are dependent.

Proof. Concatenate the $T^n \otimes I$ with the gate in Claim 7.4. □

Claim 7.6. *For any $\alpha \in (0, 1)$ the probability that $|e| > (1 + \alpha)p\zeta_\Delta$ is less than:*

$$\Pr[|e| > (1 + \alpha)\mathbf{E}[|e|]] < \frac{1 \cdot \xi_\Delta n}{\alpha^2 \zeta_\Delta^2 p^2 n^2} = o(1/n)$$

Proof. By the Chebyshev inequality, notice that the number for which $\mathbf{E}[e_i e_j] - \mathbf{E}[e_i] \mathbf{E}[e_j] \neq 0$ is less than $\xi_\Delta n$. □

Definition 7.2. *We will said that a decoder \mathcal{D} for the good quantum LDPC code is an good-local decoder if*

1. *There is a treashold μn such that if the error size is less than $|e| < \mu n$ then \mathcal{D} correct e in constant number of rounds. With probability $1 - o(1/n)$.*
2. *In any rounds \mathcal{D} performs at most $O(n)$ work (depth \times width).*
3. *The above is true in operation-noisy settings, where there is a probability of p for an error to occur after acting on a qubit. (★)*

★ The motivation for this is that if the decoder does not act on the qubit, then it also does not apply a T gate on it. Therefore, in the distillation setting, there is zero chance for an error to occur.

Claim 7.7. Suppose there is a good local decoder \mathcal{D} for the good qLDPC code. Then, there exists p_0 such that for any sufficiently large n , there is a distillation protocol that, given $\Theta(n)$ magic states at an error rate $p < p_0$, successfully distills $\Theta(n)$ perfect magic states with a probability of $1 - o(1/n)$. Furthermore, the protocol's space and time complexity (both quantum and classical) are $\Theta(n)$ and $\Theta(n^2)$, respectively.

References

- [MN98] Cristopher Moore and Martin Nilsson. *Parallel Quantum Computation and Quantum Codes*. 1998. arXiv: [quant-ph/9808027 \[quant-ph\]](#).
- [BH12] Sergey Bravyi and Jeongwan Haah. “Magic-state distillation with low overhead”. In: *Physical Review A* 86.5 (2012), p. 052329.
- [LZ22] Anthony Leverrier and Gilles Zémor. *Quantum Tanner codes*. 2022. arXiv: [2202.13641 \[quant-ph\]](#).