# The Sweep-Rule Strikes Back

David Ponarovsky

School of Computer Science, Hebrew University

October 27, 2026

**Abstract**

We study fault-tolerant quantum computation with a *fixed, local error-correction rule* and a geometrically simple code. Our construction uses the cubical $(d, d')$-Toric code, with $d', d - d' \geq 2$ (in particular, the 4D Toric code), and tolerates sufficiently weak local-stochastic Pauli noise in the circuit model. Classical processing is assumed noiseless and has bounded depth per physical time step. Unlike constructions whose local decoders require a hierarchy of auxiliary classical states and scale-dependent communication delays, our error-correction cycle acts directly on the current syndrome, has constant depth, and is repeated unchanged during idle logical computation.

Our proof works with errors and syndromes as chains in a cubical chain complex. It combines geometric shrinking under the sweep rule with a space–time explanation-tree analysis inspired by Toom's theorem, without relying on an expansion property of the code complex. We establish three results:

1. **An explicit higher-dimensional sweep rule.** We give a local procedure for choosing the sweep correction on cubical $(d, d')$-Toric complexes, resolving the higher-dimensional local-existence question of Kubica and Preskill [KP19].
2. **Fault-tolerant computation with a simple code and local correction.** We prove a circuit-level threshold theorem for repeated noisy sweep cycles interleaved with logical operations. In particular, the 4D Toric code supports a fixed, constant-depth syndrome-based correction cycle without a multiscale classical decoder or expansion-based encoding. The construction is not claimed to have constant total-depth overhead.
3. **Ideal decoding under local-stochastic noise.** Starting from a local-stochastic Pauli error of rate $p$ below a threshold, $n^{d+1}$ *noiseless* sweep cycles on a side-length-$n$ $(d, d')$-Toric code recover the encoded state with probability at least $1 - O(\mathrm{poly}(n))p^{\Omega(n)}$. This extends earlier sweep-decoding guarantees for independent errors [KP19].

# Contents


**1 Introduction** **2**
- 1.1 Background and motivation . . . 2
- 1.2 Our results . . . 3
- 1.3 Discussion and scope . . . 5

**2 Outline of the Proof** **5**

**3 Notations and Preliminaries** **11**

**4 The $(d, d')$-Dimensional Toric Code** **15**
- 4.1 Sweep Rule . . . 19
- 4.2 Infinite Sides Torics . . . 22
- 4.3 Reduced Error . . . 25
- 4.4 Shrinking . . . 31
  - 4.4.1 Ideal decoder . . . 33
- 4.5 Logical Gates . . . 34
- 4.6 Propagation Through Gate-Teleportation . . . 40

**5 Toom's Contours** **42**
- 5.1 The Barrier Argument . . . 42
- 5.2 Toom's Contours . . . 48
- 5.3 Space-Time Graph . . . 51
- 5.4 Minimal Explantation Argument . . . 58

**6 Proof of the Theorem** **61**

**7 The Sweep-rule is Itself a Decoder** **65**

**8 Appendix** **68**
- 8.1 Counting Subtrees. . . . 68
- 8.2 Tree Separator Lemma . . . 69

# 1 Introduction

## 1.1 Background and motivation

A fault-tolerant quantum computer must protect its logical state while gates, measurements, and error correction are themselves subject to faults. An important design choice is not just the quantum code but the *classical and quantum mechanism used to keep errors under control*. A conceptually attractive target is a regular code for which each correction round consists of the same bounded-depth local procedure, determined only by the syndrome currently observed. Such a procedure neither stores a growing decoding history nor organizes the correction into successively larger scales.

The quantum threshold theorem established the feasibility of fault-tolerant computation below a constant noise threshold [AB99; Sho95]. A major subsequent direction reduced the qubit overhead using high-rate quantum LDPC codes and, in several constructions, expander-based complexes [Got14; Gro19; FGL18; NP25]. Expansion supplies powerful control of errors and their syndromes, but it is a substantive structural assumption. We pursue a complementary question: *Can a simple, nonexpanding topological code support a local correction cycle within a rigorous fault-tolerant computation?* We answer this question affirmatively for the cubical $(d, d')$-Toric code when $d', d - d' \geq 2$. We do not aim to optimize the total depth or the space overhead of the simulation.

The Toric code is particularly suited to this question. Its qubits, stabilizer checks, and logical operators are described by the cells of a regular cubical complex. Unlike a code whose analysis requires expansion, it admits a direct topological description: errors are chains, their syndromes are boundaries, and logical faults correspond to nontrivial homology classes. Our proof exploits this description rather than trying to maintain a strong probabilistic invariant on the entire physical error after every round. In particular, the chain-complex relation $\partial^2 = 0$ lets us separate physically large but stabilizer-trivial errors from syndrome configurations that could signal logical failure.

**Toom-type recovery for the 4D Toric code.** Local recovery for the 4D Toric code was already proposed in the literature. Dennis, Kitaev, Landahl, and Preskill [**Dennis2002**] discussed anisotropic local dynamics inspired by Toom's rule. Ahn studied 4D Toom correction [Ahn04]; we discuss gaps in her proof in a companion paper. More recently, Drechsler, Oreg, and Aharonov [DOA26] established quantum–classical correspondences for quantum memories in both asynchronous continuous-time and synchronous discrete-time settings. Their specific 4D Toric/Toom memory application *uses Ahn's threshold estimate*: it gives a synchronous quantum-channel memory and a periodically driven (Floquet) Lindbladian memory, while a time-independent asynchronous 4D Toom-memory theorem remains open. Thus the classical threshold input, the quantum-memory framework, and a full fault-tolerant computation are distinct questions.

Kubica and Preskill [KP19] introduced the *sweep rule*, extending Toom's oriented local dynamics to topological codes, and proved ideal-decoding results for independent noise. Their formulation also identifies an existence question for certain higher-

dimensional local corrections. We work with the ordinary cubical Toric complex, give an explicit local implementation of the sweep rule, and analyze it both under continuously occurring faults and as a noiseless decoder for initially correlated local-stochastic errors.

**Related local fault-tolerant architectures and their classical hardware.** An important comparison is the cellular-automaton line of work, including Balasubramanian, Davydova, and Lake [BDL26]. In particular, *Selub, Bhardwaj, and Lake* [SBL26] have already achieved fault-tolerant quantum computation based on a *local decoder for a topological code*: their two-dimensional surface-code architecture has time-translation-invariant local decoding dynamics and bounded-speed classical communication. Its constant-resource-density realization, however, implements a multiscale hierarchy with auxiliary classical state and classical wires whose lengths grow with the decoding scale. The propagation delays along those wires *function as distributed timers*: rather than storing a large timer in each processor, the hardware uses physical signal travel to implement the longer periods of the higher-level updates. For this scheduling task, a long delay line is the hardware analogue of a stored timer: the requisite waiting time is encoded in wire length rather than counter bits. Thus the timing resource is relocated into spatial communication hardware, not eliminated. This is an architectural tradeoff, not a claim that their decoder has growing local Boolean-circuit depth.

*Our correction cycle requires neither such distributed timers nor a multiscale communication network.* Each local correction is a fixed function of the presently measured syndrome on a constant-size neighborhood, and all locations execute the same finite schedule in each sweep cycle. In particular, an idle logical identity is implemented by repeated copies of this cycle, with no persistent decoder messages or hierarchy-dependent clocks. We emphasize the precise scope of the comparison: these statements concern the *repeated error-correction procedure on the native 4D Toric lattice*. They do not assert a fully autonomous or clock-free device, remove classical processing for logical gates, or eliminate the potential physical cost of embedding four-dimensional connectivity in lower-dimensional hardware. In this respect, the 2D physical locality achieved by [SBL26] is a genuine advantage of their construction.

These results also sharpen our mathematical contribution. One can obtain a local decoder for a nonexpanding topological code by supplying additional hierarchical decoding hardware. Our result shows that *expansion is unnecessary even when the correction rule is a single fixed, local, syndrome-based map without such a hierarchy*, provided the code geometry is allowed to be four-dimensional. The proof mechanism is different from expansion-based estimates: it tracks the combinatorial histories of syndromes viewed as boundaries in a chain complex.

## 1.2 Our results

**Fault-tolerant computation with repeated local correction.** Fix integers $d, d'$ satisfying $d', d - d' \geq 2$. The $(d, d')$-Toric code is the CSS code associated with the cubical chain groups of a side-length-$n$ $d$-dimensional torus. Each encoded block undergoes a constant-depth *sweep cycle*, consisting of parallel local updates in the two

CSS sectors. The update rule and the finite sequence making up a cycle are independent of the elapsed time, the block size, and the number of preceding correction rounds.

We use the circuit model with local-stochastic Pauli noise on quantum locations and reliable classical bits and logic. More precisely, if $\mathcal{N}_\mathcal{E}$ is a distribution over fault sets with rate $p$, then for every predetermined finite set $S$ of space–time locations,

$$\mathbf{Pr}_{\mathcal{E}\sim\mathcal{N}_\mathcal{E}}\big[S \subseteq \mathrm{Loc}(\mathcal{E})\big] \le p^{|S|}.$$

This condition allows correlations between faults; independence is not assumed. At any physical time step, only constant-depth noiseless classical computation is allowed.

**Theorem** (Informal version of Theorem 6.3)**.** *There is a constant $p_0 > 0$ such that for local-stochastic Pauli noise of rate $p < p_0$, every ideal circuit of width $w$ and depth $\mu$ has a 4D-Toric-code-encoded simulation using side-length-$n$ blocks whose logical failure probability is at most*

$$O(\mathrm{poly}(w, \mu, n))\, p^{\Omega(n)}.$$

*For sufficiently large $n$, the encoded circuit has depth $\Theta\big(\mu(n + \mathrm{polylog}\, n)\big)$ and width $\Theta\big((w + \mu)n^8\, \mathrm{polylog}\, n\big)$. After fault-tolerant initialization, the encoded blocks use the 4D Toric code, and each intervening correction cycle has constant depth and applies the same local sweep rule.*

The stated costs include the implementation of logical operations; in particular, gate teleportation may need a classical decoding computation of nonconstant total duration. Our claim of constant depth is therefore *about the recurring correction cycle*, not the entire simulation of each logical gate. Unlike the local-decoding constructions in which code expansion is the essential geometric input, our theorem uses a nonexpanding cubical chain complex. The correction dynamics require no scale-dependent auxiliary control network.

**An explicit higher-dimensional sweep rule.** At a vertex of the cubical complex, the sweep rule examines syndrome checks in a designated positive neighborhood and seeks a nearby correction chain supported on positive faces. Kubica and Preskill [KP19] established the usefulness of this rule and posed the local existence question in higher dimensions. We prove the required existence statement and give an explicit choice of local correction. Since the dimension is fixed, this choice can be implemented by bounded-depth classical processing on a constant-size neighborhood.

**Ideal decoding of local-stochastic errors.** Our third result concerns the same correction rule used *without faults during decoding*. It is separate from the above threshold theorem, where noise may occur between and during repeated correction cycles.

**Theorem** (Informal version of Theorem 7.3)**.** *Fix $d, d'$ with $d', d - d' \ge 2$. There is a constant $p_0 > 0$ such that a codeword of the side-length-$n$ $(d, d')$-Toric code, corrupted by a local-stochastic Pauli error of rate $p < p_0$, is recovered after $n^{d+1}$ noiseless sweep cycles with probability at least*

$$1 - O(\mathrm{poly}(n))\, p^{\Omega(n)}.$$

The earlier analysis in [KP19] treats independent initial errors. Our extension allows correlated local-stochastic errors; the crucial probabilistic estimates follow from counting fault explanations rather than assuming error independence.

### 1.3 Discussion and scope

The main message is a separation of two often-confounded ingredients of local quantum decoding: *geometric expansion of the code* and *the ability to control errors by local updates*. For the 4D Toric code, the latter is provable without the former. Moreover, the decoder's rule has no persistent auxiliary state, so there is no need to store large local timers or implement them by scale-dependent wire delays. The construction still relies on a synchronous constant-depth correction cycle, ideal classical computation, and a four-dimensional lattice geometry; none of these hardware assumptions is eliminated by the theorem.

The proof may also be of independent interest. It translates an idea from reliable classical cellular automata—explaining a large error by a space–time dependency tree—into homological language. In a CSS chain complex, errors of large Hamming weight may be stabilizers, while a syndrome is a boundary; thus the relevant objects to track are not the erroneous qubits themselves but the evolving supports and geometric spans of syndrome chains. We use this distinction to make a first-passage argument for logical errors and to count the fault histories that could produce them.

**Acknowledgment and AI disclosure.** The author thanks Prof. Michael Ben-Or for discussions, supervision, and support. ChatGPT assisted with editing, proof checking, and brainstorming. The mathematical ideas and responsibility for the paper remain with the author.

## 2 Outline of the Proof

The proof has two intertwined parts. The *deterministic* part expresses errors, checks, and local corrections as cubical chains and proves that a sweep moves the boundary of a finite error cluster inward. The *probabilistic* part describes a large late-time syndrome by a bounded-degree graph of earlier syndrome witnesses and faults. Combining these parts proves that logical failures require an exponentially unlikely number of specified faults, without invoking expansion.

**Chains, boundaries, and local sweep corrections.** Consider the cubical chain complex over $\mathbb{F}_2$ associated with the $d$-dimensional Toric lattice,

$$\cdots \longrightarrow C_{d'+1} \xrightarrow{\partial_{d'+1}} C_{d'} \xrightarrow{\partial_{d'}} C_{d'-1} \longrightarrow \cdots, \qquad \partial_{d'}\partial_{d'+1} = 0.$$

Qubits correspond to $d'$-faces, so an $X$-error can be represented by a chain $e \in C_{d'}$ and its measured $Z$-syndrome by the boundary $\sigma = \partial_{d'} e \in C_{d'-1}$. For the complementary Pauli sector we use the dual cubical complex. A local correction $c \in C_{d'}$ changes the

error to $e + c$ and the syndrome to $\sigma + \partial_{d'} c$; a stabilizer boundary $c = \partial_{d'+1} b$ does not affect the syndrome. The identity $\partial^2 = 0$ is therefore built into the error-correction problem. Logical operators are detected by nontrivial homology, rather than simply by the Hamming weight of a Pauli chain.

To describe a face locally, use the notation $\theta_{v,S'}$ of **??**: the face is rooted at vertex $v$ and directed along a set $S'$ of coordinate generators. The following TikZ picture from the original outline illustrates this notation on a two-dimensional Toric complex.





Figure 1: Here we consider a 2D Toric complex. We name the set of generators $S = \{g_1, g_2\}$, where $g_1$ is the generator that sends us one step in the north direction, and $g_2$ sends us in the east direction. For vertices $v, u, w$, we mark in blue three faces that are rooted at them.

At each vertex $v$, the sweep rule reads the syndrome on positively oriented nearby $(d'-1)$-faces and chooses a correction on positive $d'$-faces, whenever one satisfies the local boundary constraints. The correction is a bounded-dimensional chain problem in the link of $v$; it is therefore local even though the surrounding code has a large block size. We prove the local existence claim conjectured in [KP19] and derive an explicit algorithm for choosing the chain. Both the primal and dual rules together constitute one sweep cycle (Definition 4.6).





Figure 2: An example of applying the sweep rule within the $(3, 2)$-Toric code. In the $(3, 2)$-Toric code, bits are placed on the squares and $Z$-stabilizers (parity checks) on the edges. The view is restricted to two vertices, $u$ and $v$. On the left, the unsatisfied positive checks of $u$ and $v$ are highlighted in blue. On the right, the bits to be flipped are marked in green. Given the syndrome, vertex $v$ flips one of its positive faces, whereas for $u$, there is no subset of positive faces that, when flipped, satisfies local checks. Therefore, $u$ flips no bit.

**Shrinking syndromes in the infinite cover.** We lift the $d$-dimensional Toric complex to its infinite periodic cover, where we can distinguish finite syndrome clusters from homologically nontrivial errors. For finite connected syndrome components, a fixed set of linear potential functions determines extremal *walls* that enclose the component in a simplex-like bounding region. The directional sweep advances the appropriate extremal wall, while keeping the other relevant extremal coordinates under control. This gives a quantitative shrinking statement for the span of finite syndrome clusters, developed in **??** and Section 4.4.





Figure 3: A graphical example of the maximal values of the potential walls. Here we consider the $(2, 1)$-Toric code, namely the bits are set on the edges where the $Z$-stabilizers (parity checks) are set on the vertices. The grid is a finite $6 \times 6$ patch of the infinite 2D plane. The edges marked in blue correspond to a bits assignment $z$. Each of the dashed lines marks the line of vertices whose $L_i$ value converges with the maximal value reached by a vertex in $z$. Moving into the infinite plane enables us to determine those lines and draw the triangle that bounds $z$.

**Why a logical error must cross a syndrome barrier.** A homologically nontrivial chain can have zero syndrome. Consequently, one cannot prove fault tolerance merely by examining the final syndrome after a full noisy circuit layer: a collection of faults in that layer may already implement a logical operator. We therefore split the computation, including each fault layer, into a time-respecting sequence of elementary steps containing one bounded-support operation. Since each step changes the local chain data in a bounded region, an evolution from a correctable configuration to a logically nontrivial one must first pass through a step with a sufficiently large connected syndrome span. This is the *barrier argument* of Claim 5.9. The first step at which the barrier is crossed allows us to analyze only histories that have remained

below the barrier at all earlier steps.





Figure 4: Example of a subjected quantum circuit: the even layers (0, 2, 4) contain the original gates, while the faults are imposed on the odd layers and marked in red.

**Fault propagation through logical gates.** After initialization by standard fault-tolerant procedures [AB99; Gro19; Got14], each register is encoded in a 4D Toric code. Pauli operations and controlled-NOT have transversal realizations; the other gates in the universal set $\mathbf{X}, \mathbf{Z}, \mathbf{CX}, \mathbf{H}, \mathbf{S}, \mathbf{T}$ are implemented using encoded resource states and gate teleportation [ZLC00]. A logical teleportation step may take multiple sweep cycles while its reliable classical readout is processed; the destination register remains protected during that processing. The fold-transversal Hadamard of [BB24] is used for the relevant $X$-basis measurement. We analyze the propagation of the chain and its boundary through these gadgets so that the local geometric control is compatible with computation, not only with passive memory (Section 4.5).

**Toom-type contours from syndrome histories.** We adapt the explanation-tree idea of Berman and Simon [BS88] and its later formulation [Gac21]. The vertices of our space–time graph are lattice vertices supporting nonzero syndrome chains, rather than erroneous qubits. Arrows track the possible influence of one syndrome witness on a later one; forks capture the merging of causal explanations. This choice exploits the chain-complex representation: stabilizer boundaries may change the error chain without creating a syndrome, and therefore should not themselves count as surviving defects.

A *slice* is a connected group of syndrome witnesses at a given time, with size measured by the geometric span of its projection in the infinite cover. If a final slice has size $s$, the shrinking property forces any explanation of it to have a bounded-degree tree with $O(s)$ edges and $\Omega(s)$ terminal fault witnesses. The covering map can send several witnesses to the same physical fault location, so we extract a large substructure whose leaves project to distinct locations before applying a probability bound. A final partially executed time layer is treated separately, with added local connections between witnesses meeting a common syndrome check. These connections make the barrier's large connected component visible to the contour argument, without altering the induction on earlier layers; see **??**, Section 5.3, and Section 5.4.





Figure 5: Above: The application of a sweep-cycle, where the green faces represent the bits assignment $z$, and the blue edges correspond to unsatisfied checks $\partial^- z$. The vertices witnessing a syndrome, namely belonging to $\partial^- z$, are labeled as $v_1, v_2, \ldots, v_8$. Notice that the leftmost bottom-inner vertex is not witnessing a syndrome even though it belongs to $z$. Below: The Toom's contour derived from the single computation layer that matches the cycle. Arrows are colored in blue, while forks are colored in green. Note that $(v_1, t+1)$ doesn't belong to the Toom's contour (since $v_1$ doesn't see an unsatisfied check at time $t+1$).

There are at most exponentially many bounded-degree explanation trees of a given size, while a local-stochastic noise model assigns probability at most $p^r$ to any fixed collection of $r$ distinct fault locations. For sufficiently small $p$, this yields an exponentially decaying bound in $s$ for the existence of an explanatory contour. The argument requires no stochastic independence between different fault locations and no expansion inequality for the underlying code.

**Completing the fault-tolerance and ideal-decoding results.** For a noisy encoded computation, logical failure implies that some intermediate step crosses a barrier with syndrome span $\Omega(n)$. The contour bound makes that event at most $\mathrm{poly}(w, \mu, n)p^{\Omega(n)}$ after a union bound over positions, steps, and encoded registers. This leads to the circuit-level theorem in Theorem 6.3.

For the ideal-decoding theorem, an initial local-stochastic Pauli error is followed by *noiseless* sweep cycles. On the high-probability event that no dangerous syndrome slice appears, repeated shrinking removes every nonzero syndrome within $n^{d+1}$ cycles and the barrier argument excludes a change of logical class. Thus the same combinatorial framework proves both robustness under ongoing noisy correction and successful

decoding from an initially correlated error distribution (Theorem 7.3).

# 3 Notations and Preliminaries

We follow the standard notations commonly used in the literature. For an integer $n$, we denote by $[n]$ the set of integers $\{1, 2, \ldots, n\}$. To present a countable set, which might or might not be finite, where the number of elements does not matter, we use curly brackets with a subscript denoting the first index of the set. For example, $\{u_i\}_{i=1}$ represents the set $u_1, u_2, \ldots$. For finite sets, we might add a superscript to present the size of the set. If the first index is clear from the context, then we might omit the assignment. We use a colon inside curly brackets to specify a set of elements satisfying a condition, i.e., for sets $A, B$, the notation $\{a : a \in A, a \in B\}$ equals $A \cap B$. Curly brackets without subscripts or conditions refer to singletons. For example, for a given integer $i$, the set $\{u_i\}$ is the set that contains only the element $u_i$. The size of a set $A$ is denoted by $|A|$. For an integer $i$, we denote by $\mathbf{1}_i$ the vector consisting of one at the $i$th coordinate and zero elsewhere. The char $|$ symbolizes a restriction, for example $x|_y$, is the restriction of the 'entity $x$' to '$y$'. The particular behavior of the restriction would change depending on the target type.

When not otherwise mentioned, we consider quantum states over qubits, each lying in a two-dimensional Hilbert space $\mathcal{H}_2$, and denote by $\mathcal{H}_{2^n}$ the Hilbert space of an $n$-qubit system. The $\otimes$ operator stands for tensor product, for example: $\mathcal{H}_{2^n} = \mathcal{H}_2^{\otimes n}$. The space of linear operators on the Hilbert space is denoted by $L(\mathcal{H})$. Pure quantum states and their dual presentations are denoted by $|\psi\rangle, \langle\psi|$, and in the matrix representation, we use $|\psi\rangle\langle\psi|$ to denote its density matrix. We will use $\rho$ to denote a mixed state. The action of an operator $A$ on a mixed state is written as $A \circ \rho$. For example, if $A$ is a unitary operator, then $A \circ \rho = A\rho A^\dagger$. The letters, $X$ and $Z$, will usually denote the single qubit $X$ and $Z$ Pauli operators. Yet, where the Pauli matrices are out of context, we use these letters for other variables. The Pauli group itself, over $n$ qubits, is denoted by $\mathcal{P}^{\otimes n}$, and when the number of qubits is either clear or doesn't matter, we omit the superscript. For a Pauli $P \in \mathcal{P}$, we denote by $X(P)$ and $Z(P)$ the $X$- and the $Z$-components of $P$ such that $P = X(P)Z(P)$. The gates 'Controlled Not' and 'Controlled Z' are denoted by **CX** and **CZ**, and the gates Hadamard, S, and T are denoted by:

$$\mathbf{H} = \frac{1}{\sqrt{2}}\begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix}, \mathbf{S} = \begin{bmatrix} 1 & 0 \\ 0 & i \end{bmatrix}, \mathbf{T} = \begin{bmatrix} 1 & 0 \\ 0 & e^{i\frac{\pi}{4}} \end{bmatrix}$$

For a quantum gate $U$, we denote by $|U\rangle$ the resource state that can be used to simulate $U$. Notice that, in general, the resource state is not unique. In this work, we address specific states that will be discussed later. The function $\mathbf{Pr}[\,\cdot\,]$ is the probability function. In the language of groups, for a group $\mathcal{G}$ and elements $g_1, \ldots, g_l$, we denote by $\langle\{g_1, \ldots, g_l\}\rangle$ the subgroup generated by $g_1, \ldots, g_l$.

Throughout the paper, we will deal with CSS codes [CS96], [Ste96]. For a linear subspace $A$, we use $|A\rangle$ to denote the uniform superposition over the vectors in $A$. A CSS code will usually be denoted by the pairs $\mathcal{C}_X, \mathcal{C}_Z$ such that the $Z$-stabilizers

match the codewords of $\mathcal{C}_Z^\perp$, and the logical codewords in the computational basis are the elements in $\mathcal{C}_X/\mathcal{C}_Z^\perp$. The logical zero codeword is $\left|\mathcal{C}_Z^\perp\right\rangle$. We denote the equivalence relation up to $Z$-stabilizer addition by $\sim_{\mathcal{C}_X}$. Namely, for $x_1, x_2 \in \mathbb{F}_2^n$, we have $x_1 \sim_{\mathcal{C}_X} x_2$ if $x_1 + x_2 \in \mathcal{C}_Z^\perp$. By the same way we define $\sim_{\mathcal{C}_Z}$.

**The Computation Model.** Informally, a quantum circuit is a placement of a collection of quantum gates, taken from a finite set, at different space-time locations. Each such location records when the gate is applied and on which qubits it acts. Formally:

**Definition 3.1** (Quantum Circuit)**.** *A* space-time location *is a pair $l = (t, S)$, where $t$ is a time coordinate and $S = (s_1, \ldots, s_\Delta)$ is an ordered tuple of qubit indices. For a finite collection of quantum gates*

$$\mathcal{G} \subset \left\{ g \colon L(\mathcal{H}_2^{\otimes\Delta}) \to L(\mathcal{H}_2^{\otimes\Delta}) \right\},$$

*and integers $w, d \in \mathbb{N}$, a quantum circuit $C$ of depth $d$ and width $w$ is a collection of tuples*

$$C = \{u_i = (g_i, l_i)\}_i,$$

*where each $g_i \in \mathcal{G}$ and each location $l_i = (l_{i,1}, l_{i,2})$ belongs to $[d] \times [w]^\Delta$. We call the tuples $u_i$ the gates of $C$. They must satisfy the following compatibility condition: if two gates have the same time coordinate, then their supports are disjoint. Namely, for $u_i = (g_i, l_i), u_j = (g_j, l_j) \in C$, the equality $l_{i,1} = l_{j,1}$ implies that the sets of qubit indices appearing in $l_{i,2}$ and $l_{j,2}$ are disjoint. We denote by*

$$\mathrm{Loc}(C) := \{l_i : u_i = (g_i, l_i) \in C\}$$

*the set of locations occupied by the gates of $C$. We define the $t$-layer of $C$ to be its restriction to gates at time $t$:*

$$C|_t := \{u_i = (g_i, l_i) \colon u_i \in C \text{ and } l_{i,1} = t\}.$$

Later, we will restrict $\mathcal{G}$ to contain $\mathbf{X}, \mathbf{Z}, \mathbf{CX}, \mathbf{H}, \mathbf{S}, \mathbf{T}$, and measurements. To define the action of a quantum circuit $C$ on a given mixed state, we first associate $C$ with a directed acyclic graph.

**Definition 3.2** (Associated Computation DAG)**.** *Let $C = \{u_i\}_i$ be a quantum circuit with depth $d$ and width $w$. We define the associated computation DAG of $C$, denoted by $\pi_C$, to be the directed acyclic graph $\pi_C = (\mathcal{U}, E)$ as follows:*

1. *The vertex set is the gate set of $C$, namely $\mathcal{U} = \{u_i\}_i$.*
2. *For $u_i = (g_i, l_i)$ and $u_j = (g_j, l_j)$, there is a directed edge $(u_i, u_j) \in E$ if and only if $j$ is one of the minimizers of*

$$\left\{ l_{k,1} : (g_k, l_k) \in \mathcal{U},\ l_{k,1} > l_{i,1},\ l_{k,2} \cap l_{i,2} \neq \emptyset \right\}.$$

*Equivalently, $u_j$ is one of the earliest later gates whose support intersects the support of $u_i$. There may be more than one such minimizer, so the out-degree may exceed one.*

*Suppose that $J = (j_1, j_2, \ldots, j_k)$ is an ordering of the gate indices that agrees with a topological order induced by $\pi_C$. Then we define the associated partial circuits $C|_J = \{C|_{J,\to i}\}_{i=1}^k$ by*

1. *$C|_{J,\to 1} = \{u_{j_1}\}$.*
2. *For $1 \leq i < k$, set $C|_{J,\to i+1} = C|_{J,\to i} \cup \{u_{j_{i+1}}\}$.*

*We call $C|_{J,\to i}$ the partial computation circuit up to step $i$. When the order itself does not play a role, except for being time-respecting (namely, a gate $u$ that is applied before gate $u'$ has a lower step than $u'$'s step in $J$), we will omit $J$ from the subscript and briefly write $C|_{\to i}$ to describe a partial circuit up to that step.*

**Definition 3.3.** *Let $\rho$ be a density matrix over $w$ qubits, and let $C = \{u_i\}_{i=1}$ be a quantum circuit with depth $d$ and width $w$. For any density matrix $\sigma$, quantum gate $g \in \mathcal{G}$, and location $l$, the application of the gate-location tuple $(g, l)$ on $\sigma$, denoted by $(g, l) \circ \sigma$, is the application of $g$ on $\sigma$ where wires are ordered such that the first qubit in the input to $g$ is $l_{2,1}$, the second is $l_{2,2}$, and so on. The result of the application of $C$ on $\rho$, denoted by $C \circ \rho$, is given by iterative applications of the gates $\{u_i\}_{i=1}$ on $\rho$, according to a topological order induced by $\pi_C$.*

*We say that $\rho_1, \rho_2, \ldots, \rho_k$ is a computation prefix if $\rho_1 = \rho$ and $\rho_{i+1} = u'_i \circ \rho_i$, where $\{u'_i\}_{i=1}$ is a prefix of a topological ordering of $\{u_i\}_{i=1}$. If $\{u'_i\}_{i=1}$ contains all the gates in $\{u_i\}_{i=1}$, then we call $\rho_1, \rho_2, \ldots, \rho_k$ a running.*

For a quantum circuit $C$, we would like to discuss its action in the presence of different outcomes of faults. The following definition encodes the running in the presence of a specific set of faults $\mathcal{E}$.

**Definition 3.4** ($C$ subjected to $\mathcal{E}$ every $m$ computational layers)**.** *Let $C = \{u_i\}_i$ be a quantum circuit with depth $d$ and width $w$, let $m \in \mathbb{N}$, and set*

$$d_m := \left\lceil \frac{d}{m} \right\rceil .$$

*Let $\mathcal{L} \subset [d_m] \times [w]$ be a set of locations, and let $\mathcal{E}$ be a quantum circuit, such $Loc(\mathcal{E}) = \mathcal{L}$. We name $\mathcal{E}$ subsets of faults, and we name the layers of $\mathcal{E}$ fault layers. The circuit $C$ subjected to $\mathcal{E}$ every $m$ computational layers, denoted by $C[\mathcal{E}]_m$, is obtained by setting the first layer to be the first layer of $\mathcal{E}$, then placing in order the layers of $C$ and inserting one fault layer after every $m$ consecutive $C$'s layers. Thus the second fault layer is inserted after the layers $1, \ldots, m$ of $C$, the third is inserted after the layers $m+1, \ldots, 2m$ of $C$, and so on. Concretely, each gate $u_i = (g_i, (t_i, S_i))$ of $C$ is moved to the time coordinate*

$$t_i + \left\lfloor \frac{t_i - 1}{m} \right\rfloor ,$$

*while each fault gate* $(g,(t,S)) \in \mathcal{E}$ *is placed at time coordinate*

$$t(m+1).$$

*When* $m = 1$*, the gates occupy the even time coordinates, and the fault layers occupy the odd time coordinates. When the subscript parameter is omitted, we mean that the noise layers are injected between any two logical layers, and the logical layers are clear from the context. We denote the associated computation DAG of* $C[\mathcal{E}]_m$ *by* $\pi_{C[\mathcal{E}]}$*.*

**Remark 3.5.** *Formally, a fault circuit is just a particular quantum circuit whose gates are interpreted as faults rather than as computational operations. Thus the distinction between a quantum circuit and a fault circuit is semantic rather than structural: both are circuits in the sense of Definition 3.1, but they play different roles in the analysis.*

**Example 3.6.** *When* $m = 3$*, the 'computational' layers are sent to the times*

$$2, 3, 4, 6, 7, 8, 10, 11, 12, \ldots,$$

*while the fault layers are sent to the times*

$$1, 5, 9, 13, \ldots.$$

Later, all the quantum registers will be encoded via stabilizer codes. Then, following the common approach in the literature, we define the fault layers to end with stabilizer measurements, thereby forcing the faults to be Paulis (see [Got97]). Hence, we confine ourselves to noise channels of only this type.

**Definition 3.7** (Noise channel and local stochastic noise channel)**.** *A noise channel* $\mathcal{N}_{\mathcal{E}}$ *is a distribution over sets of faults and their locations. Let* $p \in (0,1)$*, we say that the noise channel* $\mathcal{N}_{\mathcal{E}}$ *is local stochastic with rate* $p$ *if for every finite set of locations* $S \subset \mathbb{N} \times \mathbb{N}$*,*

$$\mathbf{Pr}_{\mathcal{E}\sim\mathcal{N}_{\mathcal{E}}}\left[S \subset \mathrm{Loc}(\mathcal{E})\right] \leq p^{|S|}.$$

*Through this work, the sampled faults will be assumed to be Pauli.*

So, $N_{\mathcal{E}}$ defines a probability space. The set of faults $\mathcal{E}$ is an atomic outcome, and for a given circuit $C$, the subjected circuit $C[\mathcal{E}]$ is a random variable. Equipped with this notation, we are allowed to assume having constant depth cycles that don't observe faults. The following definition considers the effective circuit when the running is restricted such that the outcomes of the measurement are fixed.

**Definition 3.8.** *Let* $C$ *be a quantum circuit that contains* $l$ *measurements. For possible outcomes* $\alpha \in \mathbb{F}_2^l$*, let* $C[,\alpha]$ *be the circuit obtained by conditioning that* $\alpha_1, .., \alpha_l$ *were measured. We extend the notation for the subjected circuit by denoting* $C[\mathcal{E},\alpha]$ *as the subjected circuit where the measurements are assumed to outcome* $\alpha_1, .., \alpha_l$*.*

There might be multiple different ways to present a conditioned circuit with a collection of gates and their locations. Since we would like to keep the step-order invariant to a conditioning of the measurement outcome, we choose a representation that substitutes the original gates with gates that act on the same location. The following remark explains how to do that explicitly.

**Remark 3.9.** *Consider the presentation of a conditioned circuit as a subset of gates acting on locations. For an outcome $\alpha \in \mathbb{F}_2^{(\cdot)}$ for which a conditional gate (for example, a* **CCZ***, where the control bits are conditioned on measurement outcomes) in the original circuit $C$ is mapped to a Pauli in $C[,\alpha]$, we substitute this gate with the Pauli on the target tensored with identity acting on the control locations. Thus, the order of the steps, the locations of each gate, and the computation graph of $C[,\alpha]$ are the same as for $C$ (and independent of the outcomes). We summarize this by briefly saying that the locations are invariant to the conditioning of measurements.*

In our case, the conditioned circuit $C[\mathcal{E},\alpha]$ is a Clifford + projections circuit; in particular, it induces a 'structured trajectory' tracking on the accumulated error. This brings us to define, for a given set of faults $\mathcal{E}$ and outcomes $\alpha$, a 'propagation' that describes the evolution of the faults through the circuit.

**Definition 3.10** (Propagation)**.** *Let $C[\mathcal{E}]$ be a subjected quantum circuit at depth $\mu$, and let $\alpha \in \mathbb{F}_2^{(\cdot)}$ be a possible outcome vector for $C[\mathcal{E}]$. Suppose that $C$ is a Clifford+measurements circuit, so $C[\mathcal{E},\alpha]$ is a Clifford + projections circuit. We define the propagation through the conditioned circuit $C[\mathcal{E},\alpha]$ to be the tuple $(\mathbf{P},\mathbf{a})$ such that $\mathbf{P}$ consists of $\mu+1$ Paulis $\mathbf{P} := P_1,\ldots,P_{\mu+1}$ and $\mathbf{a}$ consists of $\mu+1$ outcome measurements $\mathbf{a} := \alpha^1,\alpha^2,\ldots,\alpha^{\mu+1}$ satisfying that $P_1 = \mathcal{E}|_1, \alpha^1 = \alpha$ and for any $i \in [2,\mu+1]$:*

$$P_i C[,\alpha^i]|_{\to i} = C[\mathcal{E},\alpha]|_i P_{i-1} C[,\alpha^{i-1}]|_{\to i-1} = C[\mathcal{E},\alpha]|_{\to i}$$

*We extend the notation to step-propagation by considering the propagation of the circuit obtained from $C[\mathcal{E},\alpha]$ by flattening the circuit such that each gate is applied at the time that equals its step.*

**Remark 3.11.** *Notice that, for two different measurement outcomes $\alpha,\alpha'$, the conditioned $C[,\alpha]$ and $C[,\alpha']$ might differ also by their Clifford gates (and not only by the projections).*

# 4 The $(d,d')$-Dimensional Toric Code

The main error correction code that we will use is the Toric code invented by Kitaev. In the 2D case, the code is obtained by taking a Toric, tiling it with squares, setting qubits on the edges, and checks as follows: For every vertex, the parity of the qubits adjoining it is even, and for any square, the parity of the qubits lying on its sides, in the phase basis, is even. A high-dimensional version can be obtained by taking a high-dimensional Toric, encoded as a cubical complex, and then setting the $X$-checks,

the qubits, and the $Z$-checks to be faces at sequenced dimensions. Throughout this paper, qubits will be set on $d'$-dimensional faces, and the $X$-checks and $Z$-checks on the $d' \mp 1$ dimensional faces. For a review, we refer to [Kit97], [Den+02].

For defining a decoder and proving its 'correctness,' we will have to overload notation. We derive the Toric complex from the skeleton of the Cayley graph of the cyclic group, using the generating subset as a collection of positive directions. The $\theta_{\mathbf{v},\mathbf{S'}}$ encodes a face, one vertex $v$ that serves as its 'root' and a subset of directions $S'$. Formally:

**Definition 4.1** ($d$-Dimensional Toric Complex)**.** *For integers $d$ and $n$, denote the group resulting from the $d$-directed power of the cyclic group of order $n$ by $\mathcal{G}_n^d = \mathbb{Z}_n^{\times d}$, and denote the standard generating set of $\mathcal{G}_n^d$ by $S = \{1_i \colon i \in [d]\}$. We define the $d$-dimensional Toric complex to be the hypergraph obtained from the Cayley graph $Cay(\mathcal{G}_n^d, S)$ by taking its vertices as the 0-faces and for any $i \in [d]$ we define the $i$-faces as follow: First, for a vertex $v \in \mathcal{G}_n^d$ and for a subset of generators $S' \subset S$ of size $|S'| = i$, the $i$-face rooted at $v$ and spanned by $S'$, denoted by $\theta_{v,S'}$, is:*

$$\theta_{v,S'} := \bigcup_{I \subset S'} \left\{ \left( \prod_{g \in I} g \right) v \right\}$$

*The $i$-faces of the complex are the collection of all the possible rooted spanned $i$-faces induced by $Cay(\mathcal{G}_n^d)$. We will denote them by $\mathcal{F}_i$. Additionally, let us define the multiplication of the generators subset $S' \subset S$ by a vertex $v \in V(\mathcal{G})$ as follows:*

$$S'v = \left( \prod_{g \in S'} g' \right) v$$

*Finally, we name $n$ and $d$, the side length and the dimension of the complex.*

Next, we formalize binary assignments on the Toric complex and introduce boundary operators. These boundary operators are the same as standard boundary operators in the chain complex formalism.

**Definition 4.2** (Assignments on a Toric complex)**.** *Let $\mathcal{T}$ be a $d$-dimensional Toric complex. For each $i$, the set of $i$-faces induces a vector space $\mathbb{F}_2^{|\mathcal{F}_i|}$. An element $z \in \mathbb{F}_2^{|\mathcal{F}_i|}$ is called an assignment on the $i$-faces of $\mathcal{T}$.*

*For a vertex $v$ and a subset of generators $S' \subset S$ of size $|S'| = i$, let $\theta_{\mathbf{v},\mathbf{S'}}$ denote the standard basis vector corresponding to the $i$-face $\theta_{v,S'}$. Thus the family*

$$\left\{ \theta_{\mathbf{v},\mathbf{S'}} : v \in \mathcal{F}_0,\ S' \subset S,\ |S'| = i \right\}$$

*is the standard coordinate basis of $\mathbb{F}_2^{|\mathcal{F}_i|}$.*

*Let $z$ be an assignment on the $i$-faces. Let $v_1, \ldots, v_k \in \mathcal{F}_0$ and $S'_1, \ldots, S'_k \subset S$ be such that $\theta_{v_1,S'_1}, \theta_{v_2,S'_2}, \ldots, \theta_{v_k,S'_k}$ are precisely the $i$-faces in the support of $z$, namely:*

$$z = \sum_{i=1}^{k} \theta_{\mathbf{v_i},\mathbf{S'_i}}$$

*We refer to* $\theta_{v_1,S'_1}, \theta_{v_2,S'_2}, \ldots, \theta_{v_k,S'_k}$ *as the collection of faces that form* $z$*, or briefly, the faces form* $z$*. For* $i > 0$*, we define the linear map* $\partial^- : \mathbb{F}_2^{|\mathcal{F}_i|} \to \mathbb{F}_2^{|\mathcal{F}_{i-1}|}$ *such that*

$$\partial^- \theta_{\mathbf{v},\mathbf{S'}} := \sum_{g \in S'} \left( \theta_{\mathbf{v},\mathbf{S'/g}} + \theta_{\mathbf{gv},\mathbf{S'/g}} \right)$$

*For* $i < d$*, we define the linear map* $\partial^+ : \mathbb{F}_2^{|\mathcal{F}_i|} \to \mathbb{F}_2^{|\mathcal{F}_{i+1}|}$ *such that*

$$\partial^+ \theta_{\mathbf{v},\mathbf{S'}} := \sum_{g \in S/S'} \left( \theta_{\mathbf{v},\mathbf{S'\cup g}} + \theta_{\mathbf{g^{-1}v},\mathbf{S'\cup g}} \right)$$

*We define the restriction of* $z$ *at vertex* $v$ *to be the linear map* $|_v \colon \mathbb{F}_2^{|\mathcal{F}_i|} \to \mathbb{F}_2^{|\mathcal{F}_i|}$ *such that:*

$$\theta_{\mathbf{u},\mathbf{S'}}|_v := \begin{cases} \theta_{\mathbf{u},\mathbf{S'}} & v \in \theta_{u,S'} \\ 0 & else \end{cases}$$

*We refer to the faces rooted at* $v$ *as the positive faces of* $v$*, and define the positive restriction at vertex* $v$ *to be the linear map* $|_{v+} \colon \mathbb{F}_2^{|\mathcal{F}_i|} \to \mathbb{F}_2^{|\mathcal{F}_i|}$ *such that:*

$$\theta_{\mathbf{u},\mathbf{S'}}|_{v+} := \begin{cases} \theta_{\mathbf{u},\mathbf{S'}} & u = v \\ 0 & else \end{cases}$$

*Two* $i$*th dimensional faces will be said to be connected if their intersection is* $i-1$*th dimensional face. So, an assignment* $z$ *is connected if the graph that is induced by taking the faces that support* $z$ *as vertices and defining the edges to be the adjacency relation between them is connected. We define the connected components of* $z$ *to be its subsets such that each of them is a connected assignment. For a* $j$*-face* $f$*, we say that* $f \in z$ *if* $z$ *has a support on* $\theta_{\mathbf{v},\mathbf{S'}}$ *such that* $f \in \theta_{v,S'}$*. Consider an assignment* $z \in \mathbb{F}_2^{\mathcal{F}_i}$ *and a vertex* $v \in \mathcal{G}_n^d$*. We say that* $z$ *is a rooted assignment at vertex* $v$ *if there are subsets* $S'_1, \ldots, S'_k \subset S^{\times k}$ *such that each of* $S'_j$ *is at size* $i$ *and* $z$ *is decomposed as:*

$$z = \sum_{j}^{k} \theta_{\mathbf{v},\mathbf{S'_j}}$$

*Put differently,* $z$ *is the result of taking a collection of* $i$*-faces that are rooted at* $v$*.*

We are ready to give a formal definition of the $(d, d')$-Toric code.

**Definition 4.3** ($(d, d')$ Toric Code)**.** *Let* $d, d'$ *be integers such that* $1 \leq d' \leq d$*. For any integer* $n$*, we construct the* $n$*th instance of the quantum code family* $(d, d')$ *Toric Code as follows: Let* $G = (\mathcal{F}_0, \ldots, \mathcal{F}_d)$ *be the* $d$*-dimensional Toric complex obtained from* $\mathcal{G}_n^d$ *as defined in Definition 4.1. We associate the (q)bits with the* $\mathcal{F}_{d'}$*, the* $X$*-checks with the* $\mathcal{F}_{d'-1}$*, and the* $Z$*-checks with the* $\mathcal{F}_{d'+1}$*. An* $X$*-check,* $c_x$*, is satisfied if the parity of (q)bits set on the* $d'$*-face containing* $c_x$ *is even. Similarly, a* $Z$*-check,* $c_z$*, is satisfied if the parity, in the Hadamard basis, of the (q)bits set on the* $d'$*-faces contained in* $c_z$ *is even.*

We argue that the $(d, d')$-Toric code is indeed a CSS, and prove that by showing that boundary operators $\partial^{\pm} : \mathbb{F}_2^{|\mathcal{F}_i|} \to \mathbb{F}_2^{|\mathcal{F}_{i\pm1}|}$ induce a chain complex.

**Claim 4.4** (CSS structure)**.** *The $(d, d')$-Toric code is a CSS code.*

*Proof.* We will show that $\mathbb{F}_2^{|\mathcal{F}_i|} \xrightarrow{\partial^{\pm}} \mathbb{F}_2^{|\mathcal{F}_{i\pm1}|}$ are a chain complex and its dual chain. First, we show that $(\partial^+)^\top = \partial^-$. Consider vertices $v, u \in V$ and two generator subsets $A, B \subset S$. Consider the basis elements defined by them: $\theta_{\mathbf{v},\mathbf{A}}$ and $\theta_{\mathbf{u},\mathbf{B}}$. Suppose that:

$$(\partial^+ \theta_{\mathbf{v},\mathbf{A}})\theta_{\mathbf{u},\mathbf{B}} = 1$$

Means that there exists $g \notin A$ such that $A \cup \{g\} = B$ and either $v = u$ or $g^{-1}v = u$. But that is equivalent to saying that there is $g \in B$ such that $B \setminus \{g\} = A$ and either $v = u$ or $v = g^{-1}u$. In other words:

$$\begin{aligned} &(\partial^+ \theta_{\mathbf{v},\mathbf{A}})\theta_{\mathbf{u},\mathbf{B}} = \theta_{\mathbf{v},\mathbf{A}}(\partial^- \theta_{\mathbf{u},\mathbf{B}}) \\ \Rightarrow &\left(\partial^+\right)^\top = \partial^- \end{aligned}$$

So it's left to show that the boundary of a boundary is zero. Consider a basis vector $\theta_{\mathbf{v},\mathbf{S}'}$:

$$\begin{aligned} \partial^-\left(\partial^- \theta_{\mathbf{v},\mathbf{S}'}\right) &= \partial^- \left( \sum_{g \in S'} \theta_{\mathbf{v},\mathbf{S}'/\mathbf{g}} + \sum_{g \in S'} \theta_{\mathbf{gv},\mathbf{S}'/\mathbf{g}} \right) \\ &= \sum_{\substack{g', g \in S' \\ g' \neq g}} \left( \theta_{\mathbf{v},\mathbf{S}'/\{\mathbf{g},\mathbf{g}'\}} + \theta_{\mathbf{g}'\mathbf{v},\mathbf{S}'/\{\mathbf{g},\mathbf{g}'\}} + \theta_{\mathbf{gv},\mathbf{S}'/\{\mathbf{g},\mathbf{g}'\}} + \theta_{\mathbf{g}'\mathbf{gv},\mathbf{S}'/\{\mathbf{g},\mathbf{g}'\}} \right) \\ &= 0 \end{aligned}$$

Where we used that the term in the closure is invariant to sweeping between $g$ and $g'$, and therefore any term in the sum appears twice. Similarly:

$$\begin{aligned} \partial^+\left(\partial^+ \theta_{\mathbf{v},\mathbf{S}'}\right) &= \partial^+ \left( \sum_{g \in S/S'} \theta_{\mathbf{v},\mathbf{S}' \cup \mathbf{g}} + \sum_{g \in S/S'} \theta_{\mathbf{g}^{-1}\mathbf{v},\mathbf{S}' \cup \mathbf{g}} \right) \\ &= \sum_{\substack{g', g \in S/S' \\ g' \neq g}} \left( \theta_{\mathbf{v},\mathbf{S}' \cup \{\mathbf{g},\mathbf{g}'\}} + \theta_{\mathbf{g}'^{-1}\mathbf{v},\mathbf{S}' \cup \{\mathbf{g},\mathbf{g}'\}} + \theta_{\mathbf{g}^{-1}\mathbf{v},\mathbf{S}' \cup \{\mathbf{g},\mathbf{g}'\}} + \theta_{\mathbf{g}'^{-1}\mathbf{g}^{-1}\mathbf{v},\mathbf{S}' \cup \{\mathbf{g},\mathbf{g}'\}} \right) \\ &= 0 \end{aligned}$$

The conditions $(\partial^{\pm})^{\circ 2} = 0$ imply that $\mathbb{F}_2^{|\mathcal{F}_i|} \xrightarrow{\partial^{\pm}} \mathbb{F}_2^{|\mathcal{F}_{i\pm1}|}$ are chain complexes. Therefore, for any $d'$, every $d' - 1$ face and every $d' + 1$ face overlap on an even number of $d'$-faces, so the corresponding $X$- and $Z$-checks commute. This is exactly the CSS condition. □

The fact that $\partial^{\pm} : \mathbb{F}_2^{|\mathcal{F}_i|} \to \mathbb{F}_2^{|\mathcal{F}_{i\pm1}|}$ induces a chain complex motivates referring to the collection of qubits/checks/vertices as chains of various dimensions. Next, we give a definition of the 'positive' vertices that a vertex $v$ sees, which lie on a chain $z$.

**Definition 4.5** (Positive Neighborhood)**.** *For a vertex $v$ and a chain $z$, we use the notation $\boldsymbol{Str}_{0+}(v,z)$ to denote the vertices in $z$ that are connected to $v$ through a stepping via generator, namely all the vertices that support a face in $z$ of the form $gv$ for some $g \in S$. We think of $\boldsymbol{Str}_{0+}(v,z)$ as the positive neighborhood of $v$ in $z$.*

## 4.1 Sweep Rule

The sweep-rule is the core of our construction. A decoding cycle begins with each vertex $v$ reading the syndrome on the $X$-checks rooted at $v$ (the positive $X$-checks of $v$) and, based on what it sees, applying a Pauli correction supported on the qubits rooted at $v$. The sweep-rule defines the correction to be over the positive qubits such that it will turn off the positive syndrome. It's not hard to see that for the $(2,2)$-Toric complex, the Toom's and the sweep rules are the same. Compared to other correction cycles on topological codes, the main advantage of the sweep is that it is independent of time. The invention of the sweep-rule is attributed to Aleksander Kubica and John Preskill [KP19]. Here we extend their work to cubical complexes.

**Definition 4.6** (Sweep Rule)**.** *Let $\sigma$ be a $d'-1$-dimensional chain. The sweep rule decoding procedure at a vertex $v \in \mathcal{G}_n^d$ is defined as follows: Measure the checks rooted at $v$ and look for a rooted chain $\tilde{z}$ at $v$ such that:*

1. *The vertices in $\tilde{z}$ are contained in the vertices of $\sigma$, namely: $\mathbf{Str}_{0+}(v,\tilde{z}) \subset \mathbf{Str}_{0+}(v,\sigma)$*
2. *The boundary of $\tilde{z}$ agrees with $\sigma$ on the checks rooted at $v$, namely: $(\partial^- \tilde{z})|_{v+} = \sigma|_{v+}$.*

*If such an assignment exists, flip $\tilde{z}$.*

The first property is analogous to the second property of 'causal structure' defined in [KP19][1]. There, they conjectured that vertices that see a syndrome only on their positive checks can suggest a correction that is 'supported' on the vertices of their unsatisfied checks. For lower dimensions, they mentioned that the property can be easily checked. Here, we provide a proof for any dimensions where the face dimension is greater than one. We use the language of cubical complexes; however, since the 'positive' local view at a vertex is identical for both cubical and simplicial complexes, generalizing the proof for simplicial complexes is a matter of adjusting notations. By that, we affirmatively answer their conjecture. Moreover, the proof will provide us with an algorithm to find $\tilde{z}$, which is significantly better than running all options.

**Claim 4.7.** *Consider a nontrivial $d'-1$-dimensional chain $\sigma$. If there is a $d'$-dimensional chain $z$ that is rooted at $v$ and whose boundary agrees with $\sigma|_{v+}$, then there is a $d'$-dimensional chain $\tilde{z}$ rooted at $v$ that satisfies the sweep-rule conditions.*

*Proof.* We prove it by induction on $d'$. Without loss of generality, we can assume that $\sigma$ has support only over the positive faces of $v$, namely $\sigma|_{v+} = \sigma$.

[1] In their language: $\diamondsuit(\tilde{z}) = \diamondsuit(\sigma|_v)$.

1. Base. Consider $d' = 2$ and let $d$ be any integer equal to or greater than 3. We argue that the support size of $\sigma$ has to be even. To see that, denote the faces in $z$ by $\theta_{\mathbf{v},\mathbf{S}'_\mathbf{i}}$, where $S'_i = \{g_{i,1}, g_{i,2}\}$. Using the fact that $\sigma$ is the boundary of $z$ at $v$, we have:

$$\sigma = (\partial^-(z))|_v = \sum_{\theta_{\mathbf{v},\mathbf{S}'} \in z} \sum_{g \in S'} \theta_{\mathbf{v},\mathbf{S}'/\mathbf{g}} = \sum_i \theta_{\mathbf{v},\{\mathbf{g_{i,1}}\}} + \theta_{\mathbf{v},\{\mathbf{g_{i,2}}\}}$$

So the number of terms in the sum is even, and since a term is zeroed out only if it appears an even number of times, we have that after excluding the vanishing terms, $\sigma$ has an even number of faces. Since the number of faces is even, there is a perfect matching between them. It's easy to see that the 2-chain $\tilde{z}$, whose each face corresponds to the union of the two edges in a match, satisfies the sweep-rule conditions.

2. Assume the correctness of the claim for every face dimension lower than $d'$. Now for a face dimension $d'$ and an arbitrary generator $g \in S$ such $gv \in \sigma$, divide $\sigma$ into a sum of two chains, the first contain the faces of $\sigma$ that supported on the vertex $gv$ where the second contains the compliment. Denote them by $\sigma|_{gv}$ and $\sigma|_{/gv}$, so $\sigma = \sigma|_{gv} + \sigma|_{/gv}$.

   Now let $\sigma^*$ the chain obtained from $\sigma|_{gv}$ by removing from any face of it the vertex $gv$, thus $\sigma^*$ is a $d' - 2$-dimensional chain. Moreover, let $z^*$ be the $d' - 1$-dimensional chain complex obtained from $z|_{gv}$ by excluding $gv$ from its faces. Observes that

$$(\partial^- z^*)|_v = \sum_{\theta_{\mathbf{v},\mathbf{S}'} \in z|_{gv}} \sum_{g' \in S'/g} \theta_{\mathbf{v},\mathbf{S}'/\{\mathbf{g},\mathbf{g}'\}} = \sum_{\theta_{\mathbf{v},\mathbf{S}'} \in (\partial^- z)|_{gv}} \theta_{\mathbf{v},\mathbf{S}'/\{\mathbf{g}\}} = \sigma^*$$

   Thus, by the induction assumption, there is a $d' - 1$-dimensional chain $\tilde{z}^*$ such that:

   (a) $\mathbf{Str}_{0+}(v, \tilde{z}^*) \subset \mathbf{Str}_{0+}(v, \sigma^*)$

   (b) $(\partial^- \tilde{z}^*)|_{v+} = \sigma^*|_{v+}$

   The first condition implies that $gv \notin \tilde{z}^*$. Hence, we can define the $d'$-dimensional chain $\tilde{z}$ by adding the vertex $gv$ to each face of $\tilde{z}^*$. From the second it follows that:

$$\begin{aligned}(\partial^- \tilde{z})|_v &= \big(\partial^-\big(\sum_{\theta_{\mathbf{v},\mathbf{S}'} \in \tilde{z}^*} \theta_{\mathbf{v},\mathbf{S}' \cup \{\mathbf{g}\}}\big)\big)|_v = \sum_{\theta_{\mathbf{v},\mathbf{S}'} \in \tilde{z}^*} \big(\sum_{g' \in S'/g} \theta_{\mathbf{v},\mathbf{S}'/\{\mathbf{g}'\} \cup \{\mathbf{g}\}}\big) + \theta_{\mathbf{v},\mathbf{S}'} \\ &= \sum_{\theta_{\mathbf{v},\mathbf{S}'} \in (\partial^- \tilde{z}^*)|_v} \theta_{\mathbf{v},\mathbf{S}' \cup \{\mathbf{g}\}} + \tilde{z}^* = \sigma|_{gv} + \tilde{z}^*\end{aligned}$$

   Therefore,

$$\begin{aligned}\sigma + (\partial^- \tilde{z})|_v &= \sigma|_{gv} + \sigma|_{/gv} + \sigma|_{gv} + \tilde{z}^* \\ &= \sigma|_{/gv} + \tilde{z}^*\end{aligned}$$

Thus we reduce the question to handle the $d'-1$-dimensional chain $\sigma + (\partial^- \tilde{z})|_v$. However, since $gv \notin \sigma + (\partial^- \tilde{z})|_v$ it follows that:

$$|\mathbf{Str}_{0+}(v, \sigma + (\partial^- \tilde{z})|_v)| \leq |\mathbf{Str}_{0+}(v, \sigma)| - 1$$

Thus, we can repeat recursively until the resulting $d'-1$ chain is 'supported' on fewer than $d'$ vertices. In that case, the chain must be trivial.

□

The algorithm given in the proof of Claim 4.7 for finding $\tilde{z}$ is as follows: given $\sigma$, pick a $g \in S$ such that $gv \in \sigma$. Then, define $\sigma^*$ by removing $gv$ from each face of $\sigma|_{gv}$. Let $\tilde{z}^*$ be the result of the recursive call on $\sigma^*$, and return '$\tilde{z}^* \cup \{gv\}$' plus the recursive call on $\sigma|_{/gv} + \tilde{z}^*$.

We stop the recursion whenever either $d' = 2$ or $|\mathbf{Str}_{0+}(v, \sigma)| < d'$. The work in each recursion step consists of decomposing $\sigma$ into $\sigma|_{gv}$ and $\sigma|_{/gv}$ and summing $\binom{d}{d'}$-length vectors. We summarize by introducing the following claim which gives the running time of the algorithm in the RAM computation model.

**Claim 4.8.** *Let $T(d, d', k) : \cdot \to \mathbb{R}$ be the upper bound function for the running time of the algorithm given in Claim 4.7, where $d$ is the dimension of the skeleton, $d'$ is the face dimension, and $k$ is the number of vertices supporting the local view, namely $k = |\mathbf{Str}_{0+}(v, \sigma)|$. Then:*

$$T(k, d') = O\big(2^k \binom{d}{d'}\big)$$

*Proof.* In each recursive call, the vertex support of $\sigma$ matches a different subset of the vertices in $\mathbf{Str}_{0+}(v, \sigma)$; thus, the number of recursive calls is at most the number of subsets, namely $2^k$. The decomposition of $\sigma$ into $\sigma|_{gv}$ and $\sigma|_{/gv}$, and the summation $\sigma|_{/gv} + \tilde{z}^*$ are linear in the vector's length, namely linear in $\binom{d}{d'}$. So we bound the total work by the number of recursive steps multiplied by the maximal work at each recursive step. That becomes at most:

$$T(d, d', k) \leq O\big(2^k \binom{d}{d'}\big)$$

□

Later (see Definition 4.31 and Definition 4.32), we will see that an isomorphism between the $(d, d')$-Toric code and its dual, which is the $(d, d-d')$-Toric code, can be realized by transversal Hadamards followed by the following permutation over the qubits.

$$\phi(\theta_{\mathbf{v},\mathbf{S}'}) \to \theta_{\mathbf{S}'\mathbf{v},\mathbf{S}/\mathbf{S}'}$$

A full decoding cycle consists of four steps: first, applying the sweep rule regarding the $X$-syndrome; next, moving to the dual code; then applying the sweep rule again; and finally getting back to the code.

**Definition 4.9** (Sweep cycle)**.** *We define the sweep cycle to be the following procedure:*

1. *For each vertex, perform the sweep rule.*
2. *Apply the Hadamard transform* $\mathbf{H}^{\otimes \mathcal{F}^n_{d'}}$ *followed by the* $\phi$*-transpose.*
3. *Again, apply the sweep rule at each vertex.*
4. *Reverse stage 2 by reordering the qubits according to the* $\phi^{-1}$*-transpose, and then apply the Hadamard transform* $\mathbf{H}^{\otimes \mathcal{F}^n_{d'}}$*.*

## 4.2 Infinite Sides Torics

The Toric skeleton provides a notation for positive directions. However, to demonstrate that an 'error cluster' shrinks as a result of the decoding cycle, or at least does not expand too much during the operation of the logical operator, we will need a way to mark extremities (for example, the northernmost point). To achieve this, we will analyze the view over the finite Toric as a projection derived from a view over the infinite plane. For this purpose, given our initial (subjected) quantum circuit, we construct a representation in which any gate that originally acted on a quantum register, namely on the finite Toric, is mapped to infinite translations of it, each acting on qubits on the infinite plane. Using the Wrapping Lemma, proved in [SW04], and combining that the mapping respects a periodic condition, the finite and the infinite presentations are isomorphic.

The following definition extends the notion of location to differentiate between a coordinate that encodes a register and a coordinate of the location inside the register. This will be useful, as in the infinite plane representation, each register will be mapped to a unique infinite register.

**Definition 4.10** (Toric register coordinate system)**.** *Let* $C = \{u_i\}_i$ *be a quantum circuit of width* $w$ *with registers* $\mathcal{R} = R_1, \ldots, R_k$*, each encoded in the* $(d, d')$*-Toric code, induced by a* $d$*-dimensional Toric with a side length* $n$*. We define the 'Toric register coordinate system' to be the coordinate system that encodes spatial location with two coordinates as follows: In the first coordinate, the register number is recorded, and in the second, the qubit is encoded by the face associated with it. We call the first the register coordinate and the second the inner coordinate.*

We will need two types of gate translation. The first is the standard spatial translation, which means that any of the inner coordinates of the gate are advanced by the same vector. The second is 'rooted translation.' Here, we assume that the locations of the gate are given in a relative-to-root fashion, meaning that there is a root vertex, and all the locations are given by positive paths from the root. Then, we first translate the root and then advance the inner coordinate of any of the other locations to be on the path from the translated root. When considering a product gate, the translations act the same.

**Definition 4.11** (Translation by vertex $v$)**.** *Let $u$ be a gate, and denote the inner coordinates of $u$'s locations by $\theta_{v_1,J_1},\ldots,\theta_{v_\Delta,J_\Delta}$. The translation of $u$ by vertex $v$ is defined to be the gate obtained from $u$ by replacing the inner coordinates of its locations by: $\theta_{vv_1,J_1},\ldots,\theta_{vv_\Delta,J_\Delta}$, where the multiplication $v\cdot v_i$ is with respect to the infinity cover $\mathcal{G}^d$. Furthermore, for a $d$-dimensional Toric complex with side length $n$, we define a translation by an integer vector $a\in\mathbb{Z}^d$ as a translation by the vertex:*

$$(g_1^n)^{a_1},(g_2^n)^{a_2},..,(g_d^n)^{a_d}$$

*We denote the translation by an integer vector $a$ as $a*u$.*

**Definition 4.12** (Rooted gate at vertex $v$)**.** *Let $u$ be a quantum gate that acts on a register whose qubits are associated with a Toric complex at dimension $d$. We say that a gate $u$ is rooted at vertex $v$ if the inner coordinate of its location can be encoded by lists of pairs $(I_1,J_1),(I_2,J_2),\ldots,(I_l,J_l)$ such that $I_i\in S^d, J_i\subset S$, and the $i$th qubit on which it acts is in the face $\theta_{I_iv,J_i}$.*

**Definition 4.13** (Root translation in Register System)**.** *For a gate $u$ that is a rooted gate at vertex $v$, we define its translation by a vertex $v'$ to be the gate obtained by copying $u$ and replacing its inner location encoding the root by $v'v$.*

*Similarly to the standard translation by an integer vector, we extend the action to a root translation by an integer vector $a\in\mathbb{Z}^d$, as the root translation by the vertex:*

$$(g_1^n)^{a_1},(g_2^n)^{a_2},..,(g_d^n)^{a_d}$$

*We denote the root translation by an integer vector $a$ as $a*_r u$.*

Now we are ready to give an explicit description of the mapping. Given a quantum circuit $C$, we name its presentation over the infinite plane the *$\infty$-lift of $C$*.

**Definition 4.14.** *Let $n$ be an integer, and let $C=\{u_i\}_{i=1}$ be a quantum circuit with width $w$ and quantum registers $\mathcal{R}=R_1,\ldots,R_k$ such that each register $R_i$ encodes a $(d,d')-$Toric code with side at length $n$. We define the $\infty$-lift of $C$, denoted by $C^\infty$, as follows:*

1. *Each register $R_i$ in $\mathcal{R}$ is mapped to a register $R_i'$, which it's qubits are associated with the $d'$-dimensional faces of the infinite $d$-dimensional Toric.*
2. *The gate $u_i\in C$ is mapped to an infinite collection of gates, each being a rooted translation by an integer vector, as follows:*

$$u_i\mapsto\bigcup_{a\in\mathbb{Z}^d}\{a*_r u_i\}$$

*The restriction of the qubits in $C^\infty$'s registers to finite Torices with side length $n$ will be denoted by $\cdot|_{[w]}$, and it includes all the faces whose root vertex has 'powers' (the powers of $g_1,\ldots,g_d$) in the range $[0,n-1]$. For a set of faults $\mathcal{E}=\{f_i\}_{i=1}$, and measurements outcomes $\alpha\in\mathbb{F}_2^{(\cdot)}$, we denote by $C^\infty[\mathcal{E},\alpha]$ the $\infty$-lift of $C[\mathcal{E},\alpha]$.*

*We define the $\infty$-lift of a Pauli operator $P \in \mathcal{P}^{(\cdot)}$ be the result of lifting the circuit composed only of $P$. Denote it by $P^{\infty}$. Finally, the $\infty$-lifting of a chain $x \in (\mathcal{F}^n_{d'}; \mathbb{F}_2)$ is the chain in the infinite complex $(\mathcal{F}_{d'}; \mathbb{F}_2)$ obtained by taking all the translations of $x$ by integer vectors.*

The infinite presentation of a circuit agrees with it in terms of action. We give, without proof, an adaptation of the Wrapping Lemma, proved in [SW04].

**Claim 4.15** ( Adaptation of [SW04] )**.** *The $\infty$-lifting is an isomorphism. In particular, consider a conditioned subjected quantum circuit $C[\mathcal{E}, \alpha]$, such that it has a propagation $P_1, P_2, \ldots$, it holds that:*

$$P_i^{\infty} = (C[\mathcal{E}, \alpha]|_i P_{i-1})^{\infty} = C[\mathcal{E}, \alpha]|_i^{\infty} P_{i-1}^{\infty}$$

The computation DAG lifts naturally to the $\infty$-lift gates that arise as translates of the same local gate act on disjoint translated supports inside different periods, so they may be executed simultaneously. The same periodic lifting applies to the underlying geometric objects, passing from the finite Toric complex to its infinite cover.

We close that subsection by introducing the *potential walls*. Analyzing the infinite presentation enables us to bound a subset of errors by 'triangles'. A potential wall is a linear function $\mathbb{R}^d \to \mathbb{R}$. For the subset of vertices (that might be the subset that supports some error), the maximal value of the potential wall on it is achieved at the point of tangency between the subsets and its bounding triangle. With the assistance of potential walls, we can discuss the endpoint of a bunch of qubits and the 'size' of the (hyper)triangle that bounds them. Soon, the qubits will be associated with the support of an error, and showing that an action decreases the maximums of the potential walls implies that the error shrinks. The next definition explains how the embedding of vertices of the infinite in $\mathbb{R}^d$ is handled.

**Definition 4.16** (The standard embedding)**.** *Consider the $d$-dimensional infinite grid $\mathcal{G}^d$. The standard embedding $\mathcal{G}^d \to \mathbb{R}^d$ is given by fixing a vertex in $\mathcal{G}^d$ to be sent to the origin and then mapping the generators of the grid to the standard basis. We extend notation as follows: for a vertex $v \in \mathcal{G}^d$, a generator $g \in S$, and a coordinate $i \in [d]$, such that under the embedding $g \to i$, we denote by $v_i = v_g$ the $i$'th coordinate of the image of $v$.*

Now we are ready to define the *potential walls*:

**Definition 4.17** (Potential Walls)**.** *We define the potential walls to be the $d+1$ functions $L_1, L_2, .., L_{d+1}$, from the vertices of $\mathcal{G}^d$ to the reals as follow:*

1. *For any coordinate $i \in [d]$, we define $L_i \colon \mathcal{G}^d \to \mathbb{R}$ as $L_i(v) := v_i$. In addition, for the generator $g \in S$ which is mapped to $i$, i.e $g \to i$, we identify $L_g = L_i$.*
2. *We define $L_{d+1} \colon \mathcal{G}^d \to \mathbb{R}$ by $L_{d+1}(v) := -\sum_{i=1}^{d} v_i$.*

*Consider an assignment $z$ over the faces. For a vertex $v \in z$, and a potential wall $l \in \{L_1, .., L_{d+1}\}$, we say that $v$ is a local maximum of $l$ in $z$ if for any neighbor $u$ of $v$, such that $u \in z$, we have $l(v) \geq l(u)$. When the assignment $z$ is clear from the context, we might omit it and briefly say that $v$ is a local maximum of $l$. In addition we define the function* $\mathbf{Size}(\cdot) : \mathcal{G}^d \to \mathbb{R}$*, to act on a subset of points $A \subset \mathcal{G}^d$, as follows:*

$$\mathbf{Size}(A) := \sum_{g \in S} \max_{v \in A} L_g(v) + \max_{v \in A} L_{d+1}(v)$$

*and extend the function to act over assignment on faces $z$, by taking its action on the set of vertices that support $z$.*

The following claim shows that size has a similar behavior to a metric:

**Claim 4.18.** *Let $A, B \subset \mathbb{R}^d$ such that there $A \cap B \neq \emptyset$ then:*

$$\mathbf{Size}(A \cup B) \leq \mathbf{Size}(A) + \mathbf{Size}(B)$$

*Proof.* Let $p$ be a point in $A \cap B$. Then:

$$\begin{aligned}
\mathbf{Size}(A \cup B) &= \sum_{i \in [d+1]} \max_{v \in A \cup B} L_i(v) \\
&= \sum_{i \in [d+1]} \max\{\max_{v \in A} L_i(v), \max_{v \in B} L_i(v)\} \\
&= \sum_{i \in [d+1]} \max_{v \in A} L_i(v) + \max_{v \in B} L_i(v) - \min\{\max_{v \in A} L_i(v), \max_{v \in B} L_i(v)\} \\
&\leq \sum_{i \in [d+1]} \max_{v \in A} L_i(v) + \max_{v \in B} L_i(v) - L_i(p) \\
&\leq \mathbf{Size}(A) + \mathbf{Size}(B) - \sum_{i \in [d+1]} L_i(p) = \mathbf{Size}(A) + \mathbf{Size}(B)
\end{aligned}$$

Where in the last pass, we used that the size of a single point is zero. □

## 4.3 Reduced Error

Errors can be thought of as assignments on the $d'$-dimensional faces that have non-vanishing boundaries. In particular, $X$-errors can be characterized as $d'$-dimensional chains $z \in (\mathcal{F}_{d'}; \mathbb{F}_2)$ such that $\partial^- z \neq 0$. In this section, we assume dealing with the $\infty$-lift of a circuit (see Definition 4.14), so the cubical complex is the $d$-dimensional grid with infinite side length. The *reduced* form of an error is its representative, a translation by a stabilizer, which minimizes its size. Here we prove that the sizes of a reduced error and its boundary (derived from $\partial^-$) are the same[2]. In particular, they share poles of the potential walls. That will come into use in analyzing the behavior of the sweep-rule, as it is defined to decide on correction upon the syndrome it sees.

[2]In fact, the hypertriangles bounding them are the same.

For doing so we present two codes that describe local views of vertices. They are the *stabilizers code at vertex $v$* and the *small code at vertex $v$*. The first corresponds to stabilizers rooted at the vertex, while the second is the collection of local views on faces rooted at $v$ that satisfy the checks rooted at $v$. Then, in Claim 4.21, we consider a vertex whose $X$-checks don't admit a syndrome, meaning that its local view is in its *small code*, and show that there is a codeword of its *stabilizers code* that agrees with its positive faces. Addition by that stabilizer yields a new chain excluding $v$. If $v$ were a unique maximum of $L_{d+1}$, then the vertices on the yielded chain would have a lower value of $L_{d+1}$. Subsequently, since the exclusion decreases the size, it follows that the 'corner'—the vertex achieving the maximal $L_{d+1}$ value—of a reduced error sees a syndrome.

**Definition 4.19** (Stabilizers Code at Vertex $v$)**.** *We define stabilizer code at vertex $v$, denoted by $Stab_v$, as the restriction of the $(d, d')$-Toric code to the $d'$-dimensional faces such that their vertices are at a distance of at most one positive step in each direction from $v$. That is equivalent to the union of all the $d'$-dimensional faces rooted at $v$ with the $d$-dimensional faces of each of its sibling $gv$, excluding faces containing $g$ as their generator. Namely:*

$$\begin{aligned} Stab_v := \big\{ z : \partial^- z = 0 \ \textit{and} \\ z \in Span\big(\big\{\theta_{\mathbf{v},\mathbf{S'}} : S' \subset S, |S'| = d'\big\} \\ \bigcup_{g\in S} \big\{\theta_{\mathbf{gv},\mathbf{S'/g}} : S' \subset S/g, |S'| = d'\big\}\big)\big\} \end{aligned}$$

The checks of the code, are of the following three types:

1. Checks that are rooted at $v$, each identified by choosing $d-1$ generators from $S$. Namely:

   $$\big\{\theta_{\mathbf{v},\mathbf{S'}} : S' \subset S, |S'| = d' - 1\big\}$$

   For each check, the bits that connect to it, are given by restricting the coboundary of the check to bits domain of $\mathrm{Stab}_v$:

   $$\big(\partial^+ \theta_{\mathbf{v},\mathbf{S'}}\big)|_{\mathrm{Stab}_v} = \big(\sum_{g\in S/S'} \theta_{\mathbf{v},\mathbf{S'\cup g}} + \sum_{g\in S'} \theta_{\mathbf{g^{-1}v},\mathbf{S'\cup g}}\big)|_{\mathrm{Stab}_v} = \sum_{g\in S/S'} \theta_{\mathbf{v},\mathbf{S'\cup g}}$$

2. Checks are rooted at the positive sibling of $v$. Consider such a sibling, let's say $gv$ (namely the vertex that is given by stepping in the direction $g \in S$ from $v$). Notice that any face rooted at $gv$ that contains $ggv$ cannot be contained in faces rooted at $v$. Thus, the checks of $gv$ correspond to choosing subsets from $S/g$. Namely:

   $$\bigcup_{g\in S} \big\{\theta_{\mathbf{gv},\mathbf{S'}} : S' \subset S/g, |S'| = d' - 1\big\}$$

And each check is supported by:

$$\begin{aligned}\big(\partial^+\theta_{\mathbf{gv},\mathbf{S'}}\big)|_{\mathrm{Stab}_v} &= \big(\sum_{g'\in S/S'}\theta_{\mathbf{gv},\mathbf{S'}\cup\mathbf{g'}} + \sum_{g'\in S'}\theta_{\mathbf{g'^{-1}gv},\mathbf{S'}\cup\mathbf{g'}}\big)|_{\mathrm{Stab}_v}\\ &= \big(\sum_{\substack{g'\in S/S'\\ g'\neq g}}\theta_{\mathbf{gv},\mathbf{S'}\cup\mathbf{g'}}\big) + \theta_{\mathbf{v},\mathbf{S'}\cup\mathbf{g}}\end{aligned}$$

3. Checks that their roots are at a two-step distance from $v$, namely vertices of the form $g'gv$ where $g, g' \in S$, and $g \neq g'$. By the arguments presented in the second type, the checks are the $d'-1$ faces which do not have the generators on the path leading from $v$ to them, i.e., $g, g'$, in their generator set.

$$\bigcup_{g,g'\in S'}\big\{\theta_{\mathbf{g'gv},\mathbf{S'}} : S'\subset S/\{g,g'\}, |S'| = d'-1\big\}$$

And for each check, its support is:

$$\begin{aligned}\big(\partial^+\theta_{\mathbf{g'gv},\mathbf{S'}}\big)|_{\mathrm{Stab}_v} &= \big(\sum_{g''\in S/S'}\theta_{\mathbf{gg'v},\mathbf{S'}\cup\mathbf{g''}} + \sum_{g\in S'}\theta_{\mathbf{g''^{-1}gg'v},\mathbf{S'}\cup\mathbf{g''}}\big)|_{\mathrm{Stab}_v}\\ &= \theta_{\mathbf{gv},\mathbf{S'}\cup\mathbf{g'}} + \theta_{\mathbf{g'v},\mathbf{S'}\cup\mathbf{g}}\end{aligned}$$

**Definition 4.20** (Small Code at Vertex $v$)**.** *For a vertex $v$, we denote by $\mathcal{C}_v$ the small code at vertex $v$, which consists of all the $d'$-dimensional chains rooted at $v$ that satisfy the checks rooted at $v$, namely:*

$$\begin{aligned}\mathcal{C}_v := \big\{z : (\partial^- z)|_{v+} = 0 \ \textit{and}\\ z \in \mathit{Span}\big(\big\{\theta_{\mathbf{v},\mathbf{S'}} : S'\subset S, |S'| = d'\big\}\big)\big\}\end{aligned}$$

*The checks of the code are exactly the first type checks of $\mathit{Stab}_v$.*

**Claim 4.21.** *Let $v$ be a vertex. For any $d' \geq 2$, $d \geq d'+1$, and any $z \in \mathcal{C}_v$, there is a stabilizer $w \in \mathit{Stab}_v$ such that $z = w|_v$; namely, $z$ and $w$ agree on the faces rooted at $v$. Moreover, the vertex support of $w|_v$ is contained in the vertex support of $z|_v$, namely:*

$$\boldsymbol{Str}_{0+}(v,w) \subset \boldsymbol{Str}_{0+}(v,z)$$

*Proof.* By induction on the dimensions $d, d'$. We extend the notation of the stabilizer and the small codes at vertex $v$ to $\mathcal{C}_v^J, \mathrm{Stab}_v^J$, where $J$ is a subset of $S$, to refer to the codes derived from the skeleton generated by $J$. Showing that the belonging $z \in \mathcal{C}_v^J$ implies the existence of $w \in \mathrm{Stab}_v^J$ such that $w|_v = z|_v$ proves the claim.

1. Base. For the base cases, let $d$ be any number greater than or equal to three, and let $d'$ be two. First, observe that, in the case $d' = 2$, the code $\mathcal{C}_v^J$ is a Tanner code, where the bits are set on edges of the form $\{vg_i, vg_j\}$ and checks are associated with vertices of the form $\{vg_i\}$. Therefore, any codeword is a cycle. Let:

$$\{vg_1, vg_2\}, \{vg_2, vg_3\}, .., \{vg_k, vg_1\}$$

Be the cycle corresponding to $z$. Namely:

$$z = \theta_{\mathbf{v},\{\mathbf{g_1},\mathbf{g_2}\}} + \theta_{\mathbf{v},\{\mathbf{g_2},\mathbf{g_3}\}} + .. + \theta_{\mathbf{v},\{\mathbf{vg_k},\mathbf{vg_1}\}}$$

And consider the stabilizer $w$ defined as:

$$w = \partial^- \left(\theta_{\mathbf{v},\{\mathbf{g_1},\mathbf{g_2},\mathbf{g_3}\}} + \theta_{\mathbf{v},\{\mathbf{g_1},\mathbf{g_3},\mathbf{g_4}\}} + .. + \theta_{\mathbf{v},\{\mathbf{g_1},\mathbf{g_i},\mathbf{g_{i+1}}\}} + .. + \theta_{\mathbf{v},\{\mathbf{g_1},\mathbf{g_{k-1}},\mathbf{g_k}\}}\right)$$

Clearly, $w \in \mathrm{Stab}_v^J$, and in addition its restriction to $v$ equals:

$$\begin{aligned} w|_v &= \left(\sum_{i=2}^{k-1} \partial^- \theta_{\mathbf{v},\{\mathbf{g_1},\mathbf{g_i},\mathbf{g_{i+1}}\}}\right)|_v = \sum_{i=2}^{k-1} \theta_{\mathbf{v},\{\mathbf{g_i},\mathbf{g_{i+1}}\}} + \theta_{\mathbf{v},\{\mathbf{g_1},\mathbf{g_i}\}} + \theta_{\mathbf{v},\{\mathbf{g_1},\mathbf{g_{i+1}}\}} \\ &= \left(\sum_{i=3}^{k-1} \theta_{\mathbf{v},\{\mathbf{g_i},\mathbf{g_{i+1}}\}}\right) + \theta_{\mathbf{v},\{\mathbf{g_1},\mathbf{g_2}\}} + \theta_{\mathbf{v},\{\mathbf{g_k},\mathbf{g_1}\}} = z \end{aligned}$$

2. Assume the correction of the claim for dimensions lower than $d, d'$. Consider a generators subset $J \subset S$ and let $z \in \mathcal{C}_v^J$. In addition, consider a generator $g \in J$.

   Decompose $z = z|_{gv} + z|_{/gv}$ where $z|_{gv}$ and $z|_{/gv}$ are the chains consisting of all the faces in $z$ that have support on $gv$ and its complement. Define $z^*$ to be the $d'-1$-dimensional chain obtained by excluding $gv$ from any face of $z|_{gv}$. Notice that $(\partial^- z^*)|_v$ has to be zero since it contains all the faces of $\partial^- z$ that contain $gv$ (up to the removal). In other words, $z^* \in \mathcal{C}_v^{J/g}$. Thus, we can use the induction assumption and infer the existence of $w^* \in \mathrm{Stab}_v^{J/g}$ such that $z^* = w^*|_v$.

   Now, since $w^* \in \mathrm{Stab}_v^{J/g}$, then $\partial^- w^* = 0$. And since the local complex is contractible, $w^*$ can be decomposed into a sum of stabilizers rooted in $v$. Let $\theta_{\mathbf{v},\mathbf{S'_1}}, \theta_{\mathbf{v},\mathbf{S'_2}}, \theta_{\mathbf{v},\mathbf{S'_3}}, \ldots, \theta_{\mathbf{v},\mathbf{S'_l}}$ be the $d'$-dimensional chains corresponding to the stabilizers composing $w^*$. Namely:

   $$w^* = \sum_i \partial^- \theta_{\mathbf{v},\mathbf{S'_i}}$$

   Since those stabilizers are basis elements of $\mathrm{Stab}_v^{J/g}$, we have that $g \notin S'_i$ for any $i$. Hence, we can define the extended $d'$-dimensional chain $w$ to be the chain obtained by adding $g$ to each of the stabilizers deriving $w^*$. Namely:

   $$w = \sum_i \partial^- \theta_{\mathbf{v},\mathbf{S'_i}\cup\mathbf{g}}$$

   However, $\theta_{\mathbf{v},\mathbf{S'_1}\cup\mathbf{g}}, \ldots, \theta_{\mathbf{v},\mathbf{S'_l}\cup\mathbf{g}}$ are $d'+1$-dimensional chains corresponding to the stabilizers, which are basis elements of $\mathrm{Stab}_v^J$. Therefore, $w \in \mathrm{Stab}_v^J$. In addition, opening up the boundary operator yields:

   $$\begin{aligned} w|_v &= \sum_i \left(\partial^- \theta_{\mathbf{v},\mathbf{S'_i}\cup\mathbf{g}}\right)|_v = \sum_i \Big( \sum_{g' \in S'_i/g} \theta_{\mathbf{v},\mathbf{S'_i}/\mathbf{g'}\cup\mathbf{g}} + \theta_{\mathbf{v},\mathbf{S'_i}}\Big) \\ &= \sum_{\theta_{\mathbf{v},\mathbf{S'}} \in w^*|_v} \theta_{\mathbf{v},\mathbf{S'}\cup\mathbf{g}} + \sum_i \theta_{\mathbf{v},\mathbf{S'_i}} = z|_{gv} + \sum_i \theta_{\mathbf{v},\mathbf{S'_i}} \end{aligned}$$

Thus, adding $w|_v$ to $z$ results in:

$$z + w|_v = z|_{/gv} + \sum_i \theta_{\mathbf{v},\mathbf{S}'_\mathbf{i}}$$

Which is a $d'$-dimensional chain, supported on vertices of the form $g'v$ for $g' \in J/g$, namely a $d'$-dimensional chain on the complex induced by the $d-1$-dimensional skeleton. In addition, since the boundary operator can only advance the root of a face forward, we have that $\partial^- w|_v = (\partial^- w)|_v$ (as $w$ is rooted in $v$) and therefore $\partial^-(z + w|_v) = \partial^- z + (\partial^- w)|_v = 0$.

To summarize, we have both $z+w|_v \in \mathcal{C}_v^{J/g}$ and $z+w|_v$ sets on a $d-1$-dimensional skeleton. Therefore, we can repeat in a recursive manner, with each step resulting in a $d'$-dimensional chain in a skeleton with dimension decreased by one. We stop when $d = d'$; in that case, the resulting chain has to be trivial.

□

We would like to differentiate chains whose projection onto the finite Toric with side length $n$ closes a non-trivial cycle from those which don't. For this, we fix a rough threshold via the size function. Chains which have size less than $n$ will be called finite. Observe that a chain might have a projection that doesn't close a non-trivial loop on the Toric and still be marked, according to our definition, as infinite. So, the classification is rough, yet it will turn out to be sufficient.

**Definition 4.22.** *Let $z$ be a $d'$-dimensional chain. We will say that a chain $z$ is finite if:*

$$\mathbf{Size}(z) \leq n - 1$$

*Similarly, $z$ is infinite if it's size is greater than or equal to $n$.*

**Remark 4.23.** *Observe that if $\mathbf{Size}(z) < n$, then the projection of $z$ on the $n$-side length Toric does not close a non-trivial loop.*

The next claim states that the translation by stabilizer that minimizes its size of a finite chain admits a boundary with size equal to itself.

**Claim 4.24.** *Let $x \in (\mathcal{F}_{d'}; \mathbb{F}_2)$ be a $d'$-dimensional finite chain, consider the stabilizer $z \in \mathcal{C}_Z^\perp$ which adding it to $x$ minimize the size , Namely:*

$$z = \arg\min_{z \in \mathcal{C}_Z^\perp} \mathbf{Size}(x + z)$$

*Then:*

$$\mathbf{Size}(x + z) = \mathbf{Size}(\partial^-(x + z))$$

*Proof.* First, observe that since the vertex domain of $\partial^- x$ is contained in the vertex domain of $x$, it follows that for any $x$ the inequality $\mathbf{Size}(x) \geq \mathbf{Size}(\partial^- x)$ holds. Combining this with the fact that $\partial^- z = 0$ for any $z \in \mathcal{C}_Z^\perp$, we have that $\mathbf{Size}(x+z) \geq \mathbf{Size}(\partial^-(x+z))$. Now suppose that $\mathbf{Size}(x) > \mathbf{Size}(\partial^- x)$; that implies the existence of $v \in x/\partial^- x$ such that $v$ is a local maximum of one of the potential walls in $x$ and $(\partial^- x)|_v = 0$. Let's split into cases, depending on the potential wall type.

1. If $v$ is a maximum of $L_{d+1}$, then by Claim 4.21, there exists a stabilizer $z$ rooted at $v$, such that $z|_v = z|_{v+} = x|_{v+} = x|_v$ (where we used that $v$ is a local maximum of $L_{d+1}$ in $x$ to infer $x|_v = x|_{v+}$). Therefore, $(x+z)|_v = 0$, meaning adding $z$ to $x$ excludes $v$. In addition, since the rooted stabilizer $z$ is supported only on the vertices in $\mathbf{Str}_{0+}(v, x)$, the addition cannot introduce a vertex with a higher $L_g$ value than the maximal $L_g$ value in $\mathbf{Str}_{0+}(v, x)$ into $x$. So, repeating the process until excluding all the vertices that get the maximal $L_{d+1}$-value in $x$, and summing the stabilizers, results in a stabilizer $z$ for which $L_{d+1}(x+z) < L_{d+1}(x)$.

2. If, for some generator $g \in S$, $v$ is a maximum of $L_g$, then without loss of generality, pick $v$ among the maximum points of $L_g$ with the highest value of $-L_{d+1}$ (maximize $\sum_{g \in S} L_g(v)$). Since stepping through the positive direction can only increase the value of $-L_{d+1}$, it follows that $v$ is also a local max of $-L_{d+1}$. Now consider the skeleton system where the directions are flipped, and $\theta_{v,S'}$ is set to be the face containing the vertices that are reached by the selection of reverse steps from $S'$ (i.e., $g^{-1}v \in \theta_{v,S'}$). Similarly, for the sake of the proof, let's present the following notation for the positive neighborhood (Definition 4.5) in the reversed system:

   $$\mathbf{Str}_{0-}(v, x) := \left\{u \in x \colon \exists g \in S \text{ such } u = g^{-1}v\right\}$$

   So, $\mathbf{Str}_{0-}$ plays the same role as $\mathbf{Str}_{0+}$ does in the original skeleton. In that system, we can apply Claim 4.21 (in the reversed direction) and get that there is a stabilizer $z$ such that adding it to $x$ excludes $v$ from $x$. By the same argument as above, no vertex with a higher $L_{g'}$-value (although $L_{d+1}$ can increase, that's fine[3]) than what it already has in $\mathbf{Str}_{0-}(v, x)$ is introduced into $x$. Repeating the process excludes all the vertices with the maximal value of $L_g$ in $x$, so eventually, we end up with $x + z$, such that $L_g(x+z) < L_g(x)$.

We keep excluding vertices until we get the desired equality.

□

We close the section by defining the *reduced* form of a finite $d'$-dimensional chain.

**Definition 4.25.** *Let $x \in (\mathcal{F}_{d'}; \mathbb{F}_2)$ be a $d'$-dimensional finite chain. We will say that $x$ is reduced if for any vertex $v \in x$ that is a maximum point of a potential wall $L \in L_1, \ldots, L_{d+1}$, $v$ is also in $\partial^- x$. In particular, we have that $\mathbf{Size}(x) = \mathbf{Size}(\partial^- x)$ and that the reduced form of a given chain is obtained by the construction presented in the proof of Claim 4.24.*

[3] If it happens, we will apply the first case in the next exclusion.





Figure 6: Consider the $(3, 2)$-Toric code, with qubits and $X$-checks set on the 2- and 1-dimensional faces. In blue, we have a 2-dimensional chain where the vertex achieving the maximum of $L_{d+1}$, denoted by $v$, does not see any unsatisfied checks in its positive local view. The green faces represent a 2-dimensional chain, which is the **reduced** form of the blue. In particular, any local maximum of $L_{d+1}$ (vertices $u$ and $w$) sees a non-trivial syndrome in its positive local view. Namely, the maximal points of $L_{d+1}$ in the chain are also the maximal points in the boundary $\partial^-$.

We emphasize that the reduced form is not unique. Throughout the paper, every time we choose a reduced form of a chain, we mean obtaining it from the given algorithm presented in Claim 4.24, so the reduced form is effectively unique.

## 4.4 Shrinking

We are about to prove that the sweep rule shrinks finite errors. The following claim relates the local maximum points of the potential walls $L_1, \ldots, L_d$ in an assignment $z$ to the structure of the syndrome they observe. Later, we will use that relation to infer that the decoding step of the sweep rule can't spread the error to a vertex[4] with a higher value than the current global maximum of $L_1, \ldots, L_d$. In other words, the error does not spread in the positive directions.

**Claim 4.26.** *Let $z$ and $\xi$ be $d'$-dimensional finite chains such that $\xi$ results from the application of the sweep rule on $z$. For any generator $g \in S$, the maximal values of $L_g$ in $\xi$ and $\partial^-\xi$ are lower than the maximal values in $z$ and $\partial^- z$. Namely:*

$$\max\{L_g(u) : u \in \xi\} \leq \max\{L_g(u) : u \in z\}$$
$$\max\{L_g(u) : u \in \partial^-\xi\} \leq \max\{L_g(u) : u \in \partial^- z\}$$

*Proof.* First, we argue that for a vertex $v$ in $\partial^- z$, and a generator $g \in S$, such that $v$ is a local maximum of $L_g$ in either $z$ or $\partial^- z$, it implies that $gv \notin \partial^- z$. The contradiction where $v$ is a maximum of $L_g$ in $z$ follows immediately, since containment in $\partial^- z$ implies containment in $z$. Where $v$ is a maximum in $\partial^- z$, suppose through contradiction that $gv \in \partial^- z$, then

$$L_g(gv) = (gv)_g = 1 + v_g = 1 + L_g(v)$$

[4]To faces whose vertices have higher values of $L_1, \ldots, L_d$ than the current global maximum values.

In contradiction to $v$ being a local maximum of $L_g$ in $\partial^- z$.

For a vertex $v \in \partial^- z$ denote the correction it applies by $\varphi_v \in (\mathcal{F}_{d'}; \mathbb{F}_2)$, so

$$\xi = \sum_{v \in \partial^- z} \varphi_v + z \quad \text{and} \quad \partial^- \xi = \sum_{v \in \partial^- z} \partial^- \varphi_v + \partial^- z$$

So for any vertex $u \in \xi / z$, there is a vertex $v \in \partial^- z$ such that $u \in \varphi_v$. Moreover, since $\phi_v$ is a rooted chain, it follows that $L_g(u) \leq L_g(v) + 1$, where the equality holds when $g$ belongs to the generator's subset of the face $\varphi_v$. Similarly for $u \in \partial^- \xi / \partial^- z$.

Now, combining with the sweep rule's first condition, which restricts the correction applied by a vertex to have a vertex support that is contained in the positive syndrome it sees, we have that for any vertex $v$ which is a local maximum of $L_g$ (in either $z$ or $\partial^- z$), any $u \in \varphi_v$ satisfies $L_g(u) = L_g(v)$. In other words, $\xi$ and $\partial^- \xi$ don't contain vertices of the form $gv$ where $v$ is a local maximum of $L_g$ in $z$ and $\partial^- z$, and the desired inequalities follow. □

Next, we prove that for a finite $X$-error, the sweep-cycle advances the corner (the maximum of $L_{d+1}$) of its reduced form. We assume we are given a finite error in its reduced form, and therefore whose corner sees a syndrome, and show that the sweep-rule application excludes the corner. In other words, the sweep-rule shrinks $X$-errors.

**Claim 4.27.** *Let $z$ be a finite reduced $d'$-dimensional chain, and let $\xi$ be the reduced result of applying the sweep rule to it. Then:*

1. *For any generator $g \in S$:* $\max\left\{L_g(v) : v \in z\right\} \geq \max\left\{L_g(v) : v \in \xi\right\}$
2. *And for $L_{d+1}$ :* $\max\left\{L_{d+1}(v) : v \in z\right\} \geq \max\left\{L_{d+1}(v) : v \in \xi\right\} + 1$

*In particular,* $\mathbf{Size}(\xi) \leq \mathbf{Size}(z) - 1$.

*Proof.* The first inequality was proved in Claim 4.26, so it's left to prove the second. Denote by $\varphi$ the applied correction and by $v$ the vertex on which $L_{d+1}$ gets the maximal value in $z$, if there are more then one vertex then choose $v$ arbitrarily. Since $z$ is reduced, then by Claim 4.24 it holds that $v \in \partial^- z$. Moreover, since $v$ is a local max of $L_{d+1}$ in $z$ the two follows:

1. Claim 4.7 guarantees that $\partial^- \varphi|_v = \partial^- z|_v$. Thus, adding $\varphi|_v$ to $z$ excludes $v$ from the boundary.
2. For any other vertex $u \in z$, there is no face $\theta_{\mathbf{u},\mathbf{S}'} \in z$ such that $v \in \theta_{\mathbf{u},\mathbf{S}'}$. Otherwise, it would contradict $v$ being a local maximum of $L_{d+1}$ in $z$. Thus, $v \notin \mathbf{Str}_{0+}(u, \partial^- z)$, so by Claim 4.7, $v \notin \varphi|_u$.

Combining the two, we get that $v \notin \partial^-(z + \varphi)$, so the reduced form of $z + \varphi$ does not contain $v$. Namely, $v \notin \xi$. Repeating the above for all the other vertices which get the maximal $L_{d+1}$-value in $z$ yields that $L_{d+1}(\xi) \leq L_{d+1}(z) - 1$.

□

Consider a vertex on the boundary of a chain resulting from an application of the sweep rule. That vertex did not come from nowhere; there must be vertices on the preceding chain, which sit on its boundary, and are the cause for the local view seen by the vertex. The following claim formulates that insight; moreover, it states a relation between the potential walls' values of the vertex and the (part of) vertices who caused it.

**Claim 4.28.** *Let $z$ be a finite $d'$-dimensional chain, and let $\xi$ be the result of applying the sweep rule to it. Let $v$ be a vertex in $\partial^- \xi$, then there is a vertex $u \in \partial^- z$ such $L_i(u) \geq L_i(v)$ for $i \neq d+1$ and $L_{d+1}(u) > L_{d+1}(v)$ if $i = d+1$, and there is a $d'$-dimensional face $f$ such $v, u \in f$.*

*Proof.* Without loss of generality, we can assume that $z$ and $\xi$ are reduced. We start by proving for $i = d+1$. Now, it splits upon whether $v \in z + \xi$:

1. If $v \in z+\xi$, then $v$ belongs to a face that flipped during the correction, denote it's root by $u$ and by definition of the sweep-rule $(\partial^- z)|_{u+} \neq 0$. Therefore, $u \in \partial^- z$, and $u, \xi$ share a face which $u$ is it's root. Since $u$ it's the root of the face we get $L_{d+1}(u) > L_{d+1}(v)$.

2. Else, if $v \notin z + \xi$, then $v$ has to be in $z$. Combining with the fact that $v \in \xi$, it follows that $v$ is not a local maximum of $L_{d+1}$ in $\partial^- z$, otherwise the application of the sweep-rule would exclude $v$ (See the proof of Claim 4.27), so it wouldn't be in $\xi$. Pick $u$ to be the neighbor of $v$ in $\partial^- z$ such that $L_{d+1}(u) > L_{d+1}(v)$.

It remains to prove for $i \in [d]$, in this case if $v \in \partial^- z$ then take $u = v$. Otherwise, there must be a face $f$ that was flipped during the sweep-rule containing $v$. Denote by $g$ the corresponding generator for $i$ and by $u'$ the root of $f$. If $L_g(u') = L_g(v)$ then set $u = u'$. Otherwise, $g$ is one of the generators that span $f$, the second condition of the sweep-rule (Definition 4.6) requires that for $u'$ flipping a face in the $g$ direction, it has to see the vertex $gu'$ in $\partial^- z$, in that case, set $u = g'u$. □

We finished analyzing the first part of the sweep-cycle that acts in the computational basis. In the next subsection, we introduce the transformation into the dual code. Since the dual code is a $(d, d-d')$-Toric code, we also find that the sweep-cycle shrinks reduced phase errors.

### 4.4.1 Ideal decoder

Although the main role of the section is to show that a single sweep-cycle keeps error clusters under control during a noisy run (by admitting a modest shrinking), an immediate corollary of this is that the application of non-noisy multiple iterations of the sweep-cycle has the potential to erase errors, namely a decoder. Here, a classical measurement is given, we act on classical bits, and the sweep-cycle consists only of the first stage that works over the computational basis, without moving to the dual code. We formulate the corollary as follows:

**Corollary 4.29.** *Consider the $(d, d')$-Toric code, induced by a Toric with side length $n$. Given a finite connected reduced error $z \in (\mathcal{F}_{d'}; \mathbb{F}_2)$ on that Toric, with* $\mathbf{Size}(z) \leq n-1$. *Then an application of* $\mathbf{Size}(z)$ *sweep cycles (partial cycles consisting only of the first stage) erases the error.*

When $z$ is not connected, disjoint components might merge, and it is no longer true that the size of the chain decreases in each iteration. However, we will see later (Claim 7.1, Claim 7.2, and Lemma 6.2) that performing $\Theta(n^{2d+1})$ sweep-cycles erases the error with high probability, if $z$ is assumed to be distributed according to local stochastic noise.

## 4.5 Logical Gates

The $\theta_{\mathbf{v},\mathbf{S}'}$ notation gives a nice interpretation of the logical code words. Particularly, an $X$-type logical codeword is given as follows: Take a subset of generators $S' \subset S$ and consider the subgroup generated by it, $\langle S' \rangle$; let us denote the subgroup by $K$. Then the logical codeword is the $X$-product over all $\theta_{\mathbf{u},\mathbf{S}'}$ such that $u \in K$. Moreover, replacing $K$ by a coset whose base subgroup is $\langle S' \rangle$, we get another presentation of the same logical codeword.

**Claim 4.30.** *For any generator subset $S'$ of size $d'$, denote by $x_{S'}$ and $z_{S'}$ the following $d'$-dimensional chains:*

$$x_{S'} := \sum_{u \in \langle S' \rangle} \theta_{\mathbf{u},\mathbf{S}'} \qquad z_{S'} := \sum_{u \in \langle S/S' \rangle} \theta_{\mathbf{u},\mathbf{S}'}$$

*Then $x_{S'}$ and $z_{S'}$ are binary representations of anticommuting logical codewords of the $(d, d')$-Toric code. In particular, $x_{S'} \in \mathcal{C}_X/\mathcal{C}_Z^{\perp}$, $z_{S'} \in \mathcal{C}_Z/\mathcal{C}_X^{\perp}$, and $x_{S'} z_{S'} = 1$. In addition, let $X_{S'}$ and $Z_{S'}$ be the Pauli matrices obtained by multiplying each non-trivial coordinate of them by $X$ or $Z$, respectively.*

*Proof.* By definition, $x_{S'}$ and $z_{S'}$ are binary assignments on the $d'$-dimensional faces. We start by showing that $x_{S'} \in \mathcal{C}_X$ and $z_{S'} \in \mathcal{C}_Z$; namely, that the boundaries $\partial^- x_{S'}$ and $\partial^+ z_{S'}$ vanish.

$$\begin{aligned}
\partial^- \sum_{u \in \langle S' \rangle} \theta_{\mathbf{u},\mathbf{S}'} &= \sum_{u \in \langle S' \rangle} \sum_{g \in S'} \theta_{\mathbf{u},\mathbf{S}'/\mathbf{g}} + \theta_{\mathbf{gu},\mathbf{S}'/\mathbf{g}} \\
&= \sum_{g \in S'} \sum_{u \in \langle S' \rangle} \theta_{\mathbf{u},\mathbf{S}'/\mathbf{g}} + \sum_{u \in \langle S' \rangle} \theta_{\mathbf{gu},\mathbf{S}'/\mathbf{g}} \\
&= \sum_{g \in S'} \sum_{u \in \langle S' \rangle} \theta_{\mathbf{u},\mathbf{S}'/\mathbf{g}} + \sum_{u \in \langle S' \rangle} \theta_{\mathbf{u},\mathbf{S}'/\mathbf{g}} = 0 \\
\partial^+ \sum_{u \in \langle S' \rangle} \theta_{\mathbf{u},\mathbf{S}/\mathbf{S}'} &= \sum_{u \in \langle S' \rangle} \sum_{g \in S'} \theta_{\mathbf{u},\mathbf{S}/\mathbf{S}'\cup\mathbf{g}} + \theta_{\mathbf{g}^{-1}\mathbf{u},\mathbf{S}/\mathbf{S}'\cup\mathbf{g}} \\
&= \sum_{g \in S'} \sum_{u \in \langle S' \rangle} \theta_{\mathbf{u},\mathbf{S}/\mathbf{S}'\cup\mathbf{g}} + \sum_{u \in \langle S' \rangle} \theta_{\mathbf{g}^{-1}\mathbf{u},\mathbf{S}/\mathbf{S}'\cup\mathbf{g}} \\
&= \sum_{g \in S'} \sum_{u \in \langle S' \rangle} \theta_{\mathbf{u},\mathbf{S}/\mathbf{S}'\cup\mathbf{g}} + \sum_{u \in \langle S' \rangle} \theta_{\mathbf{u},\mathbf{S}/\mathbf{S}'\cup\mathbf{g}} = 0
\end{aligned}$$

Thus $x_{S'} \in \mathcal{C}_X$ and $z_{S'} \in \mathcal{C}_Z$, now for showing that they are not binary representations of stabilizers, it's enough to show they admit no vanishing product.

$$x_{S'} z_{S'} = \sum_{u \in \langle S' \rangle} \theta_{\mathbf{u},\mathbf{S'}} \sum_{u \in \langle S/S' \rangle} \theta_{\mathbf{u},\mathbf{S'}} = \theta_{\mathbf{e},\mathbf{S'}} \theta_{\mathbf{e},\mathbf{S'}} = 1$$

Therefore, the Paulis $X_{S'}$ and $Z_{S'}$ are $X$- and $Z$-type anticommuting logical code words. □




Figure 7: In blue and green are the binary presentations $x_S$ and $z_S$ of logical code words of the $(2,1)$-Toric code. The edge $\{(5,4),(0,4)\}$ is omitted for clarity (it should be a green edge that hovers over the green line).

The $(d,d')$-Toric code admits a fold-transversal realization of an isomorphism gate into the $(d,d-d')$-Toric code, for any dimensions $d,d'$. Particularly, the gate exchanges logical Pauli $X_{S'}$ (of the first code) with logical Pauli $Z_{S/S'}$ (of the second code) and vice versa. It is realized by an application of transversal Hadamards followed by permuting the qubits according to a transformation which we name the *$\phi$-transpose map*. We define the transpose map as follows:

**Definition 4.31** (The Transpose Map)**.** *Let $d,d'$ be integers such that $d' < d$, and let $\mathcal{G}$ be a $(d,d')$-Toric complex generated by the generator set $S$. We define the transpose map $\phi : (\mathcal{F}_{d'}^n; \mathbb{F}_2) \to (\mathcal{F}_{d-d'}^n; \mathbb{F}_2)$ by acting on the basis elements as follows:*

$$\phi(\theta_{\mathbf{v},\mathbf{S'}}) \to \theta_{\mathbf{S'v},\mathbf{S}/\mathbf{S'}}$$

Notice that the action of the transpose map over the qubits is a one-to-one map between the qubits of the $(d,d')$-Toric code and the qubits of the $(d,d-d')$-Toric code, and therefore can be realized at constant depth using ancillas.

**Definition 4.32** ( Hadamard-Type Gate $\mathbf{H}_\phi$)**.** *We define the logical Hadamard-type gate* $\mathbf{H}_\phi$*:* $L(\mathcal{H}) \to L(\mathcal{H})$*, to be a code isomorphism* $(d, d')$*-Toric* $\to$ $(d, d-d')$*-Toric, as follows, for any* $S' \subset S$*, of size* $d'$*:*

$$\mathbf{H}_\phi(X_{S'}) \to Z_{S/S'} \qquad \mathbf{H}_\phi(Z_{S'}) \to X_{S/S'}$$

**Claim 4.33.** *The Hadamard-type gate* $\mathbf{H}_\phi$ *has a fold-transversal implementation by, first applying* $\mathbf{H}^{\otimes \mathcal{F}^n_{d'}}$ *over all the physical qubits, and then permuting them by the transpose map* $\phi$*, namely* $\hat{\mathbf{H}}_\phi = \phi \circ \mathbf{H}^{\otimes \mathcal{F}^n_{d'}}$*.*

*Proof.* Clearly, for any subset of generators $S' \subset S$, the map $\phi$ sends $x_{S'}$ to $z_{S/S'}$:

$$\phi(x_{S'}) = \phi(\sum_{u \in \langle S' \rangle} \theta_{\mathbf{u},\mathbf{S'}}) = \sum_{u \in \langle S' \rangle} \theta_{\mathbf{S'u},\mathbf{S/S'}} = \sum_{u \in \langle S' \rangle} \theta_{\mathbf{u},\mathbf{S/S'}} = z_{S/S'}$$

Moreover, $\phi$ sends binary representations of $Z$-stabilizers of the $(d, d')$-Toric code to binary representations of $X$-stabilizers of the $(d, d-d')$-Toric code, and vice versa. To see this, consider a $d'+1$ dimensional face, and consider the image of the stabilizer it defines.

$$\begin{aligned}
\phi\left(\partial^- \theta_{\mathbf{v},\mathbf{S'}}\right) &= \phi\left(\sum_{g \in S'} \theta_{\mathbf{v},\mathbf{S'/g}} + \theta_{\mathbf{gv},\mathbf{S'/g}}\right) \\
&= \sum_{g \in S'} \theta_{\mathbf{g^{-1}S'v},(\mathbf{S/S'})\cup\mathbf{g}} + \theta_{\mathbf{g^{-1}S'gv},(\mathbf{S/S'})\cup\mathbf{g}} \\
&= \partial^+ \theta_{\mathbf{S'v},\mathbf{S/S'}}
\end{aligned}$$

And for the checks set on the $d'-1$-dimensional face we have:

$$\begin{aligned}
\phi\left(\partial^+ \theta_{\mathbf{v},\mathbf{S/S'}}\right) &= \phi\left(\sum_{g \in S'} \theta_{\mathbf{g^{-1}v},(\mathbf{S/S'})\cup\mathbf{g}} + \theta_{\mathbf{v},(\mathbf{S/S'})\cup\mathbf{g}}\right) \\
&= \sum_{g \in S'} \theta_{(\mathbf{S/S'})\mathbf{v},\mathbf{S'/g}} + \theta_{\mathbf{g}(\mathbf{S/S'})\mathbf{v},\mathbf{S'/g}} \\
&= \partial^- \theta_{(\mathbf{S/S'})\mathbf{v},\mathbf{S'}}
\end{aligned}$$

Thus, $\phi \circ \mathbf{H}^{\otimes \mathcal{F}^n_{d'}}$ sends $Z$-stabilizers (at dimension $d'$) to $X$-stabilizers ( at dimension $d-d'$) and vice versa, thereby sending the satisfied checks to satisfied checks. Combining this with the above, $\phi \circ \mathbf{H}^{\otimes \mathcal{F}^n_{d'}}$ realizes the logical isomorphism $\mathbf{H}_\phi$ from the $(d, d')$-Toric code into the $(d, d-d')$-Toric code. □

**Example 4.34.** *Consider the* $(2,1)$*-Toric code. Name the generators in* $S$ *by* $g_1 = (1,0)$ *and* $g_2 = (0,1)$*. Consider the check corresponding to the* $Z$*-stabilizer* $\partial^+ \theta_{(\mathbf{2},\mathbf{3}),\{\}}$*.*

$$\partial^+ \theta_{(\mathbf{2},\mathbf{3}),\{\}} = \{\theta_{(\mathbf{2},\mathbf{3}),\{(\mathbf{1},\mathbf{0})\}}, \theta_{(\mathbf{2},\mathbf{3}),\{(\mathbf{0},\mathbf{1})\}}, \theta_{(\mathbf{1},\mathbf{3}),\{(\mathbf{1},\mathbf{0})\}}, \theta_{(\mathbf{2},\mathbf{2}),\{(\mathbf{0},\mathbf{1})\}}\}$$





Figure 8: An outline of Example 4.34. The $\phi$-transpose sends $Z$-stabilizers to $X$-stabilizers and vice versa. Here we consider the $(2,1)$ Toric code; namely, the $Z$-stabilizers (parity checks) are set on the vertices, and the $X$-stabilizers (phase checks) are set on the squares. In blue and green, we have the edges corresponding to checks $\partial^{+}\theta_{(\mathbf{2},\mathbf{3}),\{\}}$ and $\partial^{-}\theta_{(\mathbf{2},\mathbf{3}),\{(\mathbf{0},\mathbf{1}),(\mathbf{1},\mathbf{0})\}}$. The example shows that indeed $\phi$ maps between the two.

*The $\phi$-transpose map acts on it as follows:*

$$\begin{aligned}
\phi(\theta_{(\mathbf{2},\mathbf{3}),\{(\mathbf{1},\mathbf{0})\}}) &= \theta_{(\mathbf{3},\mathbf{3}),\{(\mathbf{0},\mathbf{1})\}} \\
\phi(\theta_{(\mathbf{2},\mathbf{3}),\{(\mathbf{0},\mathbf{1})\}}) &= \theta_{(\mathbf{2},\mathbf{4}),\{(\mathbf{1},\mathbf{0})\}} \\
\phi(\theta_{(\mathbf{1},\mathbf{3}),\{(\mathbf{1},\mathbf{0})\}}) &= \theta_{(\mathbf{2},\mathbf{3}),\{(\mathbf{0},\mathbf{1})\}} \\
\phi(\theta_{(\mathbf{2},\mathbf{2}),\{(\mathbf{0},\mathbf{1})\}}) &= \theta_{(\mathbf{2},\mathbf{3}),\{(\mathbf{1},\mathbf{0})\}}
\end{aligned}$$

*What gives edges on a rectangle that converges with the bits on the support of the $X$-stabilizer $\theta_{(\mathbf{4},\mathbf{3}),\{(\mathbf{0},\mathbf{1}),(\mathbf{1},\mathbf{0})\}}$.*

Equipped with $\mathbf{H}_{\phi}$, we gain a mapping into the dual code that both keeps the Toric skeleton and sends the $Z$-checks to $d'-1$ dimensional faces. This enables the use of the same local decoder to act on both $\mathcal{C}_X$ and its dual. We summarize it in the following immediate corollary:

**Corollary 4.35.** *Consider an Pauli $P \in \mathcal{P}$, acting on the infinite complex, whose $X$- and $Z$-components are set on the reduced chains $x, z \in (\mathcal{F}_{d'}; \mathbb{F}_2)$. Denote by $\tilde{P}$ the Pauli operator result by an application of the sweep-rule on $P$ and by $\tilde{x}, \tilde{z} \in (\mathcal{F}_{d'}; \mathbb{F}_2)$ the chains corresponding to the $X$- and $Z$-components of $\tilde{P}$. If both $x, \phi(z)$ are finite chains, Then:*

1. *For any $i \in [d]$:*

$$\max_{v \in x} L_i(v) \geq \max_{v \in \tilde{x}} L_i(v) \qquad \max_{v \in \phi(z)} L_i(v) \geq \max_{v \in \phi(\tilde{z})} L_i(v)$$

*2. And for $i = d+1$ :*

$$\max_{v\in x} L_{d+1}(v) \geq \max_{v\in \tilde{x}} L_{d+1}(v) + 1 \qquad \max_{v\in \phi(z)} L_{d+1}(v) \geq \max_{v\in \phi(\tilde{z})} L_{d+1}(v) + 1$$

*In particular:*

$$\mathbf{Size}(\tilde{x}) \leq \mathbf{Size}(x) - 1 \qquad \mathbf{Size}(\phi(\tilde{z})) \leq \mathbf{Size}(\phi(z)) - 1$$

Throughout the construction, we encode each qubit in a code block; namely, we restrict ourselves to using only a single codeword of the $(d, d')$-Toric code. From now on, we will think of $S' \subset S$ as a fixed $d'$-size subset of generators that were picked from the head. And we will decode the logical $|1\rangle$ state by $x_{S'}$. To simplify terminology, we call such usage 'nice encoding'.

**Definition 4.36** (The Nice Encoding)**.** *Consider $(d, d')$-Toric code and fix a subset $S' \subset S$, at size $d'$. We define the nice encoding to be the subsystem code, which uses $x_{S'}$ to encode a single logical qubit. Namely, the logical codewords are:*

$$|\bar{0}\rangle = \left|\mathcal{C}_Z^{\perp}\right\rangle$$
$$|\bar{1}\rangle = \left|x_{S'} + \mathcal{C}_Z^{\perp}\right\rangle$$

We are now ready to give a full description of the realization of the logical operators. The logical Paulis $\mathbf{X}$ and $\mathbf{Z}$ are realized by the application of $X_{S'}$ and $Z_{S'}$. For the gates $\mathbf{S}$ and $\mathbf{T}$, we use single-qubit gate teleportation as presented in Figure 12. In single-qubit gate teleportation, the resource $|\mathbf{S}\rangle$ is initialized as $\mathbf{S}\,|+\rangle$, similarly for $|\mathbf{T}\rangle$. The gate $\mathbf{1}_{S'}$ stands for the classical procedure that, given the measurement results, checks whether the logical bit $|1\rangle$ is turned on. We will return to this gate with a higher resolution depiction of it after the description of the Hadamard teleportation.




Figure 9: Simulating the $\mathbf{S}$ and $\mathbf{T}$ gates, using the $|\mathbf{S}\rangle$, $|\mathbf{T}\rangle$ magic states.

For the Hadamard gate, we use a modification of the standard two-qubit gate teleportation as shown in Figure 13. The realization differs from the standard realization as the measurement in the phase basis is done by first moving to the dual space via the application of physical $\mathbf{H}^{\otimes \mathcal{F}_{d'}^n}$, measuring, reorganizing the qubits through $\phi$, and then checking for the $x_{S/S'}$ outcome (thus, it can be thought of as the application of $\mathbf{H}_\phi$ and then measurement). In addition, unlike the single-qubit gate teleportation, here $|\mathbf{H}\rangle$ is initialized as $I \otimes \mathbf{H}(|00\rangle + |11\rangle)$ (up to normalization).

The classical procedure of logical codeword checking, namely $\mathbf{1}_{x_{S'}}$ / $\mathbf{1}_{x_{S/S'}}$, is divided into five stages. In the first, we find all the connected components of the $\partial^-$-boundary.





Figure 10: Gate teleportation of the Hadamard gate, using the resource $|\mathbf{H}\rangle$. We emphasize that although the Hadamard (at least Hadamard-type) has an $O(1)$-depth gate realization (at least when $d' = d/2$), we still need all the operations on the quantum register to be strictly transversal for the sake of the proof. Thus, we realize the Hadamard via gate teleportation.

Finding connected components can be done in $O(\log^2(n))$ depth (see [SV82] and [AS87] for logarithmic time connected components in the PRAM model and [Lev80] for the simulation of PRAM machines using bounded-fan circuits). Then, we broadcast the connected components. Conceptually, each connected component is sent to its own Toric; technically, we copy components of the syndromes into clean registers. The broadcast also requires at most $O(\log(n))$ depth since there can be at most #checks $= O(n^d)$ connected components and therefore at most $O(n^d)$ copies. Then, we decode each of the copies in parallel. The separation of the components guarantees that during decoding, components will not merge with each other. For the decoding, we iterate sweep-rule cycles (defined in Definition 4.6) until erasing the syndrome. Later, we will see that $n$ cycles succeed to erase the syndrome with high probability[5]. We erase the syndrome by combining the results of all the decoding sessions together by Xoring their correction suggestions. Each of the Xor operations is between at most $O(n^d)$ qubits and therefore requires at most $O(\log(n))$ depth. At this point, we assume that the combined register stores the measurement without errors. We finish by getting back into the logical space, namely a multiplication of binary matrix, which can be done at logarithmic depth $O(\log(n))$ (at the cost of broadcasting into $O(n^{2d})$-wide again). So the overall depth for performing a logical measurement is $O(n)$. The additional classical width cost is due to the broadcasting which introduce at most $O(n^{2d})$ additional classical bits.

[5]In the proof of the Theorem 6.3 we show that $\Theta(n)$-size connected component of the syndrome is not likely to occur.

## 4.6 Propagation Through Gate-Teleportation

Having an explicit description of the gate's realizations enables tracking how faults propagate through the computation. The next claim formulates the transitions of faults via the gate-teleportation gadgets.

**Claim 4.37.** *The propagation of a Pauli through the (conditioned) gate teleportation gadgets has a well-defined structure.*

*Proof.* For chains $x, z \in (\mathcal{F}_d^n; \mathbb{F}_2)$, we denote by $P_{x,z}$ the Pauli consisting of $X$'s and $Z$'s on the faces of $x$ and $z$. We prove the claim by propagating Paulis manually. We start by propagating Pauli through the **S**-teleportation, let $P_{x_1,z_1}$ and $P_{x_2,z_2}$ be the Paulis that act on the first and the second registers. Then:





Figure 11: Pauli propagation trough **S** teleportation.

For the **T**-teleportation, we denote by $P_{x_3,z_3}$ the Pauli act on the third register containing the resource state $|\mathbf{S}\rangle$, which might be used through the gadget to 'correct' the teleportation. Let $\mathbf{1}^2_{x_{S'}}$ be the indicator for the event in which measuring the resource register (that prior to the entangle, holds the state $P_{x_2,z_2}|\mathbf{T}\rangle$) results in $|\bar{1}\rangle$. Then:





Figure 12: Pauli propagation trough **T** teleportation.

Where to infer the last passage we used to the Pauli-propagation through **S**-teleportation. Finally, for the **H**-teleportation we have:





Figure 13: Pauli propagation trough **H** teleportation.

Notice that the Pauli $P_{z_3,x_3}$ consists of applying $X$'s on the $d'$-dimensional faces of the chain $z_3$, and applying $Z$'s on the $d'$-dimensional faces of $x_3$. □

We summarize by restating the claim above for Clifford + measurement gates, which also use sweep-cycles.

**Corollary 4.38.** *Let $C$ be a quantum circuit, such that all its registers are encoded via the nice encoding, and the gates of $C$ are either logical Pauli, transversal* **CX**, *sweep-cycles, or* $\mathbf{H}, \mathbf{S}$, *and* $\mathbf{T}$ *realized via gate-teleportation. Then the propagation of Pauli through a (conditioned) subjection of $C$ has a well defined structure. In particular, the logical operators propagate Paulis in transversal manner.*

# 5 Toom's Contours

## 5.1 The Barrier Argument

We are going to move between the infinite and the finite back and forth, so we will need to extend the size function, and the reduced notion to chains on the finite-complex.

**Definition 5.1.** *Consider a $d'$-dimensional chain on the $d$-dimensional Toric $x \in (\mathcal{F}^n_{d'}; \mathbb{F}_2)$. We extend the notation of size to $x$ as follows. Let $x'$ be the $\infty$-lift of $x$, so $x' \in (\mathcal{F}_{d'}; \mathbb{F}_2)$. Let the chain $y \in (\mathcal{F}_{d'}; \mathbb{F}_2)$ be a subset chain of $x'$ such:*

1. *The projection of $y$ back to finite complex covers $x$.*
2. *The size of $y$ is minimal.*

*Then, we set:*

$$\mathbf{Size}(x) := \mathbf{Size}(y)$$

*The chain $y$ will be referred to as the minimizing cover of $x$. We extend the notation of reduced form to a $d'$-dimensional chain on the finite complex $x \in (\mathcal{F}^n_{d'}; \mathbb{F}_2)$, to be its translation by stabilizers that gets the minimal size. Namely, for $z \in Im\ \partial^- : (\mathcal{F}^n_{d'+1}; \mathbb{F}_2) \to (\mathcal{F}^n_{d'}; \mathbb{F}_2)$, the chain $x+z$ is a reduced form of $x$ if $\mathbf{Size}(x+z)$ is minimal among the choices of $z$.*

In the following, we prove that the definition of the size of chains in the finite complex respects the triangle inequality.

**Claim 5.2.** *Let the chains $x, y \in (\mathcal{F}^n_{d'}; \mathbb{F}_2)$ such that $V(x) \cap V(y) \neq \emptyset$, then:*

$$\mathbf{Size}(x+y) \leq \mathbf{Size}(x) + \mathbf{Size}(y)$$

*Proof.* First, notice that if the $\infty$-lifted chains $x', y' \in (\mathcal{F}_{d'}; \mathbb{F}_2)$ satisfy that the projection of $x'$ covers $x$ and the projection of $y'$ covers $y$, then the projection of $x' \cup y'$ covers $x + y$. Denote the $d'$-dimensional faces in $x, y$ that intersect by $f, g$, and pick $x', y'$ such that $f, g$ are also in $x', y'$. Thus, $V(x') \cap V(y') \neq \emptyset$, and by Claim 4.18, we have:

$$\mathbf{Size}(x+y) \leq \mathbf{Size}(x' \cup y') \leq \mathbf{Size}(x') + \mathbf{Size}(y')$$

To finish, we argue that we can choose $x', y'$ such that $\mathbf{Size}(x) = \mathbf{Size}(x')$ and $\mathbf{Size}(y) = \mathbf{Size}(y')$. Let $\tilde{x} \in (\mathcal{F}_{d'}; \mathbb{F}_2)$ be the $d'$-dimensional chain on the infinite skeleton such that $\mathbf{Size}(x) = \mathbf{Size}(\tilde{x})$. Split into cases depending on whether $f \in \tilde{x}$.

- If $f \in \tilde{x}$, then we can just choose $x' = \tilde{x}$.
- If not, then since the projection of $\tilde{x}$ covers $x$, there must be a vertex $v \in \mathcal{G}_d$, such that $v$ is a product of the integer powers of $g_1^n, \ldots, g_d^n$, and a $d'$-dimensional face $\tilde{f}$ in $\tilde{x}$ such that $\tilde{f}$ is a translation of $f$ by $v$. Then, construct $x'$ by taking the translations of $\tilde{x}$ faces by $v^{-1}$. The size function is invariant to translations, so:

  $$\mathbf{Size}(x) = \mathbf{Size}(\tilde{x}) = \mathbf{Size}(v^{-1}x') = \mathbf{Size}(x')$$

  and in addition, $f = v^{-1}\tilde{f} \in x'$. Moreover, since the projecting is invariant to translation by integer powers of $g_1^n, \ldots, g_d^n$, the projection of $\tilde{x}$ equals the projection of $x'$, namely, covers $x$.

So,

$$\mathbf{Size}(x + y) \leq \mathbf{Size}(x') + \mathbf{Size}(y') = \mathbf{Size}(x) + \mathbf{Size}(y)$$

□

We will use the following two elementary lifting facts and omit their proofs. They are discrete instances of the standard local relation between a Torus and its universal cover: below the periodicity scale, the covering map is injective on the relevant region, so chains may be treated as chains in the infinite lattice. In the Toric-code literature, the same principle appears in the identification of non-trivial logical operators with homologically non-trivial cycles of linear extent [Den+02], and in the restriction of Toric arguments to local regions whose diameter is smaller than the system size [KP19]. The claims below merely formulate this observation for the size function and minimizing covers used here.

**Claim 5.3.** *Let $x \in (\mathcal{F}^n_{d'-1}; \mathbb{F}_2)$ be a $d'-1$ dimensional chain of the finite complex, and let $y \in (\mathcal{F}_{d'-1}; \mathbb{F}_2)$ be the $d'-1$ dimensional chain on the infinite complex such that $y$ is the minimizing cover of $x$. If $\mathbf{Size}(x) < n$, and:*

$$x \in Im\ \partial^- : (\mathcal{F}^n_{d'}; \mathbb{F}_2) \to (\mathcal{F}^n_{d'-1}; \mathbb{F}_2)$$

*Then, also:*

$$y \in Im\ \partial^- : (\mathcal{F}_{d'}; \mathbb{F}_2) \to (\mathcal{F}_{d'-1}; \mathbb{F}_2)$$

**Claim 5.4.** *Let $x \in (\mathcal{F}^n_{d'}; \mathbb{F}_2)$ be a $d'$-dimensional chain of the finite complex. Suppose that $\mathbf{Size}(x) < n$. Then there is a translation $x'$ of $x$ (on the finite complex), such that $x'$ has a minimizing cover $y \in (\mathcal{F}_{d'}; \mathbb{F}_2)$, such that the faces of $y$ align with the finite complex. In other words, '$x' = y$'.*

Next, we translate the fact that a chain enclosing a non-trivial loop has a size which is at least the side of the Toric.

**Claim 5.5.** *Suppose that the chain $x \in (\mathcal{F}^n_{d'}; \mathbb{F}_2)$ closes a non-trivial loop on the Toric, then* $\mathbf{Size}(x) \geq n-1$.

*Proof.* Let $x' \in (\mathcal{F}_{d'}; \mathbb{F}_2)$ be a minimizing cover for $x$. In particular, there are vertices $v_1, \ldots, v_l$ in $x'$ such that their projection corresponds to the non-trivial loop in $x$. Assume the non-trivial cycle is in the $g$-direction, thus the $L_g$ values of the projections of $v_1, \ldots, v_l$ cover all the integer range $\{0, 1, \ldots, n-1\}$. Thus, there are two vertices $v, u \in v_1, \ldots, v_l$ such that their $L_g$-difference is at least $L_g(u) - L_g(v) \geq n-1$. Thus,

$$\mathbf{Size}(x) = \mathbf{Size}(x') \geq \mathbf{Size}(\{u, v\}) \geq n-1$$

□

Using the claim above, we are able to introduce the notion of filling boundaries. The following claim states that if the connected components of the boundary are all of size lower than $n$, then we can match each of them to a chain such that its boundary agrees with the component and its size is lower than the component size. That will lead us to define the filling operator (Definition 5.7).

**Claim 5.6.** *Let $x \in (\mathcal{F}^n_{d'}; \mathbb{F}_2)$ be a $d'$-dimensional chain. Suppose that there is an integer $l \leq n-1$ such each connected component of $\partial^- x$ has size $< l$. Then there are $d'$-dimensional chains $y_1, y_2, \ldots$ such that each $\partial^- y_i$ is a connected component of $\partial^- x$ and* $\mathbf{Size}(y_i) \leq \mathbf{Size}(\partial^- y_i)$.

*Proof.* Consider a $d'$-dimensional chain $x \in (\mathcal{F}^n_{d'}; \mathbb{F}_2)$ such that $\partial^- x$ has a decomposition $\partial^- x = \tilde{x}_1 + \tilde{x}_2$, where $\tilde{x}_1, \tilde{x}_2$ are $d'-1$-dimensional chains, and $\tilde{x}_1$ is a connected component of $\partial^- x$. In particular $\tilde{x}_1$ is not connected to $\tilde{x}_2$. By disconnectivity, $\tilde{x}_1$ does not share a $d'-2$ dimensional face with $\tilde{x}_2$. Thus, $\partial^- \tilde{x}_1$ and $\partial^- \tilde{x}_2$ are disjoint. On the other hand, since $\partial^{-\circ 2} x = 0$, then combining with disjointness, it follows that:

$$\partial^- (\tilde{x}_1 + \tilde{x}_2) = 0 \Rightarrow \partial^- \tilde{x}_1 = \partial^- \tilde{x}_2 = 0$$

Namely, $\tilde{x}_1 \in \ker \partial^- : (\mathcal{F}^n_{d'-1}; \mathbb{F}_2) \to (\mathcal{F}^n_{d'-2}; \mathbb{F}_2)$. Suppose $\tilde{x}_1 \notin \text{Im } \partial^- : (\mathcal{F}^n_{d'}; \mathbb{F}_2) \to (\mathcal{F}^n_{d'-1}; \mathbb{F}_2)$, then we have that $\tilde{x}_1$ is a non-trivial codeword of the $(d, d'-1)$-Toric code. Since $d' \geq 2$, and $\tilde{x}_1$ has to close a non-trivial loop, so by Claim 5.5, the size of $\tilde{x}$ is at least $n-1$, which is a contradiction. So we get that $\tilde{x}_1 \in \text{Im } \partial^- : (\mathcal{F}^n_{d'}; \mathbb{F}_2) \to (\mathcal{F}^n_{d'-1}; \mathbb{F}_2)$. In particular, there is a $d'$-dimensional chain $x_1$ such that $\partial^- x_1 = \tilde{x}_1$. We argue that $x_1$ can be chosen such $\mathbf{Size}(x_1) \leq \mathbf{Size}(\tilde{x}_1)$.

By Claim 5.4, since $\mathbf{Size}(\tilde{x}_1) < n$, there is a translation of the finite complex for which the minimizing cover of the translation of $\tilde{x}_1$ aligns with the finite complex. Since the size function is invariant to translations, we can assume, without loss of generality, that the given finite complex is already translated. Consider the minimizing cover of $\tilde{x}_1$, and denote it by $\tilde{y_1}$ Since $\mathbf{Size}(\tilde{x}_1) < n$, then by Claim 5.3 we have that $\tilde{y}$ can be chosen such:

$$\tilde{y} \in \text{Im } \partial^- : (\mathcal{F}_{d'}; \mathbb{F}_2) \to (\mathcal{F}_{d'-1}; \mathbb{F}_2)$$

Let $y \in (\mathcal{F}_{d'}; \mathbb{F}_2)$ be a $d'$-dimensional reduced chain such that $\partial^- y = \tilde{y}$. By the definition of the algorithm in Claim 4.24, from which $y$ is obtained, it follows that the potential walls that bound $\tilde{y}$ also bound $y$, and therefore $y$ is also aligned with the finite complex. Thus, we can take $x_1$ to be equal to $y$. By Claim 4.24:

$$\mathbf{Size}(x_1) = \mathbf{Size}(y) = \mathbf{Size}(\partial^- y) = \mathbf{Size}(\tilde{y}) = \mathbf{Size}(\tilde{x}_1)$$

So $x_1$ satisfies the desired condition for the connected component $\tilde{x}_1$. To complete, we repeat recursively on the connected components of $\tilde{x}_2$. □

**Definition 5.7.** *Let $x \in (\mathcal{F}^n_{d'}; \mathbb{F}_2)$ be a $d'$-dimensional chain. $x$ will be said to be a fillable chain if each of the connected components of its $\partial^-$-boundary, namely $\partial^- x$, has size $< n-1$. By Claim 5.6, there are $d'$-dimensional reduced chains $x_1, \ldots,$ such that each $\partial^- x_i$ is a connected component of $\partial^- x$. Thus:*

$$\partial^-(x + \sum_i x_i) = 0 \quad \Rightarrow x + \sum_i x_i \in \ker \partial^- \colon (\mathcal{F}^n_{d'}; \mathbb{F}_2) \to (\mathcal{F}^n_{d'-1}; \mathbb{F}_2)$$

*Namely, $x + \sum_i x_i$ is a codeword in $\mathcal{C}_X / \mathcal{C}_Z^{\perp}$. We define the filling operator, denoted by $[x]$, which for a given fillable chain $x$, returns the homology class (logical operator) of $x + \sum_i x_i$. Lastly, to ensure that the filling operator is canonical, fix for each $d'-1$-dimensional chain, which is a connected component, a unique reduced $d'$-dimensional chain. With the notations above, for each $\partial x_i$ fix a unique $x_i$.*

The following claim tracks the evolution of the connected component of the boundary (in terms of the maximal size), where the process is restricted such that in each step the chain is allowed to differ by at most a single face.

**Claim 5.8.** *Let $x_1, x_2 \in (\mathcal{F}^n_{d'}; \mathbb{F}_2)$ be $d'$-dimensional chains, and let $l$ be an integer such the Hamming distance between $x_1$ and $x_2$ is at most $l$. Denote by $r$ the size of the maximal connected component of $\partial^- x_1$. Then the maximal size of a connected component of $\partial^- x_2$ is at most $4\binom{d'}{2} l(r+1)$*

*Proof.* Consider the adjacency graph (definition 4.2) with respect to the $d'-1$-dimensional chain $\partial^- x_1$, where each vertex is a $d'-1$-dimensional face of $\partial^- x_1$, and each edge in the graph is a $d'-2$ face in the intersection of two $d'-1$-dimensional faces in $\partial^- x_1$. A $d'$-dimensional chain contains $4\binom{d'}{2}$. Hence, introducing a new $d'$-dimensional face to $x_1$ adds at most $4\binom{d'}{2}$ edges to the adjacency graph, each corresponding to a $d'-2$ face contained in the new $d'$-dimensional face. So introducing $l$ faces into $x'_i$ adds at most $4\binom{d'}{2} l$ new edges, and therefore connects at most the same number of connected components in $\partial^- x'_1$, or a connected component induced by the additional $l$ faces. Using the triangle inequality for intersecting sets (Claim 5.2), we have that any connected component of $\partial^- x'_2$ is at most $4\binom{d'}{2} l$ times the maximal size of a connected component of $\partial^- x_1$, namely $4\binom{d'}{2} l(r+1)$ (Where the 1 in the closure stands for the connected components of a single face, each corresponding to one of the additional $l$ faces.) □

Next, we present the main claim of the section, which argues that for a sequence of chains $x_1, \ldots, x_t$, such that any two sequential chains differ by at most a single face, if $[x_1] \neq [x_t]$, then there must be an intermediate step $i$ such that $\partial^- x_i$ has a connected component with sufficiently large size. After that, we present claim 5.10, which generalizes the claim to allow sequential elements to be at a distance greater than one.

**Claim 5.9.** *Let $x_1, \ldots, x_t \in (\mathcal{F}^n_{d'}; \mathbb{F}_2)$ be $d'$-dimensional chains, such that $x_1$ is a trivial chain and for any $i \in [t-1]$, the Hamming distance between $x_i$ and $x_{i+1}$ is one. There is a constant $c \in (0,1)$, depending only on $d, d'$, such that if $n$ is sufficiently large, and for any $x_i \in x_1, \ldots, x_t$, the size of each of the connected components of $\partial^- x_i$ is bounded by $cn$, then:*

$$[0] = [x_1] = [x_2] = ... = [x_t]$$

*Proof.* Assume through contradiction that there is $i$ such that $0 = [x_i] \neq [x_{i+1}]$. Denote by $x_i^1, x_i^2, \ldots$ and $x_{i+1}^1, x_{i+2}^2, \ldots$ the reduced $d'$-dimensional chains such that $\partial^- x_i^j$ is a connected component of $\partial^- x_i$, as defined in Definition 5.7. Hence:

$$[x_{i+1}] \sim_{\mathcal{C}_{Z^\perp}} [x_{i+1}] + [x_i] \sim_{\mathcal{C}_{Z^\perp}} x_i + x_{i+1} + \sum_j x_i^j + \sum_j x_{i+1}^{j+1}$$

Denote by $w$ the chain:

$$w := x_i + x_{i+1} + \sum_j x_i^j + \sum_j x_{i+1}^{j+1}$$

Since the Hamming distance between $x_i$ and $x_{i+1}$ is at most one, and since each $d'$-dimensional face contributes a constant support over $d'-1$-dimensional chains, the $\partial^-$-boundaries of $x_i$ and $x_{i+1}$ are at a Hamming distance that is at most constant. Therefore, there are only constant connected components of $\partial^- x_i$ which are not connected components in $\partial^- x_{i+1}$ and vice versa. Denote by $y_1, \ldots, y_m$ the chains in $x_i^1, \ldots$ and $x_{i+1}^1, \ldots$ such that they belong to only one of the collections. Where $m$ is bounded by a function of $d, d'$, namely $m \leq M(d, d')$. So:

$$\sum_j x_i^j + \sum_j x_{i+1}^{j+1} = \sum_j^m y_j$$

Moreover, the vertices of any of $y_1, \ldots, y_m$ and $x_{i+1} + x_i$ have a nontrivial intersection. To see this, suppose that the vertices of $y_j$ do not intersect the face $x_{i+1} + x_i$, and assume without loss of generality that $\partial^- y_j$ is a connected component of $\partial^- x_i$. Then, the vertices of $\partial^- y_j$ also do not intersect the vertices of $\partial^-(x_i + x_{i+1})$. So $\partial^- y_j$ is also a connected component of

$$\partial^- x_i + \partial^-(x_{i+1} + x_i) = \partial^- x_{i+1}$$

which is contradiction to the choices of the $y_i$s. Therefore:

$$\mathbf{Size}(w) \leq \mathbf{Size}(x_i + x_{i+1}) + \sum_{j}^{m} \mathbf{Size}(y_j) \leq d + M(d,d')cn$$

Thus, for sufficiently large $n$ ,if $c < \frac{1}{M(d,d')+1}$, we have that $\mathbf{Size}(w) < n-1$, a contradiction for $w$ being a non-trivial codeword. □

**Claim 5.10.** *Let $x_1, \ldots, x_t \in (\mathcal{F}_{d'}^n; \mathbb{F}_2)$ be $d'$-dimensional chains defined as in Claim 5.9, with the change that any two sequential chains $x_i, x_{i+1}$ are at a Hamming distance of at most $\Delta$, and setting the constant $c' \leftarrow c/(8\binom{d'}{2}\Delta)$. Then the claim still holds.*

*Proof.* Let $x'_1, \ldots, x'_{\Delta t+1}$ be the chains obtained from $x_1, \ldots, x_t$ by taking the stacking between any two sequential elements $\Delta - 1$ chains, such that any two sequential chains of the resulted set are at Hamming distance at most one. Namely, for any $i \in [t]$, we have that $x'_{1+i\Delta} = x_{i+i}$ and $x'_{i+1}$ differs from $x'_i$ by at most one coordinate. By Claim 5.8, each connected component of $\partial^- x'_i$ has a size of at most $4\binom{d'}{2}\Delta(c'n+1) \leq cn$.

Thus, by Claim 5.9,we have that:

$$[0] = [x'_1] = [x'_2] = \ldots = [x'_{\Delta t+1}]$$

In particular:

$$\begin{aligned} &[0] = [x'_1] = [x'_{1+\Delta}] = \ldots = [x'_{1+i\Delta}] = \ldots = [x'_{\Delta t+1}] \\ \Rightarrow &[0] = [x_1] = [x_2] = \ldots = [x_t] \end{aligned}$$

□

We summarize the section with the following corollary that incorporates the above insight into an ongoing computation. Namely, changing the logical codeword implies an intermediate step with a sufficiently large connected component of the syndrome. In the computation context, the sequence of the chains is derived from the Paulis in the step-propagation of a conditioned subject circuit.

**Corollary 5.11** (Barrier argument)**.** *Let $c' \in (0,1)$ be the constant as defined in Claim 5.10. Let $P_1, \ldots, P_{\tau_f}$ be a step-propagation of a conditioned subjected circuit $C[\mathcal{E}, \alpha]$ (Definition 3.10). Assume that the arity of the gates of $C$ is bounded by $\Delta$, and that each of the registers in $C$ is encoded in the $(d,d')$-Toric code. Denote by $R$ the number of quantum registers in $C$. For a Pauli $P_\tau$ in the step-propagation, denote by $x_\tau \in (\mathcal{F}_{d'}^n; \mathbb{F}_2)^{\otimes R}$ the $X$-component of $P_\tau$ and by $x_\tau|_{R_j}$ the restriction of $x_\tau$ to register $R_j$. Then, if for any step $\tau$ and for any register $R_j$, there is not a connected component of $\partial^- x_\tau|_{R_j}$ of size greater than $c'n$, then:*

$$[x_{\tau_f}|_{R_j}] = [0]$$

*A similar result holds for the $Z$-components, where we define $z_\tau|_{R_j}$ to be the $d-d'$-dimensional chain obtained by applying the $\phi$-transpose on the chain supporting the $Z$-component of $P_\tau$ restricted to the register $R_j$.*

*Equivalently, if the subjected computation introduces a logical error, then at some intermediate step one of the $X$- or $Z$-syndromes has a connected component of size at least $c'n$.*

*Proof.* The proof follows immediately from Claim 5.10, where we use the fact that the arity is bounded by $\Delta$, and therefore sequential Paulis in the step-propagation are at a Hamming distance of at most $\Delta$. □

**Remark 5.12.** *Consider the application of an iterative sweep rule over a chain whose boundary is at a size lower than $c'n$. Since the sweep rule only decreases the size of the boundary, it is easy to see that along the application, the size of the connected component of the boundary is kept below $c'n$. Thus, each time, the filling operator will accomplish the chain to the same codeword. In particular, we get that decoding a measurement as presented in Definition 4.36 doesn't result in a logical error, provided that each of the connected components of the boundary, prior to the broadcast, does not have a size exceeding $c'n$.*

## 5.2 Toom's Contours

We are about to zoom out from a single register encoded in the Toric code to describe a fully fault-tolerant computation. For a given quantum circuit, assumed to consist of gates $\mathbf{X}, \mathbf{Z}, \mathbf{CX}, \mathbf{H}, \mathbf{S}, \mathbf{T}$ and measurements, we define its Toric encoded circuit as its version where each qubit is encoded by the Toric code. Formally:

**Definition 5.13** (Troic Encoded Circuit)**.** *Let $C$ be a quantum circuit. We say that $C$ is a Toric encoded circuit if the following holds:*

1. *Any layer of the circuit consists of classical and quantum registers, such that there is a Toric code $\mathcal{C}$ such that the quantum registers are encoded by the nice encoding of $\mathcal{C}$. At time $t = 0$, the quantum registers are initialized to be either $|\bar{0}\rangle$, encoded $|\mathbf{H}\rangle$, encoded $|\mathbf{S}\rangle$, or encoded $|\mathbf{T}\rangle$. The classical registers are initialized to be zeros.*

2. *The layers of $C$ on the quantum registers at even times are sweep-cycles, and the layers at odd times are realizations of either logical Paulis, $\mathbf{CX}$, or measurements in the computational and parity bases. On the classical registers, including the measured register, we allow any two-bit gates.*

For Toric encoded circuits, we define their *base graph*, which can be thought of as a recording of a running from the Toric's point of view. The *base graph* is obtained by taking the Toric's vertices at different times as the vertices and connecting any two sequential in time if they are support faces — qubits — which are either the same or are entangled by a quantum gate.

**Definition 5.14** (Base graph $G_o$)**.** *Let $C$ be a Toric encoded circuit at depth $\mu$. Notice that measurements take quantum registers into classical, Thus any quantum register has a maximal depth, which we denote by $\{\mu_i\}$. Let's denote by $\{\mathcal{G}_i\}$ the skeleton of the $\infty$-lift of the Toric complexes that induce the codes. We define the base graph of $C$, denoted by $G_o = (V_o, E_o)$, as follows:*

1. *The vertices $V_o$ are tuples, where the first coordinates correspond to a vertex in the disjoin union over the vertices in $\{\mathcal{G}_i\}$, and the second coordinate is associated with a time. Namely:*

$$V_o := \bigcup_i \big(V(\mathcal{G}_i) \times [\mu_i]\big)$$

2. *The edges $E_o$ are derived from the original edges in $\mathcal{G}_1, \ldots, \mathcal{G}_k$, with the addition that any two vertices in preceding times $t$ and $t+1$ that support qubits (faces) such that $C^\infty$ acts non-trivially on those qubits at time $t$ are also connected by an edge. Namely:*

$$\begin{aligned} E_o := \big\{\{(v,t),(u,t')\} :\ & \textit{if} \\ & \textit{either there exists } i \textit{ such } \{v,u\} \in \mathcal{G}_i \textit{ and } t' = t+1 \\ & \textit{or there exists } u_i = (g_i, l_i) \in C^\infty \textit{ such } v,u \in l_{i,2} \textit{ and } t = l_{i,1}, t' = l_{i,1}+1\big\} \end{aligned}$$

*Where we define a vertex $v$ to belong to location $l$ if there is a qubit-face $f$ in $l$ such that $v$ belongs to its associated face.*

Notice that since the gates' locations are invariant to the conditioning of outcomes measurement (Remark 3.9), we have that for any outcomes vector $\alpha \in \mathbb{F}_2^{(\cdot)}$, the base graph of the conditioned circuit $C[\mathcal{E}, \alpha]$ is the same as for $C[\mathcal{E}]$.

As a concept, if the base graph is a recording of a run from the Torices' point of view, then a *Toom's contour* is a recording of the deviation's evolution in the eyes of the Torices' vertices. We use the notion of $x, z$-component of a lifted Pauli and the Pauli-path to describe a deviation:

**Definition 5.15.** *Let $P \in \mathcal{P}^{(\cdot)}$ be a Pauli, and let $Q \in \mathcal{P}^{(\cdot)}$ be its $\infty$-lift. Assume that $P$ acts on a Toric encoded circuit, namely it has a decomposition such that each element of it acts on a register encoded in the $(d, d')$-Toric code. We denote by $x(Q)$ the $d'$-dimensional chain in the infinite complex that supports the $X$-component of $Q$, and by $z(Q)$ the $d-d'$-dimensional chain, such that the inversion of the $\phi$-transpose sends it to the $d'$-dimensional chain that supports the $Z$-component of $Q$, namely $\phi^{-1}(z(Q))$ is the chain that supports the $Z$-component.*

**Definition 5.16.** *Consider the propagation $(\mathbf{P}, \mathbf{a})$ of a conditioned subject circuit $C[\mathcal{E}, \alpha]$ (Definition 3.10). A Pauli-path of $C[\mathcal{E}, \alpha]$ is the $\infty$-lift of the Paulis in $\mathbf{P}$.*

For a Pauli-path $P_1, .., P_{\mu+1}$, the Toom's contour is the restriction of the base graph to vertices that witness a deviation, namely, those that belong to qubits supporting $P_1, P_2, .., P_{\mu+1}$.

**Definition 5.17** (Toom's Contour Graph of $C(\mathcal{E}, \alpha)$, (Standard form))**.** *For a Toric encoded quantum circuit $C$, set of faults $\mathcal{E}$, measurements outcomes $\alpha$, and a Pauli-path $P_1, ..$ of $C[\mathcal{E}, \alpha]$. We define the Toom's contour graph $\mathcal{H} = (V_\mathcal{H}, E_\mathcal{H})$ as follows:*

1. *The vertices $V_{\mathcal{H}} = V_{\mathcal{H},X} \cup V_{\mathcal{H},Z}$ correspond to vertices of faces supporting the Pauli-path. They consist of the triple $(v,t,\cdot)$ where $(v,t)$ is a vertex of the base graph, and the third is a symbolic coordinate that is either $\{X\}$ or $\{Z\}$ corresponding to the component of the Pauli that $v$ supports at time $t$.*

$$\begin{aligned} V_{\mathcal{H},X} :=& \big\{ v_t \times \{X\} : v_t = (v,t) \in V_o \\ & \qquad \text{and there exists a face } f \in \partial^- x(P_t) \text{ such } v \in f \big\} \\ V_{\mathcal{H},Z} :=& \big\{ v_t \times \{Z\} : v_t = (v,t) \in V_o \\ & \qquad \text{and there exists a face } f \in \partial^- z(P_t) \text{ such } v \in f \big\} \end{aligned}$$

2. *The edges $E_{\mathcal{H}}$ is partitioned into two types $A_{\mathcal{H}}$ and $F_{\mathcal{H}}$. For any realization of logical gate $g$ which applied in time $t$ in $C[\mathcal{E}]^\infty$, we denote by $E_o|_g$ the edges in $E_o$ which induced by $g$. Then, we add edge to $A_{\mathcal{H}}$ as follow:*

   (a) *If $g$ does not belong to the faults, namely $g \notin \mathcal{E}$, and $g$ is not a measurement in the phases-basis, then we add the arrows:*

$$\begin{aligned} &\big\{ \{\tilde{u} = (u,t,\cdot), \tilde{v} = (v,t+1,\cdot)\} : \{\{u,t\},\{v,t+1\}\} \in E_o|_g \text{ and } \tilde{v}, \tilde{u} \in V_{\mathcal{H},X} \\ &\quad \text{or } (v,t+1,\cdot)\} : \{\{u,t\},\{v,t+1\}\} \in E_o|_g \text{ and } \tilde{v}, \tilde{u} \in V_{\mathcal{H},Z} \big\} \end{aligned}$$

   *Where if $g$ is a measurement in the phase-basis, then we add type-alternating arrows as follows:*

$$\begin{aligned} &\big\{ \{\tilde{u} = (u,t,\{Z\}), \tilde{v} = (v,t+1,\{X\})\} : \{\{u,t\},\{v,t+1\}\} \in E_o|_g \\ &\quad \text{and } \tilde{v} \in V_{\mathcal{H},X}, \tilde{u} \in V_{\mathcal{H},Z} \big\} \end{aligned}$$

   (b) *Else, if $g \in \mathcal{E}$ then, we add:*

$$\big\{ \{\tilde{u} = (v,t,\cdot), \tilde{v} = (v,t+1,\cdot)\} : \text{ such either } \tilde{u} \in V_{\mathcal{H},X} \text{ or } \tilde{u} \in V_{\mathcal{H},Z} \big\}$$

   *To construct $F_{\mathcal{H}}$, we connect any pair of vertices $(v,t)$, $(u,t)$ if there exists a vertex $(w,t+1)$ such both of them are connected to it trough $A_{\mathcal{H}}$. Namely:*

$$F_{\mathcal{H}} = \big\{ e = \{u,v\} : \text{ exists } w \in V_{\mathcal{H}} \text{ such } \{v,w\},\{u,w\} \in A_{\mathcal{H}} \big\}$$

*We call $A_{\mathcal{H}}$ and $F_{\mathcal{H}}$ the arrows and forks edges respectively.*

For the analyses, we would like to extend Toom's contour to record in their final layer a partial time-step, namely a computation up to a certain step. For this, we first consider Toom's contour of the partial computation circuit up to a step (Definition 3.2). Then, since we would like to refer to the connected chain at the final layer as the 'final error clusters', we add at the end a layer whose purpose is to connect in time (by arrows) the connected components of Toom's contour in the prior layer, which are connected by checks (their union is identified with a connected chain).

**Definition 5.18** (Analysis Toom's Contour Up to Step $\tau$)**.** *For a Toric encoded quantum circuit $C$, a set of faults $\mathcal{E}$, outcomes $\alpha$, and a step $\tau$, let $C[\mathcal{E},\alpha]_\tau$ be the partial computation circuit of $C[\mathcal{E},\alpha]$ up to step $\tau$. We define the analysis Toom's contour at step $\tau$ $\mathcal{H}_\tau = (V_\mathcal{H}, E_\mathcal{H})$ to be the graph obtained by taking the Toom's contour of $C[\mathcal{E},\alpha]_\tau$ and adding edges as follows:*

1. *Let $t$ be the depth of $C[\mathcal{E},\alpha]_\tau$. We add the following additional arrows:*

   $\big\{\{\tilde{u} = (u, t-1, \cdot), \tilde{v} = (v, t, \cdot)\}$ *if either there exists*
   *a $d'-2$ dimensional face $f$ such $\tilde{u}, \tilde{v} \in V_{\mathcal{H},X}$ and $u, v \in f$*
   *or there exists a $d-d'-2$ dimensional face $f$ such $\tilde{u}, \tilde{v} \in V_{\mathcal{H},Z}$ and $v, u \in f\big\}$*

2. *Then, we add forks to preserve the property that any two vertices with the same time coordinate, which are connected to a third (with a $+1$ higher time coordinate) via arrows, are also connected by a fork.*

## 5.3 Space-Time Graph

Not a few of the results about Tooms contours are derived from their 'directed' structure, regardless of their connection to Torices. Thus, we split the discussion to talk about *space-time graphs*, which are graphs whose edges can be partitioned into arrows and forks.

Here, we present the results and proofs first given by Berman and Simon [BS88] and later by Gacs [Gac21] about *space-time grahps*. Although the proofs we give are almost identical, we chose to present them rather than referring to the sources. The reason for this is that in the language appearing in [BS88] and [Gac21], vertices are bits[6], so conceptually their Toom's contours track different creatures. Thus, jumping into their text while keeping our image in mind might cause confusion, which we would like to avoid.

**Definition 5.19.** *Consider a graph $G = (V, A, F)$, where $V$ is a set of vertices, and $A$ and $F$ are sets of undirected edges. Let $T\colon V \to \mathbb{N}$, We say that $(G, T)$ is a space-time graph if and only if:*

1. $\{x, y\} \in A \Rightarrow T(y) = T(x) \pm 1$
2. *For $x, y \in V$ $\{x, y\} \in F$ if and only if there exists $z \in V$ such both $\{x, z\}, \{y, z\} \in A$, and $T(x) = T(y) = T(z) - 1$.*

*Additionally, for any vertex $v \in V$ of the space-time graph, denote by $pre(v)$ the set of vertices defined as follow:*

$$pre(v) := \{u \in V\colon \{u, v\} \in A \text{ and } T(v) = T(u) + 1\}$$

[6] It is also true that the gates are different, yet that difference alone does not constitute a conceptual change.

*We extend the notion for subsets of vertices $X \subset V$ by $pre(X) = \bigcup_{v \in X} pre(v)$. We will call $T$ the time coordinate, $A$ arrows, and $F$ forks. Observe that from the second requirement, it follows that forks can connect only vertices that have the same time value (set by $T$).*

**Remark 5.20.** *The Toom's contour graph defined in Definition 5.17 is, by definition of it's construction, a time-graph.*

The history of a vertex consists of all the vertices that are connected to it by arrows. Here we allow passing trough arrows in both directions, so it might be possible that the history of vertex $u$ contains vertices with the same time coordinate as $u$. That motivates to define *slices*. A *slice* is a (maximal) subset of vertices with the same time coordinate such they share the same history. In [BS88], slices take the role of error droplets.

**Definition 5.21** (History, Slice)**.** *For a time graph $(G, T)$ and a vertex $u \in V$, let the history of $u$, denoted by $H_u$, be the restriction of $G$ to vertices that both precede $u$ in time (namely, vertices whose time $\leq T(u)$) and connect to $u$ via a path of arrows. A slice is a maximal subset of vertices $K \subset V$ such that for any two vertices $u, v \in K$, $H_u = H_v$ is satisfied. As a consequence, the time coordinate in $K$ has to be constant. Thus, we can extend the time coordinate and the history to slices and write for a slice $K$, $T(K)$ and $H_K$.*

The following claim ensures us an 'independent' argument about slices. Here we state that two slices with the same time coordinate have to hold disjoint histories. Another way to think about this is that if the first and the second slices are 'induced by $n_1$ and $n_2$ faults,' then the slice obtained by merging them 'is induced by $n_1 + n_2$ faults.'

**Claim 5.22.** *Let $K_1, K_2$ be two slices such that $T(K_1) = T(K_2)$, then either $K_1 = K_2$ or $H_{K_1}, H_{K_2}$ are disjoint.*

*Proof.* Assume a non-empty intersection, so there exists $z \in H_{K_1} \cap H_{K_2}$ such that for any $x \in K_1$ and $y \in K_2$, there exist arrow-paths $z \to x$ and $z \to y$. Thus, for any $w \in H_{K_1}$, one can concatenate a path $w \to x \to z \to y$ and conclude that $y \in H_{K_2}$. □

Next, we would like to study how slices look a moment before they merge. For this, we define the *graph of a slice*. We construct this graph by taking a slice and considering all the slices that precede it by a single time unit. We take those slices as vertices and connect any two of them that have vertices sharing a fork.

**Definition 5.23** (The Graph of Slice)**.** *Let $K$ be a slice. The graph of $K$, denoted by $G_K = (V_K, E_K)$, is the graph whose vertices are slices $R \subset H_K$ with $T(R) = T(K) - 1$. Two vertices are connected by an edge if and only if there is a fork whose ends belong to the slices associated with them. Namely, $S, R \in V_K$ are connected in $G_K$ if and only if there is $\{s, r\} = f \in F$ such that $s \in S$ and $r \in R$.*

The graph of slices is connected. That fact means that a spanning tree of a (subgraph of) a slice's history can be found by combining the spanning trees of its processors. The following gives the proof:

**Claim 5.24.** *$G_K$ is connected.*

*Proof.* Let $R, S \in V_K$ and consider $r, s \in V$ such that $r \in R, s \in S$. Recall that $R, S \subset H_K$ and therefore $r, s \in H_K$, Thus, by definition of the 'History' there exists a path, passing trough arrows only, from $r$ to $s$ in $H_K$. Consider a path that is minimal in the number of vertices with a time coordinate equal to $T(K)$; denote that number by $k$. We prove by induction on $k$ that $R$ and $S$ are connected in $G_K$.

1. Base. $k = 0$, In this case, any vertex on the path between $r$ and $s$ has an equal or lower time coordinate than $r$ and is also connected to $r$ via a path of arrows, namely belongs to $H_r$. In particular, $s$ is also a vertex on the path, and therefore $s \in H_r \Rightarrow H_r = H_s$, so $R = S$.

2. Induction step. Since $k > 0$, there exists a vertex $y$ on the path from $r$ to $s$ such that $T(y) = T(K)$. Let $x$ be the vertex which precedes $y$ on the path, and $z$ be the vertex that follows $y$. Since the values of $T$ at the two ends of an arrow differ by 1, and since $y$ gets the maximal $T$ value in $H_K$ it follows that:

   (a) $\{x, z\} \subset \mathrm{pre}(y) \Rightarrow \{x, z\} \in F$.

   (b) The slices of $x$ and $z$, say $K_x$ and $K_z$ has time value $T(K_x) = T(K_z) = T(K) - 1$, Namely they are both members of $V_K$.

   Since the path connecting $r, x$ in $H_K$ has $k - 1$ vertices with $T(\cdot) = T(K)$, then by the induction hypothesis, $R$ and $K_x$ are connected in $G_K$, and by similar argument so are $K_z$ and $S$. On the other hand, $\{x, z\} \Rightarrow \{K_x, K_z\} \in E_K$. Thus, $R$ and $S$ are connected in $G_K$.

□

Now, we would like to plug in the fact that the vertices originate from the infinite plane. To do so, we equip slices with poles. The poles are the vertices in the slice, which are the maximal points of potential walls.

**Definition 5.25** (Poles Selection)**.** *Let $(G, T)$ be a space-time, whose vertices are associated with points in $\mathbb{R}^d$. Let $A$ be either a slice, arrow, or a fork in $(G, T)$. We define a poles selection for $A$ to be a selection of $d+1$ vertices, $v_1, .., v_{d+1}$ , not necessary different, from $A$. The size of $A$ is defined to be:*

$$\mathbf{Size}(A) := \sum_{i}^{d+1} \max_{v \in A} L_i(v)$$

*Thus, for any selection of poles $v_1, .., v_{d+1}$ we have that:*

$$\mathbf{Size}(A) \geq \max_{v \in A} L_i(v_i)$$

*For a vertex $u$, we define the ith predecessor of a $u$, denoted by $pre_i(u)$, to be it's predecessor which achieves the maximal value of $L_i$, namely:*

$$pre_i(u) := \arg \max_{v \in pre(u)} L_i(v)$$

The following claim relates the size of a given slice to the sizes of its predecessor slices.

**Claim 5.26.** *Consider a time graph $(G, T)$ whose vertices are associated with points in $\mathbb{R}^d$. Let $K$ be a slice in $G$, such that $K \neq H_K$. Let $v_1, \ldots, v_{d+1}$ be a pole selection for $K$. Then for some integer $k$, there exist $k+1$ slices $K_0, K_1, \ldots, K_k$ and $k$ forks $F_1, \ldots, F_k$ with pole selections for them that satisfy:*

1. *For any $i \in [d+1]$, the ith predecessor $pre_i(v_i)$ belongs to the selected poles of $K_0, \ldots, K_k$.*
2. *Consider the graph whose vertices are associated with $K_0, \ldots, K_{k+1}$, and there is an edge between $K_i$ and $K_j$ if and only if there is a fork in $F_1, \ldots, F_k$ that intersects both $K_i$'s and $K_j$'s selected poles. Then the graph formed from $K_0, \ldots, K_k$ is connected.*
3. *For any $j \in [0, k]$, denote by $v_j^1, .., v_j^{d+1}$ the selected poles for $K_j$, then:*

$$\sum_{j=0}^{k} \sum_{i=1}^{d+1} L_i(v_j^i) + \sum_{i=1}^{k} \mathbf{Size}(F_i) \geq \sum_{i=1}^{d+1} L_i\left(pre_i(v_i)\right)$$

*Proof.* First, notice that $K$ doesn't contain leaves in $(V, A)$, since a leaf is connected only to itself via arrows, and therefore its 'slice' equals its 'History'. Thus, $\text{pre}_i(v_i)$ is not empty for any $i \in [d+1]$. Next, consider the graph $G_K = (V_K, E_K)$ from Definition 5.23. Since $\{v_i, \text{pre}_i(v_i)\}$ is an arrow, $\text{pre}_i(v_i)$ belongs to a slice in $V_K$. For $i = 1, \ldots, d+1$, denote by $R_i$ the slice in $V_K$ that contains $\text{pre}_i(v_i)$.

By Claim 5.24 $G_K$ is connected and therefore there exist a minimal collection $K_0, .., K_k$ of slices form $V_K$ which contains $R_1, R_2, ..R_{d+1}$, and which is connected in $G_K$. We pick a set of forks $\mathbf{F} = \{F_1, .., F_k\}$ which realizes a spanning tree for this collection of slices.

Let us denote by $J_0, .., J_{2k}$ the enumerated union $K_0, ..K_k, F_1, .., F_k$. Observes that for any choice of $(d+1)(2k+1)$ elements $z_0^1, z_0^2, z_0^3, .., z_0^{d+1} .., z_{2k}^{d+1}$ in $\mathbb{R}^d$, such that $z_j^i \in J_j$ it holds that:

$$\sum_{j=0}^{k} \sum_{i=1}^{d+1} L_i(z_j^i) + \sum_{i=1}^{k} \mathbf{Size}(F_i) \geq \sum_{j,i} L_i(z_j^i) \tag{1}$$

Later, we are going to take the points $\{z_j^i\}$ from the intersection of $J_j$'s. For convenience, let us assume that for the index subset $X \subset [2k] \cup \{0\}$, the intersection $\bigcap_{j \in X} J_j$ returns a single point. If there is more than one, then decide on the point

in a way that all the chosen points simultaneously satisfy that for any index subsets $Y, X$, such that $X \cap Y$ and they both introduce a non-trivial intersection $\bigcap_{j\in Z} J_j : Z \in \{X, Y\}$, then:

$$\bigcap_{j\in X} J_j = \bigcap_{j\in Y} J_j$$

Now consider a non-trivial maximal intersection $\bigcap_{j\in X} J_j$. The intersection is maximal in the sense that for any $j' \notin X$, it holds that $\bigcap_{j\in X\cup\{j'\}} J_j = \emptyset$. We claim that for any $i$ and for any such $X$, there is $t \in X$ such that $J_t$ is the successor of $J_j$ on the path to $R_i$ for any $j \in X/\{t\}$. Assume not. Let $x, y \in X$, and denote the paths from $J_x, J_y$ to the $R_i$ by $J_x, J_{x_2}, \ldots, R_i$, and $J_y, J_{y_2}, \ldots, R_i$, such that $J_y \neq J_{x_2}$. If $y = x_2$, $y_2 = x$, or $x_2 = y_2 \in X$, then pick other $x, y$ (if there is no such, we get an immediate contradiction). In that case, $J_x, J_y, J_{y_2}, \ldots, R_i$ is a path from $J_x$ to $R_i$ which is different from $J_x, J_{x_2}, \ldots, R_i$. Therefore, there are at least two paths from $J_x$ to the $R_i$, namely, there is a cycle in contradiction to the that the collection $K_0, \ldots, K_k, F_1, .., F_k$ is a tree.

We will choose the $z^i_j$ by the following process. Pick a $z^i_j$ that has not been set yet. If $J_j = R_i$, then set $z^i_j \leftarrow \mathrm{pre}_i(v_i)$ - we call this a type-1 assignment. Otherwise, consider the path from $J_j$ to $R_i$ (by connectivity, it has to be such a one, and by minimality, there is exactly one). Let $J_t$ be the successor on the path, then pick $z^i_j \in J_j \cap J_t$ - similarly, we call this assignment a type-2 assignment. Since any type-2 assignment is associated with a non-trivial intersection, and any non-trivial intersection induces a type-2 assignment for all $i$'s (since for all $i$'s, one of the $J_j$ on its support is a successor of the rest on their path to the $R_i$), we have that:

$$\begin{aligned}
\sum_{j,i} L_i(z^i_j) &= \sum_{j,i,z^i_j\in\text{type-1}} L_i(z^i_j) + \sum_{j,i,z^i_j\in\text{type-2}} L_i(z^i_j) \\
&= \sum_{i}^{d+1} L_i\left(\mathrm{pre}_i(v_i)\right) + \sum_{X\colon \bigcap_{j\in X} J_j\neq\emptyset} (|X|-1) \sum_{i}^{d+1} L_i\left(\bigcap_{j\in X} J_j\right) \qquad (2) \\
&= \sum_{i}^{d+1} L_i\left(\mathrm{pre}_i(v_i)\right)
\end{aligned}$$

To complete, we select the $i$th pole of $K_j$ to be $z^i_j$. Then, for $i = 1, \ldots, d+1$, the $i$th predecessor $\mathrm{pre}_i(v_i)$ is the $i$th pole of $R_i$. This assures (1). Since for any intersection $K_i \cap F_j$ a type-2 assignment is picked from the intersection to $K_i$, we have that the type-2 selected poles of $K_0, K_1, \ldots, K_k$ are covered by the vertices of $F_1, F_2, \ldots, F_k$. This assures (ii). Plugging Equation (2) into Equation (1) assures (3). □

Until now, the claims stated were true for any kind of space-time graph (where their vertices can be associated with coordinates in $\mathbb{R}^d$). The next claims assume that the given time graph is a Toom's contour induced by the noisy running of a Toric encoded circuit.

**Claim 5.27.** *For Toom's contours, the maximal size of a fork is at most* $2d$.

*Proof.* Consider the rules of forks connecting in Definition 5.17. For forks obtained by rules (a), (b), or as a result of a fault, it's clear that their vertices at their ends are on intersecting faces (when projecting the vertices on $\mathcal{G}$). The maximal fork, in those cases, has the form of:

$$F = \{v, (\prod_{g \in S'_1} g)(\prod_{g \in S'_2} g)v\}$$

Where $S'_1$ and $S'_2$ are subsets of $S$ of size either $d'$ or $d - d'$, and therefore the size of such forks is at most $\mathbf{Size}(F) = 2\max\{d', d - d'\} \leq 2d$. □

While in the construction presented in [BS88], all the layers were the same (consisting of the same gates up to wiring), here different layers might differ both in realization and role. Thus, we would like to distinguish between them. We will define the *predecessor decomposition* of a slice to be the collection of slices and forks which satisfy the condition in Claim 5.26. The order of a slice is a number in $\{0, 1, 2, 3\}$ that matches the time modulo four of the layer that results in the slice. Therefore, it encodes the layer type.

**Definition 5.28.** *Let $K$ be a slice, and let $v_1, \ldots, v_{d+1}$ be a selection of poles for it. Then, let $K_0, \ldots, K_k$ be slices in $H_K$, and let $F_1, \ldots, F_k$ be forks, such that $K_0, \ldots, K_k$, $F_1, \ldots, F_k$ satisfy the conditions in Claim 5.26 with respect to the poles selection. We call $K_0, \ldots, K_k$, $F_1, \ldots, F_k$ the predecessor decomposition of $K$ with respect to the pole selection $v_1, \ldots, v_{d+1}$. When the pole selection is either clear from the context or can be chosen arbitrarily, we will omit it.*

*Furthermore, we say that $K$ is a result of a sweep-cycle, faults, or a logical operation if the layer at time $T(K) - 1$ consists of sweep-cycle gates, fault gates (whose source is $\mathcal{E}$), or either measurement or logical Pauli. The order of the slice is its time plus 3 modulo 4, namely $order(K) = T(K) + 3 \mod 4$. So the orders of slices that result from a sweep-cycle, faults, logical operation, and again faults are $0, 1, 2, 3$ respectively.*

The distinction between slices resulting from different layers allows us to adjust Claim 5.26 by conditioning on the slice type. Yet, before doing so, we will have to extend the infinity characterization to slices.

**Corollary 5.29.** *Consider a slice $K$ in it, and a selection of poles $v_1, \ldots, v_{d+1}$, such that $K \neq H_K$. Since $K \neq H_K$, it follows that $K$ has a predecessor decomposition with respect to $v_1, \ldots, v_{d+1}$, denoted by $K_0, \ldots, K_k, F_1, \ldots, F_k$. For each slice $K_j$, denote its selected poles by $z_j^1, \ldots, z_j^{d+1}$. The inequality in Claim 5.26 becomes:*

1. *If $K$ is a result of a sweep-cycle, then:*

$$\sum_{j=0}^{k} \sum_{i}^{d+1} L_i(z_j^i) + \sum_{i=1}^{k} \mathbf{Size}(F_i) \geq \sum_{i}^{d+1} L_i(v) + 1$$

2. *If $K$ is a result of either faults or a logical operation, then:*

$$\sum_{j=0}^{k} \sum_{i}^{d+1} L_i(z_j^i) + \sum_{i=1}^{k} \mathbf{Size}(F_i) \geq \sum_{i}^{d+1} L_i(v)$$

*Proof.* Let us split upon what $K$ results from:

1. For the sweep-cycle part, we use Corollary 4.35 and Claim 4.28. The first states that within an application of the sweep-cycle over a chain, the maximal $L_{d+1}$ value of the $\partial^-$-boundary of the resulting chain decreases by at least one, while the values of each $L_g$ do not increase. The second assures that for any local maximum of $L_i$ in the resulting $\partial^-$-boundary, there is a vertex in the $\partial^-$-boundary of the original such that they (1) share a $d'$-dimensional face and (2) the $L_i$-value of the vertex in the result is at most the $L_i$-value of the vertex in the original, where if $i = d+1$, the relation becomes strictly less. Thus, prior to forming the spanning tree of the predecessor slices, for every $v_i$ in $v_1, .., v_{d+1}$ we select a vertex $\mathrm{pre}_i(v_i)$ that has either at most the same $L_i$-value as $v_i$ if $i \neq d+1$ or an $L_{d+1}$-value that is bigger by at least 1. That gives the inequality.

2. If $K$ is a result of faults, then it cannot contain a vertex that supports a fault. That is because no arrow connection is made in that case, and hence, if it were to contain a vertex that supports a fault, that vertex would be the only one in $K$, namely $K = H_K$. So, we can imagine that all the vertices in $K$ support the identity operator and handle that case as a result of a logical operator.

3. Where $K$ is the result of a logical operator, we use the observation that a pure logical operator doesn't change the slices (with the exception that the measurement in the phase-basis switches the vertex types, namely $\{X\} \leftrightarrow \{Z\}$, of part of the vertices in the slice, see Claim 4.37). So we have that the support of $K$ is contained (up to vertices' types) in the support of $\cup_0^k K_i$, and therefore for any $i \in [d+1]$:

$$\max\{L_i(v) : v \in K\} \leq \max\{L_i(v) : v \in \bigcup_{i=0}^{k} K_i\}$$

□

The following claim extends the corollary to slices at the final layer of an *analysis Toom's contour up to step* $\tau$.

**Claim 5.30.** *For a step* $\tau$ *let* $\mathcal{H}_\tau$ *be Toom's contour analysis up to step* $\tau$*. Denote by* $t$ *the time at which the gate at step* $\tau$ *is applied. Then, for a slice* $K$ *and selection for its poles* $v_1, \ldots, v_{d+1}$ *such that* $T(K) = t+1$ *and* $K \neq H_K$*, the inequality in Claim 5.26 becomes:*

$$\sum_{j=0}^{k} \sum_{i}^{d+1} L_i(z_j^i) + \sum_{i=1}^{k} \mathbf{Size}(F_i) \geq \sum_{i}^{d+1} L_i(v) - 2d$$

*Proof.* We allow vertices of $V_{\mathcal{H},X}$ at the final time layer to be connected by an arrow if their counterpart on the skeleton shares a $d'-2$ dimensional face. Similarly, two vertices of $V_{\mathcal{H},Z}$, such that one of them is at the top layer, are connected if their images

in the map $\phi^{-1}$ share a $d-d'-2$ dimensional face. Therefore, for any $i \in [d]$, the value of $L_i$ for $v_i$ might be greater by at most 1 than the value of $\text{pre}_i(v_i)$, and the $L_{d+1}$ for $v_{d+1}$ might be greater by at most $\max\{d'-2, d-d'-2\}$ than the value of the $d+1$ pole of $K$. Hence, overall, we get that:

$$\begin{aligned}\sum_{i=1}^{d+1} L_i\left(\text{pre}_i(v_i)\right) &\geq \sum_{i=1}^{d}\big(L_i\left(v_i\right)-1\big) + L_{d+1}(v_{d+1}) - \max\{d'-2, d-d'-2\} \\ &\geq \textbf{Size}(K) - 2d\end{aligned}$$

□

## 5.4 Minimal Explantation Argument

We are about to prove the main lemma stating that the number of faults causing an occurrence of slice is linear in both the slice's size and the minimal number of edges required to span a Toom's contour that induces it. First, we define the explanation tree of a slice to be the subtree of its history that connects its poles. The relation between the leaves of the subtree and its arrows, forks, and the size of its origin slice is embedded as a requirement in the definition. Then, we prove that, assuming no time admits an infinite error, any slice has an explanation tree.

**Definition 5.31.** *Consider a Tooms contour graph induced by Toric encoded circuit, with sweep-cycle parameter $\xi = 1$, and let $\alpha, \beta$ be constants and $\mathcal{X}_0, \mathcal{X}_1, \mathcal{X}_2, \mathcal{X}_3 \in \mathbb{R}$ be quadruple, defining such:*

$$\alpha := 40(d+1)^2, \quad \beta := 5(d+1)$$
$$\mathcal{X}_r := 1 - r\frac{d+1}{\alpha} = 1 - \frac{r}{40(d+1)}$$

*In addition, we would like to refer to $\mathcal{X}_0, \mathcal{X}_1, \mathcal{X}_2, \mathcal{X}_3$ in a cyclic manner, so we define:*

$$\mathcal{X}_{-1} := \mathcal{X}_3$$

*Given sets $W$ of points, $A$ of arrows, and $F$ of forks. The sets $W$, $A$, and $F$ form an explanation of a slice $K$, with poles selection $v_1, \ldots, v_{d+1}$, and order $order(K) = r$, if and only if:*

1. *$W \cup \{v_1, .., v_{d+1}\} \subset H_K$ and the graph $(W \cup \{v_1, .., v_{d+1}\}, A \cup F)$ is connected.*
2. *All elements of $W$ are leaves.*
3. *For $m = |W|$ and $s = \sum_i^{d+1} L_i(v_i)$ we have $|A| \leq \alpha(m - \mathcal{X}_r) - \beta s$ and $|F| \leq m-1$.*

*Furthermore, for a step $\tau$, and a slice $K$ in the analysis of Toom's contour up to step $\tau$, with pole selection $v_1, .., v_{d+1}$, we extend the definition of explanation as above, but require the following weaker inequality instead: For $m = |W|$ and $s = \textbf{Size}(K)$, we have $|A| \leq \alpha(m+1) - \beta s$ and $|F| \leq m-1$.*

**Claim 5.32.** *Let $P_1, \ldots, P_{\mu+1}$ be the Pauli-path that induces Toom's contour. For every poles selection $v_1, \ldots, v_{d+1}$ of $K$, there is an explanation. Moreover, any slice in the analysis of Toom's contour up to step $\tau$, and any poles selection for it, there is an explanation.*

*Proof.* Let $h = T(K) - \min_{u \in H_K} T(u)$. For slices in a standard Toom's contour, we prove by induction on $h$.

1. Base: $h = 0$, meaning $T$ is constant on $H_K$, so no arrows connect points of $H_K$. Thus, $H_K$, as well as $K$, consists only of a single leaf, namely $K$ is a result of a fault, and $r = \text{order}(\mathcal{X}_r) \in \{1, 3\}$. In that case, there is a single vertex $u \in V_{\mathcal{H}}$ such that $W = \{u\}$, so $m = 1$, $s = 0$, and $|A|, |F| = 0$. It is easy to check that those values satisfy the requirement.

2. Induction Step: $h \neq 0$ implies $K \neq H_K$. By Claim 5.26, we know that for some $k$ there exist slices $K_0, \ldots, K_k$, pole selections for them, and forks $F_1, \ldots, F_k$ that satisfy Claim 5.26 with respect to the pole selection. In particular, denote by $z_j^1, .., z_j^{d+1}$ the pole selection for $K_j$. Then, for $r \neq 0$ it holds that:

$$\sum_{j=0}^{k} \sum_{i=1}^{d+1} L_i(z_j^i) + \sum_{i=1}^{k} \mathbf{Size}(F_i) \geq s$$

   Whereas, for $r = 0$:

$$\sum_{j=0}^{k} \sum_{i=1}^{d+1} L_i(z_j^i) + \sum_{i=1}^{k} \mathbf{Size}(F_i) \geq s + \xi = s + 1$$

   Consider $i \in \{0, \ldots, k\}$, and denote $s_j = \sum_i^{d+1} L_i(z_j^i)$. By the inductive hypothesis and since $T(K_i) = T(K) - 1$, we know that for $K_i$ and its selected poles $z_i^1, \ldots, z_i^{d+1}$, there is an explanation formed by a set of leaves $\mathbf{W}_i$, a set of arrows $\mathbf{A}_i$, and a set of forks $\mathbf{F}_i$. Let $m_i = |\mathbf{W}_i|$. Thus, the sets $\mathbf{A}_i$ and $\mathbf{F}_i$ have at most $\alpha(m_i - \mathcal{X}_{r-1}) - \beta s_i$ arrows and $m_i - 1$ forks. We define:

   (a) $\mathbf{W} = \cup_{i=0}^{k} \mathbf{W}_i$, Notice that $\mathbf{W}_i \subset K_i$ and that $T(K_i) = T(K_j)$ for all $i, j$, thus by Claim 5.22 $\mathbf{W}$ is a union of disjoint set, Hence $W$ contains $m = \sum_{i=0}^{k} m_i$ leaves.

   (b) $\mathbf{F} = \{F_1, .., F_k\} \cup_{i=0}^{k} \mathbf{F}_i$ with at most $k + \sum_{i=0}^{k} m_i - 1 = m - 1$ elements.

   (c) $\mathbf{A} = \{\{v_i, \text{pre}_i(v_i)\}\} \cup_{i=0}^{k} \mathbf{A}_i$. For bounding the number of arrows in $\mathbf{A}$ we condition upon whether $r = 0$, For convenient, let us denote by $Y$ the indicator, which indicate if $r = 0$.

$$\begin{aligned}
&d + 1 + \sum_{i=0}^{k} \alpha(m_i - \mathcal{X}_{r-1}) - \beta s_i \\
\leq &d + 1 + \alpha m - \mathcal{X}_{r-1}\alpha(k+1) - \beta\left(s + Y\xi - k \cdot \mathbf{Size}(\text{fork})\right) \\
= &\alpha\left(m - \mathcal{X}_r\right) - \beta s + \left(\alpha(\mathcal{X}_r - \mathcal{X}_{r-1}) + d + 1 - \mathcal{X}_{r-1}k\alpha - \beta Y\xi + \beta k \cdot \mathbf{Size}(\text{fork})\right)
\end{aligned}$$

So it's left to show that the term in the closure is negative for all integers $k$:

$$\alpha(\mathcal{X}_r - \mathcal{X}_{r-1}) + d + 1 - \mathcal{X}_{r-1}k\alpha - \beta Y\xi + \beta k \cdot \textbf{Size}(\text{fork})$$

We do that by showing that for the choice of the parameter values, $\alpha, \beta, \mathcal{X}_0, \ldots, \mathcal{X}_3$, the slope is negative, and then the value of the term at $k$ equals zero is negative. For the slope to be negative, we require:

$$-\alpha\mathcal{X}_{r-1} + \beta\textbf{Size}(\text{fork}) \leq 0 \Rightarrow \textbf{Size}(\text{fork}) \leq \frac{\alpha}{\beta}\mathcal{X}_{r-1}$$

For negativity at the origin, $k = 0$, we require for $r \neq 0$:

$$\begin{aligned}\alpha(\mathcal{X}_r - \mathcal{X}_{r-1}) + d + 1 &\leq 0 \\ \Rightarrow \mathcal{X}_r &\leq \mathcal{X}_{r-1} - \frac{d+1}{\alpha}\end{aligned}$$

And for $r = 0$:

$$\begin{aligned}\alpha(\mathcal{X}_0 - \mathcal{X}_3) + d + 1 - \beta\xi &\leq 0 \\ \Rightarrow \mathcal{X}_0 &\leq \mathcal{X}_3 - \frac{d+1}{\alpha} + \frac{\beta}{\alpha}\xi\end{aligned}$$

So in total:

$$\begin{aligned}\mathcal{X}_1 &\leq \mathcal{X}_0 - \frac{d+1}{\alpha} \\ \mathcal{X}_2 &\leq \mathcal{X}_0 - 2\frac{d+1}{\alpha} \\ \mathcal{X}_3 &\leq \mathcal{X}_0 - 3\frac{d+1}{\alpha} \\ \mathcal{X}_0 &\leq \mathcal{X}_0 - 4\frac{d+1}{\alpha} + \frac{\beta}{\alpha}\xi \\ \textbf{Size}(\text{fork}) &\leq \frac{\alpha}{\beta}\mathcal{X}_r\end{aligned}$$

The first three inequalities hold by the definitions of the $\mathcal{X}_r$, the fourth is satisfied since $\frac{\beta}{\alpha}\xi = 5\frac{d+1}{\alpha}$, the last is obtained due to Claim 5.27, that states that the maximal size of a fork is at most $2d$, and that $\frac{\alpha}{\beta}\mathcal{X}_r$ is greater than $4d$.

Finally, by Claim 5.26, the graphs induced by $\mathbf{A}_i \cup \mathbf{F}_i$ are connected to each other trough $F_1, .., F_k$, thus the graph induced by $\mathbf{A} \cup \mathbf{F}$ is also connected. Therefore, $\mathbf{W}, \mathbf{A}, \mathbf{F}$ form an explanation of $K$.

It's left to prove for slices in the analysis of Toom's contours. Notice that the 'forming rules' of the analysis of Toom's contour are different from the standard Toom's contour only at the last layer. Therefore, the induction proof captures all the slices not in the

last layer. For any slice at the last layer, we repeat the induction step while using Claim 5.30 to bound the expansion in size. So the bounding over $\mathbf{A}$'s size becomes:

$$\begin{aligned}|\mathbf{A}| &\leq \alpha\,(m+1) - \beta s \\ &\quad + (-\alpha(1+\mathcal{X}_{r-1}) + d + 1 - \mathcal{X}_{r-1}k\alpha + 2d + \beta k \cdot \mathbf{Size}(\text{fork})) \\ &\leq \alpha\,(m+1) - \beta s \\ &\quad + (-\alpha + d + 1 - \mathcal{X}_{r-1}k\alpha + 2d + \beta k \cdot \mathbf{Size}(\text{fork}))\end{aligned}$$

Where we used the fact that $\mathcal{X}_{r-1} \in (0,1)$ for $r \in \{0,1,2,3\}$. Clearly, the bound is satisfied since $\alpha \geq 3d$ and $\mathcal{X}_{r-1}\alpha \geq \beta \cdot \mathbf{Size}(\text{fork})$. □

We summarize by using the linear relation between the leaves of a Toom's contour and the faults that induce it. That gives an upper bound on the probability of a slice occurring when the noise is local stochastic.

**Corollary 5.33.** *Let $K$ be a slice with size $s$, and explanation with $|A|$ arrows, and $|F|$ forks. Then it is induced by at least the following number of faults:*

$$\frac{1}{2^{\max\{d',d-d'\}}}\frac{1}{2}\left(|F| + 1 + \alpha^{-1}(|A| + \beta s - 1)\right)$$

*Furthermore, the ratio of leaves to edges in an explanation is greater than $\frac{1}{2\alpha} = \frac{1}{80(d+1)^2}$.*

*Proof.* We bound Claim 5.32 by the number of leaves in the explanation and use the fact that any $d'$-face has $2^{d'}$ vertices, so each $X$-fault and $Z$-fault contributes at most $2^{d'}$ and $2^{d-d'}$ leaves to the explanation. □

# 6 Proof of the Theorem

We are ready to prove the main theorem (Theorem 6.3). We start by giving a formal definition of a simulation.

**Definition 6.1** (Simulation and Logical Errors)**.** *Consider a quantum code $\mathcal{C}$ of length $n$ and dimension $k$. A quantum circuit $D\colon L(\mathcal{H}_2^{\otimes n}) \to L(\mathcal{H}_2^{\otimes n})$ will be said to be a referee for $\mathcal{C}$ if, when given a codeword of $\mathcal{C}$, it results in the first $k$ output qubits, the logical state of the given. We say that a Pauli operator $P \in \mathcal{P}^{\otimes n}$ is a logical error with respect to $D$ if $DP \neq D$.*

*For quantum circuits $C$ and $\tilde{C}$, a noise channel $N_{\mathcal{E}}$, and $p \in (0,1)$, we say that $\tilde{C}$ simulates $C$ with probability at least $1-p$ if*

1. *There is a mapping between the qubits of $C$ and the registers of $\tilde{C}$, along with a referee such that, at the end of running $\tilde{C}$ (on the zero state), decoding the registers back to the logical space results in the same quantum states as those produced by running $C$.*

2. *Let $\mathcal{E} \sim N_{\mathcal{E}}$ be a set of faults. The probability induced by $N_{\mathcal{E}}$ that at the end of the running of $\tilde{C}[\mathcal{E}]$, one of its quantum registers introduces a logical error (with respect to the referee) is less than $p$.*

The next lemma is the core of the theorem; it analyzes the probability of a logical error occurring after the initialization stage, namely when assuming the given input is encoded.

**Lemma 6.2.** *For any $d, d'$, there are constants $a, b \in \mathbb{R}^+$ and $p_0 \in (0,1)$ that depend only on $d, d'$ and satisfy the following. Consider a quantum circuit $C$ with depth $\mu$ and width $w$, and let $\mathcal{N}_\mathcal{E}$ be a local stochastic noise channel with a noise rate $p < p_0$. There is a Toric encoded circuit $\tilde{C}$ such that each of its quantum registers is encoded by an $n$-side length, $(d, d')$-Toric code, and it simulates $C$ with probability:*

$$q = 1 - O\left(poly(w, \mu, n)\right)\left(ap^b\right)^{\frac{n}{2d}}$$

To prove the lemma, we will need the following two claims. The first bounds, for a given regular graph, the number of its subgraphs having at most $k$ edges. This claim will be used to infer the number of possible explanation trees for a given slice. The second states that each tree has a subtree with fewer than half of the edges and a leaves-to-edge ratio that is at least half of the ratio of the original tree. This claim will be used to infer that any explanation has a subtree where, under the projection to the finite Toric, its faults are mapped uniquely, meaning no fault is counted twice.

**Claim** (Claim 8.1)**.** *Let $G = (V, E)$ be a $\Delta + 1$-regular graph, and let $k$ be an integer less than $|E|$. Fix a vertex $r \in V$. There is a constant number $\sigma$, depending only on $\Delta$, such that the number of subgraphs rooted at $r$ with fewer than $k$ edges is at most $\sigma^k$.*

**Claim** (Claim 8.4)**.** *Let $\gamma, \beta \in \mathbb{R}_{>0}$ and $n$ be a positive integer. For any tree $T$ with $\tau \geq \beta n$ edges and $m$ leaves such that $\tau \leq \gamma m$, there is a subtree $T'$ of $T$ with a number of edges $\tau'$ less than $\frac{\beta}{2}n$ and a number of leaves greater than $\frac{\beta}{4\gamma}n$.*

The proofs of the claims are given in the appendix. We continue with the proof of the lemma.

*Proof.* We construct $\tilde{C}$ as follows: for each input wire of $C$, we initialize the logical zero $|\mathbf{0}\rangle$ of the $(d, d')$-Toric code. For each of the gates **H** and **S**, we initialize the encoded $|\mathbf{H}\rangle$ and $|\mathbf{S}\rangle$ states, and for each **T**, we initialize copies of both $|\mathbf{T}\rangle$ and $|\mathbf{S}\rangle$ states. The even layers of $\tilde{C}$ are sweep cycles, while on the odd layers, we set the realization of the logical gates. For **CX**, we set the transversal realization, and for **H**, **S**, and **T**, we use gate teleportation. Thus the width of $\tilde{C}$ expands to at most $(w + 2\mu)n^{2d}$.

We realize the gate teleportation as described in Definition 4.36, so the gate teleportation admits $O(n + \log n)$ and $O(n^{2d})$ depth and width overhead. Thus, the depth of $\tilde{C}$ expands to $\Theta(\mu n)$[7]. We will denote the procedure of inferring the logical measurement in the gate teleportation[8] by $D$, and we also use $D$ as a realization of measurement in the computational basis and as our referee (Definition 6.1). Denote by $S$ the number of locations, so $S = O(w\mu^2 n^{2d+1})$.

[7]The constant inside the $\Theta$ also accounts for the fact that the realization of a logical gate might contain multiple gate teleportations.

[8]This is the codeword checking procedure - $\mathbf{1}_{x_{S'}}$ / $\mathbf{1}_{x_{S/S'}}$ as appears in Definition 4.36

Consider a set of faults $\mathcal{E}$, and consider the representation of the subjected circuit $C[\mathcal{E}]$ as a distribution over conditioned measured circuits:

$$C[\mathcal{E}] = \sum_{\alpha} \mathbf{Pr}\left[\alpha|\mathcal{E}\right] C[\mathcal{E}, \alpha]$$

Denote by $\tau_f$ the last step of $C[\mathcal{E}, \alpha]$, and let $(\mathbf{P}, \mathbf{a})$ be a step-propagation of $C[\mathcal{E}, \alpha]$, where $\mathbf{P} := P_1, P_2, .., P_{\tau_f+1}$ and $\mathbf{a} := \alpha^1, \alpha^2, .., \alpha^{\tau_f+1}$ (Definition 3.10). Thus, if $D \circ C[\mathcal{E}] \neq C$, then there is at least one option of outcomes $\alpha$ for which $D \circ C[\mathcal{E}, \alpha] \neq C$, namely:

$$D \circ C[\mathcal{E}, \alpha] = D \circ P_{\tau_f+1} C[, \alpha^{\tau_f+1}] \neq C$$

For this, one of the following two has to occur: either the decoder $D$ fails to decode $P_{\tau_f+1}$, or the conditioned circuit $C[, \alpha^{\tau_f+1}]$ deviates from the ideal circuit, namely $C[, \alpha^{\tau_f+1}] \neq C$. The second occurs only if, along the running, a gate-teleportation fails, meaning the decoding procedure that erases errors from the measured register failed, and therefore the gate applied following the measurement was incorrect.

By the barrier argument (Corollary 5.11), occurrence of both options implies that there is a connected component of either the $X$-syndrome or $Z$-syndrome of at least one of the Paulis in the propagation $P_1, .., P_{\tau_f+1}$ at a size greater than $cn$ (where $c$ is the constant $c'$ defined in Claim 5.10), and hence, the Pauli-path induced by the propagation has a connected component of the syndrome at a size at least $cn$.

Since connectivity by faces in the analysis of Toom's contour implies connectivity by arrows, it follows that an occurrence of that event implies the existence of a step $\tau$ such that the analysis of Toom's contour $\mathcal{H}_\tau$ of $C[\mathcal{E}, \alpha]_\tau$ has a slice of size at least $cn$. So it's sufficient to prove that with probability at least $q$, for the sampled faults $\mathcal{E}$, there are no possible outcomes $\alpha$ and a step $\tau$ such that the analysis of Toom's contour $\mathcal{H}_\tau$ of $C[\mathcal{E}, \alpha]_\tau$ has a slice of size at least $cn$.

Denote by $B_\tau$ the event where $\tau$ is the first step such that $\mathcal{H}_\tau$ has a slice at size greater than $cn$, and by $A_\tau$ the event where all explanations of slices (and any of their pole selections) in $\mathcal{H}_\tau$ have fewer than $\frac{n}{2d}$ edges. Using the conditional probability formula, we have:

$$\begin{aligned}\mathbf{Pr}_{\sim\mathcal{N}_\mathcal{E}}\left[B_\tau\right] &= \mathbf{Pr}_{\sim\mathcal{N}_\mathcal{E}}\left[B_\tau \cap A_\tau\right] + \mathbf{Pr}_{\sim\mathcal{N}_\mathcal{E}}\left[B_\tau \cap \bar{A}_t\right] \\ &\leq \mathbf{Pr}_{\sim\mathcal{N}_\mathcal{E}}\left[B_\tau \cap A_\tau\right] + \mathbf{Pr}_{\sim\mathcal{N}_\mathcal{E}}\left[\bar{A}_t\right]\end{aligned}$$

We begin by bounding the contribution of the right term. According to Corollary 5.33, there exists a constant $c_1$, depending only on $d$, such that the ratio of leaves to edges in the explanation is at least $c_1$. By Claim 8.4, it follows that any such explanation has more than $\frac{n}{2d}$ edges containing a subtree with fewer than $\frac{n}{4d}$ edges, with a leaves-to-edges ratio greater than $\frac{1}{2}c_1$. Using the union bound, we bound the probability that there is a vertex in the base graph that is a root of such a subtree. Since the

construction of the $\infty$-lift sets periodic conditions, it's sufficient to ask if there is such a vertex in the restriction to the finite $n$-side length Toric.

$$\mathbf{Pr}_{\sim\mathcal{N}_\mathcal{E}}\left[\bar{A}_\tau\right] \leq \bigcup_{\substack{v\in V_o,\tau'\leq\tau \\ L_g(v)\in[0,n]}} \mathbf{Pr}_{\sim\mathcal{N}_\mathcal{E}}\Big[v \text{ is a root of subtree in } \mathcal{H}_{\tau'} \text{ with less than } \frac{n}{4d} \text{ edges and more than } \frac{1}{2}c_1\frac{n}{4d} \text{ leaves}\Big]$$

Now, since any two connected vertices are at a space distance of at most

$$\max\{\mathbf{Size}(\text{arrow}), \mathbf{Size}(\text{fork})\} \leq 2d$$

It follows that all the vertices in the subtree are at a space distance of at most $\frac{1}{2}n$ from each other. Thus, no two of them have the same space coordinate modulo $n$. In particular, projecting the infinite plane back to the finite Toric sends each of the leaves of the subtree to a unique target, namely no fault is counted twice. Therefore the number of faults that induce the explanation is at least:

$$\frac{1}{2^{\max\{d',d-d'\}}}\frac{1}{2}\frac{1}{2}c_1\frac{n}{4d} \geq \frac{1}{2^{d+4}}c_1\frac{n}{d}$$

Plugging into the union bounds and combining Claim 8.1 yields:

$$\mathbf{Pr}_{\sim\mathcal{N}_\mathcal{E}}\left[\bar{A}_\tau\right] \leq O(S)\sigma^{\frac{n}{4d}}p^{\frac{c_1 n}{2^{d+4}d}} \leq O(S)\left(\sigma p^{\frac{1}{2^{d+2}}c_1}\right)^{\frac{n}{4d}}$$

It's left to bound the probability of $B_\tau \cap A_\tau$. By Claim 5.32 any slice, and any pole selection of it, in $\mathcal{H}_\tau$, have an explanation. Confining to the event $A_\tau$, any explanation implies that any explanation has fewer than $\frac{n}{2d}$ edges and therefore, by the same argument as above, the projection of each explanation tree into the finite Toric sends its leaves to unique targets.

Any slice of size at least $cn$, has poles selection $v_1..,v_{d+1}$ such:

$$\sum_{i}^{d+1} L_i(v_i) \geq cn \tag{3}$$

Consider a slice with size at least $cn$ and a pole selection for it satisfying Equation (3). Claim 5.32 and Corollary 5.33 state that there are constants $c_2, c_3 > 0$ such that any explanation for the slice and the selection, with $x$ edges, has at least $c_2cn + c_3x$ leaves. Therefore, we obtain:

$$\mathbf{Pr}_{\sim\mathcal{N}_\mathcal{E}}\left[B_\tau \cap A_\tau\right] \leq \bigcup_{\substack{v\in V_o,x\geq 1 \\ L_g(v)\in[0,n]}} \mathbf{Pr}_{\sim\mathcal{N}_\mathcal{E}}\Big[v \text{ is a root of explanation with } x \text{ edges and at least } c_2cn + c_3x \text{ leaves, which are projected to different targets }\Big]$$

So, for sufficiently small $p$ such that $\sigma p^{c_3} < 1$, the probability is bounded by:

$$\sum_{x=1}^{\infty} O(S) p^{c_2 cn} \left(\sigma p^{c_3}\right)^x \leq O(S) p^{c_2 cn}$$

Combing the bounds we have, that there is constant $c_4$ depending only on $d, d'$ such:

$$\mathbf{Pr}_{\sim \mathcal{N}_\mathcal{E}}\left[B_\tau\right] \leq O(S) p^{c_4 n}$$

Now, by the union bound over the time steps, with a probability greater than:

$$1 - O\left(S^2\right) p^{c_4 n}$$

No step admits a slice of size at least $cn$ in its corresponding analysis of Toom's contour, so the barrier argument holds; in other words, the propagated errors do not accumulate into a logical error. □

The lemma gives the theorem almost immediately. To complete the proof, we need to plug in the initialization phase, which initializes encoded zeros and resource states subjected to local stochastic noise. We emphasize that the resulting states are subjected to local stochastic noise (in addition to the computation). We neither prove nor describe that phase here; instead, we refer to [Gro19], [Got14], [FGL18], and [NP25].

**Theorem 6.3.** *There exists a constant $p_0 \in (0,1)$ such that for any local stochastic noise channel $\mathcal{N}_\mathcal{E}$ with rate $p < p_0$, and a quantum circuit $C$ with depth $\mu$ and width $w$, there exists a Toric encoded circuit $\tilde{C}$, with depth $\Theta(\mu(n + \ Polylog(n)))$ and width $\Theta((w+\mu)n^8 \ Polylog(n))$ that simulates $C$ with probability:*

$$1 - O\left(poly(w, \mu, n)\right) p^{\Omega(n)}$$

*and in addition:*

1. *After a short initialization stage (at depth $\Theta(poly(\log n))$), each of the qubits is encoded in the $n$-length 4D Toric code.*
2. *An error correction cycle takes $O(1)$ depth, and the gates in each correction cycle don't depend on time. In particular, if $C$ is the identity circuit, then after the initialization stage, the layers in $\tilde{C}$ are the same.*

# 7 The Sweep-rule is Itself a Decoder

The role of the sweep-rule in the fault tolerance construction is to restrain the errors in the system rather than erase them. Here, we show that it can also be used as a decoder. Concurrently, if the initial error is distributed according to local stochastic noise, then the excitation of noiseless sweep-cycles for $n^{d+1}$ times - the number of vertices times the side's length - erases the errors, with high probability.

The following claim states that an ideal run (not subject to noise) of $n^{d+1}$ sweep-cycles, with the additional assumption that no slice has reached a size greater than $n$, succeeds in erasing the syndrome.

**Claim 7.1.** *Let $|\psi\rangle$ be a logical codeword of the $(d, d')$-Toric code with side length $n$, and let $P \in \mathcal{P}^{(\cdot)}$. Let $C$ be the quantum circuit that takes $P|\psi\rangle$ as an input and performs over it $n^{d+1}$ sweep-cycles. For a possible measurement outcome $\alpha \in \mathbb{F}_2^{(\cdot)}$ (of stabilizer measurements), consider the Toom's contour $\mathcal{H}$ induced by $C[,\alpha]$. Assume that no slice of $\mathcal{H}$ has size greater than $n$. Then, at the end of the running of $C[,\alpha]$, the syndrome is erased.*

*Proof.* We will prove that the decoder erases the $\partial^-$-boundary corresponding to the $X$-component of $P$, and the proof for the $Z$-component is identical. Let $P^\infty$ be the $\infty$-lift of $P$ and let $v_1, v_2, \ldots$ be the vertices supporting the faces of $\partial^- x(P^\infty)$. During the ideal computation, no new faults are introduced, and therefore $v_1, v_2 \ldots$ are the only leaves in the induced Toom's contour. Without loss of generality, assume that the first $m$ vertices $v_1, .., v_m$ align with the vertices of the finite Toric (namely non-translated vertices), denote them by $V'$.

They set a natural relation over its slices as follows: two slices $K_1$ and $K_2$, not necessarily with the same time coordinate, will be said to be *history-related*, $K_1 \sim K_2$, if there are leaves $u, w$ such that both $u$ and $w$ are translations of a vertex $v_i \in V'$ and $u, w$ belong to the histories of $K_1, K_2$ respectively. Thus, for a time $t$ and a leaf $v \in V'$, we can define the notation $K_{v,t}$ to be the slice at time $t$ that is reached from leaf $v$ by arrows. We emphasize that $\sim$ is not an equivalence relation, since it doesn't satisfy transitivity. Yet, let us match slices to 'classes' when the map is many-to-many. Here, a class is a grouping of translations of slices which are all history-related. For a vertex $v \in V'$, the delegate of the slices reached from vertex $v$ and its translations, namely the translations of slices $\{K_{v,t} : t\}$, will be denoted by $\mathbf{K}_v$. Proving that at the end of time $n^{d+1}$, for any leaf $v$, the slice $K_{v,t}$ is empty, or equivalently is of size zero, and therefore its translations, implies the correctness of the claim.

For proving this, let us present the following terminology. For leaves $v, u, w$, and a time coordinate $t$, consider the following:

1. Suppose that $K_{v,t}$ and $K_{u,t+1}$ are slices at times $t$ and $t+1$, such $K_{v,t} \sim K_{u,t+1}$. If $\mathbf{Size}(K_{u,t+1}) > \mathbf{Size}(K_{v,t})$, we will say that the class $\mathbf{K}_v$ grows at time $t$. Similarly, if $\mathbf{Size}(K_{u,t+1}) < \mathbf{Size}(K_{v,t})$, then we will say that class $\mathbf{K}_v$ shrank at time $t$.

2. Suppose that $K_{v,t}$ and $K_{u,t}$ are slices at time $t$, and $K_{w,t+1}$ is a slice at time $t+1$, such that $K_{v,t} \not\sim K_{u,t}$, $K_{w,t+1} \sim K_{v,t}$, and $K_{w,t+1} \sim K_{u,t}$. Then we will say that $\mathbf{K}_v$ and $\mathbf{K}_u$ merged at time $t$.

3. The size of a class $\mathbf{K}_v$ at time $t$ is $\mathbf{Size}(K_{v,t})$.

Since no new faults are introduced during the computation, we have that in each step, the only option for a class to grow is by merging. Notice that, by definition, classes cannot 'split'. Namely, if $K_{v,t} \sim \mathbf{K}_u$, then for any time $t' \geq t$, it holds that $K_{v,t'} \sim \mathbf{K}_u$. Specifically, a correction by the sweep rule that disconnects two connected components of the syndrome that were connected, prior to correction, belonged to the same slice and therefore to the same class, would still belong to the same class after the correction.

Therefore, there can be at most $m-1$ merges. And since the number of classes is bounded by the number of vertices on the finite Toric, we have that $m \leq n^d$, namely at most $n^d - 1$ merges can occur. Hence, during the $n^{d+1}$ sweep-cycles, there has to be a continuous sequence of $n$ cycles for which no merge occurs.

During the continuous sequence of those $n$ cycles, each sweep cycle decreases the size of any slice by at least 1. This is followed by Corollary 5.29, combining that no merging occurred, meaning there is only one predecessor slice. Thus, using the given assumption that no slice in $\mathcal{H}$ reaches a size greater than $n$, namely $\mathbf{Size}(K_{v,t}) \leq n$ for any vertex $v$ and time $t$, we have that at the end of that sequence of $n$ cycles, all the slices' sizes shrink to zero; namely, the slices are erased after those cycles. □

Claim 7.1 guarantees only that the syndrome is erased; in particular, it says nothing about whether a logical error has or hasn't occurred. To complete the correctness of the decoder, we would like to use the barrier argument. Yet, instead of showing that during the ideal correction no connected component of the syndrome passes the barrier, it will be more convenient to reduce the passing question to the subjected-to-noise setting. We introduce a replacement argument, stating that the probability of an event occurring during a computation where part of its layers are non-noisy is lower than the probability of having the same event in a computation where all its layers are noisy. More precisely, any bound that assumes only that the noise channel is local stochastic captures both cases.

**Claim 7.2** (Replacement argument)**.** *Let $C$, $|\psi\rangle$, and $P$ be the quantum circuit, the quantum state, and a Pauli as defined in Claim 7.1, with the change that $P$ is distributed according to local stochastic noise $\mathcal{N}_\mathcal{E}$ with an error rate $p \in (0,1)$ rather than being fixed.*

*Denote by $A$ the event in which, at the end of the running of $C$, namely after the $n^{d+1}$ **ideal** (non-noisy) iterations of the sweep-cycle, the error is not erased, and denote by $B$ the event that, during the application of a subsection of $C$ to $\mathcal{N}_\mathcal{E}$, there is a step for which the analysis of Toom's contour up to that step admits a slice of size at least $cn$.*

*Let $f : (n, d, d', p) \to \mathbb{R}$ be an upper bound on $\mathbf{Pr}\big[B\big]$. Then, we have:*

$$\mathbf{Pr}\big[A\big] \leq f(n, d, d', p) \tag{4}$$

*Proof.* A corollary of combining Claim 7.1 with Corollary 5.11 (The barrier argument) is that if during the $n^{d+1}$ ideal sweep-cycles, there is no step for which its propagation admits a slice of size at least $cn$ (and therefore no step admits a syndrome's connected component that passes the barrier), then the syndrome is erased and no logical error occurred. So it's sufficient to show that the probability that the condition does not hold is lower than $f(n, d, d', p)$. To do that, we show that there is a local stochastic noise channel $\mathcal{N}'_\mathcal{E}$ with an error rate $p$ such that $C[\mathcal{E}] = C$ where $\mathcal{E} \sim \mathcal{N}'_\mathcal{E}$. We do that by defining $\mathcal{N}'_\mathcal{E}$ to be the identity channel. Clearly, it satisfies the local stochastic noise inequality Definition 3.7, and therefore Equation (4) has to hold. □

We now prove that the sweep rule is itself a decoder.

**Theorem 7.3.** *There exists a constant $p_0 \in (0,1)$ such that for any local stochastic noise channel $\mathcal{N}_\mathcal{E}$ with rate $p < p_0$, and a quantum state $\rho = \mathcal{N}_\mathcal{E}(|\psi\rangle)$, where $|\psi\rangle$ is a codeword of the $(d,d')$-Toric code, the application of $n^{d+1}$ (ideal) sweep-cycles on $\rho$ results in $|\psi\rangle$ with probability at least:*

$$1 - O\left(poly(n)\right) p^{\Omega(n)}$$

*Proof.* By the replacement argument (Claim 7.2), it is sufficient to consider the application of $n^{d+1}$ sweep-cycles subjected to $\mathcal{N}_\mathcal{E}$, and bound the probability that during the subjected application there is a step $\tau$ and an analysis of Toom's counter $\mathcal{H}_\tau$ such that $\mathcal{H}_\tau$ contains a slice of size at least $cn$. Denote by $B_\tau$ the event in which step $\tau$ admits a slice of size at least $cn$. The proof of Lemma 6.2 bounds the probability of $B_\tau$ by the location's number multiple $p^{\Omega(n)}$ for $p < p_0$. Taking the union bound over the steps gives the desired result. □

# References


[Lev80] G. Lev. "Size Bounds and Parallel Algorithms for Networks". PhD thesis. University of Edinburgh, 1980. URL: https://era.ed.ac.uk/handle/1842/17015.

[SV82] Yossi Shiloach and Uzi Vishkin. "An O(logn) parallel connectivity algorithm". In: *Journal of Algorithms* 3.1 (1982), pp. 57–67. ISSN: 0196-6774. DOI: https://doi.org/10.1016/0196-6774(82)90008-6. URL: https://www.sciencedirect.com/science/article/pii/0196677482900086.

[AS87] Awerbuch and Shiloach. "New Connectivity and MSF Algorithms for Shuffle-Exchange Network and PRAM". In: *IEEE Transactions on Computers* C-36.10 (1987), pp. 1258–1263. DOI: 10.1109/TC.1987.1676869.

[BS88] Piotr Berman and J'anos Simon. "Investigations of fault-tolerant networks of computers". In: *Proceedings of the Twentieth Annual ACM Symposium on Theory of Computing*. STOC '88. Chicago, Illinois, USA: Association for Computing Machinery, 1988, pp. 66–77. ISBN: 0897912640. DOI: 10.1145/62212.62219. URL: https://doi.org/10.1145/62212.62219.

[Sho95] Peter W. Shor. "Scheme for reducing decoherence in quantum computer memory". In: *Phys. Rev. A* 52 (4 Oct. 1995), R2493–R2496. DOI: 10.1103/PhysRevA.52.R2493. URL: https://link.aps.org/doi/10.1103/PhysRevA.52.R2493.

[CS96] A. R. Calderbank and Peter W. Shor. "Good quantum error-correcting codes exist". In: *Physical Review A* 54.2 (Aug. 1996), pp. 1098–1105. DOI: 10.1103/physreva.54.1098. URL: https://doi.org/10.1103%2Fphysreva.54.1098.

[Ste96] Andrew Steane. In: *Proceedings of the Royal Society of London. Series A: Mathematical, Physical and Engineering Sciences* 452.1954 (Nov. 1996), pp. 2551–2577. ISSN: 1471-2946. DOI: 10.1098/rspa.1996.0136. URL: http://dx.doi.org/10.1098/rspa.1996.0136.

[Got97] Daniel Gottesman. *Stabilizer Codes and Quantum Error Correction*. 1997. arXiv: quant-ph/9705052 [quant-ph]. URL: https://arxiv.org/abs/quant-ph/9705052.

[Kit97] A Yu Kitaev. "Quantum computations: algorithms and error correction". In: *Russian Mathematical Surveys* 52 (1997), pp. 1191–1249. URL: https://api.semanticscholar.org/CorpusID:250816585.

[AB99] Dorit Aharonov and Michael Ben-Or. *Fault-Tolerant Quantum Computation With Constant Error Rate*. 1999. arXiv: quant-ph/9906129 [quant-ph].

[ZLC00] Xinlan Zhou, Debbie W. Leung, and Isaac L. Chuang. "Methodology for quantum logic gate construction". In: *Physical Review A* 62.5 (Oct. 2000). ISSN: 1094-1622. DOI: 10.1103/physreva.62.052316. URL: http://dx.doi.org/10.1103/PhysRevA.62.052316.

[Den+02] Eric Dennis et al. "Topological quantum memory". In: *Journal of Mathematical Physics* 43.9 (Sept. 2002), pp. 4452–4505. DOI: 10.1063/1.1499754. URL: https://doi.org/10.1063%2F1.1499754.

[Ahn04] Charlene Sonja Ahn. "Extending Quantum Error Correction: New Continuous Measurement Protocols and Improved Fault-Tolerant Overhead". PhD thesis. California Institute of Technology, 2004. DOI: 10.7907/THD5-A335. URL: https://thesis.caltech.edu/1873/.

[SW04] B. Schumacher and R. F. Werner. *Reversible quantum cellular automata*. 2004. arXiv: quant-ph/0405174 [quant-ph]. URL: https://arxiv.org/abs/quant-ph/0405174.

[Got14] Daniel Gottesman. *Fault-Tolerant Quantum Computation with Constant Overhead*. 2014. arXiv: 1310.2984 [quant-ph].

[FGL18] Omar Fawzi, Antoine Grospellier, and Anthony Leverrier. "Constant Overhead Quantum Fault-Tolerance with Quantum Expander Codes". In: *2018 IEEE 59th Annual Symposium on Foundations of Computer Science (FOCS)*. IEEE, Oct. 2018, pp. 743–754. DOI: 10.1109/focs.2018.00076. URL: http://dx.doi.org/10.1109/FOCS.2018.00076.

[Gro19] Antoine Grospellier. "Constant time decoding of quantum expander codes and application to fault-tolerant quantum computation". Theses. Sorbonne Université, Nov. 2019. URL: https://theses.hal.science/tel-03364419.

[KP19] Aleksander Kubica and John Preskill. "Cellular-Automaton Decoders with Provable Thresholds for Topological Codes". In: *Physical Review Letters* 123.2 (July 2019). ISSN: 1079-7114. DOI: 10.1103/physrevlett.123.020501. URL: http://dx.doi.org/10.1103/PhysRevLett.123.020501.

[Gac21] Peter Gacs. *A new version of Toom's proof*. 2021. arXiv: 2105.05968 [cs.FL]. URL: https://arxiv.org/abs/2105.05968.

[BB24] Nikolas P. Breuckmann and Simon Burton. "Fold-Transversal Clifford Gates for Quantum Codes". In: *Quantum* 8 (2024), p. 1372. ISSN: 2521-327X. DOI: 10.22331/q-2024-06-13-1372. URL: http://dx.doi.org/10.22331/q-2024-06-13-1372.

[NP25] Quynh T. Nguyen and Christopher A. Pattison. *Quantum fault tolerance with constant-space and logarithmic-time overheads*. 2025. arXiv: 2411.03632 [quant-ph]. URL: https://arxiv.org/abs/2411.03632.

[BDL26] Shankar Balasubramanian, Margarita Davydova, and Ethan Lake. "A local automaton for the 2D toric code". In: *Quantum* 10 (2026), p. 2125. ISSN: 2521-327X. DOI: 10.22331/q-2026-06-02-2125. URL: http://dx.doi.org/10.22331/q-2026-06-02-2125.

[DOA26] Nadav Drechsler, Yuval Oreg, and Dorit Aharonov. *Autonomous Quantum Memories from Classical Stochastic Processes*. 2026. arXiv: 2610.05589 [quant-ph]. URL: https://arxiv.org/abs/2610.05589.

[SBL26] Nathaniel Selub, Aditya Bhardwaj, and Ethan Lake. *Local decoders for fault-tolerant quantum computation and translation-invariant stabilizer codes*. 2026. arXiv: 2609.11457 [quant-ph]. URL: https://arxiv.org/abs/2609.11457.

# 8 Appendix

## 8.1 Counting Subtrees.

**Claim 8.1.** *Let $G = (V, E)$ be a $\Delta+1$-regular graph, and let $k$ be an integer less than $|E|$. Fix a vertex $r \in V$. There is a constant number $\alpha$, depending only on $\Delta$, such that the number of subgraphs rooted at $r$ with fewer than $k$ edges is at most $\alpha^k$.*

*Proof.* Denote by $T_\Delta$ and $T_2$ the infinity $\Delta$ and binary tress. There is an injection between the subtrees of $G$, rooted at $v$, with at most $k$ edges, to the subtrees of $T_\Delta$ rooted at $v$, with at most $k$ edges. Moreover, there is an injection from the subtrees of $T_\Delta$ rooted at $v$, with at most $k$ edges to the subtrees of $T_2$, rooted at $v$, with at most $k \log \Delta$ edges. The injection is obtained by replacing each of the vertex with a (complete) binary tree over $\Delta - 1$-leaves, each leaf is associated with a outgoing edge of the original vertex.

Thus, it's enough to bound the number of of subtrees in $T_2$ rooted at $v$, with at most $k \log \Delta$ edges, that number is less than the number of binary tress with $k \log \Delta + 1$

leaves. For exact leaves number we get the $k \log \Delta$ Catalan number, which its limit is:

$$\sim \frac{4^{k \log \Delta}}{(k \log \Delta)^{\frac{3}{2}} \sqrt{\pi}} \leq \frac{\Delta^{2k}}{(k \log \Delta)^{\frac{3}{2}} \sqrt{\pi}}$$

Therefore we can bound by:

$$\sum_{j=1}^{k} \frac{\Delta^{2j}}{(j \log \Delta)^{\frac{3}{2}} \sqrt{\pi}} \leq \frac{\Delta^{2k}}{\sqrt{\pi} \log^{\frac{3}{2}} \Delta} \sum_{j=1}^{k} \frac{1}{j^{\frac{3}{2}}} \leq \zeta(\frac{3}{2}) \cdot \frac{\Delta^{2k}}{\sqrt{\pi} \log^{\frac{3}{2}} \Delta}$$

□

## 8.2 Tree Separator Lemma

For a tree $T = (V, E)$ and a vertex $v \in V$, we call the subtree obtained by taking the descendants of $v$ the subtree rooted at $v$.

**Claim 8.2.** *Let $T = (V, E)$ be a tree with $m > 3$ leaves and $\tau$ edges, then it has a subtree with $m' \in (\frac{1}{3}m, \frac{2}{3}m)$ leaves and at most $\frac{m'}{m}\tau$ edges.*

*Proof.* Order the vertices according to their heights. Denote by $v \in V$ the lowest vertex for which the subtree rooted at $v$ has at least $\frac{1}{3}m$ leaves. Now, denote by $T_1$ the subtree obtained through the following iterative process over $v$'s children:

1. Initialize $T_1$ as the subtree rooted at $v$.
2. For a child $u$ of $v$:
   (a) Check if erasing from $T_1$ the subtree rooted at $u$ doesn't decrease the number of leaves below $\frac{1}{3}m$. If so, then we update $T_1$ to be the result of the erasure.

Clearly, the algorithm is defined such that $T_1$ has to have at least $\frac{m}{3}$ leaves. Furthermore, since any child of $v$ is a root of a subtree with fewer than $\frac{m}{3}$ leaves (otherwise we get a contradiction to the minimality of $v$'s height), we have that if $T_1$ would have more than $\frac{2}{3}m$ leaves, then the subtraction of any of its children would yield a tree with at least $\frac{2}{3}m - \frac{1}{3}m = \frac{1}{3}m$ leaves. Namely, $v$ has in $T_1$ a child $u$ such that the subtraction of the subtree rooted at $u$ from $T_1$ results in a subtree with more than $\frac{1}{3}m$ leaves. But if indeed there were such a child, then the algorithm would erase it, so there is not.

Now let $T_2 = T/T_1 \cup v$, namly the tree induced by the subtraction of $T_1$'s edges from $T$. Observes that since the summation of leaves in $T_1$ and $T_2$ is the leaves in $T$, and $T_1$ has no more than $\frac{2}{3}m$ leaves, and no less than $\frac{1}{3}$ leaves, it holds that the number of leaves in $T_2$ is also in the range $(\frac{1}{3}m, \frac{2}{3}m)$. We claim that at least one of the subtrees has fewer than $\frac{m'}{m}\tau$ edges.

To see this, denote by $m_1, m_2$ and by $\tau_1, \tau_2$ the leaves and the edges in $T_1, T_2$ respectively. Now:

$$\frac{\tau}{m} = \frac{\tau_1 + \tau_2}{m_1 + m_2} = \frac{m_1}{m_1 + m_2}\frac{\tau_1}{m_1} + \frac{m_2}{m_1 + m_2}\frac{\tau_2}{m_2}$$

Namely, $\frac{\tau}{m}$ is a weighted average of $\frac{\tau_1}{m_1}$ and $\frac{\tau_2}{m_2}$, and therefore it is greater than their minimum. Peak the subtree with the minimal quotient. □

By repeating recursively on the above construction, we get the following corollary:

**Corollary 8.3.** *Let $T = (V, E)$ be a tree with $m$ leaves and $\tau$ edges. Then, for any $\alpha > 0$, it has a subtree with $m' \in \left(\frac{1}{3}\alpha m, \frac{2}{3}\alpha m\right)$ leaves and at most $\frac{m'}{m}\tau$ edges.*

**Claim 8.4.** *Let $\gamma, \beta \in \mathbb{R}_{>0}$ and $n$ be a positive integer. For any tree $T$ with $\tau \geq \beta n$ edges and $m$ leaves such that $\tau \leq \gamma m$, there is a subtree $T'$ of $T$ with a number of edges $\tau'$ less than $\frac{\beta}{2}n$ and a number of leaves greater than $\frac{\beta}{4\gamma}n$.*

*Proof.* Since the construction of claim 8.2 preserves the ratio of edges to leaves, we have that for a $T'$ obtained using the construction, the number of edges satisfies $\tau' \leq \gamma m'$. So, it's enough to look for the maximal $\alpha$ such that:

$$\gamma m' \leq \gamma \frac{2}{3}\alpha m \leq \frac{\beta}{2}n \Rightarrow \alpha = \frac{3\beta}{4\gamma}\frac{n}{m}$$

Which gives $m' \geq \frac{1}{3}\alpha m = \frac{\beta}{4\gamma}n$.

□