

Heaps - Recitation 4

Correctness, Loop Invariants And Heaps.

November 5, 2022

Apart of quantify the resource requirement of our algorithms we are also interested to prove that they indeed work. In this Recitation we will demonstrate how to prove correctness via the notation of loop invariant. In addition we will present the first (non-trivial) data structure in course, and prove that it allows us to compute the maximum efficiently.

Correctness And Loop Invariant.

In this course, any algorithm is defined relative to a task/problem/function. And it will be said correct if for any input it computes desirable output. For example, suppose that our task is to extract the maximum element from a given array. So the input space are all the arrays of numbers, and proving that a given algorithm is correct, requires to prove that for an arbitrary array the algorithm's output is the maximal number. Formally:

Correctness.

We will say that an algorithm \mathcal{A} (an ordered set of operations) computes $f : D_1 \rightarrow D_2$ if for every $x \in D_1 \Rightarrow f(x) = \mathcal{A}(x)$. Sometimes when it's obvious what is the goal function f , we will abbreviate and say that \mathcal{A} is correct.

Other Examples of functions f might be including any computation tasks: file saving, summing numbers, posting a message in the forum, etc. Let's dive back into the maximum extraction problem and see how correctness should be proved in practice.

Task: Maximum Finding. Given $n \in \mathbb{N}$ numbers $a_1, a_2, \dots, a_n \in \mathbb{R}$ write an Algorithm which returns their maximum.

Consider the following suggestion. How would you prove it correct?

Maximum finding.

Result: returns the maximum of $a_1 \dots a_n \in \mathbb{R}^n$

```
1 let  $b \leftarrow a_1$ 
2 for  $i \in [2, n]$  do
3    $b \leftarrow \max(b, a_i)$ 
4 return  $b$ 
```

Usually it will be convenient to divide the algorithms into subsections and then characterize, and prove correctness for each of them separately. One main technique is using the notation of Loop Invariants. Loop Invariant is a property that characterizes a loop segment code and satisfies the following conditions: