Lecture 5

Transport Layer: part II

Programming Assignment

- Implementing a Reliable Transport Protocol (Bidirectional Go-Back-N version)
  - Problem description: ProgAssn.pdf
  - Due 6/5 23:59:59 (late submission allowed up to 3 days with 10 pts reduction per day)
  - Upload your source file (w/ proper comments) and a design document to KLAS



Implementing Bidirectional GBN

- To write an application-level code simulating Bidirectional Go-Back-N (GBN) protocol
- Your code will have to execute in a simulated hardware/software environment
  - Event-driven simulation
    - Events occur at times determined stochastically by sim. env.
  - e.g. Programming interface from above and from below
  - e.g. Stopping/starting of timers
    - timer interrupts will cause your timer handling routine to be activated
- 8-bit or 16-bit 1's complement checksum operation with bit-wise addition operation is optional (for Extra Credit of 10 pts)
  - Decimal addition ('+') will not receive E.C.
- Piggybacking is required

Chapter 3: Transport Layer

Our goals:

- understand principles behind transport layer services:
  - multiplexing/demultiplexing
  - reliable data transfer
  - flow control
  - congestion control
- learn about transport layer protocols in the Internet:
  - UDP: connectionless transport
  - TCP: connection-oriented transport
  - TCP congestion control

Chapter 3 outline

- 3.1 Transport-layer services
- 3.2 Multiplexing and demultiplexing
- 3.3 Connectionless transport: UDP
- 3.4 Principles of reliable data transfer
- 3.5 Connection-oriented transport: TCP
  - segment structure
  - reliable data transfer
  - flow control
  - connection management
- 3.6 Principles of congestion control
- 3.7 TCP congestion control

TCP: Overview **RFCs: 793, 1122, 1323, 2018, 2581**

- point-to-point:
  - one sender, one receiver
- reliable, in-order *byte steam:*
  - no "message boundaries"
- pipelined:
  - TCP congestion and flow control set window size
- *send & receive buffers*



- full duplex data:
  - bi-directional data flow in same connection
  - MSS: maximum segment size
- connection-oriented:
  - handshaking (exchange of control msgs) init's sender, receiver state before data exchange
- flow controlled:
  - sender will not overwhelm receiver

TCP segment structure



URG: urgent data (generally not used)

ACK: ACK # valid

PSH: push data now (generally not used)

RST, SYN, FIN: connection estab (setup, teardown commands)

Internet checksum (as in UDP)

counting by bytes of data (not segments!)

bytes rcvr willing to accept

TCP seq. #'s and ACKs

Seq. #'s:

- byte stream "number" of first byte in segment's data

ACKs:

- seq # of next byte expected from other side
- cumulative ACK

Q: how receiver handles out-of-order segments

- A: TCP spec doesn't say, - up to implementor



simple telnet scenario

TCP Round Trip Time and Timeout

Q: how to set TCP timeout value?

- longer than RTT
  - but RTT varies
- too short: premature timeout
  - unnecessary retransmissions
- too long: slow reaction to segment loss

Q: how to estimate RTT?

- **`SampleRTT`**: measured time from segment transmission until ACK receipt
  - ignore retransmissions
- **`SampleRTT`** will vary, want estimated RTT "smoother"
  - average several recent measurements, not just current **`SampleRTT`**

TCP Round Trip Time and Timeout

$$\texttt{EstimatedRTT} = (1-\alpha)*\texttt{EstimatedRTT} + \alpha*\texttt{SampleRTT}$$

- Exponential weighted moving average
- influence of past sample decreases exponentially fast
- typical value: $\alpha = 0.125$

Example RTT estimation:



TCP Round Trip Time and Timeout

Setting the timeout

- **`EstimtedRTT`** plus "safety margin"
  - large variation in **`EstimatedRTT ->`** larger safety margin
- first estimate of how much SampleRTT deviates from EstimatedRTT:

```
DevRTT = (1-β)*DevRTT +
             β*|SampleRTT-EstimatedRTT|

(typically, β = 0.25)
```

Then set timeout interval:

```
TimeoutInterval = EstimatedRTT + 4*DevRTT
```

TCP reliable data transfer

- TCP creates rdt service on top of IP's unreliable service
- Pipelined segments
- Cumulative acks
- TCP uses single retransmission timer
- Retransmissions are triggered by:
  - timeout events
  - duplicate acks
- Initially consider simplified TCP sender:
  - ignore duplicate acks
  - ignore flow control, congestion control

TCP sender events:

data rcvd from app:

- Create segment with seq #
- seq # is byte-stream number of first data byte in segment
- start timer if not already running (think of timer as for oldest unacked segment)
- expiration interval: `TimeOutInterval`

timeout:

- retransmit segment that caused timeout
- restart timer

Ack rcvd:

- If acknowledges previously unacked segments
  - update what is known to be acked
  - start timer if there are outstanding segments

TCP sender window



```
NextSeqNum = InitialSeqNum
SendBase = InitialSeqNum

 loop (forever) {
   switch(event)

   event: data received from application above
        create TCP segment with sequence number NextSeqNum
        if (timer currently not running)
             start timer
        pass segment to IP
        NextSeqNum = NextSeqNum + length(data)

    event: timer timeout
        retransmit not-yet-acknowledged segment with
              smallest sequence number
        start timer

    event: ACK received, with ACK field value of y
        if (y > SendBase) {
             SendBase = y
            if (there are currently not-yet-acknowledged segments)
                  start timer
            }

  }  /* end of loop forever */
```

TCP sender
(simplified)

<u>Comment:</u>
- SendBase-1: last cumulatively ack'ed byte

<u>Example:</u>
- SendBase-1 = 71; y= 73, so the rcvr wants 73+ ; y > SendBase, so that new data is acked

TCP: retransmission scenarios



Lost ACK scenario

premature timeout

TCP retransmission scenarios (more)



Cumulative ACK scenario

TCP ACK generation [RFC 1122, RFC 2581]

Event at Receiver	TCP Receiver action
Arrival of in-order segment with expected seq #. All data up to expected seq # already ACKed	Delayed ACK. Wait up to 500ms for next segment. If no next segment, send ACK
Arrival of in-order segment with expected seq #. One other segment has ACK pending	Immediately send single cumulative ACK, ACKing both in-order segments
Arrival of out-of-order segment higher-than-expect seq. # . Gap detected	Immediately send *duplicate ACK*, indicating seq. # of next expected byte
Arrival of segment that partially or completely fills gap	Immediate send ACK, provided that segment starts at lower end of gap

TCP Flow Control

- receive side of TCP connection has a receive buffer:



- app process may be slow at reading from buffer
- speed-matching service: matching the send rate to the receiving app's drain rate

flow control

sender won't overflow receiver's buffer by transmitting too much, too fast

TCP Flow control: how it works



(Suppose TCP receiver discards out-of-order segments)

- spare room in buffer

= `RcvWindow`

= `RcvBuffer-[LastByteRcvd - LastByteRead]`

- Rcvr advertises spare room by including value of **`RcvWindow`** in segments
- Sender limits unACKed data to **`RcvWindow`**
  - guarantees receive buffer doesn't overflow

TCP Connection Management

Recall: TCP sender, receiver establish "connection" before exchanging data segments

- initialize TCP variables:
  - seq. #s
  - buffers, flow control info (e.g. **`RcvWindow`**)
- *client:* connection initiator

```
Socket clientSocket = new
  Socket("hostname","port number");
```

- *server:* contacted by client

```
Socket connectionSocket =
  welcomeSocket.accept();
```

Three way handshake:

Step 1: client host sends TCP SYN segment to server
- specifies initial seq #
- no data

Step 2: server host receives SYN, replies with SYNACK segment
- server allocates buffers
- specifies server initial seq. #

Step 3: client receives SYNACK, replies with ACK segment, which may contain data

TCP Connection Management



TCP Connection Management (cont.)

<u>Closing a connection:</u>

client closes socket:
  `clientSocket.close();`

<u>Step 1:</u> client end system sends TCP FIN control segment to server

<u>Step 2:</u> server receives FIN, replies with ACK. Closes connection, sends FIN.



TCP Connection Management (cont.)

Step 3: client receives FIN, replies with ACK.

- Enters "timed wait" - will respond with ACK to received FINs

Step 4: server, receives ACK. Connection closed.

Note: with small modification, can handle simultaneous FINs.



TCP Connection Management (cont)



TCP client lifecycle

TCP server lifecycle



Chapter 3 outline

- 3.1 Transport-layer services
- 3.2 Multiplexing and demultiplexing
- 3.3 Connectionless transport: UDP
- 3.4 Principles of reliable data transfer
- 3.5 Connection-oriented transport: TCP
  - segment structure
  - reliable data transfer
  - flow control
  - connection management
- 3.6 Principles of congestion control
- 3.7 TCP congestion control

Principles of Congestion Control

Congestion:

- informally: "too many sources sending too much data too fast for *network* to handle"
- different from flow control!
- manifestations:
  - lost packets (buffer overflow at routers)
  - long delays (queueing in router buffers)
- a top-10 problem!

Approaches towards congestion control

Two broad approaches towards congestion control:

End-end congestion control:

- no explicit feedback from network
- congestion inferred from end-system observed loss, delay
- approach taken by TCP

Network-assisted congestion control:

- routers provide feedback to end systems
  - single bit indicating congestion (SNA, DECbit, TCP/IP ECN, ATM)
  - explicit rate sender should send at

Chapter 3 outline

- 3.1 Transport-layer services
- 3.2 Multiplexing and demultiplexing
- 3.3 Connectionless transport: UDP
- 3.4 Principles of reliable data transfer
- 3.5 Connection-oriented transport: TCP
  - segment structure
  - reliable data transfer
  - flow control
  - connection management
- 3.6 Principles of congestion control
- 3.7 TCP congestion control

TCP congestion control: additive increase, multiplicative decrease

- *Approach:* increase transmission rate (window size), probing for usable bandwidth, until loss occurs
  - *additive increase:* increase **CongWin** by 1 MSS every RTT until loss detected
  - *multiplicative decrease*: cut **CongWin** in half after loss

Saw tooth behavior: probing for bandwidth



TCP Congestion Control: details

- sender limits transmission:

`LastByteSent-LastByteAcked` $\leq$ `CongWin`

- Roughly,

$$\boxed{\text{rate} = \frac{\text{CongWin}}{\text{RTT}} \text{ Bytes/sec}}$$

- **`CongWin`** is dynamic, function of perceived network congestion

How does sender perceive congestion?

- loss event = timeout *or* 3 duplicate acks
- TCP sender reduces rate (**`CongWin`**) after loss event

three mechanisms:

- AIMD
- slow start
- conservative after timeout events

TCP Slow Start

- When connection begins, **`CongWin`** = 1 MSS
  - Example: MSS = 500 bytes & RTT = 200 msec
  - initial rate = 20 kbps
- available bandwidth may be >> MSS/RTT
  - desirable to quickly ramp up to respectable rate
- When connection begins, increase rate exponentially fast until first loss event

TCP Slow Start (more)

- When connection begins, increase rate exponentially until first loss event:
  - double `CongWin` every RTT
  - done by incrementing `CongWin` for every ACK received
- <u>Summary:</u> initial rate is slow but ramps up exponentially fast



Refinement

Q: When should the exponential increase switch to linear?

A: When **`CongWin`** gets to 1/2 of its value before timeout.



Implementation:

- Variable Threshold
- At loss event, Threshold is set to 1/2 of CongWin just before loss event

Refinement: inferring loss

- After 3 dup ACKs:
  - **`CongWin`** is cut in half
  - window then grows linearly
- But after timeout event:
  - **`CongWin`** instead set to 1 MSS;
  - window then grows exponentially
  - to a threshold, then grows linearly

Philosophy:

- 3 dup ACKs indicates network capable of delivering some segments
- timeout indicates a "more alarming" congestion scenario

Summary: TCP Congestion Control

- When **`CongWin`** is below **`Threshold`**, sender in slow-start phase, window grows exponentially.
- When **`CongWin`** is above **`Threshold`**, sender is in congestion-avoidance phase, window grows linearly.
- When a triple duplicate ACK occurs, **`Threshold`** set to **`CongWin/2`** and **`CongWin`** set to **`Threshold`**.
- When timeout occurs, **`Threshold`** set to **`CongWin/2`** and **`CongWin`** is set to 1 MSS.

Chapter 3: Summary

- principles behind transport layer services:
  - multiplexing, demultiplexing
  - reliable data transfer
  - flow control
  - congestion control
- instantiation and implementation in the Internet
  - UDP
  - TCP