Lecture 6

Chap. 4 Network Layer, part I

Chapter goals

- understand principles behind network layer services:
  - network layer service models
  - forwarding versus routing
  - how a router works
  - routing (path selection)
  - dealing with scale
  - advanced topics: IPv6
- instantiation, implementation in the Internet

Overview

- 4. 1 Introduction
- 4.2 Virtual circuit and datagram networks
- 4.3 What's inside a router
- 4.4 IP: Internet Protocol
  - Datagram format
  - IPv4 addressing
  - ICMP
  - IPv6
- 4.5 Routing algorithms
  - Link state
  - Distance Vector
  - Hierarchical routing
- 4.6 Routing in the Internet
  - RIP
  - OSPF
  - BGP
- 4.7 Broadcast and multicast routing

Network Layer

- Transport segment from sending to receiving host
- On sending side encapsulates segments into datagrams
- On rcving side, delivers segments to transport layer
- Network layer protocols in *every* host, router
- Router examines header fields in all IP datagrams passing through it



Key Network-Layer Functions

- *forwarding:* move packets from router's input to appropriate router output
- *routing:* determine route taken by packets from source to dest.
  – *Routing algorithms*

analogy:

- routing: process of planning trip from source to dest
- forwarding: process of getting through single interchange

Interplay between routing and forwarding



Overview

- 4. 1 Introduction
- 4.2 Virtual circuit and datagram networks
- 4.3 What's inside a router
- 4.4 IP: Internet Protocol
  - Datagram format
  - IPv4 addressing
  - ICMP
  - IPv6
- 4.5 Routing algorithms
  - Link state
  - Distance Vector
  - Hierarchical routing
- 4.6 Routing in the Internet
  - RIP
  - OSPF
  - BGP
- 4.7 Broadcast and multicast routing

Network layer connection and connection-less service

- Datagram network provides network-layer connectionless service
- VC network provides network-layer connection service
- Analogous to the transport-layer services, but:
  - Service: host-to-host
  - No choice: network provides one or the other
  - Implementation: in the core

Virtual circuits

"source-to-dest path behaves much like telephone circuit"

- performance-wise
- network actions along source-to-dest path

- call setup, teardown for each call *before* data can flow
- each packet carries VC identifier (not destination host address)
- *every* router on source-dest path maintains "state" for each passing connection
- link, router resources (bandwidth, buffers) may be *allocated* to VC

Datagram networks

- no call setup at network layer
- routers: no state about end-to-end connections
  - no network-level concept of “connection”
- packets forwarded using destination host address
  - packets between same source-dest pair may take different paths



IP Packet Forwarding

- Each packet has destination address
- Each switch has forwarding table of destination → next hop
  - At v and x: destination → east
  - At w and y: destination → south
  - At z: destination → north
- Distributed routing algorithm for calculating forwarding tables
- https://www.youtube.com/watch?v=jnJO9ypv3m8

Forwarding table

4 billion
possible entries!

Destination Address Range	Link Interface
11001000 00010111 00010000 00000000 through 11001000 00010111 00010111 11111111	0
11001000 00010111 00011000 00000000 through 11001000 00010111 00011000 11111111	1
11001000 00010111 00011001 00000000 through 11001000 00010111 00011111 11111111	2
otherwise	3

Longest prefix matching

Prefix Match	Link Interface
11001000 00010111 00010	0
11001000 00010111 00011000	1
11001000 00010111 00011	2
otherwise	3

Examples

DA: 11001000 00010111 00010110 10100001 Which interface?

DA: 11001000 00010111 00011000 10101010 Which interface?

How do we set up Routing Tables?

- Graph theory to compute “shortest path”
  - Switches = nodes
  - Links = edges
  - Delay, hops = cost
- Need to adapt to changes in topology

Overview

- 4. 1 Introduction
- 4.2 Virtual circuit and datagram networks
- 4.3 What's inside a router
- 4.4 IP: Internet Protocol
  - Datagram format
  - IPv4 addressing
  - ICMP
  - IPv6
- 4.5 Routing algorithms
  - Link state
  - Distance Vector
  - Hierarchical routing
- 4.6 Routing in the Internet
  - RIP
  - OSPF
  - BGP
- 4.7 Broadcast and multicast routing

Router Architecture Overview

Two key router functions:

- run routing algorithms/protocol (RIP, OSPF, BGP)
- *forwarding* datagrams from incoming to outgoing link



Input Port Functions



Physical layer:
bit-level reception

Data link layer:
e.g., Ethernet
see chapter 5

Decentralized switching:

- given datagram dest., lookup output port using forwarding table in input port memory
- goal: complete input port processing at 'line speed'
- queuing: if datagrams arrive faster than forwarding rate into switch fabric

Three types of switching fabrics



Switching Via Memory

First generation routers:

- traditional computers with switching under direct control of CPU
- packet copied to system's memory
- speed limited by memory bandwidth (2 bus crossings per datagram)



Switching Via a Bus

- datagram from input port memory to output port memory via a shared bus
- bus contention: switching speed limited by bus bandwidth
- 1 Gbps bus, Cisco 1900: sufficient speed for access and enterprise routers (not regional or backbone)



Switching Via An Interconnection Network

- overcome bus bandwidth limitations
- Crossbar provides full NxN interconnect
  - Expensive
- Banyan networks, other interconnection nets initially developed to connect processors in multiprocessor
- Advanced design: fragmenting datagram into fixed length cells, switch cells through the fabric.
- Cisco 12000: switches Gbps through the interconnection network

Output Ports



- *Buffering* required when datagrams arrive from fabric faster than the transmission rate
- *Scheduling discipline* chooses among queued datagrams for transmission

Output port queueing



- buffering when arrival rate via switch exceeds output line speed
- *queueing (delay) and loss due to output port buffer overflow!*
- Scheduling discipline chooses among queued datagrams for transmission
  - Can be simple (e.g., first-come first-serve) or more clever (e.g., weighted round robin)

Overview

- 4. 1 Introduction
- 4.2 Virtual circuit and datagram networks
- 4.3 What's inside a router
- 4.4 IP: Internet Protocol
  - Datagram format
  - IPv4 addressing
  - ICMP
  - IPv6
- 4.5 Routing algorithms
  - Link state
  - Distance Vector
  - Hierarchical routing
- 4.6 Routing in the Internet
  - RIP
  - OSPF
  - BGP
- 4.7 Broadcast and multicast routing

The Internet Network layer

Host, router network layer functions:



IP datagram format

IP protocol version number

header length (bytes)

"type" of data

max number remaining hops (decremented at each router)

upper layer protocol to deliver payload to



total datagram length (bytes)

for fragmentation/ reassembly

e.g. timestamp, record route taken, specify list of routers to visit.

<u>how much overhead with TCP?</u>

- 20 bytes of TCP
- 20 bytes of IP
- = 40 bytes + app layer overhead

IP Fragmentation & Reassembly

- network links have MTU (max.transfer size) - largest possible link-level frame.
  – different link types, different MTUs
- large IP datagram divided (“fragmented”) within net
  – one datagram becomes severa datagrams
  – “reassembled” only at final destination
  – IP header bits used to identify, order related fragments



IP Fragmentation and Reassembly

Example

- 4000 byte datagram
- MTU = 1500 bytes



1480 bytes in data field

offset = 1480/8

IP Addressing: introduction

- IP address: 32-bit identifier for host, router *interface*
- *interface:* connection between host/router and physical link
  - router's typically have multiple interfaces
  - host typically has one interface
  - IP addresses associated with each interface



223.1.1.1 = $\underbrace{11011111}_{223}\ \underbrace{00000001}_{1}\ \underbrace{00000001}_{1}\ \underbrace{00000001}_{1}$

Addressing in IP

- IP addresses are names of interfaces
- Domain Name System (DNS) names are names of hosts
- DNS binds host names to interfaces

Addressing Considerations

- Fixed length or variable length?
- Issues:
  - Flexibility
  - Processing costs
  - Header size
- Engineering choice: IP uses fixed length addresses

Addressing Considerations

- Structured vs flat
- Issues
  - What information would routers need to route to Ethernet addresses?
    - Need structure for designing scalable binding from interface name to route!
  - How many levels? Fixed? Variable?

IP Addresses

- Fixed length: 32 bits
- Initial classful structure (1981)
- Total IP address size: 4 billion
  - Class A: 128 networks, 16M hosts
  - Class B: 16K networks, 64K hosts
  - Class C: 2M networks, 256 hosts

High Order Bits	Format	Class
0	7 bits of net, 24 bits of host	A
10	14 bits of net, 16 bits of host	B
110	21 bits of net, 8 bits of host	C

IP Address Classes
(Some are Obsolete)



Some Special IP Addresses

- 127.0.0.1: local host (a.k.a. the loopback address)
- Host bits all set to 0: network address
- Host bits all set to 1: broadcast address

Interaction with Link Layer

- How does one find the Ethernet address of a IP host?
- ARP
  - Broadcast search for IP address
    - E.g., “who-has 128.2.184.45 tell 128.2.206.138” sent to Ethernet broadcast (all FF address)
  - Destination responds (only to requester using unicast) with appropriate 48-bit Ethernet address
    - E.g, “reply 128.2.184.45 is-at 0:d0:bc:f2:18:58” sent to 0:c0:4f:d:ed:c6

Original IP Route Lookup

- Address classes
  - A: 0 | 7 bit network | 24 bit host (16M each)
  - B: 10 | 14 bit network | 16 bit host (64K)
  - C: 110 | 21 bit network | 8 bit host (256)
- Address would specify prefix for forwarding table
  - Simple lookup

Original IP Route Lookup – Example

- ce.kw.ac.kr address 128.134.54.178
  - Class B address – class + network is 128.134
  - Lookup 128.134 in forwarding table
  - Prefix – part of address that really matters for routing
- Forwarding table contains
  - List of class+network entries
  - A few fixed prefix lengths (8/16/24)
- Large tables
  - 2 Million class C networks

Subnets

- IP address:
  - subnet part (high order bits)
  - host part (low order bits)
- *What's a subnet ?*
  - device interfaces with same subnet part of IP address
  - can physically reach each other without intervening router



network consisting of 3 subnets

Subnets

Recipe

- To determine the subnets, detach each interface from its host or router, creating islands of isolated networks. Each isolated network is called a subnet.



Subnet mask: /24

Subnets

How many?



Subnet Addressing
RFC917 (1984)

- For class B & C networks
- Very few LANs have close to 64K hosts
  - For electrical/LAN limitations, performance or administrative reasons
- Need simple way to get multiple “networks”
  - Use bridging, multiple IP networks or split up single network address ranges (subnet)
  - Must reduce the total number of network addresses that are assigned

Subnetting

- Variable length subnet masks
  - Could subnet a class B into several chunks



Subnetting Example

- Assume an organization was assigned address 150.100
- Assume < 100 hosts per subnet
- How many host bits do we need?
  - Seven
- What is the network mask?
  - 11111111 11111111 11111111 10000000
  - 255.255.255.128

IP addresses: how to get one?

Q: How does *host* get IP address?

- hard-coded by system admin in a file
  - Wintel: control-panel->network->configuration->tcp/ip->properties
  - UNIX: /etc/rc.config
- DHCP: Dynamic Host Configuration Protocol: dynamically get address from as server
  - "plug-and-play"

IP addressing: the last word...

Q: How does an ISP get block of addresses?

A: ICANN: Internet Corporation for Assigned Names and Numbers

- allocates addresses
- manages DNS
- assigns domain names, resolves disputes

NAT: Network Address Translation



All datagrams *leaving* local network have *same* single source NAT IP address: 138.76.29.7, different source port numbers

Datagrams with source or destination in this network have 10.0.0/24 address for source, destination (as usual)

NAT: Network Address Translation

- Motivation: local network uses just one IP address as far as outside world is concerned:
  - range of addresses not needed from ISP: just one IP address for all devices
  - can change addresses of devices in local network without notifying outside world
  - can change ISP without changing addresses of devices in local network
  - devices inside local net not explicitly addressable, visible by outside world (a security plus).

NAT: Network Address Translation

Implementation: NAT router must:

- *outgoing datagrams: replace* (source IP address, port #) of every outgoing datagram to (NAT IP address, new port #)

  . . . remote clients/servers will respond using (NAT IP address, new port #) as destination addr.

- *remember (in NAT translation table)* every (source IP address, port #) to (NAT IP address, new port #) translation pair

- *incoming datagrams: replace* (NAT IP address, new port #) in dest fields of every incoming datagram with corresponding (source IP address, port #) stored in NAT table

NAT: Network Address Translation

2: NAT router changes datagram source addr from 10.0.0.1, 3345 to 138.76.29.7, 5001, updates table

1: host 10.0.0.1 sends datagram to 128.119.40.186, 80



3: Reply arrives dest. address: 138.76.29.7, 5001

4: NAT router changes datagram dest addr from 138.76.29.7, 5001 to 10.0.0.1, 3345

NAT: Network Address Translation

- 16-bit port-number field:
  - 60,000 simultaneous connections with a single LAN-side address!
- NAT is controversial:
  - routers should only process up to layer 3
  - violates end-to-end argument
    - NAT possibility must be taken into account by app designers, eg, P2P applications
  - address shortage should instead be solved by IPv6

ICMP: Internet Control Message Protocol

- used by hosts & routers to communicate network-level information
  - error reporting: unreachable host, network, port, protocol
  - echo request/reply (used by ping)
- network-layer "above" IP:
  - ICMP msgs carried in IP datagrams
- ICMP message: type, code plus first 8 bytes of IP datagram causing error

Type	Code	description
0	0	echo reply (ping)
3	0	dest. network unreachable
3	1	dest host unreachable
3	2	dest protocol unreachable
3	3	dest port unreachable
3	6	dest network unknown
3	7	dest host unknown
4	0	source quench (congestion control - not used)
8	0	echo request (ping)
9	0	route advertisement
10	0	router discovery
11	0	TTL expired
12	0	bad IP header

Traceroute and ICMP

- Source sends series of UDP segments to dest
  - First has TTL =1
  - Second has TTL=2, etc.
  - Unlikely port number
- When nth datagram arrives to nth router:
  - Router discards datagram
  - And sends to source an ICMP message (type 11, code 0)
  - Message includes name of router& IP address

- When ICMP message arrives, source calculates RTT
- Traceroute does this 3 times

Stopping criterion

- UDP segment eventually arrives at destination host
- Destination returns ICMP "host unreachable" packet (type 3, code 3)
- When source gets this ICMP, stops.