



Registration APIs

Enterprise API

Contents

1. Introduction	3
1.1 Authorization Token	3
1.2 Refresh Token	5
2. Header Registration	6
2.1 Register a Header	6
3. Content Template Registration	9
3.1 Register a Content Template	10
3.2 Link or de-link Headers to Content Template	12
5. Annexure	14
4.1 Status Codes	14
4.2 Categories	15

1. Introduction

This REST API document describes the API details and the fields to be sent on the API to:

- Register a new Header
- Register a new Content Template
- Link or De-Link Headers to a Content Template
- Mapping Consent Template to Content Templates
- Register a New Consent Template

You must Whitelist the IP addresses from which you will be sending these API requests, before sending any requests.

1.1 Authorization Token

Invoke this API to get the **access** and **refresh** tokens. Access token is required to invoke any further API requests. The request and response will be in JSON format.

Username: Use your DLT ID

Password: Use Generate/Reset password link on the portal (This password will be sent to your registered email).

The access token is valid for **24 hours** from the time it is created. The user must get a new access token every 24 hours.

The refresh token is valid for 30 days, post which you must invoke the below API again to get a new refresh token.

URL: <https://XX.XX.XX.XXX/api/token/>

Method: **POST**

Parameters:

Parameter	Data Type	Description
username	string (20)	DLT Entity ID for the account
password	string (20)	Password generated on Telco portal for Enterprise API

Note: Access token must be passed in authorization header as the bearer token.

Eg: Authorization: Bearer <access token>

Response:

The response will be in JSON format.

Success response:

```
{
  "refresh": "eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ0b2t1b190eXBlljoicmVmcmVzaClslmV4cCI6MTU0ODM5MzU5NCwianRpljoiYjFIZGFjYzE3ZTcxNGlwYmlyMzJkYzRlM2ZmYzFiNjMiLCJ1aWQiOiJk1fQ.GrUjW4shdeQHk4rKhK19kPs5bedX3baaAt1UgeuEtTo"
  "access": "eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ0b2t1b190eXBlljoiYWNjZXNzliwiZXwljoxNTQ1ODg3OTk0LCJqdGkiOiJwYjVhMmQzMWYyYmM0NmE3YWl2MjZlZDAzMTA4ZDFkNylsInVpZCI6OTV9.joB_MjW1tCrFXGOJGROnIUE0-cBaC5U-mYQ0B6qoqp8"
}
```

Failed response:

If no User is found with the passed credentials:

```
{
  "status": 407,
  "message": "Invalid login credentials"
}
```

If account status is not active:

```
{
  "status": 405,
  "message": "PE not active"
}
```

If API access is not enabled:

```
{
  "status": 424,
  "message": "API not enabled for this account"
}
```


2. Header Registration

Header is a unique combination of 3-6 characters representing the Brand Name of the message sender. As per the TCCCPR regulation the sender ID/source address/A-Party address is termed as 'Header'. You can use this API to register a new Header for your Enterprise by using the below API. The Promotional Headers must be numeric and the headers for all the *Other* types (Transactional, Service Implicit and Service Explicit) must be Alphabet or Alphanumeric.

2.1 Register a Header

Use the below API request to register a header for your Enterprise. The request and response will be in JSON format and method will be 'POST'.

URL: <https://XX.XX.XX.XXX/api/header>

Parameters:

Parameter	Type	Mandatory/ Optional	Description
Eid	String (20)	Mandatory	Your Entity ID which is assigned after registering on the portal.
Htype	String (2)	Mandatory	Type of Header - P/O P - Promotional O – <i>Other</i> (Transactional/Service Implicit (SI)/Service Explicit (SE)).
Hctgy	Integer	Mandatory	Category ID. Refer Annexure 5.2
Hdr	String (6)	Mandatory	Header Name (Numeric for Promotional category, Alphabet/Alphanumeric for all <i>Other</i> Types).
Hdesc	String (100)	Mandatory	Description of Header, must be alphanumeric special characters allowed are (), . ! @ # % * _ & - \$
cburl	String (100)	Optional	Callback URL to be notified about the status changes of the header.

Types of headers based on the SMS category:

1. **Promotional:** These messages are related to marketing purposes and are intended for promoting a product or a service. Promotional SMSs are sent to the Non DND numbers.

Headers for sending Promotional SMS must be of 6 numeric and based on the relevant business category. (Refer Annexure 5.2)

Examples: Promotional messages headers: 234567, 345678, 456789, 578901 and in API must use *htype*

as “P” and *hctgy* as 2 and header must be “234567”

2. **Other:** The *Other* category comprises of Transactional, Service Implicit (SI) and Service Explicit (SE).

2.1 Transactional: As per the latest TRAI Guidelines, only the OTP SMS sent by banks will come under the category of Transactional SMS. Transactional SMS can be used only by banks for sending One Time Password (OTP) to its clients. All banks including National / Scheduled / Government / Private and MNC Banks can send OTP to their clients from the Transactional route.

Note: Banks can use Transactional route for sending OTP only. Headers for Transactional details, amount debited, credited, account status and all other bank messages must not be registered as Transactional.

2.2 Service Implicit: Informative messages other than Banks OTP come under this category. Important notifications such as purchase updates, order alerts, payment status, reminders, booking confirmations, OTP SMS from other sites and other crucial updates must be registered as Service Implicit.

2.3 Service Explicit: Sending offer/marketing SMS to your registered users will come under this category. These SMS can only be sent to the registered customers after receiving their consent.

Headers Registration guidelines for sending Transactional, Service Implicit and Service Explicit messages

For Non-Government Entities: For Alphabetic/Alphanumeric headers, length should always be between 3-6 (Min:3 Max:6).

Examples: HDFCBK, gevtc, gbv5, KAR.

For Government Entities:

- i. For numeric header, it should always start with 1 and header length should be in between 3-5 numeric.
Examples: 123, 12321
- ii. For Alphabet/Alphanumeric header length should always be in between 3-6 (Min:3 Max:6).
Examples: gotb, govtcd, gov3, 333g.

Sample API request:

Request:

```
{
  "eid": "1123456789012345678",
  "htype": "P",
  "hctgy": 1,
  "hdr": "123434",
  "desc": "Sample Creation of header"
}
```

Response:

The response will be in JSON format and it contains status, message and hid (max length 19). The status 200 indicates the header request is accepted by DLT API platform and returns 19-digit unique reference hid (Header ID).

Parameter	Type	Mandatory/ Optional	Description
status	Integer	Mandatory	Refer Annexure 5.1 for list of statuses
hid	String (20)	Mandatory	Header id generated for this transaction.
msg	String (200)	Mandatory	Relevant message to identify the reason for failure/success. Refer Annexure 5.1

Success response:

```
{
  "status": 200,
  "hid": "1156789012345678234",
  "msg": "Header request submitted successfully"
}
```

Failure response:

Any status other than 200 indicates a failure response.

Sample1: API Internal error

```
{
  "status": 500,
  "msg": "System error"
}
```

Sample2: If user passes invalid value in header type parameter.

```
{
  "status": 403,
  "msg": "Invalid Argument value or type – htype "
}
```


3. Content Template Registration

As per the new TCCCPR 2018 regulation, it is mandatory for an Entity to register their SMS content as a Content Template on DLT platform. Content templates can be used to send messages to the subscribers only after approval. You can only use below 6 variables in the content template for Dynamic data:

{#numeric#}

- Usage: Strictly for numeric values such as OTPs, transaction amounts, counts.
- Example Value: 748392
- Maximum Character limit: 40 Characters
- Sample Template Message: Your OTP is {#numeric#}.

{#alphanumeric#}

- Usage: Used for mixed values containing letters and numbers like reference IDs, ticket numbers, addresses, etc.
- Example Value: SRV9821AB or 11B Worli Mumbai
- Maximum Character limit: 40 Characters
- Sample Template Message: Your service request ID is {#alphanumeric#}.

{#url#}

- Usage: Used for website URLs such as tracking links or portals.
- Example Value: <https://track.company.com/order123>
- Maximum Character limit: 40 Characters
- Sample Template Message: Track your order here {#url#}

{#urlott#}

- Usage: Used for OTT links or mobile application download links.
- Example Value: <https://wa.me/1XXXXXXXXXX>
- Maximum Character limit: 40 Characters
- Sample Template Message: Download our app from {#urlott#} to manage your account.

{#cbn#}

- Usage: Used for callback or support contact numbers.
- Example Value: 1800123456
- Maximum Character limit: 12 Characters
- Sample Template Message: For assistance, call us at {#cbn#}.

{#email#}

- Usage: Used for email addresses mentioned in SMS.
- Example Value: support@company.com
- Maximum Character limit: 40 Characters
- Sample Template Message: Write to us at {#email#}.

3.1 Registering a Content Template

The below API request to register a Content Template for an Enterprise. The request and response will be in JSON format and method will be 'POST'.

URL: https://XX.XX.XX.XXX/api/content_template

Parameters:

Parameter	Type	Mandatory/ Optional	Description
eid	String (20)	Mandatory	Your Entity ID which is assigned after registering on the portal.
ttype	String (2)	Mandatory	Type of Template - P/T/SI/SE "P" - Promotional "T" - Transactional "SI" - Service Implicit "SE" - Service Explicit Example: "P"
ctgy	Integer	Mandatory	Category ID. Refer Annexure 5.2
hdrs	Array	Mandatory	Headers array (Max 5 are allowed per request) Header Names (Numeric for Promotional and Alphabets/Alphanumerics for all the <i>Other</i> Types)
msgtype	Integer	Optional (Default:1)	Message Type, values allowed: 1-Text 2-Regional
bname	String (50)	Optional	Active Brand Name, that has been registered on the Platform.
lobid	String (20)	Optional	Active LOB ID, to link template with an LOB
tname	String (50)	Mandatory	Template Name and Only ascii characters are allowed.
tmsg	String (2000)	Mandatory	Template Message Refer Rule v
cburl	String (100)	Optional	Callback URL which will notify about the status of the Content Template
smsg	String (2000)	Mandatory	Sample Message Refer rule Vi

Rules:

- i. Category(ctgy) is mandatory for all Templates.
- ii. You can define Variables only in formats specified above.
- iii. Multiline templates must be separated with \n in template message.
- iv. If Message Type is 1 (Text) only ascii characters are allowed in template message If Message Type is 2 (Regional) must contain at least one non-ascii character in template message.
- v. Sample message should be in the same format of template message with sample values in place of variables. Static text in Sample message should be exactly matching with the static text in Template message. If not, template would be backlisted. If template message is "Hi {#alphanumeric#}, Your OTP is {#numeric#}" then Sample message must be "Hi John, Your OTP is 54321"
- vi. A maximum of 5 headers is supported per request in "hdrs" array.

The sample API request:

Request:

```
{
  "eid": "1123456789012345678",
  "ttype": "P",
  "ctgy": 1,
  "hdrs": ["123434", "124434", "122434"],
  "msgtype": 1,
  "bname": "TestBrand",
  "lobid": "1116175635855605072",
  "tname": "Sample Creation of Template Name",
  "tmsg": "Dear {#alphanumeric#}. your order {#alphanumeric#} has been confirmed and is
scheduled for delivery on {#numeric#}. Track your order here: {#url#}. For support call us at {#cbn#} or
email {#email#}.",
  "smsg": "Dear John Smith. your order ORD-2026-XYZ123 has been confirmed and is scheduled
for delivery on 25-Jan-2026. Track your order here: https://track.example.com/order123. For support
call us at 1800-123-4567 or email support@example.com."
}
```

Response:

The response will be in JSON format and it contains status, message and ctid(max length 19). The status 200 indicates the Content Template request is accepted by DLT API platform and returns 19-digit unique reference ctid (Content Template ID).

Parameter	Type	Mandatory/ Optional	Description
status	Integer	Mandatory	Refer Annexure 5.1 for list of status
ctid	String (20)	Mandatory	Content Template id for this transaction
msg	String (200)	Mandatory	Relevant message to identify the reason for failure/success. Refer Annexure 5.1

Success response:

```
{
  "status": 200,
  "ctid": "1145678901234567823",
  "msg": "Template request submitted successfully"
}
```

Failure response:

Any status other than 200 indicates a failure response.

Sample1: API Internal error

```
{
  "status": 500,
  "msg": "System error"
}
```

Sample2: If user passes invalid value in template type parameter

```
{
  "status": 403,
  "msg": "Invalid Argument value or type – ttype"
}
```

3.2 Link or de-link Headers to Content Template

Use this API to link/de-link headers for approved content templates.

The below API request to add or remove headers for existing content templates for your Entity. The request and response will be in JSON format and method will be 'POST'.

URL: https://XX.XX.XX.XXX/api/addremove_template_headers

Parameters:

Parameter	Type	Mandatory/ Optional	Description
eid	String (20)	Mandatory	Your Entity ID which is assigned after registering on the portal.
ctid	String (20)	Mandatory	Active Content Template Id which is generated on the platform.
type	Integer	Optional (Default:1)	To Link/Delink of headers use below values 1-Add (Link) 2-Remove (Delink)

hid	String (20)	Mandatory	Active Header Id which is generated on the platform.
-----	-------------	-----------	--

Sample API request:

Request to Link Header for Content Template:

```
{
  "eid": "1123456789012345678",
  "ctid": "1145678901234567823",
  "type": 1,
  "hid": "1156789012345678234"
}
```

Request to DeLink Header for Content Template:

```
{
  "eid": "1123456789012345678",
  "ctid": "1145678901234567823",
  "type": 2,
  "hid": "1156789012345678234"
}
```

Response:

The response will be in JSON format, and it contains status and message. Status 200 indicates the header is successfully linked to content template by DLT API platform.

Parameter	Type	Mandatory/ Optional	Description
status	Integer	Mandatory	Refer Annexure 5.1 for list of status
ctid	String (20)	Mandatory	Header linked to this Content Template id
msg	String (200)	Mandatory	Relevant message to identify the reason for failure/success. Refer Annexure 5.1

Success response:

```
{
  "status": 200,
  "ctid": "1145678901234567823",
  "msg": "Header added to Template successfully"
}
```

Failure response:

Any status other than 200 indicates a failure response.

Sample1: API Internal error

```
{
```

```

    "status": 500,
    "message": "System error"
  }

```

Sample2: If user passes invalid value in content template id parameter

```

{
  "status": 403,
  "message": "Invalid Argument value or type – ctid "
}

```

5. Annexure

4.1 Status Codes

Code	Description
200	Success
401	Invalid token or Token expired
402	Invalid method
403	Invalid Argument value or type - <parameter name>
404	Parameter is missing
405	PE not active
406	PE validity expired
407	Invalid login credentials
408	<parameter info> not active
409	<parameter info> not found
410	IP not whitelisted
411	PE ID mismatch
412	<parameter info> already registered
413	Invalid <parameter info>
414	Category is allowed only for promotional template messages
415	Maximum 5 headers are allowed

416	Duplicate headers in hdrs
417	Invalid template variable in tmsg
419	Template cannot be linked to Blacklisted <parameter info>
420	<parameter info> already linked to Content Template
421	<parameter info> not linked to Content Template
422	At least one header must be linked to Content Template
423	<parameter info> approval pending
424	API not enabled for this account
500	System error

4.2 Categories

ID	Description
0	Other
1	Banking/Insurance/Financial products/credit cards
2	Real Estate
3	Education
4	Health
5	Consumer goods and automobiles
6	Communication/Broadcasting/Entertainment/IT
7	Tourism and Leisure
8	Food and Beverages