📝 Notes

Mar 12, 2026

App Build Pairing

Invited David Ukauwa Lizzy Evans Milan Cvijetinovic

Attachments App Build Pairing

Meeting records Transcript

Summary

Simplification of the 154 customer mobile build process with React Native necessitates an admin dashboard workflow for build creation and version updates.

Build Automation Scope Defined
The automation scope was clarified: iOS supports full build creation and updates, but Android only supports build updates, not initial creation, due to Google Play API limitations. Phase 1 automation is limited to pushing builds to internal testers on TestFlight and App Tester, as public store submission requires manual steps.

Admin Workflow and Input Fields
A step-by-step Angular component workflow was confirmed for build generation, requiring crystal-clear guidance and tool tips for all input fields. Specific fields for iOS builds were reviewed, and a mechanism to prevent build failure was implemented by disabling deployment if Game Center is active.

Error Handling and Field Locking
To improve efficiency, fields were removed or hidden, including hardcoding the email address used for intros. For build updates, key fields like Bundle ID and Package ID must remain locked, but fields associated with sensitive keys must be editable if a build fails due to invalidated certificates.

Details

- **Current Mobile Build Process and Challenges**: The existing process for creating mobile application builds for over 154 customers is highly involved and manual, currently being managed as the full-time job of Ilia. This process requires Ilia to gather input fields, IDs, keys, and assets, bundle them, use Bit to generate the build, obtain the build file, and then manually submit it to the Apple App Store and Google Play Store, with different flows required for each native platform. App builds are timed to occur a few weeks or 30 days prior to a customer's event launch date to ensure the latest code version is included (00:00:00).
- **Application Version Update Strategy**: Version updates are not universally applied to all customers; instead, they are selectively performed based on whether an application needs the latest version to de-risk the process. Updates are cycled through based on event schedules, meaning an app for a customer with an event in September 2025 and the next in September 2026 will not be continually updated manually in the intervening period, especially since the event is deactivated 30 days after the event ends. This highly involved process covers both initial application creation and subsequent version updates (00:01:13).
- **Goal for React Native Build Simplification**: The goal with React Native is to simplify this complex and differentiated process for Ilia (00:01:13). The plan is to create a dedicated page within the Engage admin dashboard where Ilia or other personnel can generate these builds (00:02:17).
- **Proposed Build Generation Workflow**: The new system needs a step-by-step workflow with clear, crystal-clear guidance, including tool tips, for all required input fields. Guidance must explain the source of the input, whether it can be edited after initial use, and detail actions such as uploading files or clearing certificates/provisioning profiles (00:02:17). This workflow is intended for two purposes: initial application creation and subsequent updates to ensure the application gets the latest code version (00:03:33). Milan Cvijetinovic confirmed that they are implementing an Angular component with a stepper to manage this linear, step-by-step workflow, similar to existing functions in the native integration and emails sections (00:02:17).
- **Build Update Process in the New System**: When updating a build, saved information will be available. Users can navigate between steps using "next, next, next" or by clicking on the header of a specific step (e.g., clicking on the fourth step in edit mode to navigate directly there) (00:03:33).

- **Scope Definition for Android and iOS Build Automation**: There was an initial misunderstanding regarding the automation scope, specifically for Android. The clarification reached during the meeting is that they cannot automate the *initial* build creation process for Android due to a lack of an exposed API on the Google Play console, but they *can* automate the build *update* process (version updates) for Android (00:05:37). For iOS, they can automate both the build creation and version update processes (00:06:33).
- **Build Submission and Target Scope**: The automated process is intended to generate a build that can be submitted automatically (00:08:21). For iOS, the generated file will be uploaded to TestFlight. For Android, the file will be uploaded to App Tester (00:10:24). **Crucially, for the first version (Phase 1), the system will only support pushing the build to internal testers, not to public stores** (00:11:19). Pushing to public stores is out of scope because it requires additional manual steps like sending the app for review and attaching screenshots/descriptions. The ability to publish and unpublish applications via the admin portal is also out of scope for now (Phase 1/Phase 2) (00:09:09) (00:12:20).
- **Phase 1 Automation Goal and Ilia's Role**: The primary objective for Phase 1 is to automate the creation of the build file, the admin interface, and the push to TestFlight or App Testers, which will save a huge portion of Ilia's work. However, the remaining steps, such as sending the build for review, will still need to be done manually, a process Igor Petrović noted that Ilia actually prefers due to the high degree of management involved (00:12:20).
- **Retrieving App Store Approval Status**: The system will include the functionality to retrieve information from the stores regarding the approval status of the builds. This baseline feature is considered very helpful for the delivery and support teams, saving time spent figuring out which version is live (00:13:13).
- **iOS Build Input Fields and Tool Tips**: Inputs required for Apple builds, along with their sources, were reviewed: App Store App Name (30 characters, sourced from customer input); Apple Bundle ID (created in a specific format like `com.appname.appsuffix`); Apple Team ID (must be copied from the Apple Developer Portal) (00:14:20); Apple Key Name, Apple Issuer ID, and Apple Key ID (all sourced from App Store Connect) (00:15:17) (00:18:19). Tool tips are required for all fields to clearly indicate their source (00:14:20).
- **Read-Only Apple App Store Connect ID Field**: The Apple App Store Connect ID will be a read-only field (00:15:17). This ID is not filled in until the step is

completed; the API will generate and fill it. Milan Cvijetinovic confirmed that this field will only be visible in edit mode, not during initial creation (00:17:29).

- **Game Center Disabled Warning and Build Failure Prevention**: A warning message regarding Game Center being disabled will be displayed if a build generation attempt fails due to this issue. An API call checks if Game Center is enabled, and if it is, this indicates that iOS deployment is impossible (00:15:17). Instead of allowing the build to fail, Milan Cvijetinovic disabled the toggle for deployment until the user manually turns off Game Center in the Apple Developer Portal. The associated tool tip explains that the build will fail if Game Center is disabled, prompting the user to amend settings in the Apple Developer Portal (specifically the bundle ID section) to proceed (00:16:35).
- **File Upload Dependencies for Apple Builds**: The 'Upload only API key file' field requires that the Apple Team ID be entered first. This is because the Team ID determines the location of the S3 folder where the file must be placed (00:18:19). Milan Cvijetinovic explained that uploading is an immediate action triggered when the file is chosen, sending it to S3, independent of clicking "save and continue". Therefore, the upload functionality is disabled until the Apple Team ID has been entered (00:20:19). To enable the "Save and Continue" button, all required fields—including the Apple Key Name, Apple Issuer ID, and Apple Key ID—and the necessary files must be populated. If the Team ID is changed after the files have been uploaded, the user will need to re-upload the files. David Ukauwa suggested moving the upload to a separate step to lock in the Team ID, as changing it messes up the upload process (00:21:16).
- **Clear Certificates and Provisioning Profiles Functionality**: This functionality allows deletion of certificates and provisioning profiles stored in the S3 bucket. These profiles are created on the Apple Developer Portal for signing iOS builds. Clients sometimes delete the platform's certificates, which invalidates them, necessitating their deletion from S3 so that new ones can be created and stored. If certificates are deleted, all provisioning profiles are automatically invalidated, though clients may sometimes only invalidate profiles (00:23:32).
- **Context and Placement of Clear Certificates Functionality**: A user would know they need to clear certificates by checking the Apple Developer Portal or by waiting for a build to fail due to an invalid certificate (00:23:32). Igor Petrović noted that if certificates are deleted via the dashboard, Bitrise will automatically create and push new ones. This action is typically an edge case, but the buttons are included "just in case" (00:24:47). Lizzy Evans expressed concern that users might randomly click the clear buttons if the context is

unclear (00:25:48). It was concluded that the tool should only be used if a build fails due to provisioning profiles or certificates, and therefore, it should be moved from the main build creation workflow (00:27:21). Igor Petrović will investigate whether an API exists to check certificate validity (00:26:27). Milan Cvijetinovic suggested showing the logs (potentially using a JSON viewer like in the integration area) on the final step if the build fails, and adding the clear buttons near the failure message (00:28:14). The clear certificate/profile actions are separate endpoint calls (00:30:00).

- **Security Considerations for Sensitive IDs and Keys**: Discussion focused on whether keys and sensitive IDs should be masked on the frontend, similar to other tokens on the app management page (00:30:42). Milan Cvijetinovic explained that masking (e.g., with stars) is not possible for these specific fields because the form sends the keys back to the API, which writes them to a file; if masked, the API would write stars instead of the actual key values. Igor Petrović noted that these specific keys are not as sensitive as Firebase keys because, to cause damage, one would need to download a complete folder/file associated with the keys (00:31:54) (00:33:51). Lizzy Evans insisted on checking with D and Pablo for security awareness, given recent escalations regarding Firebase keys (00:31:54) (00:34:43). The page for build creation will only be accessible internally and not by implementation partners, which mitigates some risk (00:32:57) (00:35:34).
- **Android Build Prerequisites in Google Play Console**: Since Android's initial build creation cannot be automated, a clear explainer is needed to inform users (e.g., Ilia) that they must perform manual steps in the Google Play Console before using the dashboard page (00:35:34). Specifically, the app must first be created in the Google Play Console, and a user needs to be added (a step Igor Petrović detailed in a separate document) (00:36:48) (00:39:50).
- **Android Build Input Fields (Dashboard)**: The only required inputs for the Android build process on the Engage admin dashboard are the Package ID, Firebase App ID, and a list of App Tester Emails (00:40:52). The Package ID (e.g., `events.grip.appname.ID`) is sourced from the Google Play Console once the app is created there (00:41:58). The Firebase App ID is sourced from the Firebase project, which is assumed to have been created prior to this step (a task currently handled by the support team) (00:43:08). Lizzy Evans emphasized the need for clear tool tips to explain these external dependencies and where the IDs are sourced (00:44:08) (00:45:57).
- **Branch, Sentry, and OneSignal Integration**: The system will utilize Sentry and Branch, but most Branch-related configuration fields (Branch Link Domain,

Alternate Link, Support Email) do not need to be displayed on this page (00:47:06). Igor Petrović confirmed that they are pulling necessary configuration data directly from the Branch dashboard based on the existing key and secret, making the process completely automated (00:48:06).

- **Application Name and Icon Display**: The "name" required for the build is the name displayed below the icon on the mobile device home screen, which is distinct from the dashboard name (00:48:06). This specific string is requested from the customer via a separate form and currently stored in Salesforce by Ilia. Lizzy Evans suggested that they could change the workflow to have customers input this, along with app store assets and icons, directly into the dashboard, skipping the manual form and Salesforce steps (00:49:12).
- **Mobile App Setting Page Context**: The mobile app setting page currently exists and includes configuration items like the default event app banner color, app token, and show app download banner. The required fields for the build could be displayed here, potentially extending the page (00:51:20).
- **Branch Support Email Input Field**: A field for the branch support email was previously hardcoded but is required for Branch's API request and configuration setup. Lizzy Evans requested clarity on this field since it does not explicitly say "branch support email" (00:52:16) (00:54:18). The consensus was that this field is required to be in the configuration file, but it may be hardcoded or hidden, as it seems to function even if the email is not directly associated with the application. Milan Cvijetinovic agreed to hide the input field for now as it is confusing, while Lizzy Evans committed to discussing the issue with Ilia to understand its association (00:54:18) (00:57:33).
- **Input Field for Email Addresses for Intros**: It was confirmed that the required email address does not need to match an existing format and can be any valid email. Igor Petrović mentioned that they and Maria were unable to figure out the purpose of the field. Lizzy Evans suggested hardcoding the value to "dev intro," but Milan Cvijetinovic suggested having "intros" always present in the background and hiding the input field from the UI (00:58:49). The decision was made to remove the input field from the UI and hardcode the default email to "dev" (00:59:39).
- **App Scheme and URI Scheme Necessity**: Lizzy Evans questioned the requirement for the App Scheme, recalling an earlier discussion where Igor Petrović agreed to delete it. Igor Petrović clarified that they were referring to a different item, but the URI scheme is required for the branch and deep links to open the app. This scheme must be a string without spaces (00:59:39). The URI scheme is necessary because the team needs to set it up on their side,

inject it into the project, and push it to the branch configuration, meaning the value must match in two places. It should be set only once and not changed, with a suggested string limit of 16 characters (01:00:43).

- **Confusing Workflow Due to Mandatory Fields**: Lizzy Evans raised a concern that the linear workflow requiring input is confusing because several mandatory fields, like the App Scheme, do not get created until *after* the initial build is created (01:00:43). Milan Cvijetinovic confirmed with Igor Petrović that this information needs to be populated and saved in a file before the final build step is initiated (01:01:45).
- **Sourcing Information for App Scheme**: Milan Cvijetinovic initially assumed the App Scheme comes from 'branch'. Igor Petrović clarified that the person creating the app, such as Ilia, must type it in (01:02:37). Lizzy Evans questioned where the value is sourced if it is not from 'branch'. Igor Petrović stated the value comes from their internal end file, not 'branch' (01:03:26). Lizzy Evans asked if they were supposed to "make up" the value or if they were generating it. Igor Petrović confirmed they literally generate the field's value, using their imagination or a pattern based on the bundle ID or package ID (01:04:19) (01:06:28). The generated value is then sent to the branch configuration before the build starts and is also put inside the app, requiring it to be on two places (01:02:37) (01:04:19).
- **Specifications and Validation for URI Scheme**: Igor Petrović mentioned that the URI scheme specifications include a maximum of 16 characters, no spaces, and likely no special characters. Milan Cvijetinovic highlighted a previous bug where the build failed because white spaces were entered in fields like App Store name, underscoring the need for strict validation rules (01:05:12). Igor Petrović proposed creating the App Scheme field based on a pattern, such as the bundle ID or package ID, and then removing the input field entirely to avoid confusion (01:06:28).
- **Hardcoding Email and Removing Input Fields**: Milan Cvijetinovic suggested that Igor Petrović should hardcode the email value on their side, eliminating the need to send it from the front end to the back end, and then to Bitrise and S3, deeming the current process pointless. Igor Petrović agreed to hardcode the email in the scripts. Lizzy Evans expressed satisfaction with removing fields, as they agreed to eliminate two fields (01:07:33).
- **Icon Requirements and Validation**: Igor Petrović confirmed that the App Icon cannot be removed and that a separate round icon is needed for Android. They noted the need for validation to ensure the icons are a specific size and have appropriate out-padding (01:08:17). Ilia had problems with icons being

cut off if they went from edge to edge on the device (01:09:20). Milan Cvijetinovic currently only accepts PNG uploads and confirmed that because the required size is 1024x1024, a resizer would be pointless. They stated the icon must be prepared beforehand, including managing round edges and transparency (01:10:27).

- **Splash Icon Discussion**: Igor Petrović explained that the splash icon is the initial screen icon in the middle when the app opens, and they added it using the same images as the home screen App Icon (01:11:30). Lizzy Evans questioned the need for three separate inputs if the same image is used for the splash icon. Igor Petrović noted the option to use a different one, but Lizzy Evans felt that having another input complicates things for the user (01:13:01). The group agreed they could reuse the App Icon for the splash screen (01:13:59).
- **Icon Differentiation for App Stores**: Lizzy Evans confirmed that the adaptive icon is primarily for Android, while the standard App Icon is for both Android and iOS. The adaptive icon is only used on Android if the rounded icon setting is enabled (01:13:59). Igor Petrović explained that the person generating the icon (Ilia) uses a third-party tool to generate all necessary icon files based on the client's supplied icon (01:15:35). Igor Petrović mentioned client complaints about icons not looking good on Android devices when the adaptive icon setting is on. The adaptive icon must be 1024x1024 pixels, and the image should cover only 66% of the area, with the rest being transparent, according to Google documentation (01:16:31).
- **Dependencies and Workflow Structure for Initial Build**: Lizzy Evans outlined the required steps for creating the first build: starting with basic information (App Icon Name, display name, app icon, Google app icon). The next step involves Apple information, which is sourced from the Apple Store (01:17:49). Lizzy Evans questioned if they submit information to generate dependencies or if they just rely on information already in the App Store, noting the complexity of inputting App Store data here. Igor Petrović confirmed that they *are* copying information from the App Store Connect and that dependencies exist, but this process saves time by using the P8 file for the APNS certificate, which eliminates provisioning profile expiration issues (01:19:28).
- **App Store Connect Access and Workflow Benefit**: The team needs account access to the customer's developer and App Store Connect accounts, which remains the same as before. Lizzy Evans expressed doubt about the time-saving benefit of the current setup, as 80% of the fields are generated from or require input from App Store Connect (01:20:51). Igor Petrović emphasized that these fields are mandatory for authentication with Apple to

allow uploads to TestFlight. Milan Cvijetinovic and Igor Petrović concluded that while the first time setup is complex, the true benefit comes during subsequent updates, as much of the data will be prepopulated if the same team ID is used (01:21:49).

- **Build Creation and Post-Creation Steps**: Lizzy Evans noted that the flow in the documentation is not strictly linear, as steps like clearing certificates or provisioning files only occur *after* the build is created and an error is received (01:22:51). The final steps involve creating the iOS build and pushing it to App Tested, and providing an option to download the Android build APK file (01:23:41).
- **Locking Fields for Updates**: For updating builds, certain fields should be locked. Igor Petrović suggested locking the Bundle ID and Package ID (01:23:41). In the first step (Basic Info), everything can generally be changed (name, icon). In the second step (Apple Info), most fields can be locked, but some might need to be changed due to circumstances (01:25:20).
- : * **No Changes Required**: For a version update with only new code, the user simply hits the "update build" button for both iOS and Android\~=CITATION:82=\~.
  * **Asset Changes**: The most common update scenario involves asset changes (name or icon), which requires changes in Step 1 plus hitting the update button\~=CITATION:83=\~.
  * **Locked Fields**: Everything in Step 2 and Step 3, except for Firebase tester management (adding/removing testers), should generally not be changed\~=CITATION:83=\~. The Bundle ID and Package ID can never be changed\~=CITATION:85=\~\~=CITATION:91=\~.
  * **Manual Store Changes**: A scenario exists where a customer makes manual changes in the stores, invalidating keys. Attempting to build will generate an error. This also happens if the app is transferred to another account\~=CITATION:84=\~.
- **Handling Errors from Invalidated Keys**: If an error is received after pressing "update build," the team needs to check the logs to determine the cause of the failure (01:29:05). Failure can occur if the Apple Key ID, Apple Issuer ID, Apple Key Name, P8 API key, certificates, or provisioning profiles are invalidated (01:29:56). Igor Petrović confirmed that common failures involve someone deleting their certificates, profiles, or keys (01:31:22).
- **Improving Error Communication**: Lizzy Evans sought a way to tailor the error message or share information with Ilia to specifically identify the problematic item so they can fetch and re-insert the updated key or certificate. Currently,

Ilia manually checks logs and deletes or re-uploads everything, as he has access to the Bitrise logs and starts builds directly from there (01:31:22). Igor Petrović will investigate if they can extract errors from Bitrise or provide a direct link to the failed build logs (01:32:33). A link to the failed build log is currently how Ilia works, receiving a Slack notification with the link (01:33:29). Igor Petrović confirmed Slack notifications are already configured (01:34:22).

- **Editing Fields After Errors**: If a build fails due to invalidated keys, many fields in Step 2 and Step 3 will need to be editable to insert new information (01:34:22). The only fields that must remain locked are the Bundle ID (for iOS) and the Package ID (for Google) (01:35:23).
- **Next Steps**: Lizzy Evans will write out a more comprehensive scope, particularly regarding the flow. Igor Petrović noted that the discussed items represent the bare minimum requirements (01:35:23). Lizzy Evans plans to map out the steps in a process flow for David Ukauwa, while the current specification will focus on the required inputs .

Suggested next steps

- [ ] Lizzy Evans will add information regarding the manual step required on the Google Play console for Android build creation.
- [ ] Igor Petrović will check the Google official documentation again to confirm if there is no API for creating an app on Google Play Console.
- [ ] Igor Petrović will investigate if an API exists for checking if a certificate is valid for the build process.
- [ ] Lizzy Evans will share the security considerations of unmasked keys with D and P.
- [ ] Lizzy Evans will take away the task of checking the dependency process for Firebase app ID creation.
- [ ] Lizzy Evans will chat with support and ops regarding the timing and workflow for customers to provide app store assets and icon display names directly in the dashboard.
- [ ] Igor Petrović and Milan Cvijetinovic will investigate the best approach for the clear certificates and provisioning profiles functionality to decide on button placement and logic.
- [ ] Igor Petrović will check with the support team or whoever creates applications on Branch to determine if the dev email is being set, and Lizzy Evans will chat with Ilia regarding the email used for Branch configuration.

- [ ] Milan Cvijetinovic will hardcode the default email to "de intro" in the background and hide the input from the UI.
- [ ] Igor Petrović will create the URI scheme field based on a pattern (like bundle ID/package ID) to remove this field from the UI and avoid confusion.
- [ ] Igor Petrović will check if the error message for failed builds can be extracted from Bitrise API or the build process to provide tailored information.
- [ ] Lizzy Evans will write out the scope more comprehensively and map out the steps in a process flow for David Ukauwa.

You should review Gemini's notes to make sure they're accurate. [Get tips and learn how Gemini takes notes]

Please provide feedback about using Gemini to take notes in a [short survey.]

📖 Transcript

Mar 12, 2026

App Build Pairing - Transcript

00:00:00

Lizzy Evans: He gathers all the input fields, all the ids, all the keys, all the assets from various places, bundles that together, uses bit to generate that build, gets the build file, and then submits that through Apple store and Google Play Store. Because it's native, the flows for the build different. It's a very different process for each. And it's quite manual at the minute and it's his full-time job because we have over 154 customers, all of which have events, many events over the course of the month and we end up doing app updates. Uh so when an application is created for a new customer, we get access to their app store and then we create a build for them and we do that build in the runup to their event launch date. So we have like few weeks or 30 weeks out or 30 30 days out from the event start. We've got this app build created Ilia times that. So it has the latest version of the code that we've been working on. And then if the event is quite like a long period out or it's already the app's already been created,

00:01:13

Milan Cvijetinovic: Nothing.
Lizzy Evans: we'll do version updates if we think that that application needs the latest version. We don't have a blanket like everyone gets this version all the time because we derisk it and we just cycle through who needs what when and we just continually go through kind of version updates based on when the events are happening because we'll have an application for a customer and then they might have an event in September in 2025 and then they won't have another event until September 2026. So there's no point continually updating that build manually when no one's going to be using it for 30 days after the event because the event is deactivated. So we've got quite a highly like highly involved process here for managing the application creation itself for the build for the mobile and also the version updates. Is that clear?
David Ukauwa: Yeah, that makes
Lizzy Evans: Cool. So with the React Native build,
David Ukauwa: sense.
Lizzy Evans: we want to simplify this process for Ilia because it's got quite a lot of

steps that quite different.

00:02:17

Lizzy Evans: We want to make sure there is a page in the engage admin in the dashboard through which he can generate these builds and this is where I'm going to check with Milan because in my mind we're going to generate the builds. We're going to submit the builds potentially. Yes. And there might be a few other steps we can do, but we need to confirm the the scope of it on this call. So that means we've got a stepby-step workflow with quite a few input fields that need to be filled out with clear crystal clear guidance. Like so we're going to need tool tips on all these um which I think we have by default to explain where you're getting that input from if you can edit that input after it's initially been used for a build and also um being able to like preview images but also uploading certain files or taking certain actions like clearing certificates provisioning. So Milan's already started to work on this and there's an angular um component that can do this well for us because there's a stepper you know that we have a step-by-step workflow like function in a few places because it's quite a linear we need these inputs then these then these and then we can create can only create once these prior inputs have been

00:03:33

David Ukauwa: Mhm.
Lizzy Evans: added and validated and there's an update process as well because we create an initial build and then there might be an update to make sure it can get the latest version of the application. So there's two kind of purposes with this flow. An initial creation and then an update based on it needing the new version of the
David Ukauwa: When when you want to update,
Lizzy Evans: code.
David Ukauwa: will you go through all the steps again?
Lizzy Evans: You will have information saved already.
Milan Cvijetinovic: Well,
David Ukauwa: But would you still have to verify each
Lizzy Evans: So
Milan Cvijetinovic: well, well, yeah,
David Ukauwa: step?
Milan Cvijetinovic: like I added just next, next, next. So, you can skip them or you can just click in a header like native integration, you can just click on a fourth step and

navigate. If you are in edit mode, just click on the ports tab and navigate directly to the fourth one if you like or just click next
David Ukauwa: Okay.
Milan Cvijetinovic: you know four times but it's it's it's you know just a vizard we have inate integration in emails I mean yeah you already know that you created that vis

00:04:33

David Ukauwa: Okay.
Lizzy Evans: So this is kind of the initial view like ideation in terms of step by steps. I want to go through the PRD that I've got just to clarify um the overall scope and some of the actions with with Milan. Um so I'm going to skip over to the PRD quickly, but it's basically actually can I do a split screen with this? Does it show up? Does it show up? How did I do it? Sometimes I've accidentally merged two things into one tab and now I can't remember how I did
David Ukauwa: Um,
Lizzy Evans: it.
David Ukauwa: just put one on full screen then it should break it. Then you can resize I
Lizzy Evans: No, no,
David Ukauwa: think.
Lizzy Evans: no, no, no. Look, I've split it. A Okay, I'm going to share with you this link. I did it by accident. I do it by asking quite a lot but for whatever reason I can't. Okay. Have this diagram open on your page because I'm going to switch pages.

00:05:37

Lizzy Evans: Okay.
David Ukauwa: Okay.
Lizzy Evans: Uh I was hoping to do split screening because then you can see. All right. So Milan just a couple of things I want to check.
Milan Cvijetinovic: Mhm.
Lizzy Evans: At the highest level we're saying because initially Eagle was saying we can't automate the build process for Android.
Milan Cvijetinovic: Mhm.
Lizzy Evans: Are we doing are we can we can we generate the builds for both iOS and Android in the via the engage
Milan Cvijetinovic: I think the first time only the Android has to you you need to do

something manually only the first
Lizzy Evans: admin
Milan Cvijetinovic: time. Yeah, there is some as far as I remember he's Yeah, I think
Lizzy Evans: what I've put here we cannot so that's this is the scope though this is what I need to make really clear because if on this page someone thinks that they can like Ilia needs to know I can't create a build here for the first time on Android. I'm going to have to go this way and and we just need to make that clear.

00:06:33

Lizzy Evans: So my understanding is we cannot automate build creation process for Android but we can automate build update process like the version update.
Milan Cvijetinovic: Uh, there's Oh, he's typing. Give me a second.
Lizzy Evans: I know we can automate the build process, the build creation process for iOS and update
Milan Cvijetinovic: So yeah,
Lizzy Evans: versions.
Milan Cvijetinovic: he's saying like on a Google Play console, you need to do something manually first time only uh for the Android because they as far as he know I mean what rechecking they don't have that exposed API for that action.
Lizzy Evans: Okay, that's fine. So,
Milan Cvijetinovic: Yeah.
David Ukauwa: Yes,
Lizzy Evans: let me add that in.
David Ukauwa: sir.
Lizzy Evans: put in here. Yeah, that's fine. Okay, cool. Okay. And then we can automate build creation process for iOS and the update for the versions on iOS. That is a yes.
Milan Cvijetinovic: Uh, Well, but the first question it's yeah it's it's it's not it's not like a global question like this is just a pre precondition you know so you still you still can populate all these fields just as a precondition you need to do this manual step on a console you know

00:08:21

Lizzy Evans: Yeah,
Milan Cvijetinovic: so that's the yeah
Lizzy Evans: I know there's going to be other I know there's going to be other bits, but

I just want to make sure um if we can what we're getting out of that flow at the end. Are we getting a build that we can submit or are we not getting a build that we can submit for both iOS and Android?
Milan Cvijetinovic: Yeah. Yeah. Yeah. You you do get you do get the bill that you can Yeah. And and it's being submitted as well automatically.
Lizzy Evans: Okay, fine. Okay,
Milan Cvijetinovic: So it's Yeah.
Lizzy Evans: that that's changed. That's where the wording's got me. Okay.
Milan Cvijetinovic: So you get the submission part as well.
Lizzy Evans: Okay, cool. Bear with me. Warnings. Warnings. What we're going to do is just have like a warning because we want to put Google Play and Apple Console dependencies.
Milan Cvijetinovic: You want me to invite invite to this call? Maybe it's easier.

00:09:09

Lizzy Evans: Yeah, if it's easier. Um,
Milan Cvijetinovic: He
Lizzy Evans: are we facilitating the publish and unpublish as well or do we see that as a B2?
Milan Cvijetinovic: give me a second to have an idea honestly.
Lizzy Evans: Oh, okay. Fine.
Milan Cvijetinovic: He's he's joined. unpublishing a good question.
Igor Petrović: Hey.
Milan Cvijetinovic: Here you go.
Igor Petrović: Hey.
Milan Cvijetinovic: Yeah, guys have some questions. I have no idea how to answer. Just be short and focus.
Igor Petrović: What?
Milan Cvijetinovic: Please go wild. Okay. So,
Lizzy Evans: Okay. Topline scope.
Milan Cvijetinovic: uh,
Lizzy Evans: Topline scope of what we're discussing with some dependencies on keys being in the Google Play Store. Basically, we have access to the Google Play Store and the Apple Store. There might be some things that are needed in there, but broadly speaking, this app admin page, if I'm speaking about the scope of the app admin page, will be able to generate a build in iOS and Android for us, which we can submit automatically from that page to the stores.

00:10:24

Lizzy Evans: Yes or no?
Igor Petrović: iOS store. Yes. So, uh do you mean store to publish for for the users? When when you say store to publish for the users, right?
Lizzy Evans: Yep. So, one, can we can we generate the build file whatever our build from an app admin page for iOS and Android?
Igor Petrović: Yes. Yes. It will trigger.
Lizzy Evans: Okay.
Igor Petrović: It will trigger bits which will generate build.
Lizzy Evans: Yep. Yep.
Igor Petrović: So yes,
Lizzy Evans: Yep.
Igor Petrović: we will create the file and for iOS file will be up uploaded on the test
Lizzy Evans: Yep.
Igor Petrović: flight.
Lizzy Evans: Yep.
David Ukauwa: What's
Lizzy Evans: Ah. So,
Igor Petrović: So
Lizzy Evans: distinction iOS will be uploaded on test flight. What happens on Android?
Igor Petrović: Android will be uploaded on app tester.
Lizzy Evans: Okay. So, okay. Yeah, both are fine then. Yeah.
Igor Petrović: So that is the first step.
Lizzy Evans: Okay.
David Ukauwa: up?
Igor Petrović: So yeah publishing you have to define it because you can publish for the for the

00:11:19

Lizzy Evans: Yeah.
Igor Petrović: internal testers then for the external testers that is if needed and you have to publish it to be live on the store so users can download it. So there is several steps you have to to
Lizzy Evans: Yeah.
Igor Petrović: do.
Lizzy Evans: What are you saying we can do from and trigger from the dashboard at the moment?

Igor Petrović: Yeah.
Lizzy Evans: Just pushing it to internal testers or pushing it
Milan Cvijetinovic: Yeah.
Lizzy Evans: further.
Igor Petrović: Pushing it for internal testers for now.
Lizzy Evans: Okay, cool. Thank you. All
Igor Petrović: So uh for iOS for uh Android will push to the list provided
Lizzy Evans: right.
Igor Petrović: in this in this uh pile on this that third
Lizzy Evans: Yeah. Yeah.
Igor Petrović: step.
Lizzy Evans: Okay. Cool. Um, so we cannot in the first version I'm saying what's out of scope. We cannot push to public stores.
Igor Petrović: No,
Lizzy Evans: Okay. Cool.
Igor Petrović: because to push to the public store you must send it to review and then you

00:12:20

Lizzy Evans: Yeah. Yeah.
Igor Petrović: have to attach screenshots what's new description and a lot of stuff that is yeah a lot of more work.
Lizzy Evans: Yeah. Cool.
Igor Petrović: So
Lizzy Evans: Are we considering that we can publish and unpublish the applications via the admin portal or is that out of scope?
Igor Petrović: for now it's out of the scope. So everything for
Lizzy Evans: Okay, cool. Because yeah, basic checking because these are all things we've talked about in the last three weeks.
Igor Petrović: now.
Lizzy Evans: So, I just want to
Igor Petrović: Yeah. Yeah. Yeah. But but it's but yeah I I I show you I think that's phase one phase two phase three.
Lizzy Evans: check
Igor Petrović: So phase one is just to create a build create admin and push to the test flight or app testers that will save huge part of Ilia works but the rest
Lizzy Evans: Yeah.
Igor Petrović: sending up to review it still must be done manually. And to be honest,
Lizzy Evans: Yeah.

Igor Petrović: Elia prefers to do it manually because

00:13:13

Lizzy Evans: We've got a Yeah,
Igor Petrović: Yeah.
Lizzy Evans: we've got a high degree of management in terms of stuff.
Igor Petrović: Yeah.
Lizzy Evans: It's that's okay.
Igor Petrović: Yeah.
Lizzy Evans: Um, second thing, regardless of the fact that we cannot we're not pushing it to the app store, can we retrieve information from the stores around the approval status of the
Igor Petrović: Yeah. Yeah,
Lizzy Evans: builds?
Igor Petrović: you can. I think I think I ordered this and then point to you can check which which versioning currently live that pointing and Yeah.
Lizzy Evans: Yeah,
Igor Petrović: Yeah.
Lizzy Evans: I think I think that baseline would be really handy because I know that would be a massive saving for delivery and
Igor Petrović: Yeah.
Lizzy Evans: support um in terms of time spent trying to figure out who's on what. Um okay, cool. Um cool. All right. Okay. In scope, out of scope, detailed here. That clarifies that clarifies it. Thanks, Eagle. All right. Okay. going into then the details of what we need to display on this build creation process.

00:14:20

Lizzy Evans: Build inputs for Apple include the following.
Milan Cvijetinovic: Mhm.
Lizzy Evans: I've cross checked this against both of your docs. So because there's some different words in places so I was just like h you got your app store app name. Uh there'll be tool tips. So David I've included tool tip reference this for this as well. So this is a someone an app admin. So Ilia will go in and input app store name uh which is 30 characters. He'll know this because the customer has told him what this should be. Uh Apple bundle ID. We create this ID for the app in a specific
Igor Petrović: Yeah. Based on the pattern. Yeah.

Lizzy Evans: format.
Igor Petrović: Yeah. Yeah. It's com uh app name app something.
Lizzy Evans: That's fine. I've got it here. Yeah.
Igor Petrović: Yeah. Something like that. Yeah.
Lizzy Evans: Apple team ID.
Igor Petrović: Um must be copied from the developer portal to the dashboard.
Lizzy Evans: Yeah.

00:15:17

Lizzy Evans: Tool tip.
Igor Petrović: So
Lizzy Evans: Tool tip equals source in Apple developer portal. Yeah. Apple key name tool tip source from app store connect. Apple issuer ID tool tip source from app store. App store connect. Tell me tell me if this is wrong. Apple key ID tool tip store from app store connect. We can insert all of those fields. Read only field would be apps Apple store connect ID which is generated once the build is created.
Milan Cvijetinovic: Mhm.
Lizzy Evans: Game center disabled warning message again displayed once we've attempted to
Igor Petrović: Yeah.
Lizzy Evans: generate the build but it fails. When would that warning display?
Igor Petrović: Oh, there is API call. We we just checked it. it if it returns that game center is enabled then this M message should be displayed when and
Milan Cvijetinovic: This yeah second step that step API
Igor Petrović: yeah second step.
Milan Cvijetinovic: call uh it will return you true or false if the game center
Igor Petrović: Yeah.
Milan Cvijetinovic: is enabled that means we cannot deploy iOS.

00:16:35

Igor Petrović: Uh yeah we cannot run iOS. Yeah.
Milan Cvijetinovic: So on the step I disable the toggle until
Igor Petrović: And
Milan Cvijetinovic: you turn it off uh
Igor Petrović: yeah and tool tip for that will be good. Uh login
Milan Cvijetinovic: manually.

Lizzy Evans: I've got I've got build will fail as game center is disabled in app store connect.
Igor Petrović: to
Lizzy Evans: Amend settings in app store connect in order to proceed with
Igor Petrović: um uh no app uh app uh
Lizzy Evans: build.
Igor Petrović: Apple developer portal. It's not app store connect.
Lizzy Evans: Okay. Thank you. Thank you.
Igor Petrović: uh Apple developer portal uh bundle ID it's I think it's bundle ID section
Milan Cvijetinovic: I mean it, you know,
Igor Petrović: specifically
Milan Cvijetinovic: will not fail. I literally forbid you to to do I literally disable the toggle.
Igor Petrović: yeah well yeah better to disable toggle than to trigger build and it failed
Milan Cvijetinovic: Yeah,
Igor Petrović: you will not no idea why why it failed
Milan Cvijetinovic: because
Lizzy Evans: Okay, clarification.

00:17:29

Milan Cvijetinovic: it's
Igor Petrović: I build just go
Lizzy Evans: When are we getting the when are Hang on. Wait, wait, wait.
Igor Petrović: back
Lizzy Evans: Let me just Can I Can I ask a question? Apple App Store Connect ID that this is just generated is
Igor Petrović: when app is created on the
Lizzy Evans: this? Yes,
Milan Cvijetinovic: the first
Lizzy Evans: this is this isn't filled in until you've done this final
Igor Petrović: first no it's filled
Lizzy Evans: step.
Igor Petrović: API will fill
Lizzy Evans: API will fill it. Okay.
Milan Cvijetinovic: failed after.
Lizzy Evans: So, when are we triggering it? When are we triggering it? on the save of this CTA or when?
Milan Cvijetinovic: Yes. After you finish the second step.
Lizzy Evans: Okay, cool. Thank

Milan Cvijetinovic: Yeah.
David Ukauwa: Sorry. So,
Lizzy Evans: you.
David Ukauwa: so that field shows up after you've left the step.
Milan Cvijetinovic: That field will be only visible in edit mode basically.
Lizzy Evans: Yeah, got it.
Milan Cvijetinovic: Yeah.
David Ukauwa: Okay.

00:18:19

Lizzy Evans: Okay,
Milan Cvijetinovic: In create f*** it. You don't know you,
Lizzy Evans: cool.
Milan Cvijetinovic: you know, like so it's it's
David Ukauwa: Okay. Thank you.
Lizzy Evans: Cool. Got to insult it.
Milan Cvijetinovic: hidden.
Lizzy Evans: Happy days on there this way. That's fine. Uh got you right. Um okay. And then upload only API key file. Where is this from? When is this
Igor Petrović: uh uh uh Apple app store connect same as these three
Lizzy Evans: generated?
Igor Petrović: values it's it's related when this is generated and downloaded these three values key name uh Apple issuer ID and key ID are created at the same time so it's downloaded from the app store Connect
Lizzy Evans: that.
Igor Petrović: works.
Lizzy Evans: Thank you.
Milan Cvijetinovic: The important part here is that you cannot upload before you enter the Apple team ID because that determine the the location of of
Lizzy Evans: Got you. Yeah. Yeah.
Igor Petrović: Yeah.
Milan Cvijetinovic: the folder. You know the third

00:19:25

Lizzy Evans: Uh yeah. So um are there any are there any dependencies is the only link

Igor Petrović: Yeah.
Milan Cvijetinovic: one.
Lizzy Evans: between any of these items these upload files and the team ID or we need to make sure they have to enter in the Apple team ID before they can do this.
Milan Cvijetinovic: Yeah.
Lizzy Evans: But they could technically not enter the Apple key name but they could still upload the file.
Milan Cvijetinovic: No, because I I don't know the location where to put the file.
Lizzy Evans: Okay, cool. So,
David Ukauwa: So
Lizzy Evans: all of these fields, you can see my thing. All of my all of the fields above this line.
Milan Cvijetinovic: Yeah.
Lizzy Evans: So, every all of these need to be in place in order for us to upload or for us to
Milan Cvijetinovic: Well, only the third one technically, but but
Lizzy Evans: save.
Igor Petrović: Yeah.
Milan Cvijetinovic: yeah.
David Ukauwa: the team ID needs to be in place for you to upload these two.
Milan Cvijetinovic: Sorry.
David Ukauwa: Are you saying the team ID needs to be in place for you to upload the API and

00:20:19

Milan Cvijetinovic: Exactly. Exactly.
David Ukauwa: APN?
Lizzy Evans: But I think technically we just need to say all of it needs to be in place before you
Milan Cvijetinovic: Oh yeah. Yeah. Because guys, so the uploading is a separated endpoint and in our system we when you choose the
Lizzy Evans: upload.
Milan Cvijetinovic: file we immediately upload. So even if you don't click save and continue at the at the bottom the file will end up in S3 and live forever. That's how we upload things in our system. And then maybe maybe not one day we build a chrome job that will be run every month and clean the unused files you know so but every time you pick a file it will automatically go. So that's why it's important that you have a team ID in place before you click. Yeah. So I disabled the file upload until you you have anything in Apple team ID. So that's that's that's what I did right now. just yeah

Lizzy Evans: But technically any of them

00:21:16

David Ukauwa: So
Lizzy Evans: like
Milan Cvijetinovic: well I think I added validation only for Apple team ID but all all yeah all of them are required in order to enable save and continue
Lizzy Evans: yeah so that's what I'm going to say like uh you can only add these fields once
Milan Cvijetinovic: yeah
David Ukauwa: heat.
Lizzy Evans: team ID is added and then saving even continuing. Uh
Milan Cvijetinovic: everything is required here so it will yeah once you populate everything including both
Lizzy Evans: yeah,
Milan Cvijetinovic: files then save and continue will will unblock you.
Lizzy Evans: yeah, yeah,
David Ukauwa: Um,
Milan Cvijetinovic: Yeah,
David Ukauwa: if you add everything,
Lizzy Evans: yeah.
David Ukauwa: add the files and you go back and you change the team ID to a different one, what will happen?
Milan Cvijetinovic: if you so if you change the team ID well then you will be screwed. Yeah, you will need to reupload the files again.
David Ukauwa: I'm thinking, yeah,
Igor Petrović: Yeah,
David Ukauwa: I'm thinking that we should move that the upload to like a different step since so that we we lock the things in that you've put be locking everything like above this line.

00:22:24

David Ukauwa: Um, and then put that in a different step because if if you do change something,
Lizzy Evans: Yeah.
David Ukauwa: it will mess up the upload.

Igor Petrović: Well,
Milan Cvijetinovic: because check check the fifth one Apple key ID that's
Igor Petrović: yeah.
Milan Cvijetinovic: and yeah I think that's the name of the file literally. So that field and the file itself are literally connected and entity you know.
Lizzy Evans: we can we can think about the dependencies a bit D maybe from the maybe from the design point of view
Milan Cvijetinovic: So
Lizzy Evans: um because at the moment we've got yeah your team ID been added I think we can add validation on inputs and then then see Um, let's get all the info and the flow and then go and then we can work through it. Um, yeah, need to be careful though. Um, okay. We've got upload, upload, upload, and then clear certificates. So, this will delete.
Igor Petrović: Um.
Lizzy Evans: What What exactly is this doing, and why would you need to do it? And why would you choose to do it?

00:23:32

Igor Petrović: H to sign iOS build you should have certificates and you should have provisioning profiles and it have which are created on Apple developer portal and it's common that clients deletes our certificates. If client deletes our certificates it's not valid on the portal anymore.
Lizzy Evans: Cool.
Igor Petrović: So we have to delete it from our S3 bucket. So we can create a new one and store it again on on the same place. So we can create the
Lizzy Evans: So,
Igor Petrović: builds
Lizzy Evans: how would I know that I need to clear my certificate?
Igor Petrović: or you should check Apple developer portal or wait for build to fail because of invalid certificate.
Milan Cvijetinovic: You will get some error.
Lizzy Evans: Okay.
Igor Petrović: Maybe there is a end point for checking that but I'm not quite sure. Maybe maybe I can investigate. And if you delete certificates all provisioning profiles are automatically invalidated. So you have to delete them. But client sometimes can invalidate provisioning profiles only. So we have to keep it separate.

00:24:47

Lizzy Evans: Oh, okay. Do we have to do we have to prompt this from here?
Igor Petrović: deletion.
Lizzy Evans: Because it it feels like you've got to go into the stores anyway. So, if
Igor Petrović: No, you if you delete it here,
Lizzy Evans: something
Igor Petrović: Bitra will create them auto automatically. Again, I made that step. So, they will it will just create it and push it. If uh that is always something it happens because you can have there is a limited number of these certificates on the Apple developer portal. So sometimes Elia is doing login into the cleans portal and deletes a random one. So deletes probably someone else and invalidates for them. So it's
Milan Cvijetinovic: But this is yeah this is an edge case like it shouldn't happen but these buttons are just you know just in case
Igor Petrović: but it
Milan Cvijetinovic: if it happens clear that
Lizzy Evans: Well, so what I'm trying to understand is how we make sure like someone in the team does like
Igor Petrović: happens.
Lizzy Evans: doesn't click it thinking, "Oh, I'm just going to click this." And the ramifications of doing it.

00:25:48

Lizzy Evans: So if they were going, "Yeah, I think there's an error. Oh, I'm just going to clear it. I'm just going to clear it because there's an error." Um, and if that's actually problematic for us,
Igor Petrović: Um
Lizzy Evans: if we're constantly clearing it because they don't know what to do, it's just I want to make sure the context of what why we need to do it is clear.
Igor Petrović: yeah, but yeah, we we must have it.
Lizzy Evans: No,
Igor Petrović: We must clear it if if builds fails because Zil is doing everything manually now and yeah,
Lizzy Evans: no, no, no.
Igor Petrović: he will not be able to do it manually.
Lizzy Evans: Yeah. I'm not saying we don't do it.
Igor Petrović: But
Milan Cvijetinovic: We can
Lizzy Evans: I'm not saying we don't do it. I'm trying to understand the context so that

it's clear to someone when they should be doing it.
Milan Cvijetinovic: hide.
Lizzy Evans: How would someone know that I need to go in and clear the certificates or clear the provisioning profile?

00:26:27

Lizzy Evans: What message are we sending back to them on this page to go clear the search? Because they'll just sit there. If they don't see a message, they'll be like, "Uh, so what what's happening to push them to clear the certificates and provisioning
Igor Petrović: We we cannot get message for that from the betray.
Lizzy Evans: profiles
Igor Petrović: I tested it. It returns nothing useful.
Milan Cvijetinovic: Wait, wait, Eager. But when I click save and I call Apple, those three requests, some some of them should return me an error, right?
Igor Petrović: No, no, this is not related to that requests at all. This is related entirely to build process and signing bills.
Lizzy Evans: Yeah, I think my point is like how how is someone going to know that
Igor Petrović: I will check it uh I I I will check I will I will I will check if
Lizzy Evans: they
Igor Petrović: exist API for checking this if it's certificate is valid.
David Ukauwa: We
Igor Petrović: Maybe maybe it exists.
Lizzy Evans: Yeah, because if we if we show a step in a linear flow, it would be, oh, I always do this.

00:27:21

Lizzy Evans: If we show a step like this, but they'll be like,
Igor Petrović: Yeah.
Lizzy Evans: oh, yeah, always click this.
Igor Petrović: Well, yeah. Ilia knows when it should click be clicked, but yeah.
David Ukauwa: can create like an advanced settings section and just hide it over there. So at least you know that if you don't know what you're doing,
Igor Petrović: Yeah.
David Ukauwa: you shouldn't
Igor Petrović: Maybe maybe maybe we had can add tool tip for now. Delete only if build fails because of provisioning profiles or

Lizzy Evans: So that's what I'm getting at. If if if the if we go to the end of this flow and the build fails,
Igor Petrović: certificates.
Lizzy Evans: it should be more that we have a way of taking them or performing the action to clear theerterts and the provisioning profiles at that point because they cannot generate the bills there.
Igor Petrović: Yeah.
Lizzy Evans: So I know you put it together in this order because it's kind of the same thing.
Igor Petrović: Yeah.
Lizzy Evans: But if I was creating a build, is it the logical place to put it?

00:28:14

Lizzy Evans: Perhaps not because I actually only know whether I need to do this once I've tried to create the build.
Igor Petrović: Yeah. Yeah. Yeah. Probably should be moved from this from this tab. Yeah, you're
Lizzy Evans: Yeah.
Igor Petrović: correct.
Lizzy Evans: Uh and then it's uh we might not know if it's the going to be the sets or the provisioning, but you might as well clear them and try again. That's the nature of this,
Igor Petrović: Yeah. Well, we can we can maybe maybe Milan can set a link if build fails,
Lizzy Evans: right?
Igor Petrović: maybe you can set a link to the bit task for for that build. So logs can be checked manually. Okay, that is how it works currently. So yeah, we logs to the bit trace for the specific build, check the logs and see if it fails because of certificates.
Milan Cvijetinovic: I mean maybe we can show blogs here on the final step somewhere like integration we have on
Igor Petrović: Maybe maybe we can get logs.

00:29:09

Lizzy Evans: Yeah.
Igor Petrović: I'm I'm not quite sure.
Milan Cvijetinovic: the right side we have like a JSON viewer just so you can easily

see what's being mapped.
Lizzy Evans: Yeah.
Igor Petrović: Okay.
Milan Cvijetinovic: So maybe we can do some logging here, you know, just to help you out. I
Igor Petrović: Yeah. Okay.
Milan Cvijetinovic: mean,
Igor Petrović: Maybe may let me investigate then this how how it should be based on which Yeah.
Milan Cvijetinovic: I haven't added these buttons at all. That was my
Igor Petrović: So yeah, it's it's not it's not mandatory for now.
Milan Cvijetinovic: last
Igor Petrović: We can we can add it later when when we figure out Yeah. best best approach. But yeah, you're you're right. It shouldn't be
Lizzy Evans: Yeah. No, I think it's just getting the right understanding.
Igor Petrović: here.
Lizzy Evans: I can see why you've popped all this stuff in in the structure in the way that you have. But if you were going through a workflow, uh there's no dependency on it because it's at the end.

00:30:00

Igor Petrović: Yeah. Yeah. Yeah. Yeah.
Lizzy Evans: Um and then
Igor Petrović: button.
Milan Cvijetinovic: And this and and this is like a outside of my build process endpoint call. So this would be a new endpoint call that you you know click into something
Igor Petrović: Yeah.
Lizzy Evans: Yeah.
Igor Petrović: Yeah.
Milan Cvijetinovic: and add something do something.
Igor Petrović: Yeah.
Milan Cvijetinovic: I don't know. So you can put wherever you like. It's just it's going to be a separated endpoint.
Igor Petrović: Yeah.
Lizzy Evans: Yeah. Okay, cool. Thank you. This is why I think we'll go through the design.
Milan Cvijetinovic: Yeah.
Lizzy Evans: I know I will be doing it, but the whole point of Ilia is a single source of

failure aside from so we
Igor Petrović: Yeah. Yeah.
Lizzy Evans: want other people to be able to do it. Um,
Igor Petrović: Yeah. Yeah.
Lizzy Evans: not not necessarily the first thing,
Igor Petrović: Yeah.
Lizzy Evans: but I want to have it broadly in mind that we can't just rely on AIA doing it.

00:30:42

Lizzy Evans: Um, okay. I've got actions. Don't worry, David. I'm documenting this and being the PD of it and then we we can work through it. Okay,
Igor Petrović: Yeah.
Lizzy Evans: those are all my I think those are all my key questions for now. The only thing is Milan as you know on the on the app management page we
Milan Cvijetinovic: What?
Lizzy Evans: mask any keys or sensitive ids. Which of these keys do we need to mask once they've been entered because of security?
Milan Cvijetinovic: Uh well, none none of them because when I mask them,
Igor Petrović: Oh.
Milan Cvijetinovic: I literally transform the key and uh I think Yeah.
Lizzy Evans: on the front end. Well,
Milan Cvijetinovic: So
Lizzy Evans: we store it in one way, but then because on the what we've done for the app management, the other tokens,
Milan Cvijetinovic: yeah,
Lizzy Evans: we've we've or we've we've done star star and just have the last three digits, you know. So, we we need
Milan Cvijetinovic: but that's just a preview, you know, you don't do anything with that key on those places.

00:31:54

Milan Cvijetinovic: But in here, you actually this form is sending the keys back to API and the API is writing them in a file. So two-way, you know, two-way street.
Lizzy Evans: Yeah.
Milan Cvijetinovic: That's why if I mask them, I'm going to see stars in in in in file, you

know, and then I would
Lizzy Evans: Do you want to talk about the security considerations with Pablo and
Milan Cvijetinovic: need this is not sec this is
Lizzy Evans: D?
Milan Cvijetinovic: not sensitive like you know is
Igor Petrović: Well,
Milan Cvijetinovic: it
Igor Petrović: maybe this is but you should have them all in the pair with the files. So, you have to see them and to download files. So you can you cannot use them
Lizzy Evans: Just thinking about the escalation we had the other week Firebase keys and the fact that they were then publicly accessible.
Igor Petrović: without um
Lizzy Evans: Yes, technically not a secret. I guess that's why I'm thinking about
Igor Petrović: yeah but but it's different on Firebase if you had
Lizzy Evans: it.
Igor Petrović: that key you can make some damage but here if you have only the key for example that issuer ID or you cannot do anything because you don't have a pile

00:32:57

Lizzy Evans: So yeah,
Igor Petrović: So,
Lizzy Evans: that's honestly like I'm based on the information you're telling me. So yeah, is is there a risk if uh like someone had access for longer than they should have done or the wrong access, someone gave an event organizer the wrong access perhaps? Uh maybe not or like an implementation partner the wrong access. Are we going to be in a are we going to have a problem?
Milan Cvijetinovic: But who's going to who's going to see this
Lizzy Evans: Well,
Milan Cvijetinovic: page?
Lizzy Evans: so for the it will just be internal.
Igor Petrović: No.
Lizzy Evans: It's more that we manually add people. So it's just like errorrone. So the other keys we have like implementation partner I think can see those keys as well on the app management page.
Milan Cvijetinovic: Yeah, I think implementation partner also can say
Igor Petrović: Um.
Lizzy Evans: Yeah,
Igor Petrović: Uh yeah ah uh yeah yeah yeah
Lizzy Evans: I'm going to ask the question just because of all things we've had

recently.
Igor Petrović: but you are not in the problem because if some as I said if someone see the keys they have to download file

00:33:51

Lizzy Evans: Wait.
Igor Petrović: in order to use it but you cannot download file here. So yeah it's it's okay and it's it's okay to see them
Milan Cvijetinovic: Good.
Igor Petrović: because if someone yeah invalidates them or change them on the Apple store you can compare it to see if it's wrong or or or not.
Milan Cvijetinovic: Yeah, everything is protected here. So, yeah,
Igor Petrović: Yeah,
Milan Cvijetinovic: not a s***,
Igor Petrović: you you you have to download complete folder and to pair with these keys to to work.
Milan Cvijetinovic: honestly.
Igor Petrović: So
Lizzy Evans: Yeah. Well, this this is what we've done obviously for the branch and the one signal
Milan Cvijetinovic: Well,
Lizzy Evans: stuff.
Milan Cvijetinovic: that this is just an extra extra step, you know,
Lizzy Evans: Yeah.
Igor Petrović: yeah.
Milan Cvijetinovic: the the Yeah,
Lizzy Evans: But we're taking the extra steps just because of this the issues we've had.
Milan Cvijetinovic: I know. Yeah, I know.
Lizzy Evans: I don't want to be blas about it because I don't want to have another escalation.
Milan Cvijetinovic: I was building I know but the but the true but

00:34:43

Lizzy Evans: That means we
Milan Cvijetinovic: the true true fix was moving the config endpoint to a dashboard

world where it's being protected separating the configs you know that was true true fix this is just
Lizzy Evans: Yeah.
Milan Cvijetinovic: nice to have thing you know f*** it
Igor Petrović: Yeah. Yeah. I think we are not in the problem
Milan Cvijetinovic: u
Igor Petrović: there.
Milan Cvijetinovic: yeah because even if you decide to mass pass down somehow. That would be a f****** nightmare to Yeah, I'm not sure how would I do that
Igor Petrović: Yeah.
Milan Cvijetinovic: honestly.
Igor Petrović: And if you ask them, you will not be able to compare them.
Milan Cvijetinovic: Yeah,
Igor Petrović: the
Milan Cvijetinovic: I cannot compare I cannot send them mass or if I send a mass to the
Igor Petrović: Yeah.
Milan Cvijetinovic: API, the API somehow needs to decrypt them, you know, before send to us.
Lizzy Evans: Yeah. Okay.
Milan Cvijetinovic: It's a
Lizzy Evans: Let me let me let me just make the next I'm going to check. I will just I I do want to share this with D and P as well just for awareness.

00:35:34

Igor Petrović: Yeah.
Lizzy Evans: Um and then uh this page won't be accessed by implementation partners. The other one is uh but this won't be because they're they're
Milan Cvijetinovic: Okay, that's good news. Yeah,
Lizzy Evans: never going to generate outs for us.
Milan Cvijetinovic: so this only.
Lizzy Evans: Um
Milan Cvijetinovic: So
Lizzy Evans: yeah.
Milan Cvijetinovic: yeah.
Lizzy Evans: Okay. All right. Um I think I think we got some clarity on the initial app stuff. That's fine. I'm gonna move into the Google space to focus on initially. Now this is this is where I have got a bit confused because as I understand it we can't do the same that we would do for iOS as we can do for Android because we need to do

some stuff directly in bit first not somewhere
Milan Cvijetinovic: That's in
Igor Petrović: No, no. Google Play Console.
Milan Cvijetinovic: betray.
Lizzy Evans: else.
Igor Petrović: Google Play Console.
Lizzy Evans: Okay. Okay.
Igor Petrović: Yeah.
Lizzy Evans: So, there's a bit of a precursor or a little explainer that's basically like you need to go and do other stuff in in the Google Play Console before you do anything here because we're not quite doing the same process for iOS and Android because

00:36:48

Igor Petrović: Yeah. Uh yeah,
Lizzy Evans: Yeah.
Igor Petrović: app should be created. I think actually that that is already in this document. IA shared with me for creating new app. Which one was that? Create new mobile app.
Lizzy Evans: It might sound obvious, but like someone will look at this page and be like,
Igor Petrović: So
Lizzy Evans: "Oh, grand. I can create a build from here." I'll be like, "No, you can't. Not on Android." How am I going to tell them
Igor Petrović: yeah. Yeah. Well uh so we will have to add tool tip
Lizzy Evans: that?
Igor Petrović: that Google Play Console app must be created and I added that
Lizzy Evans: Yeah.
Igor Petrović: extra step for adding one user at the bottom of that Confluence page somewhere.
Milan Cvijetinovic: Can we try that again? Eigor, maybe there is a way like that's
Igor Petrović: No, they they it's not supported by API. I check.
Milan Cvijetinovic: how is that possible?
Igor Petrović: I'll not just supporting
Milan Cvijetinovic: So even when you when you were playing with expose the is thing they they

00:37:52

Igor Petrović: it.
Milan Cvijetinovic: there how are they doing it the expo cloud solution how are they
Igor Petrović: To be honest,
Milan Cvijetinovic: doing it automatically if if
Igor Petrović: I forgot it. I I I
Milan Cvijetinovic: they're if they're doing it automatically then it's f******
Igor Petrović: I think they're not creating the app
Milan Cvijetinovic: possible if if they are asking you to do it
Igor Petrović: automatic.
Lizzy Evans: Cool.
Milan Cvijetinovic: manually then That's it. Yeah.
Igor Petrović: I will I will check, but I I checked Google official documentation and there is no API for that
Milan Cvijetinovic: Yeah.
Lizzy Evans: So,
Igor Petrović: thing.
Lizzy Evans: ahead of So, there's a few dependencies for both of these processes actually, but we haven't talked about and they're up here, but I'm going to ignore them for now. But there's
Igor Petrović: Now for now we we assume that we have same permissions as now. So as we have it now. So we have we must have access to the Google Play console to the Apple de portal and to Apple uh store connect.

00:38:51

Igor Petrović: So same same level of
Lizzy Evans: Yeah. Yeah.
Igor Petrović: permissions.
Lizzy Evans: Same same stuff there. What are the additional things that need to be done in the Google Play Console regarding because in your table you've got all of this stuff in red, but I don't see this in here. So, is that just because the Google account exists or are there steps that need to be
Igor Petrović: Yeah, Android key store key store.
Lizzy Evans: done?
Igor Petrović: This three is created on the bits uh last last four actually key store file.
Lizzy Evans: Okay,
Igor Petrović: Uh so that is the file we already have.
Lizzy Evans: cool.

Igor Petrović: If app is already created I just created script to migrate from old system to new one. It will pull it from the bitray zip file now where it's stored and it will copy on S3 and if that does not exist we will create it because that is just file for signing the app and if you use it for the first time you have to use it for each update. You cannot change it.

00:39:50

Igor Petrović: It's impossible
Lizzy Evans: If we're yeah, if we're creating we've got access to the customer's developer account,
Igor Petrović: to
Lizzy Evans: we're creating an app build for the first time. What is the next step?
Igor Petrović: uh create create the app on Google Play Console and add the user. I I wrote that in the document I think. Let's just let me check.
Lizzy Evans: Yeah.
Igor Petrović: Uh
Lizzy Evans: This is this is what's different then between this and iOS because I don't think we're doing that in iOS. So
Igor Petrović: no that that is done when with iOS when you insert that uh key
Lizzy Evans: yeah,
Igor Petrović: then yeah we can do it via API Android.
Lizzy Evans: exactly that's the distinction made really clear. It's
Igor Petrović: Yeah.
Lizzy Evans: different.
Igor Petrović: So just just let me check this Firebase Firebase Firebase one signal. I know that have it somewhere. You show that to
Lizzy Evans: Yeah. So,
Igor Petrović: me.
Lizzy Evans: all of this stuff is being created in um the Google Play

00:40:52

Igor Petrović: Uh sorry.
Lizzy Evans: Console.
Igor Petrović: And which uh Google Play
Lizzy Evans: And the only thing that you can do is
Igor Petrović: app

Lizzy Evans: add the package ID. Why do we need package
Igor Petrović: package package ID is uh unique package ID on the Google console for the for the
Lizzy Evans: ID?
Igor Petrović: bundle. Uh Google Play app key uh Google Play app key.
Lizzy Evans: Yeah.
Igor Petrović: We already have uh I was able to create one and to reuse it. So we already have it. It's it that is documented in this in this uh CI at the bottom. So you have uh let me share the link with you.
Lizzy Evans: Don't don't worry. Don't worry. Don't worry. Don't worry. What I'm saying is none of these IDs are going to be input on this
Igor Petrović: H okay.
Lizzy Evans: form.
Igor Petrović: No, no. You you you just have to input package ID, Firebase app ID, and here should be list of the emails for the app tester.

00:41:58

Lizzy Evans: Yeah. Yeah, that's fine. So, the package ID uh tool tip uh sourced in Google
Igor Petrović: Yeah. Yeah.
Lizzy Evans: uh
Igor Petrović: Google Play Console when you create the app and
Lizzy Evans: yeah
Igor Petrović: DIA also have a pattern for creating it. It's we should keep it because everything is automat is uh created based on that one. Just let me check the
Lizzy Evans: Cool.
Igor Petrović: pattern.
Lizzy Evans: Once you've added that package ID, uh you can uh you can't edit
Igor Petrović: It's
Lizzy Evans: it.
Igor Petrović: no events.grip.app name and ID.
Lizzy Evans: Cool.
Igor Petrović: So this is the the pattern for
Lizzy Evans: Yeah.
Igor Petrović: creating.
Lizzy Evans: But he does that in the Google Play Console anyway. Yeah,
Igor Petrović: Yeah, is doing that or support team.
Lizzy Evans: that's
Igor Petrović: I I think is doing that.

Lizzy Evans: okay. Hang on. Where is he doing it? Where is he doing this?
Igor Petrović: Google Play
Lizzy Evans: Yeah, fine.
Igor Petrović: Console
Lizzy Evans: Thank you.

00:43:08

Lizzy Evans: Okay, cool. Next bit. Firebase. I've got Firebase stuff that's in there. um app ID input
Igor Petrović: Firebase.
Lizzy Evans: from I'm assuming the dependencies on this is that we've created a Firebase project in Google Cloud
Igor Petrović: Yeah, I added screenshot where it should be copied from the Firebase project.
Lizzy Evans: Platform
Igor Petrović: Not uh Firebase project. Huh?
Lizzy Evans: you have
Igor Petrović: Oh, it's on Firebase console. It's not on Google.
Lizzy Evans: okay uh yeah so you got to create the Firebase project for the up.
Igor Petrović: Uh I think that Tia said that he's doing support team and
Lizzy Evans: Uh, okay, cool. Yeah, well, I need to write it all down because as you say,
Igor Petrović: what and
Lizzy Evans: being done by people.
Igor Petrović: yeah
Lizzy Evans: So, this page will be great or it would be absolutely rubbish because no one knows what they need to do where at the minute they've got to do one, you know, they're doing some things like most process players at grip. There are some things that are done and added in another third party.

00:44:08

Lizzy Evans: We've got branch, one signal, firebase. there's still dependencies on inputs being created in those platforms and then them coming into the engage admin to like generate stuff. So I just want to make sure that the dependencies are like uber clear in this form because then they'll just go in and then be like cool oh where do I get that from? So I just want to make sure it's clear and if you see it's or there's problems

Igor Petrović: Yeah. Yeah. Yeah. Yeah.
Lizzy Evans: like
Igor Petrović: Yeah. Yeah. I checked with Ilia. So support team. I think it's creating everything and we set a line that we will not automate support teams. So I assume that that process will be the same.
Lizzy Evans: Yeah, I don't know. I need to take this away afterwards. Firebase app ID uh tool tip. So, this is sourced from Firebase project.
Igor Petrović: Yeah.
Lizzy Evans: Okay.
Igor Petrović: Firebase up any source from Firebase project and one user uh should be add to the Firebase project.

00:45:07

Igor Petrović: So I
Lizzy Evans: We need to store that here on this page as part of the build
Igor Petrović: I yeah
Lizzy Evans: update.
Igor Petrović: when when creating the Firebase app ID when creating app on the Firebase we have to add user for for
Lizzy Evans: Yeah. Yeah, that's fine. That's fine.
Igor Petrović: automatization.
Lizzy Evans: What I'm trying to what I'm trying to capture here is what do you need that field in the engage admin?
Igor Petrović: No, no,
Lizzy Evans: This is this is a page just for the engage admin. So,
Igor Petrović: no.
Lizzy Evans: anything that needs to be input on the engage admin for the process we can lick to automate. That's all I'm talking about here right now.
Igor Petrović: Engage admin is this one page we are creating, right?
Lizzy Evans: Yes, the dashboard.
Igor Petrović: Yeah. Okay. So, we don't need this on the
Lizzy Evans: Yes.
Igor Petrović: Yeah.
Lizzy Evans: So what I'm asking the the context I'm trying to understand the flow to know where the dependencies are in terms of where fields are generated.

00:45:57

Lizzy Evans: So I can call out where the dependency is in the place where the builds can be created. But you can't do the same like like on iOS and Android. So I just want to call out this is you can only get this ID if you've done this over here. Um because then the the journey isn't clear, right? So I just want to call it out and we'll put tool tips in place on that page. All right. Uh, but we have got the app test emails. So, yeah, everything I'm putting in in these boxes is because we need a field input for it in that dashboard page, which is what you've got here. But I'm just going through it because we might I think we might restructure it a little bit based on validation.
Igor Petrović: Yeah.
Lizzy Evans: And then that's fine.
Igor Petrović: Yeah.
Lizzy Evans: Firebase testers are for projects and engineering only. That's fine. And then uh okay so we don't initially we will be utilizing this branch stuff but we don't need to display it here.

00:47:06

Lizzy Evans: Clear? Yeah we we're utilizing sentry but we don't need to display it on this page.
Igor Petrović: No branch.
Lizzy Evans: Clear.
Igor Petrović: Uh branch.
Lizzy Evans: Don't worry, don't worry, don't worry, don't worry.
Igor Petrović: Okay.
Lizzy Evans: App management, I'm talking explicitly about the build creation flow for branch because we need the additional items here. So, just um I'm just going to get rid of Hang on. Let me just get rid of the stuff I'd selected first. Hang on two seconds. Oh, where's it gone? Delete rows. Okay, fine. And then on branch because we already have stuff here which is mask.
Igor Petrović: That is all what we need.
Lizzy Evans: So we've got key secret.
Igor Petrović: Yeah.
Lizzy Evans: Do we also need to add here branch link domain branch link alternate and branch support email? No. Good.
Igor Petrović: They they are stored in this file and I will pull them from the config uh from the branch dashboard based on the secret and API key and copy where it's needed.

00:48:06

Lizzy Evans: Got it.
Igor Petrović: So it's completely automate.
Lizzy Evans: You're pulling it directly from branch.
Igor Petrović: Yeah.
Lizzy Evans: Okay. Fine.
Igor Petrović: Yeah.
Lizzy Evans: Fine if I Okay. Qu second question actually. Is there any benefit in us storing it in the admin to make it easier to troubleshoot if something's gone wrong.
Igor Petrović: No, I can do not
Lizzy Evans: Okay, cool. Simplifies it. Nice. Delete. Okay, then final thing. create builds. So given we've got all the above information in place, sorry, the green was just me keeping track of which fields I'd reviewed. Given we've got all the above fields in place and we haven't spoken about this first step actually, then we should be able to create build. So let's go back to this first step. And the reason why I skipped over it was because What are we referring to when we say name?
Igor Petrović: uh name below the icon on the mobile device home screen. So it's it's different than dashboard name.

00:49:12

Lizzy Evans: Okay.
Igor Petrović: We don't have it. I checked with Ilia. It's completely different. Clients are asking that specific to be that string.
Lizzy Evans: Yeah. Yeah. Yeah.
Igor Petrović: Oh
Lizzy Evans: So at the moment we have a form that is sent to
Igor Petrović: yeah.
Lizzy Evans: customers that they provide this information to us. It's they fill it in. Ilia has that stored in Salesforce against the mobile ticket that manages his work. We don't store it in the dashboard. We actually could though. We could just get them to put their icon display name in the dashboard. Um so we could we could do that. Um, I need to have a chat with support and ops on the timing for this because we ask for this information so we can start to set make sure we've got access to the Apple accounts because they often don't give us access early enough to do the builds at the same time as then their event being created and everything. But we could we

could store this uh and it makes sense that we need to.

00:50:12

Lizzy Evans: But we've also got like the Apple developer account name, the Google this is all the stuff we capture in a separate form right now from the customer. We capture all of this which is also includes all the app store assets
Milan Cvijetinovic: Mhm. Yeah.
Lizzy Evans: as well. So I've documented it here just for transparency,
Milan Cvijetinovic: Mhm.
Lizzy Evans: but it includes the app name and the icon stuff that you would need as well. So we could look to just make sure that they just put it all in the dashboard.
Igor Petrović: Yep. Fine by me. But for build process we need only icon and this this bundle
Lizzy Evans: Yeah, that's that's that's fine.
Milan Cvijetinovic: Yeah, we will have their name.
Igor Petrović: name.
Milan Cvijetinovic: They are providing it in a form. Okay, great.
Lizzy Evans: Yeah. Uh, I guess what I'm saying is I can I can change the entire workflow. So, I can say don't fill in the form, just put it in the dashboard and it's a page for them in the dashboard to put in. We don't have to do this now, but that's basically that would just save the manual steps because at the moment someone's doing a form, someone's going to Salesforce and then you're putting it in the dashboard.

00:51:20

Lizzy Evans: Put it straight in the dashboard.
Milan Cvijetinovic: Yeah.
Lizzy Evans: Step skip the first two steps. Put it straight straight in the dashboard.
Milan Cvijetinovic: Would that be would that be mobile settings page? Where would that be?
Lizzy Evans: We already So, we already have a mobile set page,
Igor Petrović: What?
Lizzy Evans: but we could extend it. So for the purpose of generating the build,
Milan Cvijetinovic: Yeah.
Lizzy Evans: yes, you can display those fields here. But we've got some stuff that is just like other stuff to do with mobile that we capture elsewhere. So we currently

have this mobile app setting page which is default event app banner color and then we've got the app token here and then show app download banner. We also for the mobile itself just in terms of config leverage some of the branding stuff over here for obviously the colors uh but like um the version the logo event logo and stuff but we um yeah we don't I don't want to over complicate it. So we do have a mobile app setting page already.

00:52:16

Lizzy Evans: If we need this for the build we just state this stuff for the build. And this this email here is what what's what's that
Igor Petrović: Well,
Lizzy Evans: email
Igor Petrović: it's it's required for branch for sending API request and setting up configuration.
Lizzy Evans: right?
Igor Petrović: So yeah,
Lizzy Evans: So that is the branch support email.
Igor Petrović: branch support email. Yeah,
Lizzy Evans: So that's what I had in my that's what I
Igor Petrović: and it it it was hardcoded before to this email.
Lizzy Evans: had.
Igor Petrović: So
Lizzy Evans: Okay. That's what should be alongside because at the moment I know no idea what that is.
Igor Petrović: yeah,
Lizzy Evans: Doesn't say branch. So this this would need to be added to app management page. Sorry. This would need to be added to the app management page alongside the other branch stuff. So we do need to add some things to the app management page.
Milan Cvijetinovic: is this is this ever different? I
Lizzy Evans: We should just
Igor Petrović: for for it It it was never changed.

00:53:18

Igor Petrović: It was hardcoded to this email.
Milan Cvijetinovic: mean

Igor Petrović: So
Lizzy Evans: But we can hardcode it in then. Do we need to display it anywhere?
Igor Petrović: I think not we
Lizzy Evans: Do we need to have an input field for
Igor Petrović: can
Lizzy Evans: it?
Milan Cvijetinovic: power is I
Igor Petrović: to be honest I'm not sure if someone change it directly when support or someone when setting up a branch when creating the branch.
Lizzy Evans: We have we have different email addresses for branch because there's a project's email as well that the majority of the branch accounts I think through.
Igor Petrović: Yeah. Yeah, I know.
Lizzy Evans: Yeah.
Igor Petrović: But maybe when they're creating the app on the branch, maybe they should provide they maybe they have to provide this field. So maybe they're setting some some else. I don't know. That is something we should check maybe with support team or whoever creates applications on the branch. Are they setting
Lizzy Evans: Yeah.
Igor Petrović: that?
Lizzy Evans: Okay. Do Do we need it Do we need it to be an input here?

00:54:18

Igor Petrović: No, I think not.
Lizzy Evans: Well, why is
Milan Cvijetinovic: Well,
Igor Petrović: We can keep it hardcoded or whatever because Yeah.
Lizzy Evans: it
Igor Petrović: I'm not sure if it's in use at all.
Milan Cvijetinovic: I need to save it in a in a file. So, I can send this background,
Igor Petrović: Yeah.
Milan Cvijetinovic: you know, or I can set you this field as read only if you like. or height but
Igor Petrović: Yeah.
Milan Cvijetinovic: like
Igor Petrović: We must have it in the file because that is the only way to set up branch configuration.
Milan Cvijetinovic: yeah yeah I also haven't added branch
Igor Petrović: It's required field. Yeah.
Milan Cvijetinovic: thing okay let's hide it then f*** it it's just confusing everyone

Lizzy Evans: I'm going to chat to Ilia on that one.
Igor Petrović: No.
Lizzy Evans: Um because I don't know if what you're talking about is to do with Let me let me show you the account through which uh the application is set up or something different.
Igor Petrović: something different. Uh if you go to the app config on the branch, where is it?

00:55:28

Igor Petrović: Oh,
Lizzy Evans: Yeah. Which email?
Igor Petrović: no.
Lizzy Evans: Because I'm logged in under the projects email at the
Milan Cvijetinovic: So this is the one the admin.
Lizzy Evans: moment.
Milan Cvijetinovic: So probably he's using the credentials for that account and that's how he can call their API.
Lizzy Evans: Um,
Milan Cvijetinovic: So if this email we are f*****.
Lizzy Evans: I guess
Igor Petrović: No,
Lizzy Evans: yeah.
Igor Petrović: you're logged into this or with with
Lizzy Evans: Yeah, that's that's me logged in. Yeah.
Igor Petrović: this debit.
Milan Cvijetinovic: No, no,
Igor Petrović: I
Milan Cvijetinovic: no, no.
Lizzy Evans: No.
Milan Cvijetinovic: These are users registered in branch.
Igor Petrović: know.
Milan Cvijetinovic: So the probably this was just generic one. And you see it's a it's an admin. So you're probably using this account credentials to communicate
Igor Petrović: No,
Milan Cvijetinovic: with
Igor Petrović: no, no. I am using credentials from the dashboard. If you go to settings, I think app settings or settings, I think it's in the settings.
Lizzy Evans: I am in settings.

00:56:25

Igor Petrović: And these two, branch key and branch secret.
Lizzy Evans: Which one do you want?
Milan Cvijetinovic: I
Igor Petrović: Uh these two,
Lizzy Evans: Yeah.
Igor Petrović: I'm using these two for for communication.
Milan Cvijetinovic: didn't
Lizzy Evans: So, why do we need the
Igor Petrović: And uh if you want to send configuration there is
Lizzy Evans: email?
Igor Petrović: required field dev email. Let me check the field name exactly to be
Lizzy Evans: Okay, cool. So, what I'm thinking is if someone doesn't associate that email to an application in Bron,
Igor Petrović: sure.
Lizzy Evans: say someone was logged in in a project like I am and doesn't add the dev email to the project, then we can't do the sync.
Igor Petrović: Yeah, you fill this de. Yeah. Yeah, exactly. So, it's look like this and yeah,
Lizzy Evans: Oh, man.
Igor Petrović: I'm pasting uh because request is failing if that field is not provided. It's just required and yeah may maybe I can check in documentation. of dev email. We are setting that email otherwise we are not able to config request returns the

00:57:33

Lizzy Evans: I don't think
Igor Petrović: error.
Lizzy Evans: okay when we set branch up we're relying then on the
Milan Cvijetinovic: All
Lizzy Evans: person setting it up to make sure that the dev email is associated to that application in order for the app build to work correct.
Milan Cvijetinovic: right,
Igor Petrović: No, I think not.
Milan Cvijetinovic: Richard.
Igor Petrović: I think we can put uh to be Maria. Maria created one script and she put her email into that script. So, it works with any email, but I I was not able to find that

on the config page. So, yeah, I'm I'm not sure.
Lizzy Evans: I have to admit I'm really not following this because I like I'm not too Sure. If how does someone know what email we're putting here? And if we're hard coding it, are we putting ourselves a vulnerability if it's not for some reason associated to the application?
Igor Petrović: Well, my email was not related to application and it works actually.
Lizzy Evans: So that Okay, I get what you're saying.
Igor Petrović: for 10 email I think.

00:58:49

Lizzy Evans: So it just they just need an email. Doesn't need to match what has been added here.
Igor Petrović: No, no.
Lizzy Evans: They just need an email.
Igor Petrović: Yeah,
Lizzy Evans: Okay. Do they just need an email of the intros at domain?
Igor Petrović: I think not. I think it can be an
Lizzy Evans: Okay. All right.
Igor Petrović: email.
Lizzy Evans: Thanks. Okay.
Milan Cvijetinovic: This is getting better.
Igor Petrović: Yeah, I I I was not able to figure out that field. Maria put her email asked why. He was not she was not able to figure out that also.
Lizzy Evans: I guess this seems quite random.
Igor Petrović: Maybe m.
Lizzy Evans: Can we just hardcode it to de intro and then
Milan Cvijetinovic: I'll just have interest every time in the background and hide hide the input and
Igor Petrović: Yeah.
Lizzy Evans: Yeah. Yeah.
Milan Cvijetinovic: that's all
Lizzy Evans: I'm gonna I'm gonna say you you guys do see that.
Igor Petrović: Yeah.
Lizzy Evans: I'm going to delete and change to Firebase then again.

00:59:39

Lizzy Evans: And then um yeah, we don't need this. Right guys, I'm going have to get a biscuit. This call is is getting it's getting the energy out of me. Right. Let's let me
Igor Petrović: No, remove
Lizzy Evans: um
Milan Cvijetinovic: I have the last one
Igor Petrović: it.
Milan Cvijetinovic: literally.
Lizzy Evans: uh remove hard code default email to dev. Okay, cool. Remove from UI. All right. Uh okay. App scheme. What's that?
Igor Petrović: Uh it's required from the branch and deep links to open the app. It should be string without spaces and no no it's it's
Lizzy Evans: Is it one of these two items that I said to delete and you went, "Yeah, okay." Is
Igor Petrović: it's this one. You scheme? URI scheme.
Lizzy Evans: okay. So, it was this one, right? So, we do need this,
Igor Petrović: Yeah.
Lizzy Evans: right? Do we need to display this?
Igor Petrović: Yeah.
Lizzy Evans: because it sounds like you you said to me earlier we're fetching this all directly from branch into

01:00:43

Igor Petrović: Yeah. Yeah.
Lizzy Evans: bitrise so we don't need it here but is that not true for
Igor Petrović: Yeah. That is correct because we we have to set up this on our side inject
Lizzy Evans: this
Igor Petrović: in the project and push on the branch config. So it's two ways we have we have to match on two places. So it should be string with I think I wrote 16 characters limit or something like that
Lizzy Evans: But this this is only generated once the build is generated this
Igor Petrović: did.
Lizzy Evans: string.
Igor Petrović: Yeah. Yeah. When Yeah.
Lizzy Evans: Okay,
Igor Petrović: When we are creating the build well it should be set first time only and not changed.

Lizzy Evans: got you. Okay, cool. We're going to have to change these steps around because we've got loads of fields in a linear workflow requiring input but don't get created until after the build is initially created. Do you see how that might be confusing to an end user? Fill in this item,

01:01:45

Milan Cvijetinovic: Wait,
Lizzy Evans: but know what you can't until you've got to the end of the flow that you can't get to because all of these items are mandatory.
Igor Petrović: Yeah, it's it's mandatory to be saved in our file and then yeah build process will handle
Lizzy Evans: Yeah, this this basically the structure of these steps doesn't make much sense to me.
Igor Petrović: it.
Milan Cvijetinovic: wait, wait. Eager, Eager,
Lizzy Evans: I'm going to I'm going to get biscuit.
Milan Cvijetinovic: do I do I need to do I need to populate this s*** in a file before I hit the last step?
Igor Petrović: Yes. Yes. Yes. Yes.
Milan Cvijetinovic: I need.
Igor Petrović: Yes. Yes.
Milan Cvijetinovic: Okay, then it's necessary. f*** it. Okay,
Igor Petrović: Yeah.
Milan Cvijetinovic: so where can I find this s***? That's
Igor Petrović: You cannot find it. Someone should put it inside.
Milan Cvijetinovic: is
Igor Petrović: So it's it's typed can be app name or whatever it should be. We should prefer it to be unique.

01:02:37

Milan Cvijetinovic: okay. But this is from coming from branch,
Igor Petrović: No,
Milan Cvijetinovic: right?
Igor Petrović: no. Ilia must type that or who creates the app. What?
Milan Cvijetinovic: App scheme. App scheme. I'm talking about
Igor Petrović: Yeah. Yeah. It it must be typed in.

Milan Cvijetinovic: app.
Igor Petrović: So who creates the app, it must type it. And first time when we type it, we should keep it as it is.
Milan Cvijetinovic: Okay. So, but what what what what how is this related to branch then? For f***** sake.
Igor Petrović: We must send it to branch config.
Milan Cvijetinovic: Uhhuh. So,
Igor Petrović: We must configure branch with with
Milan Cvijetinovic: so let's see. So,
Igor Petrović: that before build process start.
Milan Cvijetinovic: we need to populate this before the build is this needs to, you know, be here.
Igor Petrović: Yeah.
Milan Cvijetinovic: I'm still not sure what f*** this is, but I need this to be populated and saved in a file before the last
Igor Petrović: Before build start.

01:03:26

Igor Petrović: Yeah.
Milan Cvijetinovic: step.
Igor Petrović: You you you cannot start build without
Lizzy Evans: But cool. But where is it from?
Igor Petrović: that.
Lizzy Evans: Is the person entering it getting it from branch?
Igor Petrović: No from from our end file from
Lizzy Evans: What?
Milan Cvijetinovic: What?
Lizzy Evans: Ah.
Milan Cvijetinovic: IA knows what the f***
Igor Petrović: an Yeah.
Milan Cvijetinovic: to put here.
Igor Petrović: No,
Milan Cvijetinovic: How
Igor Petrović: I I think No, he he doesn't know.
Milan Cvijetinovic: does
Igor Petrović: We will have to tell him because this is new field. We we didn't have that field up till now. Actually, we have that, but it was populated only for iOS. I'm not sure
Lizzy Evans: Okay. So, as we're going through this flow,

Igor Petrović: why.
Lizzy Evans: I'm creating a build for the first time. I've got the app store, the app icon name from the customer. I know that. This I come to this file. It says at scheme. Nice. Am I making it up?

01:04:19

Lizzy Evans: Am I going to put some random characters in because I feel like it. Where am I getting this from?
Igor Petrović: Just use your imagination.
Lizzy Evans: Okay. So,
Milan Cvijetinovic: It's a
Lizzy Evans: we're literally generating this.
Igor Petrović: We will we will Yeah. We generate this.
Lizzy Evans: Okay. Eagle.
Igor Petrović: We will use pattern.
Milan Cvijetinovic: f******
Lizzy Evans: That That was literally all the answer I needed. I just needed We make this field up.
Igor Petrović: Yeah.
Lizzy Evans: We make it up.
Igor Petrović: Yeah. Yeah.
Lizzy Evans: Okay.
Milan Cvijetinovic: Okay, we make up. I save in a file. So great. This is already working and okay and at
Igor Petrović: Yeah. We we already did that. Yeah.
Milan Cvijetinovic: and at some point in the third step or the fourth step when I call the bitries you bit will take this value imag and send it to branch for
Igor Petrović: Yeah. Yeah.
Milan Cvijetinovic: some okay I get
Igor Petrović: And put it inside of the app.

01:05:12

Igor Petrović: We we must have it on two
Lizzy Evans: Okay, let me check the character length. Hang on.
Igor Petrović: places.
Lizzy Evans: So, we've got so the UI UI. Let me let me find what we've got. That's all

we needed to know. Like app unique screen for branch. Okay. What What the spec I can't see in the dark. What are the specifications for that Yuri scheme? I'm looking at this.
Igor Petrović: Uh maybe I forgot to put it. I wrote it on this eraser. It's 16 characters max and shouldn't be
Lizzy Evans: Oh, you the Okay.
Igor Petrović: spaces and uh I have to check it.
Lizzy Evans: Okay.
Igor Petrović: I think not accepting special characters. Let me let me just check it quickly.
Lizzy Evans: So, yeah, we're literally just making it up. Minimum 16 characters. Must be 16 characters.
Milan Cvijetinovic: So this is this is a bug we just had, you know, we we we we tried before this call and we tried, you know, to run a build and it it was failing and like then eager check like what f*** why why why the f*** is failing?

01:06:28

Milan Cvijetinovic: Apparently I was entering uh like you know white spaces in these fields you know like ah app store name and I was like something you know white space something else you know next and apparently you cannot have white spaces in some of these fields. So we have we need to have like a strict rules for validation you know. So yeah yeah yeah it's not straightforward.
Lizzy Evans: Okay.
Igor Petrović: What uh okay just
Milan Cvijetinovic: So
Igor Petrović: yeah what do you think uh for me to create this
Lizzy Evans: Honestly,
Igor Petrović: field based on the pattern and to
Lizzy Evans: yeah.
Igor Petrović: avoid I will not
Lizzy Evans: Like if we can randomly generate this because we have to randomly generate it.
Milan Cvijetinovic: yeah,
Igor Petrović: create it randomly I will create it based on the bundle ID package ID whatever and
Milan Cvijetinovic: yeah,
Igor Petrović: push it and remove this field avoid confusion Yeah.
Milan Cvijetinovic: exactly.
Igor Petrović: Yeah. Okay. We can do that.

Lizzy Evans: Do you want to make a note of
Igor Petrović: Yeah.
Lizzy Evans: that?

01:07:33

Igor Petrović: I have to make a not regard uh to those.
Lizzy Evans: Because honestly, everyone's going to look at me like, "What?
Igor Petrović: So
Lizzy Evans: What's that? What is
Milan Cvijetinovic: Okay,
Lizzy Evans: that?
Milan Cvijetinovic: that's cool. We can remove one. We can remove two. Actually, this the the second I mean you just use the email on your side as
Igor Petrović: uh
Milan Cvijetinovic: well. Why do I have to send it?
Igor Petrović: no need we will put it in the template and it will be there or I can hardcode it.
Milan Cvijetinovic: You can hardcode.
Igor Petrović: So yeah.
Milan Cvijetinovic: Yeah,
Lizzy Evans: I do
Igor Petrović: Yeah,
Milan Cvijetinovic: like that's I don't Yeah,
Igor Petrović: I will hardcode it in the scripts. Yeah.
Lizzy Evans: this.
Milan Cvijetinovic: f*** it. Like I mean right now I'm I'm sending from the back end from the front end to back end then from the back end to
Igor Petrović: Yeah.
Milan Cvijetinovic: to you to Bit R. It's point to S3 as well. That's it's pointless kind of just hardcode it on your side.

01:08:17

Igor Petrović: Yeah.
Milan Cvijetinovic: f*** it. Okay. s***.
Lizzy Evans: They got
Milan Cvijetinovic: We should have this call like a week ago.

Igor Petrović: Yeah. Okay. It's just two fields. Yeah.
Milan Cvijetinovic: I I can easily Yeah,
Lizzy Evans: I think to be honest by the time by the time we've had a look at it with David I think we might
Igor Petrović: Yeah.
Lizzy Evans: switch.
Milan Cvijetinovic: remove more.
Lizzy Evans: I like removing stuff. It's a good
Igor Petrović: Yeah.
Lizzy Evans: thing.
Igor Petrović: Me too.
Milan Cvijetinovic: Okay.
Igor Petrović: Yeah. This cannot be removed.
Lizzy Evans: Add icon. I
Igor Petrović: Yeah. And that there is that uh round uh round icon for Android.
Lizzy Evans: get
Igor Petrović: We must have it. And probably we should have some kind of validation for outletting that
Lizzy Evans: I was going to say, well,
Igor Petrović: one.
Lizzy Evans: do we not? We need um they all need to be a specific size. So I feel like validation them because they've got they've got to be a specific

01:09:20

Igor Petrović: Yeah.
Lizzy Evans: size.
Igor Petrović: Yeah.
Lizzy Evans: But are you saying for this adaptive icon you want to validate the shape?
Igor Petrović: Yeah. No, it must be specific size,
Lizzy Evans: Mhm.
Igor Petrović: but it should be trans with the transparent edge to the some boundaries because it looks really ugly and cuts off. Ilia has a lot of problem with that and I test it. It does not look good on the device. So we will we should think something about that or maybe if if we can use some crop tool or something to make it on the upload or I can create it somehow. I I'm not sure still how how to do it. Yeah,
David Ukauwa: Can the can the pre can the preview just be
Igor Petrović: because what?

David Ukauwa: ced then so we can see um like the preview
Igor Petrović: Yeah,
David Ukauwa: that
Igor Petrović: maybe maybe we can. Yeah, I tested on device. If if it's from the edge to the edge, then it's cut off and Yeah, you cannot see it at at all.

01:10:27

Lizzy Evans: We could um I don't actually know how this works, Milan. I don't know if we can do anything sophisticated. It's just
Igor Petrović: Yeah. Yeah,
Lizzy Evans: uploads.
Igor Petrović: I I'm not sure how to do it. I we have to discuss it millon separately. But for now, yeah, maybe just to create upload and to be there.
Milan Cvijetinovic: for now I have upload and I accept PGs only and that's it.
Igor Petrović: Yeah.
Milan Cvijetinovic: So after that we can start validate. I mean we can introduce this this resizer and but I cannot introduce resizer because it has to be uh 1024 by 1024. Then it's kind of pointless resizing to have resizer. Uh can I do anything with the round edges and the transparency
Lizzy Evans: Okay.
Milan Cvijetinovic: around that? Probably not. No. No way. So you will have to you you will have to prepare that icon before you know which is kind of the rule we have everywhere. So you know we're responsible for your images.

01:11:30

Lizzy Evans: Yeah. And yeah,
Milan Cvijetinovic: So
Lizzy Evans: that can be hard. Um, okay. Uh, I'm just changing the spec around a bit. Um, what basic input which is this and and then I'll add in the adaptive icon as well. We get provided this anyway and I validated at the minute. It's just I'd rather we didn't splash icon What's uh what's this? What's the splash icon? As in the icon that gets
Igor Petrović: When you when you open the app initial screen icon in the middle.
Lizzy Evans: initi
Igor Petrović: But yeah, I added there and it's in that size. But maybe we should investigate. I didn't have time to that to check if can if it can cover full screen or how how export works with with that icon.

Lizzy Evans: I don't feel like we display an
Igor Petrović: Yeah. Yeah, we did.
Lizzy Evans: icon.
Igor Petrović: I put that but it's in the middle on the white background. It's in the middle of the

01:13:01

Lizzy Evans: Okay.
Igor Petrović: screen.
Lizzy Evans: I think that might be I don't know which one that is at the moment. I don't know if we're using
Igor Petrović: We're using same icon as on the this on the home screen is app icon and I uploaded the I uploaded the same same
Lizzy Evans: Oh, right.
Igor Petrović: images.
Lizzy Evans: All right. Well, then do we need to have three inputs here? Can we not just have two, but you apply Can we have two,
Igor Petrović: Well,
Lizzy Evans: but then you apply them to the splash?
Igor Petrović: if if we can we can but if you want to distinguish this one, we have option to use different one.
Lizzy Evans: I don't it's just another thing for them to figure out.
Igor Petrović: Yeah. Okay. Okay.
Lizzy Evans: The only thing that they might do is then do a sponsor image but then that would be confusing because then the branding for their application would be confusing.
Igor Petrović: Yeah. Well, yeah.
Lizzy Evans: say
Igor Petrović: On native app, we have just wide screen, clear screen.

01:13:59

Igor Petrović: So, yeah, we can we can we can reuse this icon. So, it's not a
Lizzy Evans: yeah.
Igor Petrović: problem.
Lizzy Evans: Yeah. I think we need to work out if we want to show it. Okay. Hang on. Use up question then.

Igor Petrović: Dog on
Lizzy Evans: Uh, where did the comment the comment
Igor Petrović: the
Lizzy Evans: comment? To be honest, we only asked for do we not need to ask for different icon files for the different stores?
Igor Petrović: Um yeah, but we cannot upload from the dashboard for the stores and there's no pointing now for for setting it there because Yeah.
Lizzy Evans: Okay. Technic. Okay. Hang on. This one is the adaptive one is basically for Android and then this other one is basically for iOS.
Igor Petrović: No. Uh first one is for both Android and iOS and adaptive one is only for Android if rounded icon is set in the Android device settings.
Lizzy Evans: Well, we I think we determined that. So, yeah, let me ask let me ask.

01:15:35

Lizzy Evans: Do we I'm just going to check. Do we ever actually set that or does the customer change it?
Igor Petrović: Yeah. Yeah. I asked them.
Lizzy Evans: Oh,
Igor Petrović: I asked him.
Lizzy Evans: what did he say?
Igor Petrović: He's generating he's getting the icon he gets from the from the client and then use some third party tool to generate all icons and then to push them.
Lizzy Evans: Yeah, he does.
Igor Petrović: Yeah.
Lizzy Evans: Okay. Doing it for all
Igor Petrović: But but the the both projects are configured all the way.
Lizzy Evans: of
Igor Petrović: So you must set each icon specifically. New way. I had a plan to do it on native but never had a chance. You can put just one icon 1024x 1024 and to cover all this. So, but for now he's generating everything manually on the on the some web page and
Lizzy Evans: Okay,
Igor Petrović: upload.
Lizzy Evans: if we can just upload one icon here, I would suggest we just upload one icon here.
Igor Petrović: We we cannot because it's it looks really ugly or if

01:16:31

Lizzy Evans: Okay.
Igor Petrović: Android that round we can actually but yeah he he had he mentioned that he got a lot of client complaints if icon is not looking good on their Android devices on the home screen when that is said.
Lizzy Evans: Yeah. Okay, cool. That helps. Uh,
Igor Petrović: So
Lizzy Evans: I think the specs for the adaptive icon I thought they were different to that. Maybe not. Maybe not. I thought they were 5 512 x 512 pixels.
Igor Petrović: no uh I think it's 1024 1024 but there is a rule that image should cover only 66% the rest should be transparent. I was reading something like that on Google documentation. I'm not sure if I wrote that down. Maybe it's in this confluence page. Let me check if I copied that. Uh Android requires. Yeah, there is a link and I posted that in the go to the confluence page. uh find adaptive. Yeah, it's here.
Lizzy Evans: Yeah. Okay. Great.

01:17:49

Igor Petrović: Yeah. And there is a documentation link for for that.
Lizzy Evans: Thank you.
Igor Petrović: So, yeah,
Lizzy Evans: Cool.
Igor Petrović: in the in the
Lizzy Evans: Thank you. Yeah. Got it. Got it. Got it.
Igor Petrović: note.
Lizzy Evans: Thank you. All right. Okay. Um, all right. We have a bit of a flow then. So, we've got the basic info that's required. App icon name which we add in. So this is just insert and and then we've got all of these fields are always mandatory in this scenario well we're do I'm talking about creating the build for the first time we can have icon display name app icon Google app icon Great. Save. Then we go on to Apple information. We know that we need the following app information and we are sourcing it from the Apple store. I think that's all fine apart from the one that we create. Once we've added the above information, are we waiting or submitting any information at this point?

01:19:28

Lizzy Evans: Are we submitting this information? Like we putting a an update anywhere in order to generate these bits or are there no dependencies between this and these within this form input? There are dependencies.
Igor Petrović: No,
Lizzy Evans: I know that.
Igor Petrović: there are dependencies. Yeah, you must upload
Milan Cvijetinovic: your name.
Lizzy Evans: as a result of adding them here.
Igor Petrović: files.
Milan Cvijetinovic: Be ready.
Lizzy Evans: Are we submitting any information or is it just because we've already got this information in the app store that we've then therefore got the upload file the files and then I just feel like I feel like we're doing a lot of stuff in the app store which we're copying into
Igor Petrović: Yes, we
Lizzy Evans: here.
Igor Petrović: are.
Lizzy Evans: I'm not 100% sure if this is going to save time anymore.
Igor Petrović: They're doing that anyway, so it's it's a must. And it will save time with this um APNS certificate because now we have provisioning profiles which are expiring and you have to renew them and watch them and if you upload this P8 file then you're ready to go and no expiration and no need for for checking it or updating it.

01:20:51

Igor Petrović: Oh, that's for the second
Lizzy Evans: Yeah. Okay.
Igor Petrović: time.
Lizzy Evans: Dependency app developer access granted. And then yeah, there's a lot of stuff still doing in um we need account access.
Igor Petrović: Uh,
Lizzy Evans: That mean that's just me saying we've got access to the customers like developer accounts.
Igor Petrović: yeah.
Lizzy Evans: We we must Yeah.
Igor Petrović: And up store connect account. So,
Lizzy Evans: Yeah. Yeah.

Igor Petrović: it it's same as it was. Yeah.
Lizzy Evans: It's the same. It's the same.
Igor Petrović: Yeah.
Lizzy Evans: But I am I am doubting the benefit of this right now. I'll admit because in order to put in any of this information, you're actually you're already getting all of this from the App Store Connect. You're already going into the App Store Connect, putting it in here. So 80% of the fields, including maybe not this. No. Yeah. All of these we're generating from the App Store Connect.
Igor Petrović: Yeah, but you must have you must populate them because they're keys for authentification with the Apple.

01:21:49

Igor Petrović: So you cannot do upload to the test flight.
Lizzy Evans: No, I get that. Yeah, I get that. But yeah. Okay, Milan, do you see what I'm saying?
Milan Cvijetinovic: Yeah, it's complex. It's complex.
Lizzy Evans: It's It's more like I feel like we're just inputting fields in another place. Um, and we're still going to need to go
Milan Cvijetinovic: Well, first time. Yeah. I mean, the first time the first time is a b****. The, you know, every next time is is the true benefit. That's how I see it. The first time is not super helpful. Probably the second time would be much much easier. Yeah.
Igor Petrović: And the second time if it's same team ID on the Apple develop organization ID it will be prepopulated because it's stored on based
Milan Cvijetinovic: And vast majority of the times is the second plus
Igor Petrović: on
Milan Cvijetinovic: time. So you know we create app one.
Igor Petrović: Yeah.
Milan Cvijetinovic: We're not creating apps every single week.

01:22:51

Milan Cvijetinovic: So we have under that that's it. Yeah.
Lizzy Evans: Yeah,
Milan Cvijetinovic: So yeah we will be much much more often updating than than creating.
Lizzy Evans: I know. I know we do all the Yeah,
Milan Cvijetinovic: So I mean it is yeah it is it's

Lizzy Evans: because we'll go through that. But um
Milan Cvijetinovic: just yeah it is yeah it is a complex
Lizzy Evans: for the Okay, so for the final step,
Milan Cvijetinovic: law.
Lizzy Evans: which is the creation of the builds. So David, you can tell what I've put in here isn't necessarily linear because we've got fields added in by like type basically, but there are some things like clear certificates, clear provisioning file that happen once we've created the build because you won't know, you won't get the error until you've received that. So we need to think about the flow a bit in terms of which fields go where. But at the moment, this doc at least explains what input fields are required and how you source the information. But we need to rejig it.

01:23:41

Lizzy Evans: I think you've already made a few notes on that anyway. Uh, okay. Once we got the information, we can create the iOS build and push to the app. Well, push push to test. Push to test. Push to test. Uh, uh, post to test.
Igor Petrović: Up tested.
Lizzy Evans: I can't remember how we test it.
Igor Petrović: Up. Tested.
Lizzy Evans: Sorry. Thank you. and the option to download Android build APK file. So we need to think about the download process for that updating build. We need to lock fields, right? So there are some fields you won't be able to edit some fields but you can edit others.
Igor Petrović: Yeah. Bundle ID and package ID field can be locked. I think uh Firebase app ID also app store app name. I think Ian never change it but it is possible to change
Lizzy Evans: I guess. Yeah,
Igor Petrović: that.
Lizzy Evans: we only want to allow what can be edited that won't break things.

01:25:20

Igor Petrović: Uh then okay first step everything can be changed. So they're doing that regularly changing the name under the icon and icons.
Lizzy Evans: Yeah. Yep.
Igor Petrović: On the second step in yeah in in best case everything can be locked but it can happens that sometimes due to some circumstances can be must be

changed.
Lizzy Evans: Cool. How do we make it clear what you do for a version update
Igor Petrović: So,
Lizzy Evans: versus needing to create an entirely new build? Are we supporting that scenario here? As in you you generated a build for the first time here for iOS, if we just talk about iOS. Um, and then you're doing a version update. for that version update you are doing what?
Igor Petrović: just hit the button. If everything is set up, just hit the button.
Lizzy Evans: Okay. So for a version update you're just going update build update build.
Igor Petrović: Yeah.
Lizzy Evans: That's it. Okay.
Igor Petrović: Yeah.
Lizzy Evans: Thank
Igor Petrović: And and uh well,

01:26:32

Lizzy Evans: you.
Igor Petrović: sometimes as I said, version update includes step one all all elements to be
Lizzy Evans: Yeah. So version update.
Igor Petrović: changed.
Lizzy Evans: I'm just going to put scenario version update with no no changes. required uh just uh new code version.
Igor Petrović: Just hit the button. Yeah.
Lizzy Evans: Yeah. Uh click upgrade.
Igor Petrović: It's same for Android.
Lizzy Evans: Yeah.
Igor Petrović: Yeah.
Lizzy Evans: Okay. Cool. And then scenario two is we are version update with like common most common one is asset changes. You're right.
Igor Petrović: Yeah.
Lizzy Evans: So that'll be uh name or icon changes and that's Yeah.
Igor Petrović: Step one plus
Lizzy Evans: Yeah. Yeah.
Igor Petrović: button.
Lizzy Evans: What can we never ever ever change because it will break
Igor Petrović: um everything in step two and step three except uh except
Lizzy Evans: everything.

Igor Petrović: Firebase tester cement. We can add testers or remove them.
Lizzy Evans: Okay, cool.
Igor Petrović: But the problem is that we are not the only one who have access to the Google Play and Google and Apple developer and Apple uh store account.

01:27:56

Igor Petrović: App Store Connect. So someone can invalidate our data there.
Lizzy Evans: Yeah, that's fine. So scenario.
Igor Petrović: Then we have to addit step two or step
Lizzy Evans: Hang on. Yeah, bear with hang on. So Firebase testers,
Igor Petrović: three.
Lizzy Evans: amen testers and um yeah, whatever. And then uh scenario four is um customer has made a change to something. Yeah. Has made a manual change in stores invalidating keys.
Igor Petrović: Yeah. Invalid think. Yeah.
Lizzy Evans: Um attempting to build will generate error.
Igor Petrović: Yeah. Or if they want to transfer the app to another account. We also had that case on Apple.
Lizzy Evans: Yep.
Igor Petrović: So that is also the
Lizzy Evans: Yeah. All right. So, in that scenario,
Igor Petrović: case.
Lizzy Evans: customer has made a manual store in validating field. We're attempting to build it. We get an error because we we're going to need press update build to know that it doesn't work.

01:29:05

Igor Petrović: Yeah.
Lizzy Evans: Right.
Igor Petrović: Yeah.
Lizzy Evans: So,
Igor Petrović: Yeah.
Lizzy Evans: if we get an error, the next step should be I'm just going to have to look in the store and see what's going on and what's being changed.
Igor Petrović: on the Yeah. Yeah. First we have to check there on the builder on the bit and then to see on the

Lizzy Evans: Okay, cool. If the ids have been changed for the application and
Igor Petrović: store
Lizzy Evans: because we've locked those fields, how can we
Igor Petrović: bundle bundle ID cannot be changed and package ID they they can
Lizzy Evans: Okay,
Igor Petrović: be locked. They never can be changed.
Lizzy Evans: but like the team ID if that
Igor Petrović: Team ID can be changed if someone want to transfer off to another team ID.
Lizzy Evans: changed. Yeah.
Igor Petrović: If team ID is changed then nothing from the below is
Lizzy Evans: Yeah.
Igor Petrović: valid below team
Lizzy Evans: Yeah. So, what I'm trying to get is which which uh things are likely to

01:29:56

Igor Petrović: ID.
Lizzy Evans: change in the store and then uh if we need to correct it, how can we correct it? Because we'll go it'll go right update update build at error. Can I understand the error what I need to change and can I change it in this form
Igor Petrović: Yeah.
Lizzy Evans: process? Yes or no?
Igor Petrović: Yeah. If you can check the logs, then you can figure out why it fails. It can fail because uh uh uh uh Apple key ID, Apple issuer ID, Apple key name is invalidated. If uh P uh upload P8 API key is invalidated or if push certificate if uh certificates or provisioning profiles are invalidated. So there is five or six calls for for that
Lizzy Evans: Yeah.
Igor Petrović: and if push notification stop with working then someone invalidated
Lizzy Evans: Yep.
Igor Petrović: our most probably our uh P8 certificate P uh P8 uh API key uh APNS. So this this second button
Lizzy Evans: Nice. Cool. Uh, nice. So, because that that does happen and has happened quite a bit as in we've had people move into a different developer.

01:31:22

Igor Petrović: No, that was not quite often,
Lizzy Evans: Um,
Igor Petrović: but quite often was that someone deletes our certificates, profiles, keys.
Lizzy Evans: yeah.
Igor Petrović: That that happens often.
Lizzy Evans: So what I want to do is if we say we need to look in the logs, I want to know if we can tailor the error message or we share something with Ilia so that he knows it's actually this item that's the issue and then he can fetch the updated one from the um developer and he can reinsert it here because at the
Igor Petrović: Yeah. Um
Lizzy Evans: moment he's at a dead end, right?
Igor Petrović: yeah, he's checking logs manually and delete everything or re-upload because everything is manual. But yeah,
Lizzy Evans: How is he logs?
Igor Petrović: he have access to the bits.
Lizzy Evans: Uh, okay. Okay.
Igor Petrović: Yeah.
Lizzy Evans: Okay.
Igor Petrović: and he he's starting builds from the beers directly now. There's no API, there's no everything. He's going there changing what is needed and then starting the builds. So he have manual process now semi-manual uh but yeah I will check if I can extract errors somehow from the bits.

01:32:33

Lizzy Evans: Yeah. Yeah. Yeah. So, yeah. Because still got a for Android on that creation piece, you still got to have Bit R and everything
Igor Petrović: Yeah.
Lizzy Evans: open
Igor Petrović: Okay.
Milan Cvijetinovic: So can we display logs here from bit trace we
Igor Petrović: Let me uh log log
Milan Cvijetinovic: have
Igor Petrović: is huge on the beta.
Lizzy Evans: this link.
Igor Petrović: I will I will check
Lizzy Evans: I I don't think as long as my main thing is just like surfacing the right

information to
Igor Petrović: that.
Lizzy Evans: point him in the right place to check. You don't necessarily need to show you that here. It's um if he needs to go into bit anyway. If he doesn't need to go into bit, it'd be great to do something if we can. But if he's got to go into bit anyway to do the process, he just needs to we just need to tell him the right message here and go it's invalidated because this ID's changed. goes the ID out and can you reinput the new ID

01:33:29

Igor Petrović: Yeah. Yeah. I have to check if I can extract that message.
Lizzy Evans: here.
Igor Petrović: I tried to get it via Bitra API. I was not able to to get it but maybe I can get it in the build process. I didn't think about that. I will check that.
Lizzy Evans: Okay. All
Igor Petrović: And the worst case we can put link to the failed build.
Lizzy Evans: right.
Igor Petrović: Go to this link and check why it's
Lizzy Evans: Yeah. Yeah.
Igor Petrović: failed.
Lizzy Evans: Yeah. Yeah. So just something to help direct the next
Igor Petrović: Yeah, that is how he he is currently working.
Lizzy Evans: action.
Igor Petrović: He got Slack notification that build failed. There is a link there in the Slack notification. and he opens that link, log into the bit trace and check the the logs.
Lizzy Evans: It's probably better that it's actually in Slack because then developers can help if they need to.
Igor Petrović: I I I will add it to the Slack anyway.

01:34:22

Lizzy Evans: Okay. Okay.
Igor Petrović: Uh it is already added.
Lizzy Evans: Good.
Igor Petrović: I just muted it because we are testing it.
Lizzy Evans: Okay.

Igor Petrović: I don't want to spam.
Lizzy Evans: Okay. Fine.
Igor Petrović: Yeah,
Lizzy Evans: The customer has made a manual install.
Igor Petrović: it's it's already there. So, yeah. So maybe in the case of build fails we can add message just check with developers or whatever. So someone from us can can check it on bit
Lizzy Evans: Yeah, that's good.
Igor Petrović: trace.
Lizzy Evans: So we can we can find out what's gone wrong in Bit R. But when we come back to this form to generate the new build, we're going to need to have these fields as editable because we'll need to insert something new.
Igor Petrović: Yeah.
Lizzy Evans: We can't block.
Igor Petrović: Yeah.
Lizzy Evans: We can't lock them. We can't lock Apple key.
Igor Petrović: Yeah.
Lizzy Evans: We can't lock the Apple key ID. Any of them except bundle ID.
Igor Petrović: Uh
Lizzy Evans: And I think that the other one you said that Yeah.

01:35:23

Igor Petrović: yeah,
Lizzy Evans: Which the ones you can't change are the bundle ID and
Igor Petrović: bundle ID can be locked and package ID on the Google can be locked. Other ones I think should remain unlocked on on the step three.
Lizzy Evans: Which one's the package ID? Because I can't see that here. Oh, right.
Igor Petrović: Uh and yeah,
Lizzy Evans: Yeah, package ID. Okay. Yeah. So, package and bundle ID are locked.
Igor Petrović: no yeah no yeah yeah no yeah no yeah no yeah no yeah no yeah no yeah no yeah no
Lizzy Evans: And those only two that can be locked. Okay,
Igor Petrović: no
Lizzy Evans: fine. Okay. Cool. So, that's got that a bit clearer. All right. I think we'll leave it there for now. Um,
Igor Petrović: Yeah.
Lizzy Evans: I'll write out the scope a bit more comprehensively. Um, I think about what we can do with the
Igor Petrović: Yeah. I think that is mostly this is the bare minimum we must have.

Lizzy Evans: Yeah. All right. Okay. Thanks for that. We'll leave it there. Um, David Oh, yeah. Um,
David Ukauwa: Yep.
Lizzy Evans: I'll go I'm going to neaten up the spec do a little bit, but Milan has also I think you've started to design some bits, Milan. I know it's going to change. I'd probably I think we might just put a little workflow together for this and then we can see what you've what you where you've got to and then we can compare we can compare what we need. But um I'll map out the steps just in a little process flow, David. But then I'll use this as this spec is just showing the inputs and then we can go from there. Okay. All right.

Transcription ended after 01:37:25

This editable transcript was computer generated and might contain errors. People can also change the text after it was created.