

```
import { useState, useEffect, useRef } from "react";
```

```
const COLORS = {  
  navy: "#0A0E1A",  
  navyMid: "#111827",  
  navyCard: "#151C2E",  
  teal: "#00D4C8",  
  tealDim: "rgba(0,212,200,0.10)",  
  tealGlow: "rgba(0,212,200,0.22)",  
  gold: "#F5C842",  
  white: "#F0EDE8",  
  slate: "#6B7A99",  
  slateLight: "#A0AABF",  
  border: "rgba(0,212,200,0.14)",  
};
```

```
const DUKE_CONTEXT = `
```

```
You are an AI assistant embedded in Duke David's professional portfolio website.  
Duke David (real name: Anuoluwa Zaccheaus) is a freelance Web3 community professi  
He is open to remote opportunities worldwide.
```

```
His core skills: community management, Discord/Telegram/X moderation, ambassador
```

```
Experience:
```

- MaAvatar: Collaboration Manager & Moderator (concluded)
- Golem Network: Community Moderator
- Arkiv Network: Community Moderator
- GiftHorse: Ambassador
- Quites: Ambassador
- Currently active with 5th Kingdom NFT/Web3 project as community advocate
- Produced multi-part X content series for Orivon Browser
- Founding Guru role at TradePulse

```
Social handles: X @iamdavidd_2 | Discord @iamdavidd_ | Telegram @iam_davidd_
```

```
He is currently available for new remote Web3 roles.
```

```
Answer questions about his background, skills, experience, and availability in a  
`;
```

```
const skills = [  
  { icon: "🏛️", title: "Community Management", desc: "Building and growing health  
  { icon: "🛡️", title: "Moderation", desc: "Active moderation across Discord and  
  { icon: "📣", title: "Ambassador Programs", desc: "Full-cycle execution: recrui
```

```

    { icon: "👉", title: "Partnerships", desc: "Identifying and pitching strategic"
    { icon: "📢", title: "KOL Outreach", desc: "Targeted, personalized outreach to"
    { icon: "👉📝", title: "Content & Threads", desc: "Culture-native X threads, Disc
];

```

```

const experiences = [
  { role: "Collaboration Manager & Moderator", company: "MaAvatar", period: "Conc
  { role: "Community Advocate", company: "5th Kingdom", period: "Active", desc: "
  { role: "Content Contributor", company: "Orivon Browser", period: "Recent", des
  { role: "Community Moderator", company: "Golem Network", period: "Past", desc:
  { role: "Community Moderator", company: "Arkiv Network", period: "Past", desc:
  { role: "Ambassador", company: "GiftHorse & Quites", period: "Past", desc: "Rep
];

```

```

const platforms = [
  { icon: "💬", name: "Discord", role: "Moderation · Community Ops", handle: "@ia
  { icon: "✈️", name: "Telegram", role: "Group Management · Moderation", handle:
  { icon: "X", name: "X / Twitter", role: "Threads · KOL Outreach", handle: "@iam
  { icon: "💼", name: "LinkedIn", role: "Professional Presence", handle: "Duke Da
];

```

```

function useTypewriter(words, speed = 80, pause = 1800) {
  const [display, setDisplay] = useState("");
  const [wordIdx, setWordIdx] = useState(0);
  const [charIdx, setCharIdx] = useState(0);
  const [deleting, setDeleting] = useState(false);

```

```

  useEffect(() => {
    const current = words[wordIdx];
    const timeout = setTimeout(() => {
      if (!deleting) {
        setDisplay(current.slice(0, charIdx + 1));
        if (charIdx + 1 === current.length) {
          setTimeout(() => setDeleting(true), pause);
        } else {
          setCharIdx(c => c + 1);
        }
      } else {
        setDisplay(current.slice(0, charIdx - 1));
        if (charIdx - 1 === 0) {
          setDeleting(false);
          setWordIdx(w => (w + 1) % words.length);
          setCharIdx(0);
        } else {
          setCharIdx(c => c - 1);
        }
      }
    }
  )
}

```

```

    }, deleting ? speed / 2 : speed);
    return () => clearTimeout(timeout);
  }, [charIdx, deleting, wordIdx, words, speed, pause]);

  return display;
}

function Nav({ active, setActive }) {
  const [scrolled, setScrolled] = useState(false);
  const sections = ["about", "skills", "experience", "contact"];

  useEffect(() => {
    const onScroll = () => setScrolled(window.scrollY > 40);
    window.addEventListener("scroll", onScroll);
    return () => window.removeEventListener("scroll", onScroll);
  }, []);

  const scrollTo = (id) => {
    document.getElementById(id)?.scrollIntoView({ behavior: "smooth" });
    setActive(id);
  };

  return (
    <nav style={{
      position: "fixed", top: 0, left: 0, right: 0, zIndex: 100,
      display: "flex", alignItems: "center", justifyContent: "space-between",
      padding: "16px 48px",
      background: scrolled ? "rgba(10,14,26,0.92)" : "transparent",
      backdropFilter: scrolled ? "blur(14px)" : "none",
      borderBottom: scrolled ? `1px solid ${COLORS.border}` : "1px solid transpar",
      transition: "all 0.3s ease",
    }}>
      <span style={{ fontFamily: "monospace", fontSize: 13, color: COLORS.teal, 1
        // duke_david
      }}>
      </span>
      <div style={{ display: "flex", gap: 32 }}>
        {sections.map(s => (
          <button key={s} onClick={() => scrollTo(s)} style={{
            background: "none", border: "none", cursor: "pointer",
            fontFamily: "sans-serif", fontSize: 12, fontWeight: 500,
            letterSpacing: "0.08em", textTransform: "uppercase",
            color: active === s ? COLORS.teal : COLORS.slateLight,
            transition: "color 0.2s",
          }}>{s}</button>
        ))}
      </div>
      <button onClick={() => scrollTo("contact")} style={{

```

```

        fontFamily: "monospace", fontSize: 11, fontWeight: 700,
        color: COLORS.navy, background: COLORS.teal,
        border: "none", padding: "8px 20px", borderRadius: 2,
        cursor: "pointer", letterSpacing: "0.05em",
    }}>Hire Me</button>
</nav>
);
}

function Hero({ setActive }) {
    const typed = useTypewriter(["communities.", "ecosystems.", "movements.", "cult

    return (
        <section id="hero" style={{
            minHeight: "100vh", display: "flex", alignItems: "center",
            padding: "120px 48px 80px",
            position: "relative", overflow: "hidden",
            background: COLORS.navy,
        }}>
            { /* Grid */ }
            <div style={{
                position: "absolute", inset: 0, pointerEvents: "none",
                backgroundImage: `linear-gradient(${COLORS.border} 1px, transparent 1px),
                backgroundSize: "56px 56px",
                WebkitMaskImage: "radial-gradient(ellipse at 30% 50%, black 20%, transpar
                maskImage: "radial-gradient(ellipse at 30% 50%, black 20%, transparent 75
            }} />
            { /* Glow */ }
            <div style={{
                position: "absolute", inset: 0, pointerEvents: "none",
                background: `radial-gradient(ellipse 55% 55% at 75% 50%, ${COLORS.tealGlo
            }} />

            <div style={{ position: "relative", maxWidth: 780 }}>
                <div style={{ fontFamily: "monospace", fontSize: 11, color: COLORS.teal,
                    <span style={{ display: "inline-block", width: 32, height: 1, backgroun
                    Web3 Community Professional · Lagos, Nigeria
                </div>

                <h1 style={{ fontFamily: "sans-serif", fontSize: "clamp(32px,5vw,60px)",
                    I build{" "}
                    <span style={{ color: COLORS.teal }}>
                        {typed}<span style={{ display: "inline-block", width: 3, height: "0.9
                    </span>
                    <br />
                    that actually ship.
                </h1>

```

```

<p style={{ fontSize: 18, fontWeight: 300, color: COLORS.slateLight, maxW
  Community manager, moderator, and ambassador program executor with a pr
</p>

<div style={{ display: "flex", flexWrap: "wrap", gap: 8, marginBottom: 44
  [{"Community Management", "Discord · Telegram · X", "KOL Outreach", "Ambas
    <span key={t} style={{
      fontFamily: "monospace", fontSize: 11, color: COLORS.teal,
      border: `1px solid ${COLORS.border}`, padding: "5px 14px",
      borderRadius: 2, background: COLORS.tealDim, letterSpacing: "0.05em
    }}>{t}</span>
  )}}
</div>

<div style={{ display: "flex", gap: 14, flexWrap: "wrap" }}>
  <button onClick={() => document.getElementById("experience")?.scrollInt
    fontFamily: "monospace", fontSize: 12, fontWeight: 700, color: COLORS
    background: COLORS.teal, border: "none", padding: "14px 32px", border
    cursor: "pointer", letterSpacing: "0.05em", transition: "transform 0.
  }}
    onMouseEnter={e => { e.target.style.transform = "translateY(-2px)"; e
    onMouseLeave={e => { e.target.style.transform = "none"; e.target.styl
  >See My Work</button>
  <button onClick={() => document.getElementById("contact")?.scrollIntoVi
    fontFamily: "monospace", fontSize: 12, color: COLORS.teal,
    background: "none", border: `1px solid ${COLORS.border}`, padding: "1
    borderRadius: 2, cursor: "pointer", letterSpacing: "0.05em",
  }}>Get in Touch</button>
</div>
</div>
<style>{@keyframes blink { 50% { opacity: 0; } }}</style>
</section>
);
}

function About() {
  const stats = [
    { n: "5+", l: "Projects" },
    { n: "3+", l: "Years in Web3" },
    { n: "100%", l: "Remote Ready" },
    { n: "∞", l: "Community First" },
  ];
  return (
    <section id="about" style={{ background: COLORS.navyMid, padding: "100px 48px
      <div style={{ maxWidth: 1000, margin: "0 auto", display: "grid", gridTempla
        <div>

```

```

    <SectionLabel>About</SectionLabel>
    <h2 style={{ fontFamily: "sans-serif", fontSize: "clamp(26px,3vw,40px)"
    {[
      <>I'm <b style={{ color: COLORS.white }}>Anuoluwa Zaccheaus</b>, know
      <>My approach is research-backed and culture-native. I learn a projec
      <>Currently open to <b style={{ color: COLORS.white }}>remote communi
    ].map((p, i) => (
      <p key={i} style={{ fontSize: 15, color: COLORS.slateLight, lineHeigh
    )))
    <div style={{ display: "flex", alignItems: "center", gap: 10, fontFamil
      <span style={{ width: 8, height: 8, borderRadius: "50%", background:
      Available for new opportunities
    </div>
    <style>{@keyframes pulse { 0% { box-shadow: 0 0 0 0 rgba(34,197,94,0.4
    </div>
    <div style={{ display: "grid", gridTemplateColumns: "1fr 1fr", gap: 2 }}>
      {stats.map(s => (
        <div key={s.1} style={{ background: COLORS.navyCard, border: `1px sol
          <div style={{ position: "absolute", top: 0, left: 0, right: 0, heig
            <span style={{ fontFamily: "monospace", fontSize: 34, fontWeight: 7
            <span style={{ fontSize: 13, color: COLORS.slate }}>{s.1}</span>
          </div>
        )))
      </div>
    </div>
  </section>
);
}

```

```

function Skills() {
  return (
    <section id="skills" style={{ background: COLORS.navy, padding: "100px 48px"
      <div style={{ maxWidth: 1000, margin: "0 auto" }}>
        <SectionLabel>What I Do</SectionLabel>
        <h2 style={{ fontFamily: "sans-serif", fontSize: "clamp(26px,3vw,40px)"
        <p style={{ fontSize: 15, color: COLORS.slateLight, marginBottom: 56, lin
        <div style={{ display: "grid", gridTemplateColumns: "repeat(3, 1fr)", gap
          {skills.map(s => (
            <SkillCard key={s.title} {...s} />
          )))
        </div>
      </div>
    </section>
  );
}

```

```

function SkillCard({ icon, title, desc }) {

```

```

const [hov, setHov] = useState(false);
return (
  <div onMouseEnter={() => setHov(true)} onMouseLeave={() => setHov(false)} sty
    background: COLORS.navyCard, border: `1px solid ${hov ? COLORS.teal : COLOR
    padding: "36px 28px", transition: "border-color 0.2s, transform 0.2s",
    transform: hov ? "translateY(-4px)" : "none",
  >>
    <span style={{ fontSize: 28, display: "block", marginBottom: 16 }}>{icon}</
    <div style={{ fontFamily: "sans-serif", fontSize: 16, fontWeight: 600, colo
    <div style={{ fontSize: 13, color: COLORS.slate, lineHeight: 1.65 }}>{desc}
    </div>
  </div>
);
}

```

```

function Experience() {
  return (
    <section id="experience" style={{ background: COLORS.navyMid, padding: "100px
    <div style={{ maxWidth: 1000, margin: "0 auto" }}>
      <SectionLabel>Experience</SectionLabel>
      <h2 style={{ fontFamily: "sans-serif", fontSize: "clamp(26px,3vw,40px)",
      <p style={{ fontSize: 15, color: COLORS.slateLight, marginBottom: 56, lin
      <div style={{ position: "relative" }}>
        <div style={{ position: "absolute", left: 0, top: 8, bottom: 0, width:
          {experiences.map((e, i) => (
            <div key={i} style={{ paddingLeft: 40, marginBottom: 48, position: "r
              <div style={{ position: "absolute", left: -5, top: 8, width: 11, he
                <div style={{ display: "flex", alignItems: "center", gap: 14, flexW
                  <span style={{ fontFamily: "sans-serif", fontSize: 17, fontWeight
                    <span style={{ fontFamily: "monospace", fontSize: 11, color: COLO
                    <span style={{ fontFamily: "monospace", fontSize: 11, color: COLO
                  </div>
                <p style={{ fontSize: 14, color: COLORS.slateLight, lineHeight: 1.7
              </div>
            </div>
          </div>
        </div>
      </div>
    </section>
  );
}

```

```

function Platforms() {
  return (
    <section style={{ background: COLORS.navy, padding: "80px 48px" }}>
      <div style={{ maxWidth: 1000, margin: "0 auto" }}>
        <SectionLabel>Platforms</SectionLabel>
        <h2 style={{ fontFamily: "sans-serif", fontSize: "clamp(24px,2.5vw,36px)"
        <div style={{ display: "grid", gridTemplateColumns: "repeat(4, 1fr)", gap

```

```

        {platforms.map(p => (
            <PlatformCard key={p.name} {...p} />
        ))}
    </div>
</div>
</section>
);
}

function PlatformCard({ icon, name, role, handle }) {
    const [hov, setHov] = useState(false);
    return (
        <div onMouseEnter={() => setHov(true)} onMouseLeave={() => setHov(false)} sty
            le={{ background: COLORS.navyCard, border: `1px solid ${hov ? COLORS.teal : COLOR
                S.navyCard}, padding: "28px 20px", textAlign: "center", transition: "border-color 0.2s",
            }}>
            <div style={{ fontSize: 30, marginBottom: 12 }}>{icon}</div>
            <div style={{ fontFamily: "sans-serif", fontSize: 14, fontWeight: 600, colo
                r: "white", display: "flex", flex-direction: "column", align-items: "center", justify-content: "center"
            }}>
            <div style={{ fontSize: 11, color: COLORS.slate, marginBottom: 8 }}>{role}<
                /div>
            <div style={{ fontFamily: "monospace", fontSize: 11, color: COLORS.teal }}>
                {handle}</div>
            </div>
        </div>
    );
}

function AskDuke() {
    const [messages, setMessages] = useState([
        { role: "assistant", content: "Hey! I'm an AI trained on Duke David's portfol
            io" }
    ]);
    const [input, setInput] = useState("");
    const [loading, setLoading] = useState(false);
    const bottomRef = useRef(null);

    useEffect(() => {
        bottomRef.current?.scrollIntoView({ behavior: "smooth" });
    }, [messages, loading]);

    const send = async () => {
        const text = input.trim();
        if (!text || loading) return;
        const newMessages = [...messages, { role: "user", content: text }];
        setMessages(newMessages);
        setInput("");
        setLoading(true);
        try {
            const res = await fetch("https://api.anthropic.com/v1/messages", {
                method: "POST",
                headers: { "Content-Type": "application/json" },
            });
            const data = await res.json();
            if (data.error) {
                console.error(data.error);
                return;
            }
            const assistantMessage = {
                role: "assistant",
                content: data.content[0].text,
            };
            setMessages([...newMessages, assistantMessage]);
            setInput("");
            setLoading(false);
        } catch (error) {
            console.error(error);
        }
    };
}

```

```

    body: JSON.stringify({
      model: "claude-sonnet-4-6",
      max_tokens: 1000,
      system: DUKE_CONTEXT,
      messages: newMessages.map(m => ({ role: m.role, content: m.content })),
    }),
  });
  const data = await res.json();
  const reply = data.content?.find(b => b.type === "text")?.text || "Sorry, I
  setMessages(prev => [...prev, { role: "assistant", content: reply }]);
} catch {
  setMessages(prev => [...prev, { role: "assistant", content: "Something went
  }
  setLoading(false);
};

return (
  <div style={{ background: COLORS.navyCard, border: `1px solid ${COLORS.border
    <div style={{ padding: "14px 20px", borderBottom: `1px solid ${COLORS.borde
      <span style={{ width: 8, height: 8, borderRadius: "50%", background: COLO
      <span style={{ fontFamily: "monospace", fontSize: 12, color: COLORS.teal,
    </div>
    <div style={{ flex: 1, overflowY: "auto", padding: "20px 20px 8px", display
      {messages.map((m, i) => (
        <div key={i} style={{ display: "flex", justifyContent: m.role === "user
          <div style={{
            maxWidth: "82%", padding: "10px 14px", borderRadius: 3, fontSize: 1
            background: m.role === "user" ? COLORS.teal : "rgba(255,255,255,0.0
            color: m.role === "user" ? COLORS.navy : COLORS.slateLight,
            fontWeight: m.role === "user" ? 600 : 400,
          }}>{m.content}</div>
        </div>
      ))}
    {loading && (
      <div style={{ display: "flex", gap: 4, paddingLeft: 4, alignItems: "cen
        {[0, 1, 2].map(i => (
          <span key={i} style={{ width: 6, height: 6, borderRadius: "50%", ba
        ))}
      </div>
    )}
    <div ref={bottomRef} />
  </div>
  <div style={{ padding: "12px 16px", borderTop: `1px solid ${COLORS.border}`
    <input
      value={input}
      onChange={e => setInput(e.target.value)}
      onKeyDown={e => e.key === "Enter" && send()}

```

```

placeholder="Ask about Duke David's experience..."
style={{
  flex: 1, background: "rgba(255,255,255,0.04)", border: `1px solid ${C
  borderRadius: 2, padding: "9px 14px", color: COLORS.white, fontSize:
  fontFamily: "sans-serif", outline: "none",
}}
/>
<button onClick={send} disabled={loading || !input.trim()} style={{
  background: COLORS.teal, border: "none", borderRadius: 2, padding: "9px
  color: COLORS.navy, fontWeight: 700, fontSize: 13, cursor: "pointer",
  opacity: loading || !input.trim() ? 0.5 : 1, transition: "opacity 0.2s"
}}>→</button>
</div>
<style>{@keyframes bounce { 0%,100%{transform:translateY(0)} 50%{transform
</div>
);
}

```

```

function Contact() {
  const links = [
    { icon: "X", label: "X / Twitter", value: "@iamdavidd_2", href: "https://twit
    { icon: "💬", label: "Discord", value: "@iamdavidd_", href: "#" },
    { icon: "✈️", label: "Telegram", value: "@iam_davidd_", href: "https://t.me/i
    { icon: "💼", label: "LinkedIn", value: "Duke David", href: "#" },
  ];
  return (
    <section id="contact" style={{ background: COLORS.navyMid, padding: "100px 48
      <div style={{ maxWidth: 1000, margin: "0 auto" }}>
        <SectionLabel>Contact</SectionLabel>
        <h2 style={{ fontFamily: "sans-serif", fontSize: "clamp(26px,3vw,40px)",
        <div style={{ display: "grid", gridTemplateColumns: "1fr 1fr", gap: 64, a
          <div>
            <h3 style={{ fontFamily: "sans-serif", fontSize: 22, fontWeight: 700,
            <p style={{ fontSize: 15, color: COLORS.slateLight, lineHeight: 1.75,
              If you're building a community-first project and need someone who's
            </p>
            <div style={{ display: "flex", flexDirection: "column", gap: 12 }}>
              {links.map(l => (
                <ContactLink key={l.label} {...l} />
              ))}
            </div>
          </div>
        </div>
      <div>
        <div style={{ fontFamily: "monospace", fontSize: 11, color: COLORS.te
          // ask_the_ai
        </div>
        <p style={{ fontSize: 13, color: COLORS.slate, marginBottom: 16, line

```

```

        Have a quick question about Duke David's background or availability
      </p>
      <AskDuke />
    </div>
  </div>
</div>
</section>
);
}

function ContactLink({ icon, label, value, href }) {
  const [hov, setHov] = useState(false);
  return (
    <a href={href} target="_blank" rel="noreferrer" onMouseEnter={() => setHov(true)}
      display: "flex", alignItems: "center", gap: 16,
      background: COLORS.navyCard, border: `1px solid ${hov ? COLORS.teal : COLOR}
      padding: "14px 20px", borderRadius: 2, textDecoration: "none",
      transform: hov ? "translateX(4px)" : "none", transition: "all 0.2s",
    >>
    <span style={{ fontSize: 18 }}>{icon}</span>
    <div>
      <div style={{ fontFamily: "monospace", fontSize: 10, color: COLORS.slate,
        <div style={{ fontSize: 13, fontWeight: 500, color: COLORS.teal }}>{value}
      </div>
    </a>
  );
}

function SectionLabel({ children }) {
  return (
    <div style={{ fontFamily: "monospace", fontSize: 11, color: COLORS.teal, letterSpacing: 0.5 }}>
      {children}
    <span style={{ display: "inline-block", width: 40, height: 1, background: COLORS.teal }}>
    </div>
  );
}

function Footer() {
  return (
    <footer style={{ background: COLORS.navy, borderTop: `1px solid ${COLORS.bord}
      <span style={{ fontFamily: "monospace", fontSize: 13, color: COLORS.teal }}>
      <span style={{ fontSize: 12, color: COLORS.slate }}>Lagos, Nigeria · Remote
    </footer>
  );
}

export default function App() {

```

```

const [active, setActive] = useState("about");

useEffect(() => {
  const observer = new IntersectionObserver(
    entries => entries.forEach(e => e.isIntersecting && setActive(e.target.id))
    { threshold: 0.4 }
  );
  ["about", "skills", "experience", "contact"].forEach(id => {
    const el = document.getElementById(id);
    if (el) observer.observe(el);
  });
  return () => observer.disconnect();
}, []);

return (
  <div style={{ background: COLORS.navy, minHeight: "100vh" }}>
    <Nav active={active} setActive={setActive} />
    <Hero setActive={setActive} />
    <About />
    <Skills />
    <Experience />
    <Platforms />
    <Contact />
    <Footer />
  </div>
);
}

```