

SKRIPSI

**MENGIKUTI MAYORITAS:
SEBUAH ALGORITMA BARU UNTUK MENGHITUNG
MEDIAN TRAJECTORY**



LIONOV

NPM: 1997730020

**PROGRAM STUDI TEKNIK INFORMATIKA
FAKULTAS TEKNOLOGI INFORMASI DAN SAINS
UNIVERSITAS KATOLIK PARAHYANGAN
2002**

UNDERGRADUATE THESIS

**FOLLOWING THE MAJORITY:
A NEW ALGORITHM FOR COMPUTING
A MEDIAN TRAJECTORY**



LIONOV

NPM: 1997730020

**DEPARTMENT OF INFORMATICS
FACULTY OF INFORMATION TECHNOLOGY AND SCIENCES
PARAHYANGAN CATHOLIC UNIVERSITY
2002**

LEMBAR PENGESAHAN

**MENGIKUTI MAYORITAS:
SEBUAH ALGORITMA BARU UNTUK MENGHITUNG
MEDIAN TRAJECTORY**

LIONOV

NPM: 1997730020

Bandung, 1 Juli 2002

Menyetujui,

Pembimbing Utama

Pembimbing Pendamping

Dr. Oerip S. Santoso

Thomas Anung Basuki, Ph.D.

Ketua Tim Penguji

Anggota Tim Penguji

Nico Saputro, M.T.

Dr. rer. nat. Cecilia Esti Nugraheni

Mengetahui,

Ketua Program Studi

Thomas Anung Basuki, Ph.D.

PERNYATAAN

Dengan ini saya yang bertandatangan di bawah ini menyatakan bahwa skripsi dengan judul:

MENGIKUTI MAYORITAS: SEBUAH ALGORITMA BARU UNTUK MENGHITUNG MEDIAN TRAJECTORY

adalah benar-benar karya saya sendiri, dan saya tidak melakukan penjiplakan atau pengutipan dengan cara-cara yang tidak sesuai dengan etika keilmuan yang berlaku dalam masyarakat keilmuan.

Atas pernyataan ini, saya siap menanggung segala risiko dan sanksi yang dijatuhkan kepada saya, apabila di kemudian hari ditemukan adanya pelanggaran terhadap etika keilmuan dalam karya saya, atau jika ada tuntutan formal atau non-formal dari pihak lain berkaitan dengan keaslian karya saya ini.

Dinyatakan di Bandung,
Tanggal 1 Juli 2002

M t rai

Lionov
NPM: 1997730020

ABSTRAK

Kami membangun dua algoritma baru untuk menghitung lintasan dari median titik lintasan. Algoritma pertama adalah $O(1.2108^m + m^5 n^5)$ terburuk waktu algoritma, dengan menggunakan konsep Jarak Fréchet. Algoritma kedua menggunakan metode penyanga. Dalam situasi praktis, algoritma ini dapat menghitung median lintasan di $O((mn)^2 \log mn)$ waktu. Untuk kedua algoritma, m adalah jumlah lintasan dalam m ngatur dan lintasan masing-masing memiliki segmen n . Kami membandingkan algoritma buffer dengan dua algoritma lain, salah satu dari mereka menggunakan konsep homotopy. Hasil kami menunjukkan bahwa algoritma penyanga melakukan agak lebih baik.

Kami membangun dua algoritma baru untuk menghitung lintasan dari median titik lintasan. Algoritma pertama adalah $O(1.2108^m + m^5 n^5)$ terburuk waktu algoritma, dengan menggunakan konsep Jarak Fréchet. Algoritma kedua menggunakan metode penyanga. Dalam situasi praktis, algoritma ini dapat menghitung median lintasan di $O((mn)^2 \log mn)$ waktu. Untuk kedua algoritma, m adalah jumlah lintasan dalam m ngatur dan lintasan masing-masing memiliki segmen n . Kami membandingkan algoritma buffer dengan dua algoritma lain, salah satu dari mereka menggunakan konsep homotopy. Hasil kami menunjukkan bahwa algoritma penyanga melakukan agak lebih baik.

Kata-kata kunci: Lintasan, Homotopy, Fréchet, Lintasan Median, Penyanga

ABSTRACT

We develop two new algorithms to compute a median trajectory from a set of trajectories. The first algorithm is an $O(1.2108^m + m^5 n^5)$ worst-case time algorithm, using the concept of Fréchet Distance. The second algorithm uses a buffering method. In practical situations, this algorithm can compute the median trajectory in $O((mn)^2 \log mn)$ time. For both algorithms, m is the number of trajectories in the set and each trajectory has n segments. We compare the buffering algorithm with two other algorithms, one of them using the homotopy concept. Our results suggest that the buffering algorithm performs somewhat better.

We develop two new algorithms to compute a median trajectory from a set of trajectories. The first algorithm is an $O(1.2108^m + m^5 n^5)$ worst-case time algorithm, using the concept of Fréchet Distance. The second algorithm uses a buffering method. In practical situations, this algorithm can compute the median trajectory in $O((mn)^2 \log mn)$ time. For both algorithms, m is the number of trajectories in the set and each trajectory has n segments. We compare the buffering algorithm with two other algorithms, one of them using the homotopy concept. Our results suggest that the buffering algorithm performs somewhat better.

Keywords: Trajectory, Homotopy, Fréchet, Median Trajectory, Buffer

Dipersembahkan untuk diri sendiri

KATA PENGANTAR

Lor m ipsum dolor sit am t, cons et tu r adipiscing lit. Ut purus lit, v stibulum ut, plac rat ac, adipiscing vita , f lis. Curabitur dictum gravida mauris. Nam arcu lib ro, nonummy g t, cons et tu r id, vulputat a, magna. Don c v hicula augu u n qu . P ll nt squ habitant morbi tristiqu s n ctus t n tus t mal suada fam s ac turpis g stas. Mauris ut l o. Cras viv rra m tus rhoncus s m. Nulla t l ctus v stibulum urna fringilla ultric s. Phas llus u t llus sit am t tortor gravida plac rat. Int g r sapi n st, iaculis in, pr tium quis, viv rra ac, nunc. Pra s nt g t s m v l l o ultric s bib ndum. A n an faucibus. Morbi dolor nulla, mal suada u, pulvinar at, mollis ac, nulla. Curabitur auctor s mp r nulla. Don c varius orci g t risus. Duis nibh mi, congru u, accumsan l if nd, sagittis quis, diam. Duis g t orci sit am t orci dignissim rutrum.

Nam dui ligula, fringilla a, uismod sodal s, sollicitudin v l, wisi. Morbi auctor lor m non justo. Nam lacus lib ro, pr tium at, lobortis vita , ultrici s t, t llus. Don c aliqu t, tortor s d accumsan bib ndum, rat ligula aliqu t magna, vita ornar odio m tus a mi. Morbi ac orci t nisl h ndr rit mollis. Susp ndiss ut massa. Cras n c ant . P ll nt squ a nulla. Cum sociis natoqu p natibus t magnis dis parturi nt mont s, nasc tur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorp r v stibulum turpis. P ll nt squ cursus luctus mauris.

Nulla mal suada porttitor diam. Don c f lis rat, congru non, volutpat at, tincidunt tristiqu , lib ro. Vivamus viv rra f rm ntum f lis. Don c nonummy p ll nt squ ant . Phas llus adipiscing s mp r lit. Proin f rm ntum massa ac quam. S d diam turpis, mol sti vita , plac rat a, mol sti n c, l o. Ma c nas lacinia. Nam ipsum ligula, l if nd at, accumsan n c, suscipit a, ipsum. Morbi blandit ligula f ugiat magna. Nunc l if nd cons quat lor m. S d lacinia nulla vita nim. P ll nt squ tincidunt purus v l magna. Int g r non nim. Pra s nt uismod nunc u purus. Don c bib ndum quam in t llus. Nullam cursus pulvinar l ctus. Don c t mi. Nam vulputat m tus u nim. V stibulum p ll nt squ f lis u massa.

Quisqu ullamcorp r plac rat ipsum. Cras nibh. Morbi v l justo vita lacus tincidunt ultric s. Lor m ipsum dolor sit am t, cons et tu r adipiscing lit. In hac habitass plat a dictumst. Int g r t mpus convallis augu . Etiam facilisis. Nunc l m ntum f rm ntum wisi. A n an plac rat. Ut imp rdi t, nim s d gravida sollicitudin, f lis odio plac rat quam, ac pulvinar lit purus g t nim. Nunc vita tortor. Proin t mpus nibh sit am t nisl. Vivamus quis tortor vita risus porta v hicula.

Fusc mauris. V stibulum luctus nibh at l ctus. S d bib ndum, nulla a faucibus s mp r, l o v lit ultrici s t llus, ac v n natis arcu wisi v l nisl. V stibulum diam. Aliquam p ll nt squ , augu quis sagittis posu r , turpis lacus congru quam, in h ndr rit risus ros g t f lis. Ma c nas g t rat in sapi n mattis porttitor. V stibulum porttitor. Nulla facilisi. S d a turpis u lacus commodo facilisis. Morbi fringilla, wisi in dignissim int rdum, justo l ctus sagittis dui, t v hicula lib ro dui cursus dui. Mauris t mpor ligula s d lacus. Duis cursus nim ut augu . Cras ac magna. Cras nulla. Nulla g stas. Curabitur a l o. Quisqu g stas wisi g t nunc. Nam f ugiat lacus v l st. Curabitur cons et tu r.

Susp ndiss v l f lis. Ut lor m lor m, int rdum u, tincidunt sit am t, laor t vita , arcu. A n an faucibus p d u ant . Pra s nt nim lit, rutrum at, mol sti non, nonummy v l, nisl. Ut l ctus ros, mal suada sit am t, f rm ntum u, sodal s cursus, magna. Don c u purus. Quisqu v hicula, urna s d ultrici s auctor, p d lor m g stas dui, t convallis lit rat s d nulla. Don c luctus. Curabitur t nunc. Aliquam dolor odio, commodo pr tium, ultrici s non, phar tra in, v lit. Int g r arcu st, nonummy in, f rm ntum faucibus, g stas v l, odio.

Sed commodo posuere per d. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit
sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst.
Per lentesque non liti. Fuscus sed justo urna porta tincidunt. Mauris felis odio, sollicitudin sed,
volutpat a, ornare ac, rat. Morbi quis dolor. Donec per lentesque, rat ac sagittis semper, nunc dui
lobortis purus, quis congue purus metus ultricies tellus. Proin tunc quam. Class aptent taciti sociosque
ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum
vel, litora faucibus, vehicula eu, lacus.

Bandung, Juli 2002

P nulis

DAFTAR ISI

KATA PENGANTAR	xv
DAFTAR ISI	xvii
DAFTAR GAMBAR	xix
DAFTAR TABEL	xxi
1 PENDAHULUAN	1
1.1 Latar Belakang	1
1.2 Perumusan Masalah	1
1.3 Tujuan dan Manfaat	2
1.3.1 Tujuan	2
1.3.2 Manfaat	2
1.4 Ruang Lingkup Masalah	2
1.5 Metodologi Penelitian dan Teknik Pengumpulan Data	2
1.5.1 Metodologi Penelitian	2
1.5.2 Teknik Pengumpulan Data	2
1.6 Sistematika Pembahasan	2
2 LADASAN TEORI	3
2.1 Tahap Data Mining	3
3 INTRODUCTION	5
3.1 Motivation	5
3.1.1 Determining the most typical trajectory	7
3.1.2 Better visualization for a set of trajectories	7
3.1.3 k -medoid clustering	9
3.2 Basic Idea of the Research	10
3.2.1 The Simple Switching Method	10
3.2.2 The Algorithm Using the Concept of Homotopy	11
3.2.3 The Proposed Solutions	14
3.3 Outline of the Thesis	15
4 INTRODUCTION	19
4.1 Motivation	19
4.1.1 Determining the most typical trajectory	21
4.1.2 Better visualization for a set of trajectories	21
4.1.3 k -medoid clustering	23
4.2 Basic Idea of the Research	24
4.2.1 The Simple Switching Method	24
4.2.2 The Algorithm Using the Concept of Homotopy	25
4.2.3 The Proposed Solutions	28

4.3	Outlin of th Thesis	29
5	INTRODUCTION	33
5.1	Motivation	33
5.1.1	D t rmin th most typical traj ctory	35
5.1.2	B tt r visualization for a s t of traj ctori s	35
5.1.3	k -m doid clust ring	37
5.2	Basic Id a of th R s arch	38
5.2.1	Th Simpl Switching M thod	38
5.2.2	Th Algorithm Using th Conc pt of Homotopy	39
5.2.3	Th Propos d Solutions	42
5.3	Outlin of th Thesis	43
	DAFTAR REFERENSI	47
	A THE PROGRAM	51
	B THE SOURCE CODE	53
	C THE SOURCE CODE	55

DAFTAR GAMBAR

2.1	Exempl of 2D traj ctori s with tim compon nt, from [1]	4
3.1	Exempl of 2D traj ctori s with tim compon nt, from [1]	5
3.2	Exempl of th m dian (l ft) and th m an (right) traj ctory [2]	6
3.3	Robustn ss of th m dian traj ctory	7
3.4	Th s t of 30 traj ctori s, starting at th blu point & nding at th gr n point	8
3.5	A s t of 30 traj ctori s with its possibl m dian traj ctory	8
3.6	Illustration of th simpl id a using switching	10
3.7	Th m dian traj ctory mak a shortcut path [2]	10
3.8	Th m dian traj ctory do s not stay in th middl [2]	11
3.9	Th m dian traj ctory follows incorr ct dir ction [2]	11
3.10	Illustration of th algorithm using homotopy conc pt	12
3.11	Traj ctori s and cross s	12
3.12	Th blu and black traj ctory ar homotopically quival nt [2]	13
3.13	Modifi d switching m thod [2]	13
3.14	Exempl cas s wh r algorithm using homotopy will fail	14
3.15	Th m dian traj ctory do s not pass through part of traj ctori s in th upp r l ft ar a	14
4.1	Exempl of 2D traj ctori s with tim compon nt, from [1]	19
4.2	Exempl of th m dian (l ft) and th m an (right) traj ctory [2]	20
4.3	Robustn ss of th m dian traj ctory	21
4.4	Th s t of 30 traj ctori s, starting at th blu point & nding at th gr n point	22
4.5	A s t of 30 traj ctori s with its possibl m dian traj ctory	22
4.6	Illustration of th simpl id a using switching	24
4.7	Th m dian traj ctory mak a shortcut path [2]	24
4.8	Th m dian traj ctory do s not stay in th middl [2]	25
4.9	Th m dian traj ctory follows incorr ct dir ction [2]	25
4.10	Illustration of th algorithm using homotopy conc pt	26
4.11	Traj ctori s and cross s	26
4.12	Th blu and black traj ctory ar homotopically quival nt [2]	27
4.13	Modifi d switching m thod [2]	27
4.14	Exempl cas s wh r algorithm using homotopy will fail	28
4.15	Th m dian traj ctory do s not pass through part of traj ctori s in th upp r l ft ar a	28
5.1	Exempl of 2D traj ctori s with tim compon nt, from [1]	33
5.2	Exempl of th m dian (l ft) and th m an (right) traj ctory [2]	34
5.3	Robustn ss of th m dian traj ctory	35
5.4	Th s t of 30 traj ctori s, starting at th blu point & nding at th gr n point	36
5.5	A s t of 30 traj ctori s with its possibl m dian traj ctory	36
5.6	Illustration of th simpl id a using switching	38
5.7	Th m dian traj ctory mak a shortcut path [2]	38
5.8	Th m dian traj ctory do s not stay in th middl [2]	39
5.9	Th m dian traj ctory follows incorr ct dir ction [2]	39

5.10	Illustration of the algorithm using homotopy concept	40
5.11	Trajectories and crossings	40
5.12	The blue and black trajectory are homotopically equivalent [2]	41
5.13	Modified switching method [2]	41
5.14	Examples where algorithm using homotopy will fail	42
5.15	The median trajectory does not pass through part of trajectories in the upper left area	42
A.1	Interface of the program	51

DAFTAR TABEL

BAB 1

PENDAHULUAN

1.1 Latar Belakang

Data mining merupakan teknik untuk mengolah *data*, mencari suatu pola, kemudian di valusi untuk mendapatkan *knowledge*. Pola yang dihasilkan oleh *data mining* dapat digunakan untuk mencari suatu hal yang menarik dan unik. Dari pola tersebut butlah, akan didapatkan suatu informasi yang sangat bermakna yang biasa disebut sebagai *knowledge*.

Pada penelitian ini, akan dilakukan analisis data penggunaan KIRI dengan menggunakan *data mining*. Pada penelitian ini, diharapkan dapat ditemukan suatu pola yang menarik dan menghasilkan suatu ide atau gagasan yang baru. Maka dari itu, penelitian ini akan membutuhkan banyak *data* penggunaan KIRI, yang dapat diperoleh dari *log* histori KIRI.

Log tersebut memiliki 5 *field* untuk setiap *entry* sebagai berikut:

- *statisticId*, primary key dari *entry*
- *verifier*, mengidentifikasi sumber dari pencarian ini
- *timestamp*, waktu ketika pengguna KIRI mencari rute angkot
- *type*, tipe log, untuk penelitian ini adalah *FINDROUTE*
- *additionalInfo*, mencatat koordinat awal, koordinat akhir, dan banyak rute yang ditemukan pada pencarian ini

Dengan menggunakan *data log* histori pencarian rute angkot dari KIRI, diharapkan bisa diperoleh pola yang menarik. Pola tersebut memiliki kemungkinan untuk digunakan kembali sebagai informasi tambahan pada perangkat lunak navigasi lainnya seperti KIRI.

1.2 Perumusan Masalah

Dengan mengacu pada uraian diskripsi diatas, maka permasalahan yang dibahas dan diteliti oleh penulis adalah

- Bagaimana cara mengolah pola yang diperoleh dari *data log histori* KIRI agar pola menjadi menarik dan bermakna?
- Bagaimana membuat perangkat lunak untuk melakukan *data mining* pada *data log history*?

1.3 Tujuan dan Manfaat

1.3.1 Tujuan

Penelitian ini bertujuan untuk

- Mencari pola dan informasi yang menarik dari *log history* KIRI
- Perangkat lunak dapat melakukan data mining dari *log history* KIRI

1.3.2 Manfaat

- Agar *data log history* KIRI dapat diolah dan didapat informasi yang menarik dan bermakna
- Mendapatkan sebuah perangkat lunak yang dapat melakukan *data mining* dari *log history* KIRI

1.4 Ruang Lingkup Masalah

Penelitian *data mining* yang diatas akan ditentukan batasan masalah yang diteliti berupa :

- Penelitian ini dibatasi hanya pada permasalahan pada penerapan *data mining* pada *data log* KIRI
- Data log yang merupakan masukan akan dibatasi sebanyak 10000 buah data

1.5 Metode Penelitian dan Teknik Pengumpulan Data

1.5.1 Metode Penelitian

Berikut adalah Metode Penelitian yang digunakan :

- Melakukan studi literatur tentang algoritma-algoritma yang berkaitan dengan permasalahan *data mining*
- Melakukan penelitian *data mining* yang diterapkan pada *log* KIRI
- Merancang dan mengimplementasikan algoritma untuk *data mining*
- Mengimplementasikan pembangkit pola *data mining*
- Melakukan pengujian dan kesimpulan

1.5.2 Teknik Pengumpulan Data

Berikut adalah teknik pengumpulan data yang digunakan :

- Mengunduh dari *data log history* KIRI


1.6 Sistematika Pembahasan

BAB 2

LADASAN TEORI

2.1 Tahap Data Mining

Proses pada *data mining* dapat dibagi menjadi beberapa tahap seperti pada gambar 2.1



Gambar 2.1: Tahap *Data Mining*, Sumber Data Mining Concepts & Techniques

BAB 3

INTRODUCTION


3.1 Motion

A trajectory is the motion path of a moving object. Various moving objects such as animals (probably in a wildlife area), hurricanes, or customers in a shopping area have trajectories that can provide valuable information. For example, trajectory data can be used to predict the movement of the same type of object in similar situation in the future.


During a tracking procedure, the location of the moving objects can be obtained using various location detection devices (e.g.: RFID, GPS devices and mobile phones). Later, this information will be stored to a database using any communication network (usually a wireless network). Because typical trajectory data is obtained during a specific interval, the trajectory data also has a temporal component, besides its spatial component.

The trajectory of a moving object is typically modeled as a sequence of consecutive locations in a multi-dimensional (generally two or three dimensional) Euclidean space [1]. Figure ?? shows an example of two trajectories from two objects which are moving in a 2D plane. With their temporal component, we can see that the trajectories are represented as polylines in a 3D space.

Nowadays, with the rapid development of technologies in mobile computing and wireless communication, many devices with location acquisition capabilities make it possible to obtain huge volumes of trajectory data from various moving objects. Furthermore, analysis of trajectory data is an important task for many applications that contain processing and managing moving objects,



Gambar 3.1: Example of 2D trajectories with time component, from [1]



Gambar 3.2: Example of the median (left) and the mean (right) trajectory [2]

such as animal movements [3, 4, 5, 6], traffic and transport analysis [7], defenses and surveillance areas [8], oceanographic observations¹, weather and natural phenomena [9], popular behavior [10] and sports [11, 12].

Previous work on trajectory data analysis shows that there are several ways to analyze sets of trajectories. For example, similarity between trajectories can be determined [13, 14, 15]. Trajectories can also be clustered into groups with similar characteristics [16, 17, 18, 19]. Other examples are common data mining tasks such as classification [20, 21] and outlier detection [22]. Furthermore, interesting movement patterns such as flocking can also be computed from a set of trajectories [23, 24, 25, 26].

Even though analysis and research on trajectories has expanded in recent years, several basic concepts still need to be studied further. Some of them are the median and the mean trajectory for a collection/set of trajectories. The median and the mean trajectory share some common properties: they should be similar to other trajectories in the set and all parts of them should be located roughly in the middle of the set. However, there are several important differences between them: Firstly, the median trajectory must use only parts of trajectories in the set. It uses only parts of one trajectory or combines parts from many different trajectories. This property might be a disadvantage for the median because some parts of it can be located not in the middle of the set, but in several situations this might be useful.


Figure ?? shows a set of four trajectories which avoid the light-blue obstacle. The possible mean trajectory (the black trajectory in the right-hand side of the figure) will pass through the obstacle because the mean must lie in the middle of all trajectories in the set. In this case, it is clear that the mean trajectory is not suitable for a path of a moving object.

The median trajectory (black trajectory in the left-hand side of the figure) gives a more suitable path because it always uses parts of other trajectories. In parts near the obstacle, the median is not really in the middle of other trajectories.

Secondly, the median trajectory is more robust against outliers than the mean trajectory. Figure ?? shows this situation: we add one trajectory (with purple color) which can be categorized as an outlier compared to other trajectories. While the median trajectory only needs to be modified a little bit, the mean trajectory has to be changed a lot (comparing to the mean trajectory in Figure ??), to keep it in the middle of other trajectories.

In this thesis, we will not cover the mean trajectory and only discuss the median trajectory and algorithms to compute it. We also ignore the temporal component of the trajectory because it is not clear yet how to take it into account when computing the median trajectory. However, some

¹W.S. Kessler, "Argo work in the coral sea." http://faculty.washington.edu/kessler/noumea/gliders/argo_coral_sea.html, March 2010.



Gambar 3.3: Robustness of the median trajectory

research on motion and kinematic data structures contains a temporal component and are related to the median/mean trajectory [27, 28].

For other types of data, a median has a clear definition. The median from a population (or a sample) of integers is the number that separates the population into two halves, where at most half of the population have a smaller value and the other half of the population have a larger value than the median.

For geometric data types, the concept of median also exists. A *center point* of a set P of n points in the plane is a point such that any closed half-plane whose bounding line contains the center point, contains at least $n/3$ points of P [29]. If we force the center point to be one of the points from P , then we obtain a 2-dimensional version of the median, although the “quality” of this median can be bad.

The median trajectory does not have any formal definition yet. Based on several properties that we mention earlier, such as its similarity with other trajectories and lying approximately in the middle of the set, we can determine a possible median, which can be useful in several ways:

3.1.1 Determine the most typical trajectory


The property of the median trajectory makes it suitable to analyze the movement behavior or movement pattern from a group of sample objects because the median somehow represents the whole trajectories in the set/collection. The median trajectory properties, such as the length, the direction or the average speed (if we include the temporal component), could give valuable information.

Example applications include the detection of outliers, which can be done by analyzing the length and the similarity of the shape of the median with other trajectories. Analyzing the average speed together with the shape of the median trajectory might be useful to understand the behavior and the movement pattern of people walking around in an area which has several interesting places to be visited (e.g., a zoo or an amusement park).


3.1.2 Better visualization for a set of trajectories

Visualization of the median trajectory, together with its set of trajectories, might give the viewer a better representation and information about the set of trajectories.

We give an example in Figure ??, where a set has 30 trajectories, which is paths of 30 objects moving from the blue point to the green point. From this figure, we can hardly tell anything



Gambar 3.4: The set of 30 trajectories, starting at the blue point & ending at the green point



Gambar 3.5: A set of 30 trajectories with its possible median trajectory

about the general behavior or the direction of these trajectories. However, we know that several trajectories are different than others and probably can predict what the majority does, but it is still difficult to visualize what the majority of these trajectories do.

In the following figure (Figure ??), we present a possible median trajectory as the red and thick trajectory. From this visualization, it is clear what the majority of trajectories do. Moreover, we can identify what parts of some trajectories are completely different from others.

The visualization of the median trajectory could be useful in some real-life applications: The median trajectory from trajectories of visitors in a national park can be used to select the most common path taken by visitors, which is probably the path that is preferred by future visitors. This information might be useful if we want to create a map that can help those visitors by providing valuable information about a path and direction on that national park in the map, so that hikers can decide which path that hiker will take.

3.1.3 k -medoid clustering


Another application that could use the median trajectory is the k -medoid algorithm, which is used in cluster analysis. The k -medoid clustering algorithm is related to the k -means algorithm, a method to partition/group a set of objects into k different clusters containing similar objects.

In general, each cluster in both algorithms has one object act as a *central object* and other members of the cluster should be similar or having a small distance to this object. The similarity or the distance between objects can be measured using different distance functions (e.g. Euclidean distance, Minkowski distance, etc), depending on the type of objects and the purpose of the clustering.


The main difference between the two algorithms is on the selection of the central object for each cluster. While the k -means simply uses the mean of objects, the k -medoid must use the medoid (an object which has the small standard of dissimilarity/distance to all other objects in the set, but it must be a member of the set). This implies that k -means could create a new object to be the central object whereas the k -medoid must use one of the objects from the set. Thus, the k -medoid algorithm is more suitable for spatial clustering purposes and less sensitive against noise and outliers.

Partitioning Around Medoids (PAM) [30] is a basic k -medoid clustering algorithm. It works as follows:

1. Define a value k and choose k objects as a set of medoids.
2. Assign every object to its closest/similar medoid and after that, compute the cost for the whole configuration.
3. Find another configuration by selecting a pair of medoid and non-medoid objects which have the small standard cost and swapping them temporarily. Then, we assign all other objects to this temporary set of medoids and obtain a new configuration.
4. If the new configuration has smaller cost than the last configuration, then we change the set of medoids and return to step 3.
5. Otherwise, stop and we find the set of medoids with their non-overlapping set of clusters.



Gambar 3.6: Illustration of the simplified algorithm using switching



Gambar 3.7: The median trajectory makes a shortcut [2]

In case we want to cluster a set of trajectories, we can use the median trajectory as a model in this algorithm. However, some changes probably should be made. For example, finding another configuration is not done by simply swapping the median with other trajectory, instead we can choose to swap part of them (with the requirement that both trajectories intersect on another).

3.2 Basic Idea of the Research


Consider a set T of m trajectories. We want to compute the median trajectory of T . In this set, all trajectories have the same start and end points. The median trajectory of T must be built using parts of trajectories in T and somehow must follow what other trajectories in T do, while staying in the “middle” of other trajectories.

3.2.1 The Simple Switching Method


A simplified algorithm to obtain a median trajectory from T is to start from the “middle” trajectory, which is the $(m+1)/2$ -th value of arrangement formed by all trajectories in T (we assume m is odd). At every intersection point, the median trajectory will switch to another trajectory and keep $(m+1)/2$ trajectories above and below the median [31].

Figure ?? shows the result (the median trajectory is the thick-blue trajectory) of this approach for two different types of sets of trajectories, one of them contains trajectories with self-intersection. From the right-hand side of the figure in Figure ??, we can see that this method cannot produce suitable median trajectory because the median does not follow the loop created by the trajectories.

In general, this method will not give a suitable median if a set of trajectories contains self-intersecting trajectories. More examples from [2] show several “incorrect” median trajectories obtained by using this simple switching method. The blue median trajectory in Figure ?? makes a



Gambar 3.8: The median trajectory does not stay in the middle [2]



Gambar 3.9: The median trajectory does not follow the correct sequence of regions [2]

shortcut path to the end point.


The median trajectory in Figure ?? does not stay in the "middle" of other trajectories. Finally, in Figure ??, the median trajectory does not follow the sequence of regions as the other trajectories. The correct sequence of regions is $1 - 2 - 3 - 4 - 5 - 6 - 7 - 8$.

3.2.2 The Algorithm Using the Concept of Homotopy


Another algorithm to compute the median trajectory uses the concept of homotopy (along with the modified simple switching method) [31]. This algorithm works by placing crosses in a relatively large face bounded by segments from a set of trajectories. Figure ?? shows an example where a cross is placed in the relatively large bounded face and two crosses are placed in the outer face.

Based on the location of the crosses, each trajectory in T will be assigned a *signature*. Figure ?? shows the trajectories and two crosses a and b . From these two crosses, four half-lines are created: a^+ and a^- are half-lines above and below a , while b^+ and b^- are half-lines above and below b , respectively.

For all trajectories in T , we give them a signature based on how they intersect with the half-



Gambar 3.10: Illustration of the algorithm using homotopy concept




Gambar 3.11: Trajectories and cross sections

lines) from the cross sections. Note that each trajectory might have a different signature, because it depends on the position of the trajectory with respect to all cross sections in the plane. In Figure ??, the blue trajectory intersects with a^- and b^+ , thus its signature will be a^-b^+ (the order is following the direction of the trajectory). In the same way, the signature of the red trajectory will be the same as the green trajectory: a^-b^- .


Two different trajectories are homotopic if one trajectory can be deformed continuously into the other one without passing through any cross sections, while the start and end points are not moved. Naturally, two trajectories are homotopically equivalent if their signatures are exactly the same. However, two homotopic trajectories do not always have the same signatures. We shown an example in Figure ?? where the blue and the black trajectory are homotopic, but their signatures are different.

To determine whether two trajectories with different signatures are homotopic or not, we perform a *reduce* operation. This *reduce* operation works by eliminating two exact same signs, if their position is next to each other in the signature. In Figure ??, the signature of the blue trajectory is $a^-b^+c^+c^+b^+b^-c^-$. Notice that it has two c^+ that we can eliminate. This will change the signature of the blue trajectory into $a^-b^+b^+b^-c^-$. Once again, we can identify that two b^+ are positioned directly to each other. Performing the *reduce* operation again, we will get the final signature of the blue trajectory: $a^-b^-c^-$. At this point, we cannot apply the *reduce* operation again to this signature, and we say that the signature has been *maximally reduced*. Finally, we conclude that if two trajectories have the same maximally reduced signature, then the two trajectories are homotopically equivalent.

The next step of the algorithm is to create a subset T' of T , and then find the median trajectory by using only parts of trajectories from T' . Creating T' is straightforward, we only need to compute maximally reduced signature for all trajectories and choose a subset with the largest number of



Gambar 3.12: The blue and black trajectory are homotopically equivalent [2]



Gambar 3.13: Modified switching method [2]


trajectories which have the same signature.

To create the median trajectory from T' , we use the modified version of the switching method. This method starts at the first segment of the “middle” trajectory. We find such a segment by determining the outer face of the set of trajectories. The first segment of the “middle” trajectory is the segment where there are $(n-1)/2$ first segments from other trajectories (assuming n is odd) between this segment and the outer face (on each side of the segment).


Then, at every intersection, the median will switch to another trajectory if the continuation along this trajectory (without ever switching again) gives the same signature with the signature of one trajectory from T' . Figure ?? shows an example of this algorithm. After starting with the red trajectory and switching to the green trajectory at the first intersection, the next intersection is with the blue trajectory (at the small blue square) and so far, the signature for the median is a^+ . Although the blue trajectory is going forward, the signature after this intersection while following the blue trajectory (until the end point) is b^-c^- .

If the median switches at this intersection, the final signature will be $a^+b^-c^-$, which is not the signature of this set ($a^+b^-b^+b^-c^-$). At this point, the median does not switch to another trajectory. Instead, it continues to move along the green trajectory. The same situation also occurs when the median (now following the blue trajectory) intersects with the green trajectory (at the small green square).

Although this algorithm can produce a more suitable median trajectory for the situation where the switching method fails, the quality of the homotopic median trajectory depends heavily on the following factors:



Gambar 3.14: Example cases where algorithm using homotopy will fail



Gambar 3.15: The median trajectory does not pass through part of trajectories in the upper left area

- placement of the crosses
- the number of trajectories which have the same signature

Therefore, in several cases the algorithm with the homotopy concept cannot produce suitable median trajectories. We give two examples in Figure ?? : in the left-hand side of figure, the final median trajectory (blue) does not follow other trajectories to the area with a narrow space. This problem arises because that narrow space is not large enough for a cross to be placed.

In the right-hand side of the figure, there are two trajectories homotopically equivalent to each other. Nevertheless, by looking at their position, the median trajectory should be the one in the middle (between the two crosses). However, the algorithm with the homotopy concept does not guarantee that a suitable median trajectory will be found because there is no subset that contains the majority of trajectories in T . Figure ?? shows an example from [2], where the median trajectory does not completely follow what other trajectories do.

3.2.3 The Proposed Solutions

To solve the problems we mention in the previous section, we propose two algorithms to compute the median trajectory from a set of m trajectories (where each trajectory has n segments).

The first algorithm is an $O(1.2108^m + m^5 n^5)$ worst-case time algorithm. This algorithm uses the Fréchet Distance [32] and works similar to the algorithm using the homotopy concept because both of them have to extract the largest subset of similar trajectories and then compute the median trajectory by using parts of trajectories in that subset. By using the Fréchet Distance, we avoid the requirement to find proper places to put crossings, but still can produce suitable median trajectory in the situation where the homotopic algorithm fails (e.g. the example with a narrow space).

The second algorithm uses the combination of the buffer concept and Dijkstra's Shortest Path algorithm. Unlike all previous algorithms, this algorithm does not need to find the largest subset consisting similar trajectories. Using this algorithm, we can compute the median trajectory in $O(h^2 \log h)$ time in the worst-case, where h is the number of all segments in T ($h = O(mn)$).

We implemented the second algorithm in Java programming language and experiments have been done to determine the quality of the resulting median trajectory produced by this algorithm. To provide the test data (sets of trajectories), we use a trajectory generator instead of using real-world data. This allows us to test much larger sets of trajectories.

3.3 Outline of the Thesis

Chapter 2 describes the properties for a set of trajectories and also some properties the median trajectory should have.

The next two chapters explain in detail the two algorithms:

- Chapter 3 starts with a brief introduction of the Fréchet Distance and after that, we will explain how to use it to compute the median trajectory.
- Chapter 4 introduces the method to compute the median trajectory using the combination of the buffer concept and Dijkstra's shortest path algorithm.

We will give an explanation about our implementation, particularly on the implementation of the trajectory generator, in Chapter 5. In Chapter 6, we present the measures used to evaluate the quality of the median trajectory, the experiments set-up and the results from the experiments. This thesis will be concluded in Chapter 7 and 8, where we draw conclusions and discuss some issues and possible directions for further research.

Lorum ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, fames. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut lacinia. Cras viverra metus rhoncus sem. Nulla tincidunt vestibulum urna fringilla ultrices. Phasellus ut lacinia sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, quismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultrices, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci tincidunt nisl hendrerit

mollis. Susp ndiss ut massa. Cras n c ant . P ll nt squ a nulla. Cum sociis natoqu p natibus t magnis dis parturi nt mont s, nasc tur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorp r v stibulum turpis. P ll nt squ cursus luctus mauris.

Nulla mal suada porttitor diam. Don c f lis rat, congru non, volutpat at, tincidunt tristique , libero. Vivamus viverra f rmentum f lis. Don c nonummy p ll nt squ ant . Phasllus adipiscings mp r lit. Proin f rmentum massa ac quam. S d diam turpis, molesti vita , plac rat a, molesti n c, l o. Ma c nas lacinia. Nam ipsum ligula, l if nd at, accumsan n c, suscipit a, ipsum. Morbi blandit ligula f ugiat magna. Nunc l if nd cons quat lor m. S d lacinia nulla vita nim. P ll nt squ tincidunt purus v l magna. Int g r non nim. Pra s nt uismod nunc u purus. Don c bib ndum quam in t llus. Nullam cursus pulvinar l ctus. Don c t mi. Nam vulputat m tus u nim. V stibulum p ll nt squ f lis u massa.

Quisqu ullamcorp r plac rat ipsum. Cras nibh. Morbi v l justo vita lacus tincidunt ultric s. Lor m ipsum dolor sit am t, cons ct tu r adipiscings lit. In hac habitass plat a dictumst. Int g r t mpus convallis augu . Etiam facilisis. Nunc l m ntum f rmentum wisi. A n an plac rat. Ut imp rdi t, nims d grvida sollicitudin, f lis odio plac rat quam, ac pulvinar lit purus g t nim. Nunc vita tortor. Proin t mpus nibh sit am t nisl. Vivamus quis tortor vita risus porta v hricula.

Fusc mauris. V stibulum luctus nibh at l ctus. S d bib ndum, nulla a faucibus s mp r, l o v lit ultrici s t llus, ac v n natis arcu wisi v l nisl. V stibulum diam. Aliquam p ll nt squ , augu quis sagittis posu r , turpis lacus congru quam, in h ndr rit risus ros g t f lis. Ma c nas g t rat in sapi n mattis porttitor. V stibulum porttitor. Nulla facilisi. S d a turpis u lacus commodo facilisis. Morbi fringilla, wisi in dignissim int rdum, justo l ctus sagittis dui, t v hricula libero dui cursus dui. Mauris t mpor ligula s d lacus. Duis cursus nim ut augu . Cras ac magna. Cras nulla. Nulla g stas. Curabitur a l o. Quisqu g stas wisi g t nunc. Nam f ugiat lacus v l st. Curabitur cons ct tu r.

Susp ndiss v l f lis. Ut lor m lor m, int rdum u, tincidunt sit am t, laor t vita , arcu. A n an faucibus p d u ant . Pra s nt nim lit, rutrum at, molesti non, nonummy v l, nisl. Ut l ctus ros, mal suada sit am t, f rmentum u, sodas cursus, magna. Don c u purus. Quisqu v hricula, urna s d ultrici s auctor, p d lor m g stas dui, t convallis lit rat s d nulla. Don c luctus. Curabitur t nunc. Aliquam dolor odio, commodo pr tium, ultrici s non, phar tra in, v lit. Int g r arcu st, nonummy in, f rmentum faucibus, g stas v l, odio.

S d commodo posu r p d . Mauris ut st. Ut quis purus. S d ac odio. S d v hricula h ndr rit s m. Duis non odio. Morbi ut dui. S d accumsan risus g t odio. In hac habitass plat a dictumst. P ll nt squ non lit. Fusc s d justo u urna porta tincidunt. Mauris f lis odio, sollicitudin s d, volutpat a, ornar ac, rat. Morbi quis dolor. Don c p ll nt squ , rat ac sagittis s mp r, nunc dui lobortis purus, quis congru purus m tus ultrici s t llus. Proin t quam. Class apt nt taciti sociosqu ad litora torqu nt p r conubia nostra, p r inc ptos hym na os. Pra s nt sapi n turpis, f rmentum v l, l if nd faucibus, v hricula u, lacus.

P ll nt squ habitant morbi tristique s n ctus t n tus t mal suada fam s ac turpis g stas. Don c odio lit, dictum in, h ndr rit sit am t, g stas s d, l o. Pra s nt f ugiat sapi n aliqu t odio. Int g r vita justo. Aliquam v stibulum fringilla lor m. S d n qu l ctus, cons ct tu r at, cons ct tu r s d, l if nd ac, l ctus. Nulla facilisi. P ll nt squ g t l ctus. Proin u m tus. S d porttitor. In hac habitass plat a dictumst. Susp ndiss u l ctus. Ut mi mi, lacinia sit am t,

plac rat t, mollis vita , dui. S d ant t llus, tristiqu ut, iaculis u, mal suada ac, dui. Mauris nibh l o, facilisis non, adipiscing quis, ultric s a, dui.

Morbi luctus, wisi viv rra faucibus pr tium, nibh st plac rat odio, n c commodo wisi nim g t quam. Quisqu lib ro justo, cons et tu r a, f ugiat vita , porttitor u, lib ro. Susp ndiss s d mauris vita lit sollicitudin mal suada. Ma c nas ultrici s ros sit am t ant . Ut v n natis v lit. Ma c nas s d mi g t dui varius uismod. Phas llus aliqu t volutpat odio. V stibulum ant ipsum primis in faucibus orci luctus t ultric s posu r cubilia Cura ; P ll nt squ sit am t p d ac s m l if nd cons et tu r. Nullam l m ntum, urna v l imp rdi t sodal s, lit ipsum phar tra ligula, ac pr tium ant justo a nulla. Curabitur tristiqu arcu u m tus. V stibulum l ctus. Proin mauris. Proin u nunc u urna h ndr rit faucibus. Aliquam auctor, p d cons quat laor t varius, ros t llus sc l risqu quam, p ll nt squ h ndr rit ipsum dolor s d augu . Nulla n c lacus.

Susp ndiss vita lit. Aliquam arcu n qu , ornar in, ullamcorp r quis, commodo u, lib ro. Fusc sagittis rat at rat tristiqu mollis. Ma c nas sapi n lib ro, mol sti t, lobortis in, sodal s g t, dui. Morbi ultric s rutrum lor m. Nam l m ntum ullamcorp r l o. Morbi dui. Aliquam sagittis. Nunc plac rat. P ll nt squ tristiqu sodal s st. Ma c nas imp rdi t lacinia v lit. Cras non urna. Morbi ros p d , suscipit ac, varius v l, g stas non, ros. Pra s nt mal suada, diam id pr tium l m ntum, ros s m dictum tortor, v l cons et tu r odio s m s d wisi.

S d f ugiat. Cum sociis natoqu p natibus t magnis dis parturi nt mont s, nasc tur ridiculus mus. Ut p ll nt squ augu s d urna. V stibulum diam ros, fringilla t, cons et tu r u, nonummy id, sapi n. Nullam at l ctus. In sagittis ultric s mauris. Curabitur mal suada rat sit am t massa. Fusc blandit. Aliquam rat volutpat. Aliquam uismod. A n an v l l ctus. Nunc imp rdi t justo n c dolor.

Etiam uismod. Fusc facilisis lacinia dui. Susp ndiss pot nti. In mi rat, cursus id, nonummy s d, ullamcorp r g t, sapi n. Pra s nt pr tium, magna in l if nd g stas, p d p d pr tium lor m, quis cons et tu r tortor sapi n facilisis magna. Mauris quis magna varius nulla sc l risqu imp rdi t. Aliquam non quam. Aliquam porttitor quam a lacus. Pra s nt v l arcu ut tortor cursus volutpat. In vita p d quis diam bib ndum plac rat. Fusc l m ntum convallis n qu . S d dolor orci, sc l risqu ac, dapibus n c, ultrici s ut, mi. Duis n c dui quis l o sagittis commodo.

Aliquam l ctus. Vivamus l o. Quisqu ornar t llus ullamcorp r nulla. Mauris porttitor phar tra tortor. S d fringilla justo s d mauris. Mauris t llus. S d non l o. Nullam l m ntum, magna in cursus sodal s, augu st sc l risqu sapi n, v n natis congru nulla arcu t p d . Ut suscipit nim v l sapi n. Don c congru . Ma c nas urna mi, suscipit in, plac rat ut, v stibulum ut, massa. Fusc ultric s nulla t nisl.

Etiam ac l o a risus tristiqu nonummy. Don c dignissim tincidunt nulla. V stibulum rhoncus mol sti odio. S d lobortis, justo t pr tium lobortis, mauris turpis condim ntum augu , n c ultrici s nibh arcu pr tium nim. Nunc purus n qu , plac rat id, imp rdi t s d, p ll nt squ n c, nisl. V stibulum imp rdi t n qu non s m accumsan laor t. In hac habitass plat a dictumst. Etiam condim ntum facilisis lib ro. Susp ndiss in lit quis nisl aliquam dapibus. P ll nt squ auctor sapi n. S d g stas sapi n n c l ctus. P ll nt squ v l dui v l n qu bib ndum viv rra. Aliquam porttitor nisl n c p d . Proin mattis lib ro v l turpis. Don c rutrum mauris t lib ro. Proin uismod porta f lis. Nam lobortis, m tus quis l m ntum commodo, nunc l ctus l m ntum mauris, g t vulputat ligula t llus u n qu . Vivamus u dolor.

BAB 4

INTRODUCTION


4.1 Motion

A trajectory is the motion path of a moving object. Various moving objects such as animals (probably in a wildlife area), hurricanes, or customers in a shopping area have trajectories that can provide valuable information. For example, trajectory data can be used to predict the movement of the same type of object in similar situation in the future.


During a tracking procedure, the location of these moving objects can be obtained using various location detection devices (e.g.: RFID, GPS devices and mobile phones). Later, this information will be stored to a database using any communication network (usually a wireless network). Because typical trajectory data is obtained during a specific interval, the trajectory data also has a temporal component, besides its spatial component.

The trajectory of a moving object is typically modeled as a sequence of consecutive locations in a multi-dimensional (generally two or three dimensional) Euclidean space [1]. Figure ?? shows an example of two trajectories from two objects which are moving in a 2D plane. With their temporal component, we can see that these trajectories are represented as polylines in a 3D space.

Nowadays, with the rapid development of technologies in mobile computing and wireless communication, many devices with location acquisition capabilities make it possible to obtain huge volumes of trajectory data from various moving objects. Furthermore, analysis of trajectory data is an important task for many applications that contain processing and managing moving objects,



Gambar 4.1: Example of 2D trajectories with time component, from [1]



Gambar 4.2: Example of the median (left) and the mean (right) trajectory [2]

such as animal movements [3, 4, 5, 6], traffic and transport analysis [7], defenses and surveillance areas [8], oceanographic observations¹, weather and natural phenomena [9], popular behavior [10] and sports [11, 12].

Previous work on trajectory data analysis shows that there are several ways to analyze sets of trajectories. For example, similarity between trajectories can be determined [13, 14, 15]. Trajectories can also be clustered into groups with similar characteristics [16, 17, 18, 19]. Other examples are common data mining tasks such as classification [20, 21] and outlier detection [22]. Furthermore, interesting movement patterns such as flocking can also be computed from a set of trajectories [23, 24, 25, 26].

Even though analysis and research on trajectories has expanded in recent years, several basic concepts still need to be studied further. Some of them are the median and the mean trajectory for a collection/set of trajectories. The median and the mean trajectory share some common properties: they should be similar to other trajectories in the set and all parts of them should be located roughly in the middle of the set. However, there are several important differences between them: Firstly, the median trajectory must use only parts of trajectories in the set. It uses only parts of one trajectory or combines parts from many different trajectories. This property might be a disadvantage for the median because some parts of it can be located not in the middle of the set, but in several situations this might be useful.


Figure ?? shows a set of four trajectories which avoid the light-blue obstacle. The possible mean trajectory (the black trajectory in the right-hand side of the figure) will pass through the obstacle because the mean must lie in the middle of all trajectories in the set. In this case, it is clear that the mean trajectory is not suitable for a path of a moving object.

The median trajectory (black trajectory in the left-hand side of the figure) gives a more suitable path because it always uses parts of other trajectories. In parts near the obstacle, the median is not really in the middle of other trajectories.

Secondly, the median trajectory is more robust against outliers than the mean trajectory. Figure ?? shows this situation: we add one trajectory (with purple color) which can be categorized as an outlier compared to other trajectories. While the median trajectory only needs to be modified a little bit, the mean trajectory has to be changed a lot (comparing to the mean trajectory in Figure ??), to keep it in the middle of other trajectories.

In this thesis, we will not cover the mean trajectory and only discuss the median trajectory and algorithms to compute it. We also ignore the temporal component of the trajectory because it is not clear yet how to take it into account when computing the median trajectory. However, some

¹W.S. Kessler, "Argo work in the coral sea." http://faculty.washington.edu/kessler/noumea/gliders/argo_coral_sea.html, March 2010.



Gambar 4.3: Robustness of the median trajectory

research on motion and kinematic data structures contains a temporal component and are related to the median/mean trajectory [27, 28].

For other types of data, a median has a clear definition. The median from a population (or a sample) of integers is the number that separates the population into two halves, where at most half of the population have a smaller value and the other half of the population have a larger value than the median.

For geometric data types, the concept of median also exists. A *center point* of a set P of n points in the plane is a point such that any closed half-plane whose bounding line contains the center point, contains at least $n/3$ points of P [29]. If we force the center point to be one of the points from P , then we obtain a 2-dimensional version of the median, although the “quality” of this median can be bad.

The median trajectory does not have any formal definition yet. Based on several properties that we mention earlier, such as its similarity with other trajectories and lying approximately in the middle of the set, we can determine a possible median, which can be useful in several ways:

4.1.1 Determine the most typical trajectory


The property of the median trajectory makes it suitable to analyze the movement behavior or movement pattern from a group of sample objects because the median somehow represents the whole trajectories in the set/collection. The median trajectory properties, such as the length, the direction or the average speed (if we include the temporal component), could give valuable information.

Example applications include the detection of outliers, which can be done by analyzing the length and the similarity of the shape of the median with other trajectories. Analyzing the average speed together with the shape of the median trajectory might be useful to understand the behavior and the movement pattern of people walking around in an area which has several interesting places to be visited (e.g., a zoo or an amusement park).


4.1.2 Better visualization for a set of trajectories

Visualization of the median trajectory, together with its set of trajectories, might give the viewer a better representation and information about the set of trajectories.

We give an example in Figure ??, where a set has 30 trajectories, which is paths of 30 objects moving from the blue point to the green point. From this figure, we can hardly tell anything



Gambar 4.4: The set of 30 trajectories, starting at the blue point & ending at the green point



Gambar 4.5: A set of 30 trajectories with its possible median trajectory

about the general behavior or the direction of these trajectories. However, we know that several trajectories are different than others and probably can predict what the majority do, but it is still difficult to visualize what the majority of these trajectories do.

In the following figure (Figure ??), we present a possible median trajectory as the red and thick trajectory. From this visualization, it is clear what the majority of trajectories do. Moreover, we can identify what parts of some trajectories are completely different from others.

The visualization of the median trajectory could be useful in some real-life applications: The median trajectory from trajectories of visitors in a national park can be used to select the most common path taken by visitors, which is probably the path that is preferred by future visitors. This information might be useful if we want to create a map that can help those visitors by providing valuable information about a path and direction on that national park in the map, so that hikers can decide which path that hiker will take.

4.1.3 k -medoid clustering


Another application that could use the median trajectory is the k -medoid algorithm, which is used in cluster analysis. The k -medoid clustering algorithm is related to the k -means algorithm, a method to partition/group a set of objects into k different clusters containing similar objects.

In general, each cluster in both algorithms has one object act as a *central object* and other members of the cluster should be similar or having a small distance to this object. The similarity or the distance between objects can be measured using different distance functions (e.g. Euclidean distance, Minkowski distance, etc), depending on the type of objects and the purpose of the clustering.


The main difference between the two algorithms is on the selection of the central object for each cluster. While the k -means simply uses the mean of objects, the k -medoid must use the medoid (an object which has the small standard of dissimilarity/distance to all other objects in the set, but it must be a member of the set). This implies that k -means could create a new object to be the central object whereas the k -medoid must use one of the objects from the set. Thus, the k -medoid algorithm is more suitable for spatial clustering purposes and less sensitive against noise and outliers.

Partitioning Around Medoids (PAM) [30] is a basic k -medoid clustering algorithm. It works as follows:

1. Define a value k and choose k objects as a set of medoids.
2. Assign every object to its closest/similar medoid and after that, compute the cost for the whole configuration.
3. Find another configuration by selecting a pair of medoid and non-medoid objects which have the small standard cost and swapping them temporarily. Then, we assign all other objects to this temporary set of medoids and obtain a new configuration.
4. If the new configuration has smaller cost than the last configuration, then we change the set of medoids and return to step 3.
5. Otherwise, stop and we find the set of medoids with their non-overlapping set of clusters.



Gambar 4.6: Illustration of the simplified algorithm using switching



Gambar 4.7: The median trajectory makes a shortcut [2]

In case we want to cluster a set of trajectories, we can use the median trajectory as a model in this algorithm. However, some changes probably should be made. For example, finding another configuration is not done by simply swapping the median with other trajectory, instead we can choose to swap part of them (with the requirement that both trajectories intersect on another).

4.2 Basic Idea of the Research


Consider a set T of m trajectories. We want to compute the median trajectory of T . In this set, all trajectories have the same start and end points. The median trajectory of T must be built using parts of trajectories in T and somehow must follow what other trajectories in T do, while staying in the “middle” of other trajectories.

4.2.1 The Simple Switching Method


A simplified algorithm to obtain a median trajectory from T is to start from the “middle” trajectory, which is the $(m+1)/2$ -th value of arrangement formed by all trajectories in T (we assume m is odd). At every intersection point, the median trajectory will switch to another trajectory and keep $(m+1)/2$ trajectories above and below the median [31].

Figure ?? shows the result (the median trajectory is the thick-blue trajectory) of this approach for two different types of sets of trajectories, one of them contains trajectories with self-intersection. From the right-hand side of the figure in Figure ??, we can see that this method cannot produce suitable median trajectory because the median does not follow the loop created by the trajectories.

In general, this method will not give a suitable median if a set of trajectories contains self-intersecting trajectories. More examples from [2] show several “incorrect” median trajectories obtained by using this simple switching method. The blue median trajectory in Figure ?? makes a



Gambar 4.8: The median trajectory does not stay in the middle [2]



Gambar 4.9: The median trajectory does not follow the correct sequence of regions [2]

shortcut path to the end point.


The median trajectory in Figure ?? does not stay in the "middle" of other trajectories. Finally, in Figure ??, the median trajectory does not follow the sequence of regions as the other trajectories. The correct sequence of regions is $1 - 2 - 3 - 4 - 5 - 6 - 7 - 8$.

4.2.2 The Algorithm Using the Concept of Homotopy


Another algorithm to compute the median trajectory uses the concept of homotopy (along with the modified simple switching method) [31]. This algorithm works by placing crosses in a relatively large face bounded by segments from a set of trajectories. Figure ?? shows an example where a cross is placed in the relatively large bounded face and two crosses are placed in the outer face.

Based on the location of the crosses, each trajectory in T will be assigned a *signature*. Figure ?? shows the trajectories and two crosses a and b . From these two crosses, four half-lines are created: a^+ and a^- are half-lines above and below a , while b^+ and b^- are half-lines above and below b , respectively.

For all trajectories in T , we give them a signature based on how they intersect with the half-



Gambar 4.10: Illustration of the algorithm using homotopy concept




Gambar 4.11: Trajectories and cross points

lines) from the cross points. Note that each trajectory might have a different signature, because it depends on the position of the trajectory with respect to all cross points in the plane. In Figure ??, the blue trajectory intersects with a^- and b^+ , thus its signature will be a^-b^+ (the order is following the direction of the trajectory). In the same way, the signature of the red trajectory will be the same as the green trajectory: a^-b^- .


Two different trajectories are homotopic if one trajectory can be deformed continuously into the other one without passing through any cross points, while the start and end points are not moved. Naturally, two trajectories are homotopically equivalent if their signatures are exactly the same. However, two homotopic trajectories do not always have the same signatures. We shown an example in Figure ?? where the blue and the black trajectory are homotopic, but their signatures are different.

To determine whether the two trajectories with different signatures are homotopic or not, we perform a *reduce* operation. This *reduce* operation works by eliminating two exact same signs, if their position is next to each other in the signature. In Figure ??, the signature of the blue trajectory is $a^-b^+c^+c^+b^+b^-c^-$. Notice that it has two c^+ that we can eliminate. This will change the signature of the blue trajectory into $a^-b^+b^+b^-c^-$. Once again, we can identify that two b^+ are positioned directly to each other. Performing the *reduce* operation again, we will get the final signature of the blue trajectory: $a^-b^-c^-$. At this point, we cannot apply the *reduce* operation again to this signature, and we say that the signature has been *maximally reduced*. Finally, we conclude that if two trajectories have the same maximally reduced signature, then the two trajectories are homotopically equivalent.

The next step of the algorithm is to create a subset T' of T , and then find the median trajectory by using only parts of trajectories from T' . Creating T' is straightforward, we only need to compute maximally reduced signature for all trajectories and choose a subset with the largest number of



Gambar 4.12: The blue and black trajectory are homotopically equivalent [2]



Gambar 4.13: Modified switching method [2]


trajectories which have the same signature.

To create the median trajectory from T' , we use the modified version of the switching method. This method starts at the first segment of the “middle” trajectory. We find such a segment by determining the outer face of the set of trajectories. The first segment of the “middle” trajectory is the segment where there are $(n-1)/2$ first segments from other trajectories (assume n is odd) between this segment and the outer face (on each side of the segment).


Then, at every intersection, the median will switch to another trajectory if the continuation along this trajectory (without ever switching again) gives the same signature with the signature of one trajectory from T' . Figure ?? shows an example of this algorithm. After starting with the red trajectory and switching to the green trajectory at the first intersection, the next intersection is with the blue trajectory (at the small blue square) and so far, the signature for the median is a^+ . Although the blue trajectory is going forward, the signature after this intersection while following the blue trajectory (until the end point) is b^-c^- .

If the median switches at this intersection, the final signature will be $a^+b^-c^-$, which is not the signature of this set ($a^+b^-b^+b^-c^-$). At this point, the median does not switch to another trajectory. Instead, it continues to move along the green trajectory. The same situation also occurs when the median (now following the blue trajectory) intersects with the green trajectory (at the small green square).

Although this algorithm can produce a more suitable median trajectory for the situation where the switching method fails, the quality of the homotopic median trajectory depends heavily on the following factors:



Gambar 4.14: Example cases where algorithm using homotopy will fail



Gambar 4.15: The median trajectory does not pass through part of trajectories in the upper left area

- placement of the crosses
- the number of trajectories which have the same signature

Therefore, in several cases the algorithm with the homotopy concept cannot produce suitable median trajectories. We give two examples in Figure ?? : in the left-hand side of figure, the final median trajectory (blue) does not follow other trajectories to the area with a narrow space. This problem arises because that narrow space is not large enough for a cross to be placed.

In the right-hand side of the figure, there are two trajectories homotopically equivalent to each other. Nevertheless, by looking at their position, the median trajectory should be the one in the middle (between the two crosses). However, the algorithm with the homotopy concept does not guarantee that a suitable median trajectory will be found because there is no subset that contains the majority of trajectories in T . Figure ?? shows an example from [2], where the median trajectory does not completely follow what other trajectories do.

4.2.3 The Proposed Solutions

To solve the problems we mention in the previous section, we propose two algorithms to compute the median trajectory from a set of m trajectories (where each trajectory has n segments).

The first algorithm is an $O(1.2108^m + m^5 n^5)$ worst-case time algorithm. This algorithm uses the Fréchet Distance [32] and works similar to the algorithm using the homotopy concept because both of them have to extract the largest subset of similar trajectories and then compute the median trajectory by using parts of trajectories in that subset. By using the Fréchet Distance, we avoid the requirement to find proper places to put crossings, but still can produce suitable median trajectory in the situation where the homotopic algorithm fails (e.g. the example with a narrow space).

The second algorithm uses the combination of the buffer concept and Dijkstra's Shortest Path algorithm. Unlike all previous algorithms, this algorithm does not need to find the largest subset consisting similar trajectories. Using this algorithm, we can compute the median trajectory in $O(h^2 \log h)$ time in the worst-case, where h is the number of all segments in T ($h = O(mn)$).

We implemented the second algorithm in Java programming language and experiments have been done to determine the quality of the resulting median trajectory produced by this algorithm. To provide the test data (sets of trajectories), we use a trajectory generator instead of using real-world data. This allows us to test much larger sets of trajectories.

4.3 Outline of the Thesis

Chapter 2 describes the properties for a set of trajectories and also some properties the median trajectory should have.

The next two chapters explain in detail the two algorithms:

- Chapter 3 starts with a brief introduction of the Fréchet Distance and after that, we will explain how to use it to compute the median trajectory.
- Chapter 4 introduces the method to compute the median trajectory using the combination of the buffer concept and Dijkstra's shortest path algorithm.

We will give an explanation about our implementation, particularly on the implementation of the trajectory generator, in Chapter 5. In Chapter 6, we present the measures used to evaluate the quality of the median trajectory, the experiments set-up and the results from the experiments. This thesis will be concluded in Chapter 7 and 8, where we draw conclusions and discuss some issues and possible directions for further research.

Lorum ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, fames. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut lacinia. Cras viverra metus rhoncus sem. Nulla tincidunt vestibulum urna fringilla ultricies. Phasellus ut lacinia sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultricies bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, quismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci tincidunt

mollis. Susp ndiss ut massa. Cras n c ant . P ll nt squ a nulla. Cum sociis natoqu p natibus t magnis dis parturi nt mont s, nasc tur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorp r v stibulum turpis. P ll nt squ cursus luctus mauris.

Nulla mal suada porttitor diam. Don c f lis rat, congru non, volutpat at, tincidunt tristique , lib ro. Vivamus viv rra f rm ntum f lis. Don c nonummy p ll nt squ ant . Phas llus adipiscings mp r lit. Proin f rm ntum massa ac quam. S d diam turpis, mol sti vita , plac rat a, mol sti n c, l o. Ma c nas lacinia. Nam ipsum ligula, l if nd at, accumsan n c, suscipit a, ipsum. Morbi blandit ligula f ugiat magna. Nunc l if nd cons quat lor m. S d lacinia nulla vita nim. P ll nt squ tincidunt purus v l magna. Int g r non nim. Pra s nt uismod nunc u purus. Don c bib ndum quam in t llus. Nullam cursus pulvinar l ctus. Don c t mi. Nam vulputat m tus u nim. V stibulum p ll nt squ f lis u massa.

Quisqu ullamcorp r plac rat ipsum. Cras nibh. Morbi v l justo vita lacus tincidunt ultric s. Lor m ipsum dolor sit am t, cons ct tu r adipiscings lit. In hac habitass plat a dictumst. Int g r t mpus convallis augu . Etiam facilisis. Nunc l m ntum f rm ntum wisi. A n an plac rat. Ut imp rdi t, nim s d gravida sollicitudin, f lis odio plac rat quam, ac pulvinar lit purus g t nim. Nunc vita tortor. Proin t mpus nibh sit am t nisl. Vivamus quis tortor vita risus porta v hricula.

Fusc mauris. V stibulum luctus nibh at l ctus. S d bib ndum, nulla a faucibus s mp r, l o v lit ultrici s t llus, ac v n natis arcu wisi v l nisl. V stibulum diam. Aliquam p ll nt squ , augu quis sagittis posu r , turpis lacus congru quam, in h ndr rit risus ros g t f lis. Ma c nas g t rat in sapi n mattis porttitor. V stibulum porttitor. Nulla facilisi. S d a turpis u lacus commodo facilisis. Morbi fringilla, wisi in dignissim int rdum, justo l ctus sagittis dui, t v hricula lib ro dui cursus dui. Mauris t mpor ligula s d lacus. Duis cursus nim ut augu . Cras ac magna. Cras nulla. Nulla g stas. Curabitur a l o. Quisqu g stas wisi g t nunc. Nam f ugiat lacus v l st. Curabitur cons ct tu r.

Susp ndiss v l f lis. Ut lor m lor m, int rdum u, tincidunt sit am t, laor t vita , arcu. A n an faucibus p d u ant . Pra s nt nim lit, rutrum at, mol sti non, nonummy v l, nisl. Ut l ctus ros, mal suada sit am t, f rm ntum u, sodas cursus, magna. Don c u purus. Quisqu v hricula, urna s d ultrici s auctor, p d lor m g stas dui, t convallis lit rat s d nulla. Don c luctus. Curabitur t nunc. Aliquam dolor odio, commodo pr tium, ultrici s non, phar tra in, v lit. Int g r arcu st, nonummy in, f rm ntum faucibus, g stas v l, odio.

S d commodo posu r p d . Mauris ut st. Ut quis purus. S d ac odio. S d v hricula h ndr rit s m. Duis non odio. Morbi ut dui. S d accumsan risus g t odio. In hac habitass plat a dictumst. P ll nt squ non lit. Fusc s d justo u urna porta tincidunt. Mauris f lis odio, sollicitudin s d, volutpat a, ornar ac, rat. Morbi quis dolor. Don c p ll nt squ , rat ac sagittis s mp r, nunc dui lobortis purus, quis congru purus m tus ultrici s t llus. Proin t quam. Class apt nt taciti sociosqu ad litora torqu nt p r conubia nostra, p r inc ptos hym na os. Pra s nt sapi n turpis, f rm ntum v l, l if nd faucibus, v hricula u, lacus.

P ll nt squ habitant morbi tristique s n ctus t n tus t mal suada fam s ac turpis g stas. Don c odio lit, dictum in, h ndr rit sit am t, g stas s d, l o. Pra s nt f ugiat sapi n aliqu t odio. Int g r vita justo. Aliquam v stibulum fringilla lor m. S d n qu l ctus, cons ct tu r at, cons ct tu r s d, l if nd ac, l ctus. Nulla facilisi. P ll nt squ g t l ctus. Proin u m tus. S d porttitor. In hac habitass plat a dictumst. Susp ndiss u l ctus. Ut mi mi, lacinia sit am t,

plac rat t, mollis vita , dui. S d ant t llus, tristiqu ut, iaculis u, mal suada ac, dui. Mauris nibh l o, facilisis non, adipiscing quis, ultric s a, dui.

Morbi luctus, wisi viv rra faucibus pr tium, nibh st plac rat odio, n c commodo wisi nim g t quam. Quisqu lib ro justo, cons et tu r a, f ugiat vita , porttitor u, lib ro. Susp ndiss s d mauris vita lit sollicitudin mal suada. Ma c nas ultrici s ros sit am t ant . Ut v n natis v lit. Ma c nas s d mi g t dui varius uismod. Phas llus aliqu t volutpat odio. V stibulum ant ipsum primis in faucibus orci luctus t ultric s posu r cubilia Cura ; P ll nt squ sit am t p d ac s m l if nd cons et tu r. Nullam l m ntum, urna v l imp rdi t sodal s, lit ipsum phar tra ligula, ac pr tium ant justo a nulla. Curabitur tristiqu arcu u m tus. V stibulum l ctus. Proin mauris. Proin u nunc u urna h ndr rit faucibus. Aliquam auctor, p d cons quat laor t varius, ros t llus sc l risqu quam, p ll nt squ h ndr rit ipsum dolor s d augu . Nulla n c lacus.

Susp ndiss vita lit. Aliquam arcu n qu , ornar in, ullamcorp r quis, commodo u, lib ro. Fusc sagittis rat at rat tristiqu mollis. Ma c nas sapi n lib ro, mol sti t, lobortis in, sodal s g t, dui. Morbi ultric s rutrum lor m. Nam l m ntum ullamcorp r l o. Morbi dui. Aliquam sagittis. Nunc plac rat. P ll nt squ tristiqu sodal s st. Ma c nas imp rdi t lacinia v lit. Cras non urna. Morbi ros p d , suscipit ac, varius v l, g stas non, ros. Pra s nt mal suada, diam id pr tium l m ntum, ros s m dictum tortor, v l cons et tu r odio s m s d wisi.

S d f ugiat. Cum sociis natoqu p natibus t magnis dis parturi nt mont s, nasc tur ridiculus mus. Ut p ll nt squ augu s d urna. V stibulum diam ros, fringilla t, cons et tu r u, nonummy id, sapi n. Nullam at l ctus. In sagittis ultric s mauris. Curabitur mal suada rat sit am t massa. Fusc blandit. Aliquam rat volutpat. Aliquam uismod. A n an v l l ctus. Nunc imp rdi t justo n c dolor.

Etiam uismod. Fusc facilisis lacinia dui. Susp ndiss pot nti. In mi rat, cursus id, nonummy s d, ullamcorp r g t, sapi n. Pra s nt pr tium, magna in l if nd g stas, p d p d pr tium lor m, quis cons et tu r tortor sapi n facilisis magna. Mauris quis magna varius nulla sc l risqu imp rdi t. Aliquam non quam. Aliquam porttitor quam a lacus. Pra s nt v l arcu ut tortor cursus volutpat. In vita p d quis diam bib ndum plac rat. Fusc l m ntum convallis n qu . S d dolor orci, sc l risqu ac, dapibus n c, ultrici s ut, mi. Duis n c dui quis l o sagittis commodo.

Aliquam l ctus. Vivamus l o. Quisqu ornar t llus ullamcorp r nulla. Mauris porttitor phar tra tortor. S d fringilla justo s d mauris. Mauris t llus. S d non l o. Nullam l m ntum, magna in cursus sodal s, augu st sc l risqu sapi n, v n natis congru nulla arcu t p d . Ut suscipit nim v l sapi n. Don c congru . Ma c nas urna mi, suscipit in, plac rat ut, v stibulum ut, massa. Fusc ultric s nulla t nisl.

Etiam ac l o a risus tristiqu nonummy. Don c dignissim tincidunt nulla. V stibulum rhoncus mol sti odio. S d lobortis, justo t pr tium lobortis, mauris turpis condim ntum augu , n c ultrici s nibh arcu pr tium nim. Nunc purus n qu , plac rat id, imp rdi t s d, p ll nt squ n c, nisl. V stibulum imp rdi t n qu non s m accumsan laor t. In hac habitass plat a dictumst. Etiam condim ntum facilisis lib ro. Susp ndiss in lit quis nisl aliquam dapibus. P ll nt squ auctor sapi n. S d g stas sapi n n c l ctus. P ll nt squ v l dui v l n qu bib ndum viv rra. Aliquam porttitor nisl n c p d . Proin mattis lib ro v l turpis. Don c rutrum mauris t lib ro. Proin uismod porta f lis. Nam lobortis, m tus quis l m ntum commodo, nunc l ctus l m ntum mauris, g t vulputat ligula t llus u n qu . Vivamus u dolor.

BAB 5

INTRODUCTION


5.1 Motion

A trajectory is the motion path of a moving object. Various moving objects such as animals (probably in a wildlife area), hurricanes, or customers in a shopping area have trajectories that can provide valuable information. For example, trajectory data can be used to predict the movement of the same type of object in similar situation in the future.


During a tracking procedure, the location of these moving objects can be obtained using various location detection devices (e.g.: RFID, GPS devices and mobile phones). Later, this information will be stored to a database using any communication network (usually a wireless network). Because typical trajectory data is obtained during a specific interval, the trajectory data also has a temporal component, besides its spatial component.

The trajectory of a moving object is typically modeled as a sequence of consecutive locations in a multi-dimensional (generally two or three dimensional) Euclidean space [1]. Figure ?? shows an example of two trajectories from two objects which are moving in a 2D plane. With their temporal component, we can see that these trajectories are represented as polylines in a 3D space.

Nowadays, with the rapid development of technologies in mobile computing and wireless communication, many devices with location acquisition capabilities make it possible to obtain huge volumes of trajectory data from various moving objects. Furthermore, analysis of trajectory data is an important task for many applications that contain processing and managing moving objects,



Gambar 5.1: Example of 2D trajectories with time component, from [1]



Gambar 5.2: Example of the median (left) and the mean (right) trajectory [2]

such as animal movements [3, 4, 5, 6], traffic and transport analysis [7], defenses and surveillance areas [8], oceanographic observations¹, weather and natural phenomena [9], popular behavior [10] and sports [11, 12].

Previous work on trajectory data analysis shows that there are several ways to analyze sets of trajectories. For example, similarity between trajectories can be determined [13, 14, 15]. Trajectories can also be clustered into groups with similar characteristics [16, 17, 18, 19]. Other examples are common data mining tasks such as classification [20, 21] and outlier detection [22]. Furthermore, interesting movement patterns such as flocking can also be computed from a set of trajectories [23, 24, 25, 26].

Even though analysis and research on trajectories has expanded in recent years, several basic concepts still need to be studied further. Some of them are the median and the mean trajectory for a collection/set of trajectories. The median and the mean trajectory share some common properties: they should be similar to other trajectories in the set and all parts of them should be located roughly in the middle of the set. However, there are several important differences between them: Firstly, the median trajectory must use only parts of trajectories in the set. It uses only parts of one trajectory or combines parts from many different trajectories. This property might be a disadvantage for the median because some parts of it can be located not in the middle of the set, but in several situations this might be useful.


Figure ?? shows a set of four trajectories which avoid the light-blue obstacle. The possible mean trajectory (the black trajectory in the right-hand side of the figure) will pass through the obstacle because the mean must lie in the middle of all trajectories in the set. In this case, it is clear that the mean trajectory is not suitable for a path of a moving object.

The median trajectory (black trajectory in the left-hand side of the figure) gives a more suitable path because it always uses parts of other trajectories. In parts near the obstacle, the median is not really in the middle of other trajectories.

Secondly, the median trajectory is more robust against outliers than the mean trajectory. Figure ?? shows this situation: we add one trajectory (with purple color) which can be categorized as an outlier compared to other trajectories. While the median trajectory only needs to be modified a little bit, the mean trajectory has to be changed a lot (comparing to the mean trajectory in Figure ??), to keep it in the middle of other trajectories.

In this thesis, we will not cover the mean trajectory and only discuss the median trajectory and algorithms to compute it. We also ignore the temporal component of the trajectory because it is not clear yet how to take it into account when computing the median trajectory. However, some

¹W.S. Kessler, "Argo work in the coral sea." http://faculty.washington.edu/kessler/noumea/gliders/argo_coral_sea.html, March 2010.



Gambar 5.3: Robustness of the median trajectory

research on motion and kinematic data structures contains a temporal component and are related to the median/mean trajectory [27, 28].

For other types of data, a median has a clear definition. The median from a population (or a sample) of integers is the number that separates the population into two halves, where at most half of the population have a smaller value and the other half of the population have a larger value than the median.

For geometric data types, the concept of median also exists. A *center point* of a set P of n points in the plane is a point such that any closed half-plane whose bounding line contains the center point, contains at least $n/3$ points of P [29]. If we force the center point to be one of the points from P , then we obtain a 2-dimensional version of the median, although the “quality” of this median can be bad.

The median trajectory does not have any formal definition yet. Based on several properties that we mention earlier, such as its similarity with other trajectories and lying approximately in the middle of the set, we can determine a possible median, which can be useful in several ways:

5.1.1 Determine the most typical trajectory


The property of the median trajectory makes it suitable to analyze the movement behavior or movement pattern from a group of sample objects because the median somehow represents the whole trajectories in the set/collection. The median trajectory properties, such as the length, the direction or the average speed (if we include the temporal component), could give valuable information.

Example applications include the detection of outliers, which can be done by analyzing the length and the similarity of the shape of the median with other trajectories. Analyzing the average speed together with the shape of the median trajectory might be useful to understand the behavior and the movement pattern of people walking around in an area which has several interesting places to be visited (e.g., a zoo or an amusement park).


5.1.2 Better visualization for a set of trajectories

Visualization of the median trajectory, together with its set of trajectories, might give the viewer a better representation and information about the set of trajectories.

We give an example in Figure ??, where a set has 30 trajectories, which is paths of 30 objects moving from the blue point to the green point. From this figure, we can hardly tell anything



Gambar 5.4: The set of 30 trajectories, starting at the blue point & ending at the green point



Gambar 5.5: A set of 30 trajectories with its possible median trajectory

about the general behavior or the direction of these trajectories. However, we know that several trajectories are different than others and probably can predict what the majority do, but it is still difficult to visualize what the majority of these trajectories do.

In the following figure (Figure ??), we present a possible median trajectory as the red and thick trajectory. From this visualization, it is clear what the majority of trajectories do. Moreover, we can identify what parts of some trajectories are completely different from others.

The visualization of the median trajectory could be useful in some real-life applications: The median trajectory from trajectories of visitors in a national park can be used to select the most common path taken by visitors, which is probably the path that is preferred by future visitors. This information might be useful if we want to create a map that can help those visitors by providing valuable information about a path and direction on that national park in the map, so that hikers can decide which path that hiker will take.

5.1.3 k -medoid clustering


Another application that could use the median trajectory is the k -medoid algorithm, which is used in cluster analysis. The k -medoid clustering algorithm is related to the k -means algorithm, a method to partition/group a set of objects into k different clusters containing similar objects.

In general, each cluster in both algorithms has one object act as a *central object* and other members of the cluster should be similar or having a small distance to this object. The similarity or the distance between objects can be measured using different distance functions (e.g. Euclidean distance, Minkowski distance, etc), depending on the type of objects and the purpose of the clustering.


The main difference between the two algorithms is on the selection of the central object for each cluster. While the k -means simply uses the mean of objects, the k -medoid must use the medoid (an object which has the small standard of dissimilarity/distance to all other objects in the set, but it must be a member of the set). This implies that k -means could create a new object to be the central object whereas the k -medoid must use one of the objects from the set. Thus, the k -medoid algorithm is more suitable for spatial clustering purposes and less sensitive against noise and outliers.

Partitioning Around Medoids (PAM) [30] is a basic k -medoid clustering algorithm. It works as follows:

1. Define a value k and choose k objects as a set of medoids.
2. Assign every object to its closest/similar medoid and after that, compute the cost for the whole configuration.
3. Find another configuration by selecting a pair of medoid and non-medoid objects which have the small standard cost and swapping them temporarily. Then, we assign all other objects to this temporary set of medoids and obtain a new configuration.
4. If the new configuration has smaller cost than the last configuration, then we change the set of medoids and return to step 3.
5. Otherwise, stop and we find the set of medoids with their non-overlapping set of clusters.



Gambar 5.6: Illustration of the simplified algorithm using switching



Gambar 5.7: The median trajectory makes a shortcut [2]

In case we want to cluster a set of trajectories, we can use the median trajectory as a model in this algorithm. However, some changes probably should be made. For example, finding another configuration is not done by simply swapping the median with other trajectory, instead we can choose to swap part of them (with the requirement that both trajectories intersect on another).

5.2 Basic Idea of the Research


Consider a set T of m trajectories. We want to compute the median trajectory of T . In this set, all trajectories have the same start and end points. The median trajectory of T must be built using parts of trajectories in T and somehow must follow what other trajectories in T do, while staying in the “middle” of other trajectories.

5.2.1 The Simple Switching Method


A simplified algorithm to obtain a median trajectory from T is to start from the “middle” trajectory, which is the $(m+1)/2$ -th value of arrangement formed by all trajectories in T (we assume m is odd). At every intersection point, the median trajectory will switch to another trajectory and keep $(m+1)/2$ trajectories above and below the median [31].

Figure ?? shows the result (the median trajectory is the thick-blue trajectory) of this approach for two different types of sets of trajectories, one of them contains trajectories with self-intersection. From the right-hand side of the figure in Figure ??, we can see that this method cannot produce suitable median trajectory because the median does not follow the loop created by the trajectories.

In general, this method will not give a suitable median if a set of trajectories contains self-intersecting trajectories. More examples from [2] show several “incorrect” median trajectories obtained by using this simple switching method. The blue median trajectory in Figure ?? makes a



Gambar 5.8: The median trajectory does not stay in the middle [2]



Gambar 5.9: The median trajectory does not follow the correct sequence of regions [2]

shortcut path to the end point.


The median trajectory in Figure ?? does not stay in the "middle" of other trajectories. Finally, in Figure ??, the median trajectory does not follow the sequence of regions as the other trajectories. The correct sequence of regions is $1 - 2 - 3 - 4 - 5 - 6 - 7 - 8$.

5.2.2 The Algorithm Using the Concept of Homotopy


Another algorithm to compute the median trajectory uses the concept of homotopy (along with the modified simple switching method) [31]. This algorithm works by placing crosses in a relatively large face bounded by segments from a set of trajectories. Figure ?? shows an example where a cross is placed in the relatively large bounded face and two crosses are placed in the outer face.

Based on the location of the crosses, each trajectory in T will be assigned a *signature*. Figure ?? shows the trajectories and two crosses a and b . From these two crosses, four half-lines are created: a^+ and a^- are half-lines above and below a , while b^+ and b^- are half-lines above and below b , respectively.

For all trajectories in T , we give them a signature based on how they intersect with the half-



Gambar 5.10: Illustration of the algorithm using homotopy concept




Gambar 5.11: Trajectories and cross points

lines) from the cross points. Note that each trajectory might have a different signature, because it depends on the position of the trajectory with respect to all cross points in the plane. In Figure ??, the blue trajectory intersects with a^- and b^+ , thus its signature will be a^-b^+ (the order is following the direction of the trajectory). In the same way, the signature of the red trajectory will be the same as the green trajectory: a^-b^- .


Two different trajectories are homotopic if one trajectory can be deformed continuously into the other one without passing through any cross points, while the start and end points are not moved. Naturally, two trajectories are homotopically equivalent if their signatures are exactly the same. However, two homotopic trajectories do not always have the same signatures. We shown an example in Figure ?? where the blue and the black trajectory are homotopic, but their signatures are different.

To determine whether two trajectories with different signatures are homotopic or not, we perform a *reduce* operation. This *reduce* operation works by eliminating two exact same signs, if their position is next to each other in the signature. In Figure ??, the signature of the blue trajectory is $a^-b^+c^+c^+b^+b^-c^-$. Notice that it has two c^+ that we can eliminate. This will change the signature of the blue trajectory into $a^-b^+b^+b^-c^-$. Once again, we can identify that two b^+ are positioned directly to each other. Performing the *reduce* operation again, we will get the final signature of the blue trajectory: $a^-b^-c^-$. At this point, we cannot apply the *reduce* operation again to this signature, and we say that the signature has been *maximally reduced*. Finally, we conclude that if two trajectories have the same maximally reduced signature, then the two trajectories are homotopically equivalent.

The next step of the algorithm is to create a subset T' of T , and then find the median trajectory by using only parts of trajectories from T' . Creating T' is straightforward, we only need to compute maximally reduced signature for all trajectories and choose a subset with the largest number of



Gambar 5.12: The blue and black trajectory are homotopically equivalent [2]



Gambar 5.13: Modified switching method [2]


trajectories which have the same signature.

To create the median trajectory from T' , we use the modified version of the switching method. This method starts at the first segment of the “middle” trajectory. We find such a segment by determining the outer face of the set of trajectories. The first segment of the “middle” trajectory is the segment where there are $(n-1)/2$ first segments from other trajectories (assume n is odd) between this segment and the outer face (on each side of the segment).


Then, at every intersection, the median will switch to another trajectory if the continuation along this trajectory (without ever switching again) gives the same signature with the signature of one trajectory from T' . Figure ?? shows an example of this algorithm. After starting with the red trajectory and switching to the green trajectory at the first intersection, the next intersection is with the blue trajectory (at the small blue square) and so far, the signature for the median is a^+ . Although the blue trajectory is going forward, the signature after this intersection while following the blue trajectory (until the end point) is b^-c^- .

If the median switches at this intersection, the final signature will be $a^+b^-c^-$, which is not the signature of this set ($a^+b^-b^+b^-c^-$). At this point, the median does not switch to another trajectory. Instead, it continues to move along the green trajectory. The same situation also occurs when the median (now following the blue trajectory) intersects with the green trajectory (at the small green square).

Although this algorithm can produce a more suitable median trajectory for the situation where the switching method fails, the quality of the homotopic median trajectory depends heavily on the following factors:



Gambar 5.14: Example cases where algorithm using homotopy will fail



Gambar 5.15: The median trajectory does not pass through part of trajectories in the upper left area

- placement of the crosses
- the number of trajectories which have the same signature

Therefore, in several cases the algorithm with the homotopy concept cannot produce suitable median trajectories. We give two examples in Figure ?? : in the left-hand side of figure, the final median trajectory (blue) does not follow other trajectories to the area with a narrow space. This problem arises because that narrow space is not large enough for a cross to be placed.

In the right-hand side of the figure, there are two trajectories homotopically equivalent to each other. Nevertheless, by looking at their position, the median trajectory should be the one in the middle (between the two crosses). However, the algorithm with the homotopy concept does not guarantee that a suitable median trajectory will be found because there is no subset that contains the majority of trajectories in T . Figure ?? shows an example from [2], where the median trajectory does not completely follow what other trajectories do.

5.2.3 The Proposed Solutions

To solve the problems we mention in the previous section, we propose two algorithms to compute the median trajectory from a set of m trajectories (where each trajectory has n segments).

The first algorithm is an $O(1.2108^m + m^5 n^5)$ worst-case time algorithm. This algorithm uses the Fréchet Distance [32] and works similar to the algorithm using the homotopy concept because both of them have to extract the largest subset of similar trajectories and then compute the median trajectory by using parts of trajectories in that subset. By using the Fréchet Distance, we avoid the requirement to find proper places to put crossings, but still can produce suitable median trajectory in the situation where the homotopic algorithm fails (e.g. the example with a narrow space).

The second algorithm uses the combination of the buffer concept and Dijkstra's Shortest Path algorithm. Unlike all previous algorithms, this algorithm does not need to find the largest subset consisting similar trajectories. Using this algorithm, we can compute the median trajectory in $O(h^2 \log h)$ time in the worst-case, where h is the number of all segments in T ($h = O(mn)$).

We implemented the second algorithm in Java programming language and experiments have been done to determine the quality of the resulting median trajectory produced by this algorithm. To provide the test data (sets of trajectories), we use a trajectory generator instead of using real-world data. This allows us to test much larger sets of trajectories.

5.3 Outline of the Thesis

Chapter 2 describes the properties for a set of trajectories and also some properties the median trajectory should have.

The next two chapters explain in detail the two algorithms:

- Chapter 3 starts with a brief introduction of the Fréchet Distance and after that, we will explain how to use it to compute the median trajectory.
- Chapter 4 introduces the method to compute the median trajectory using the combination of the buffer concept and Dijkstra's shortest path algorithm.

We will give an explanation about our implementation, particularly on the implementation of the trajectory generator, in Chapter 5. In Chapter 6, we present the measures used to evaluate the quality of the median trajectory, the experiments set-up and the results from the experiments. This thesis will be concluded in Chapter 7 and 8, where we draw conclusions and discuss some issues and possible directions for further research.

Lorum ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, fames. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut lacinia. Cras viverra metus rhoncus sem. Nulla tincidunt vestibulum urna fringilla ultricies. Phasellus ut lacinia sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultricies bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, quismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci tincidunt nisl hendrerit

mollis. Susp ndiss ut massa. Cras n c ant . P ll nt squ a nulla. Cum sociis natoqu p natibus t magnis dis parturi nt mont s, nasc tur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorp r v stibulum turpis. P ll nt squ cursus luctus mauris.

Nulla mal suada porttitor diam. Don c f lis rat, congru non, volutpat at, tincidunt tristique , libero. Vivamus viverra f rmentum f lis. Don c nonummy p ll nt squ ant . Phasllus adipiscings mp r lit. Proin f rmentum massa ac quam. S d diam turpis, molesti vita , plac rat a, molesti n c, l o. Ma c nas lacinia. Nam ipsum ligula, l if nd at, accumsan n c, suscipit a, ipsum. Morbi blandit ligula f ugiat magna. Nunc l if nd cons quat lor m. S d lacinia nulla vita nim. P ll nt squ tincidunt purus v l magna. Int g r non nim. Pra s nt uismod nunc u purus. Don c bib ndum quam in t llus. Nullam cursus pulvinar l ctus. Don c t mi. Nam vulputat m tus u nim. V stibulum p ll nt squ f lis u massa.

Quisque ullamcorp r plac rat ipsum. Cras nibh. Morbi v l justo vita lacus tincidunt ultric s. Lor m ipsum dolor sit am t, cons ct tu r adipiscings lit. In hac habitass plat a dictumst. Int g r t mpus convallis augu . Etiam facilisis. Nunc l m ntum f rmentum wisi. A n an plac rat. Ut imp rdi t, nim s d gravida sollicitudin, f lis odio plac rat quam, ac pulvinar lit purus g t nim. Nunc vita tortor. Proin t mpus nibh sit am t nisl. Vivamus quis tortor vita risus porta v hricula.

Fusc mauris. V stibulum luctus nibh at l ctus. S d bib ndum, nulla a faucibus s mp r, l o v lit ultrici s t llus, ac v n natis arcu wisi v l nisl. V stibulum diam. Aliquam p ll nt squ , augu quis sagittis posu r , turpis lacus congru quam, in h ndr rit risus ros g t f lis. Ma c nas g t rat in sapi n mattis porttitor. V stibulum porttitor. Nulla facilisi. S d a turpis u lacus commodo facilisis. Morbi fringilla, wisi in dignissim int rdum, justo l ctus sagittis dui, t v hricula libero dui cursus dui. Mauris t mpor ligula s d lacus. Duis cursus nim ut augu . Cras ac magna. Cras nulla. Nulla g stas. Curabitur a l o. Quisque g stas wisi g t nunc. Nam f ugiat lacus v l st. Curabitur cons ct tu r.

Susp ndiss v l f lis. Ut lor m lor m, int rdum u, tincidunt sit am t, laor t vita , arcu. A n an faucibus p d u ant . Pra s nt nim lit, rutrum at, molesti non, nonummy v l, nisl. Ut l ctus ros, mal suada sit am t, f rmentum u, sodas cursus, magna. Don c u purus. Quisque v hricula, urna s d ultrici s auctor, p d lor m g stas dui, t convallis lit rat s d nulla. Don c luctus. Curabitur t nunc. Aliquam dolor odio, commodo pr tium, ultrici s non, phar tra in, v lit. Int g r arcu st, nonummy in, f rmentum faucibus, g stas v l, odio.

S d commodo posu r p d . Mauris ut st. Ut quis purus. S d ac odio. S d v hricula h ndr rit s m. Duis non odio. Morbi ut dui. S d accumsan risus g t odio. In hac habitass plat a dictumst. P ll nt squ non lit. Fusc s d justo u urna porta tincidunt. Mauris f lis odio, sollicitudin s d, volutpat a, ornare ac, rat. Morbi quis dolor. Don c p ll nt squ , rat ac sagittis s mp r, nunc dui lobortis purus, quis congru purus m tus ultrici s t llus. Proin t quam. Class apt nt taciti sociosqu ad litora torqu nt p r conubia nostra, p r inc ptos hym na os. Pra s nt sapi n turpis, f rmentum v l, l if nd faucibus, v hricula u, lacus.

P ll nt squ habitant morbi tristique s n ctus t n tus t mal suada fam s ac turpis g stas. Don c odio lit, dictum in, h ndr rit sit am t, g stas s d, l o. Pra s nt f ugiat sapi n aliqu t odio. Int g r vita justo. Aliquam v stibulum fringilla lor m. S d n qu l ctus, cons ct tu r at, cons ct tu r s d, l if nd ac, l ctus. Nulla facilisi. P ll nt squ g t l ctus. Proin u m tus. S d porttitor. In hac habitass plat a dictumst. Susp ndiss u l ctus. Ut mi mi, lacinia sit am t,

plac rat t, mollis vita , dui. S d ant t llus, tristiqu ut, iaculis u, mal suada ac, dui. Mauris nibh l o, facilisis non, adipiscing quis, ultric s a, dui.

Morbi luctus, wisi viv rra faucibus pr tium, nibh st plac rat odio, n c commodo wisi nim g t quam. Quisqu lib ro justo, cons et tu r a, f ugiat vita , porttitor u, lib ro. Susp ndiss s d mauris vita lit sollicitudin mal suada. Ma c nas ultrici s ros sit am t ant . Ut v n natis v lit. Ma c nas s d mi g t dui varius uismod. Phas llus aliqu t volutpat odio. V stibulum ant ipsum primis in faucibus orci luctus t ultric s posu r cubilia Cura ; P ll nt squ sit am t p d ac s m l if nd cons et tu r. Nullam l m ntum, urna v l imp rdi t sodal s, lit ipsum phar tra ligula, ac pr tium ant justo a nulla. Curabitur tristiqu arcu u m tus. V stibulum l ctus. Proin mauris. Proin u nunc u urna h ndr rit faucibus. Aliquam auctor, p d cons quat laor t varius, ros t llus sc l risqu quam, p ll nt squ h ndr rit ipsum dolor s d augu . Nulla n c lacus.

Susp ndiss vita lit. Aliquam arcu n qu , ornar in, ullamcorp r quis, commodo u, lib ro. Fusc sagittis rat at rat tristiqu mollis. Ma c nas sapi n lib ro, mol sti t, lobortis in, sodal s g t, dui. Morbi ultric s rutrum lor m. Nam l m ntum ullamcorp r l o. Morbi dui. Aliquam sagittis. Nunc plac rat. P ll nt squ tristiqu sodal s st. Ma c nas imp rdi t lacinia v lit. Cras non urna. Morbi ros p d , suscipit ac, varius v l, g stas non, ros. Pra s nt mal suada, diam id pr tium l m ntum, ros s m dictum tortor, v l cons et tu r odio s m s d wisi.

S d f ugiat. Cum sociis natoqu p natibus t magnis dis parturi nt mont s, nasc tur ridiculus mus. Ut p ll nt squ augu s d urna. V stibulum diam ros, fringilla t, cons et tu r u, nonummy id, sapi n. Nullam at l ctus. In sagittis ultric s mauris. Curabitur mal suada rat sit am t massa. Fusc blandit. Aliquam rat volutpat. Aliquam uismod. A n an v l l ctus. Nunc imp rdi t justo n c dolor.

Etiam uismod. Fusc facilisis lacinia dui. Susp ndiss pot nti. In mi rat, cursus id, nonummy s d, ullamcorp r g t, sapi n. Pra s nt pr tium, magna in l if nd g stas, p d p d pr tium lor m, quis cons et tu r tortor sapi n facilisis magna. Mauris quis magna varius nulla sc l risqu imp rdi t. Aliquam non quam. Aliquam porttitor quam a lacus. Pra s nt v l arcu ut tortor cursus volutpat. In vita p d quis diam bib ndum plac rat. Fusc l m ntum convallis n qu . S d dolor orci, sc l risqu ac, dapibus n c, ultrici s ut, mi. Duis n c dui quis l o sagittis commodo.

Aliquam l ctus. Vivamus l o. Quisqu ornar t llus ullamcorp r nulla. Mauris porttitor phar tra tortor. S d fringilla justo s d mauris. Mauris t llus. S d non l o. Nullam l m ntum, magna in cursus sodal s, augu st sc l risqu sapi n, v n natis congru nulla arcu t p d . Ut suscipit nim v l sapi n. Don c congru . Ma c nas urna mi, suscipit in, plac rat ut, v stibulum ut, massa. Fusc ultric s nulla t nisl.

Etiam ac l o a risus tristiqu nonummy. Don c dignissim tincidunt nulla. V stibulum rhoncus mol sti odio. S d lobortis, justo t pr tium lobortis, mauris turpis condim ntum augu , n c ultrici s nibh arcu pr tium nim. Nunc purus n qu , plac rat id, imp rdi t s d, p ll nt squ n c, nisl. V stibulum imp rdi t n qu non s m accumsan laor t. In hac habitass plat a dictumst. Etiam condim ntum facilisis lib ro. Susp ndiss in lit quis nisl aliquam dapibus. P ll nt squ auctor sapi n. S d g stas sapi n n c l ctus. P ll nt squ v l dui v l n qu bib ndum viv rra. Aliquam porttitor nisl n c p d . Proin mattis lib ro v l turpis. Don c rutrum mauris t lib ro. Proin uismod porta f lis. Nam lobortis, m tus quis l m ntum commodo, nunc l ctus l m ntum mauris, g t vulputat ligula t llus u n qu . Vivamus u dolor.

DAFTAR REFERENSI

- [1] M. Vlachos, D. Gunopoulos, and G. Kollios, “Discovering similar multidimensional trajectories,” in *ICDE ’02: Proceedings of the 18th International Conference on Data Engineering*, (Washington, DC, USA), p. 673, IEEE Computer Society, 2002.
- [2] Lionov, “Median trajectory.” Experimentation Project Report, 2009.
- [3] C. Calng, S. Dray, and M. Royer-Car nzi, “The concept of animals’ trajectories from a data analysis perspective,” *Ecological Informatics*, vol. 4, no. 1, pp. 34 – 41, 2009.
- [4] V. O. Nams, “Using animal movement paths to measure response to spatial scale,” *Oecologia*, vol. 143, no. 2, pp. 179–188, 2004.
- [5] G. of Yukon, “Porcupine caribou herd satellite collar project,” March 2010.
- [6] D. R. Brillinger, H. K. Preisler, A. A. Agre, J. G. Ki, and B. S. Stewart, “Modeling movements of free-ranging animals,” technical report, University of California, Berkeley, 2001.
- [7] Y. Qu, C. Wang, and X. S. Wang, “Supporting fast search in time series for movement patterns in multiple scales,” in *CIKM ’98: Proceedings of the seventh international conference on Information and knowledge management*, (New York, NY, USA), pp. 251–258, ACM, 1998.
- [8] R. T. Ng, “Detecting outliers from large datasets,” in *Geographic Data Mining and Knowledge Discovery* (H. J. Miller and J. Han, eds.), vol. 1, pp. 218–236, CRC Press, 2001.
- [9] W. E. Hubert, “Hurricane trajectory for casts from a non-divergent, non-gostrophic, barotropic model,” *Monthly Weather Review*, vol. 85, pp. 83–87, March 1957.
- [10] L. M. Fuents and S. A. Vlastin, “Optical tracking in surveillance applications,” in *Proceedings of the 2nd IEEE International workshop on PETS*, 2001.
- [11] D. R. Brillinger, “A potential function approach to the flow of play in soccer,” *J. Quantitative Analysis*, 2007.
- [12] S. Iwasaki and H. Saito, “Tracking soccer play using multiple views,” in *Proceedings of the IAPR Workshop on Machine Vision Applications (MVA02)*, pp. 102–105, 2002.
- [13] M. Vlachos, D. Gunopoulos, and G. Kollios, “Robust similarity measures for mobile object trajectories,” in *DEXA ’02: Proceedings of the 13th International Workshop on Database and Expert Systems Applications*, (Washington, DC, USA), pp. 721–728, IEEE Computer Society, 2002.


-
- [14] B. Lin and J. Su, “Shape based trajectory queries for moving objects,” in *GIS '05: Proceedings of the 13th annual ACM international workshop on Geographic information systems*, (New York, NY, USA), pp. 21–30, ACM, 2005.
 - [15] M. van Kraveland and J. Luo, “The definition and computation of trajectory and subtrajectory similarity,” in *GIS '07: Proceedings of the 15th annual ACM international symposium on Advances in geographic information systems*, (New York, NY, USA), pp. 1–4, ACM, 2007.
 - [16] S. Gaffney and P. Smyth, “Trajectory clustering with mixtures of regression models,” in *KDD '99: Proceedings of the fifth ACM SIGKDD international conference on Knowledge discovery and data mining*, (New York, NY, USA), pp. 63–72, ACM, 1999.
 - [17] J.-G. L, J. Han, and K.-Y. Whang, “Trajectory clustering: a partition-and-group framework,” in *SIGMOD '07: Proceedings of the 2007 ACM SIGMOD international conference on Management of data*, (New York, NY, USA), pp. 593–604, ACM, 2007.
 - [18] M. Nanni and D. Pedreschi, “Time-focused clustering of trajectories of moving objects,” *J. Intell. Inf. Syst.*, vol. 27, no. 3, pp. 267–289, 2006.
 - [19] K. Buchin, M. Buchin, M. van Kraveland, and J. Luo, “Finding long and similar parts of trajectories,” in *GIS '09: Proceedings of the 17th ACM SIGSPATIAL International Conference on Advances in Geographic Information Systems*, (New York, NY, USA), pp. 296–305, ACM, 2009.
 - [20] J.-G. L, J. Han, X. Li, and H. Gonzlez, “Traclust: trajectory classification using hierarchical region-based and trajectory-based clustering,” *Proc. VLDB Endow.*, vol. 1, no. 1, pp. 1081–1094, 2008.
 - [21] J. Garcia, O. Concha, J. Molina, and G.d Migul, “Trajectory classification based on machine learning techniques over tracking data,” in *Information Fusion, 2006 9th International Conference on*, pp. 1–8, 10-13 2006.
 - [22] J.-G. L, J. Han, and X. Li, “Trajectory outlier detection: A partition-and-detect framework,” in *ICDE '08: Proceedings of the 2008 IEEE 24th International Conference on Data Engineering*, (Washington, DC, USA), pp. 140–149, IEEE Computer Society, 2008.
 - [23] J. Gudmundsson and M. van Kraveland, “Computing long-st duration flocks in trajectory data,” in *GIS '06: Proceedings of the 14th annual ACM international symposium on Advances in geographic information systems*, (New York, NY, USA), pp. 35–42, ACM, 2006.
 - [24] K. Buchin, M. Buchin, J. Gudmundsson, M. Lffler, and J. Luo, *Detecting Commuting Patterns by Clustering Subtrajectories*, vol. Volum 5369/2008 of *Lecture Notes in Computer Science*, pp. 644–655. Springer Berlin / Heidelberg, 2008.
 - [25] J. Gudmundsson, M. Kraveland, and B. Spckmann, “Efficient detection of patterns in 2d trajectories of moving points,” *Geoinformatica*, vol. 11, no. 2, pp. 195–215, 2007.

-
- [26] P. Laub and R. S. Purv s, “An approach to valuating motion pattern detection techniques in spatio-temporal data,” *Computers, Environment and Urban Systems*, vol. 30, no. 3, pp. 347–374, 2006.
- [27] P. K. Agarwal, M. Berg, J. Gao, L. J. Guibas, and S. Har-p l d, “Staying in the middle : Exact and approximate medians in \mathbb{R}^1 and \mathbb{R}^2 for moving points, manuscript,” in *In Proc. of the Canadian Conference on Computational Geometry*, pp. 42–45, 2003.
- [28] P. K. Agarwal, L. J. Guibas, J. Hershberger, and E. Vach, “Maintaining the extent of a moving point set,” in *WADS '97: Proceedings of the 5th International Workshop on Algorithms and Data Structures*, (London, UK), pp. 31–44, Springer-Verlag, 1997.
- [29] D. E. N. Amata, M. Bern and S. H. Teng, “Regression depth and center points,” *Discrete and Computational Geometry*, vol. 23, no. 3, pp. 305–323, 2000.
- [30] L. Kaufman and P. J. Rousseeuw, *Finding Groups in Data: An Introduction to Cluster Analysis*. Wiley-Interscience, 2005.
- [31] K. Buchin, M. Buchin, M. van Kreveld, M. Löffler, R. I. Silva, C. Wink, and L. Wiratma, “Median trajectories,” in *Proc. 18th European Symposium on Algorithms*, 2010.
- [32] H. Alt and M. Godau, “Computing the fréchet distance between two polygonal curves,” *International Journal of Computational Geometry & Applications*, vol. 5, pp. 75–91, 1995.

LAMPIRAN A

THE PROGRAM

The interface of the program is shown in Figure A.1:



Gambar A.1: Interface of the program

Step by step to compute the median trajectory using the program:

1. Create several waypoints. Click anywhere in the "Environment" area (1) or create them automatically by setting the parameters for waypoint (2) or clicking the button "Random" (3).

2. The “Variation” tab could be used to create variations by providing values needed to make them(4).
3. Create a set of trajectories by setting all parameters(5) and clicking the button “Create”(6).
4. Compute the median using the homotopic algorithm:
 - Define all parameters needed for the homotopic algorithm(7).
 - Create crosses by clicking the “Create Crosses” button(8).
 - Compute the median by clicking the “Compute Median” button(9).
5. Compute the median using the switching method and the buffer algorithm:
 - Define all parameters needed for the buffer algorithm(10).
 - Create valid edges by clicking the “Create Valid Edges” button(11).
 - Compute the median by clicking the “Compute Median” button(12).
6. Save the resulting median by clicking the “Save Trajectories” button(13). The result is saved in the computer memory and can be seen in “Data” tab(14)
7. The set of trajectories and its median trajectories will appear in the “Environment” area(1) and the user can change what to display by selecting various choices in “Visualize” and “Median” area(15).
8. To save all data to the disk, click the “Save”(16) button. A file dialog menu will appear.
9. To load data from the disk, click the “Load”(17) button.

A large black diagonal bar crosses the slide from the bottom-left to the top-right, obscuring the main content. The bar is solid black and has a consistent width throughout.

```
1
2 import java.util.*;
3 import java.io.*;
4 import java.math.*;
5
6 /**
7  *
8  *
9  */
10
11 // MyFurSet.java
12
13 //id of the set
14 //the furthest edge
15 //the furthest edge to the furthest
```

```
1
2 import java.util.*;
3 import java.io.*;
4 import java.math.*;
5
6 /**
7  *
8  *
9  */
10
11 // MyFurSet.java
12
13 //id of the set
14 //the furthest edge
15 //the furthest edge to the furthest
```

46

LAMPIRAN C

THE SOURCE CODE

Listing C.1: MyFurS t.java

```

1
2 import java.util.ArrayList;
3 import java.util.Collections;
4 import java.util.HashSet;
5
6 /**
7  *
8  * @author Lionov
9  */
10
11 //class for set of vertices close to furthest edge
12 public class MyFurSet {
13     protected int id; //id of the set
14     protected MyEdge FurthestEdge; //the furthest edge
15     protected HashSet<MyVertex> set; //set of vertices close to furthest edge
16     protected ArrayList<ArrayList<Integer>> ordered; //list of all vertices in the set for each
        trajectory
17     protected ArrayList<Integer> closeID; //store the ID of all vertices
18     protected ArrayList<Double> closeDist; //store the distance of all vertices
19     protected int totaltrj; //total trajectories in the set
20
21 /**
22  * Constructor
23  * @param id : id of the set
24  * @param totaltrj : total number of trajectories in the set
25  * @param FurthestEdge : the furthest edge
26  */
27 public MyFurSet(int id,int totaltrj,MyEdge FurthestEdge) {
28     this.id = id;
29     this.totaltrj = totaltrj;
30     this.FurthestEdge = FurthestEdge;
31     set = new HashSet<MyVertex>();
32     ordered = new ArrayList<ArrayList<Integer>>();
33     for (int i=0;i<totaltrj;i++) ordered.add(new ArrayList<Integer>());
34     closeID = new ArrayList<Integer>(totaltrj);
35     closeDist = new ArrayList<Double>(totaltrj);
36     for (int i = 0;i < totaltrj;i++) {
37         closeID.add(-1);
38         closeDist.add(Double.MAX_VALUE);
39     }
40 }
41
42 /**
43  * set a vertex into the set
44  * @param v : vertex to be added to the set
45  */
46 public void add(MyVertex v) {
47     set.add(v);
48 }
49
50 /**
51  * check whether vertex v is a member of the set
52  * @param v : vertex to be checked
53  * @return true if v is a member of the set , false otherwise
54  */
55 public boolean contains(MyVertex v) {
56     return this.set.contains(v);
57 }
58
59 /**
60  * create a column for table Gamma, sorted for each row
61  */
62 public void createColumn() {
63     for (MyVertex v : set) {
64         for (Integer key : v.vertexnum.keySet()) {
65             for (Integer values : v.vertexnum.get(key)) {
66                 ordered.get(key).add(values);
67             }
68         }
69     }
70     for (ArrayList<Integer> al : ordered) Collections.sort(al);
71 }
72

```

73 |
74 | }