



## Husqvarna K 760

*Our best-selling all-round power cutter. Light weight and every detail developed with ergonomics in mind. The outstanding power-to-weight ratio, the reliable start and exceptionally low vibrations (below 2.5 m/s<sup>2</sup>) mean less strain and maximised work time.*



### **LIGHT AND POWERFUL**

A light, compact and powerful machine with superior power-to-weight ratio.



### **EXCEPTIONALLY LOW VIBRATIONS**

Vibrations below 2.5 m/s<sup>2</sup> in the cutter handles for more comfort and longer operation periods.



### **LONG SERVICE INTERVALS**

A strong Poly-V belt combined with our maintenance-free starter DuraStarter™ and efficient filter-system Active Air Filtration™ ensures long service intervals.



### **EASY TO START**

The unique design of the carburettor, cylinder and digital ignition system, together with air purge and decompression valve ensure an easy start.

## Features Husqvarna K 760

- The only time the filter needs to be checked and changed is if you experience lack of power.
- Optimised engine performance through efficient cylinder design, digital ignition system and X-Torq engine technology.
- Easy to change bladeguard position
- High power with less fuel
- Less slurry and low water consumption
- Fits multiple blade bushings
- Our X-Torq® engine produces less emissions, lower fuel consumption and produces more power.
- Blade retarder
- Our dust-sealed starter, where the return spring and the pulley bearing are sealed, gives a virtually maintenance free starter. Developed with a durable starter cord.
- Reduced wear thanks to the drive belt with fully sealed transmission, which keeps out the cutting dust.
- Possible thanks to the reversible cutting arm
- Our two-step filtration system with centrifugal cleaning and a single paper filter increases product life and extends service intervals.
- Reduced vibrations in the cutter handle for more comfort and longer operation periods.
- Our virtually maintenance free starter, thanks to the dust-sealed starter and the durable starter cord.
- EasyStart ensures easier starting by reducing the compression in the cylinder.
- Provides better transmission of power, less frequent re-tensioning and extended service intervals.
- Our built-in automatic filter compensation maintains high power during the air filter life time.

TECHNICAL SPECIFICATION	
Engine	Air-cooled 2 stroke engine
Cylinder displacement	73.5 cm <sup>3</sup> / 4.48 cu.inch
Power output	3.7 kW / 5 hp
Fuel tank volume	0.9 lit / 30.4 fl oz
Idling speed	2700 rpm
Vibrations front handle	2.4/2.4 m/s <sup>2</sup>
Vibrations rear handle	2.4/2.4 m/s <sup>2</sup>
Sound pressure level at operators ear	101 dB(A)
Sound power level, guaranteed (LWA)	115 dB(A)
Blade diameter	300/350 mm / 12/14 "
Max cutting depth	100/125 mm / 4/5 "
Weight (excl. cutting equipment)	9.6/9.8 kg / 21.2/21.6 lbs

