IoT-Enabled Smart Bus Route Monitoring and Revenue Management System

Individual Focus: **Distance-based Revenue Management Component**

W. S. H. R. GUNASEKARA

Registration No: IT22228208

Supervisors:

Sanjeeva Perera | Buddima Attanayaka

A dissertation submitted in partial fulfillment of the requirements for the

B.Sc. (Hons) Degree in Information Technology

Specializing in Information Systems Engineering

Department of Information Technology

Faculty of Computing

Sri Lanka Institute of Information Technology (SLIIT)

Malabe, Sri Lanka

October 2026

Declaration of Originality

I hereby declare that this thesis entitled "From Flat Fees to Verified Kilometres: An IoT-Based Revenue Redistribution Framework for Sustaining Off-Peak Private Bus Services in Sri Lanka" represents my own work, except where due acknowledgment is made in the text. This work has not been previously included in a thesis, dissertation, or report submitted to the Sri Lanka Institute of Information Technology or to any other institution for a degree, diploma, or other qualifications.

_____

_____

W. S. H. R. Gunasekara

Student Registration No: IT22228208

Date: October 07, 2026

Sanjeeva Perera

Supervisor

Department of Information Technology

Abstract

Public bus transit systems in developing regions, particularly in Sri Lanka, face severe operational and financial inefficiencies. Key among these are poor service availability during low-demand off-peak hours (9:00 PM to 5:00 AM), manual timetable administration, unmonitored route deviations, aggressive driver behavior, and flat-rate permit fees that fail to reflect actual operational distance or service delivery. This research presents a unified, IoT-enabled intelligent transportation framework that integrates vehicle telematics, perpendicular map-matching verification, policy-driven time-slot scheduling, distance-based revenue management, and real-time driver behavior monitoring.

The system deploys onboard hardware consisting of an ESP32 microcontroller, a NEO-6M GPS module, and an MPU6050 6-axis Inertial Measurement Unit (IMU) to transmit location and telemetry data over secure MQTT/HTTPS via TLS to Azure IoT Hub. A robust Java Spring Boot backend paired with PostgreSQL/PostGIS executes map-matching algorithms (θ_{route} = 30s deviation corridor), automated time-slot classification (Peak, Normal, Night), standby vehicle assignment (< 3s response latency), distance logging, and automated permit liability and off-peak incentive calculations (R_{permit} and I_{night}). Unlike conventional passenger-focused tracking tools, this framework establishes a closed-loop economic governance mechanism that incentivizes bus operators to maintain essential night services through permit fee credits linked directly to verified distance.

Empirical evaluation demonstrates high performance across all modules: 4.2 m average GPS positioning error, 96.0% halt-detection accuracy, 94.95% route-deviation detection accuracy, 96.2% time-slot classification accuracy, 95.1% policy enforcement accuracy, 0.5 min schedule-delay MAE, 99.1% distance logging agreement, 100% permit fee and incentive calculation correctness, and 92.6% overall driver behavior detection accuracy (Overspeeding 93.3%, Aggressive Braking 91.6%, Aggressive Turning 91.8%, Abnormal Slow Movement 93.6%). The developed web and mobile client applications provide administrators, bus owners, and drivers with operational visibility, aligning physical vehicle operations with policy enforcement, safety monitoring, and economic sustainability.

Keywords: Intelligent Transportation Systems, Internet of Things (IoT), Route Compliance, Map Matching, Distance-Based Permit Revenue, Off-Peak Incentive Mechanism, Driver Telematics, Smart Cities.

Acknowledgements

I would like to express my deepest gratitude to my supervisor, Mr. Sanjeeva Perera, and co-supervisor, Mr. Buddima Attanayaka, for their invaluable guidance, constant encouragement, and insightful feedback throughout the duration of this research. Their expertise in Intelligent Transportation Systems and Information Systems Engineering has been fundamental in shaping this thesis.

I extend my sincere appreciation to the academic and administrative staff of the Department of Information Technology, Faculty of Computing at the Sri Lanka Institute of Information Technology (SLIIT) for providing the necessary infrastructure, hardware testing facilities, and academic environment required to successfully complete this project.

I am also deeply grateful to the System Administrator and officials at the Road Passenger Transport Authority (RPTA) for providing essential operational insights, private bus scheduling datasets, route geometry details, and regulatory policy context. Special thanks are due to my research project team members—Miflal Ahamed, Sachintha H. D. D., and Aththanayaka N. D.—for their collaborative effort and support. Finally, I express my heartfelt gratitude to my family and friends for their unwavering patience and support.

Table of Contents

Table of Contents

Declaration of Originality ii

Abstract iii

Acknowledgements iv

Table of Contents v

List of Tables viii

List of Figures ix

List of Abbreviations x

Chapter 1 Introduction 1

1.1 Chapter Overview 1

1.2 Background 1

1.3 Problem Statement 2

1.4 Research Gap 3

1.5 Research Question or Hypotheses 3

1.6 Research Motivation and Significance 4

1.7 Scope 4

1.8 Overview of the Proposed Solution 5

1.9 Chapter Summary 5

Chapter 2 Objectives 6

2.1 General Objective or Aim 6

2.2 Specific Objectives 6

Chapter 3 Literature Review 7

3.1 Chapter Overview 7

3.2 Domain Concepts and Theories 7

3.3 Existing Studies, Systems or Frameworks 7

3.4 Technical Approaches 9

3.5 Research Gap and Implications for Your Work 11

3.6 Chapter Summary 11

Chapter 4 Methodology 12
4.1 Research Design 12
4.2 Data, Participants or Stakeholders 12
4.3 Requirements and Analysis 13
4.4 Proposed Design 14
4.5 Development or Implementation Procedure 18
4.6 Evaluation Plan 22
4.7 Ethics and Project Management 22
4.8 Chapter Summary 26
Chapter 5 Results 27
5.1 Chapter Overview 27
5.2 Final Data or Evaluation Setting 27
5.3 Developed Artefact or Analytical Outputs 27
5.4 Functional and Nonfunctional Test Results 27
5.5 Evaluation and Comparison 30
5.6 Results by Objective 31
5.7 Chapter Summary 32
Chapter 6 Discussion and Conclusions 33
6.1 Discussion of Key Findings 33
6.2 Comparison with Literature 33
6.3 Contribution and Practical Implications 34
6.4 Limitations 34
6.5 Conclusions 34
6.6 Future Work 35
References 36
Appendices 38
Appendix A: Survey / Interview Instrument & Stakeholder Insights 38
Appendix B: Detailed System Diagrams & Data Flow Specifications 38
Appendix C: Preliminary UI Mockups & Interface Specifications 38

List of Tables

Table 3.2: Technical Comparison of Spatial Map-Matching Algorithmic Paradigms.....9

Table 3.1: Comparative Analysis of Transport Management Approaches 10

Table 4.1: Functional Requirements Specification (FR1 - FR8).....13

Table 4.2: Non-Functional Requirements Specification.....14

Table 4.3: Onboard Hardware Component Specifications & Technical Justification.....16

Table 4.4: Software Frameworks, Cloud Platforms & Database Justification.....17

Table 4.5: Development & Debugging Tools Justification.....17

Table 4.6: Project Budget & Cost Justification (LKR 142,000 Total).....22

Table 4.7: Work Breakdown Structure (WBS) Task Schedule.....24

Table 5.6: Spatial Map-Matching Performance Across Deviation Corridor Thresholds 28

Table 5.1: Real-Time Vehicle Tracking & Map-Matching Performance Evaluation 28

Table 5.2: Policy & Dynamic Time-Slot Management Performance Evaluation 29

Table 5.3: Revenue & Off-Peak Incentive Computation Performance Evaluation.....29

Table 5.4: Driver Behavior Telematics Event Detection Accuracy.....30

Table 5.5: Synthesis of Empirical Results Mapped to Specific Research Objectives.....31

Table 6.1: Comparison of Thesis Outcomes with Prior Literature 33

List of Figures

Figure 1.1: System Concept Overview & Multi-tier Data Pipeline 2

Figure 4.1: High-Level 4-Tier System Architecture Diagram 16

Figure 4.2: Distance-Based Revenue & Off-Peak Incentive Computation Workflow 16

Figure 4.3: Work Breakdown Structure (WBS) Organizational Chart 24

Figure 4.4: Research Project Execution Gantt Chart 26

List of Abbreviations

API	Application Programming Interface
AVL	Automatic Vehicle Location
CEP	Circular Error Probable
DSRM	Design Science Research Methodology
GPS	Global Positioning System
IMU	Inertial Measurement Unit
IoT	Internet of Things
ITS	Intelligent Transportation Systems
JWT	JSON Web Token
MAE	Mean Absolute Error
MQTT	Message Queuing Telemetry Transport
NTC	National Transport Commission
OSRM	Open Source Routing Machine
REST	Representational State Transfer
RPTA	Road Passenger Transport Authority
SLIIT	Sri Lanka Institute of Information Technology
SRS	Software Requirements Specification
TLS	Transport Layer Security
WBS	Work Breakdown Structure

Chapter 1 Introduction

1.1 Chapter Overview

This chapter introduces the research context, problem environment, research gaps, motivation, and scope surrounding private bus operations in Sri Lanka. It outlines the necessity of transitioning public transport regulatory models from traditional flat-rate permit fees to an automated, IoT-enabled, distance-verified revenue redistribution framework. Section 1.2 details the domain background; Section 1.3 presents the formal problem statement; Section 1.4 defines the research gap; Section 1.5 outlines the core research question; Section 1.6 states the research motivation; Section 1.7 establishes the boundary scope; Section 1.8 introduces the proposed solution architecture; and Section 1.9 summarizes the chapter.

1.2 Background

Public bus transportation serves as the primary mode of daily passenger mobility in Sri Lanka, carrying millions of commuters across urban, suburban, and rural road networks. A major share of this public transport capacity is owned and operated by private sector bus operators under route permits administered by regulatory bodies such as the Road Passenger Transport Authority (RPTA) and the National Transport Commission (NTC). Despite its critical social role, the existing private bus operational model suffers from severe structural and economic challenges.

Private bus owners operate primarily for commercial profit. Consequently, during off-peak hours—specifically between 9:00 PM and 5:00 AM—passenger demand drops significantly, leading to diminished farebox collections. Because permit fees charged by regulatory authorities are currently calculated as fixed, flat-rate annual or monthly administrative fees (ranging between LKR 25,000 and LKR 50,000 per vehicle per year) regardless of operated mileage or revenue generated, bus operators lack financial motivation to operate during off-peak windows. Operating a standard 54-seater diesel bus during night hours incurs fixed fuel costs (approximately LKR 370–450 per liter) and crew wages that far exceed the sparse farebox revenue collected from low passenger density. This creates a severe market failure, causing widespread service dropouts at night, stranding shift workers and daily commuters, reducing urban mobility, and undermining public transport reliability.

In Sri Lanka, public bus transport is governed by a dual regulatory system: the National Transport Commission (NTC) oversees inter-provincial long-distance routes, while provincial Road Passenger Transport Authorities (RPTA) administer intra-provincial routes. Both regulatory bodies rely on manual inspection checkpoints, physical logbooks, and fixed timetable scheduling. This

analog oversight mechanism cannot detect unauthorized route deviations, unapproved timetable cancellations, or reckless driving maneuvers in real time. Consequently, compliant bus operators who fulfill unprofitable off-peak schedules receive no financial recognition, while non-compliant operators who bypass low-demand stops face minimal regulatory enforcement.

To eliminate this operational fragmentation, this research introduces an integrated, IoT-enabled Intelligent Transportation System (ITS) framework. By capturing continuous 1 Hz GPS spatial coordinates and 50 Hz IMU acceleration telemetry from low-cost onboard microcontrollers (ESP32), the system dynamically evaluates route adherence, enforces policy time-slots, monitors driver safety, and calculates distance-verified permit liabilities and night incentive credits. This closed-loop approach aligns private operator incentives with public transit regulatory goals.




Figure 1.1: System Concept Overview & Multi-tier Data Pipeline

1.3 Problem Statement

The private bus transport sector in Sri Lanka operates under a flawed governance model characterized by four interrelated problem dimensions:

1. Off-Peak Service Non-Availability: Private operators abandon scheduled bus trips during off-peak hours (9:00 PM to 5:00 AM) due to low passenger demand and high operational fuel costs, leaving citizens without reliable night transport.

2. Equitability and Revenue Rigidity of Permit Fees: The government levies flat-rate route permit fees that do not reflect actual operational distance, passenger turnover, or operating time slots. This creates an unfair burden on compliant operators while limiting state regulatory revenue potential.

3. Untracked Route Deviations and Lack of Operational Visibility: Regulatory bodies cannot continuously detect when buses bypass low-demand stops or deviate from assigned road permits during off-peak hours to cut costs.

4. Unmonitored Driver Behavior: Aggressive maneuvers (overspeeding, harsh deceleration, sharp turns) are not monitored in real time, leading to higher accident risks and poor ride quality.

1.4 Research Gap

Existing literature in Intelligent Transportation Systems (ITS) has addressed vehicle localization, dynamic scheduling, map matching, driver telematics, and transit subsidies as isolated, standalone topics. Automatic Vehicle Location (AVL) systems primarily focus on passenger arrival predictions. Map-matching algorithms translate raw GPS points into road polylines without converting spatial deviations into regulatory actions. Dynamic holding and rescheduling models optimize peak headway regularity without addressing off-peak economic viability. Sensor-based telematics monitor driver safety in isolation without feeding into regulatory compliance or permit fee assessments. Furthermore, public transport subsidy literature discusses performance-based contracts using static indicators rather than continuous, automated telemetry.

The primary research gap lies in the absence of a unified, closed-loop architecture that links continuous physical vehicle telemetry with regulatory policy enforcement and distance-verified financial incentive mechanisms. Prior systems fail to connect real-time spatial movement directly to automated permit fee calculations and night service incentive credits.

1.5 Research Question or Hypotheses

This study addresses the following primary research question:
"How can an integrated IoT-enabled vehicle telematics and map-matching framework be designed to accurately track route compliance, evaluate dynamic scheduling policies, and compute distance-verified permit fees and off-peak financial incentives to sustain night private bus services in Sri Lanka?"

Sub-Questions:

• SQ1: How accurately can low-cost onboard IoT sensors (GPS and 6-axis IMU) transmit continuous spatial telemetry to detect route deviations and halt events?

• SQ2: How effectively can a backend policy engine classify trips into Peak, Normal, and Night operating slots and dynamically handle disruptions like delays and breakdowns?

• SQ3: How can distance-based permit liabilities (R_permit) and off-peak incentive credits (I_night) be computed with 100% mathematical correctness from verified telemetry?

• SQ4: How reliably can tri-axial acceleration and gyro data classify unsafe driving behaviors (overspeeding, aggressive braking, sharp turning, abnormal slow movement)?

1.6 Research Motivation and Significance

Solving these transport operational challenges holds significant social, economic, and regulatory value:

• Social Significance: Ensures 24-hour public transport availability, protecting night shift workers, emergency travelers, and daily commuters while improving road safety through real-time driver monitoring.

• Economic Significance for Operators: Provides financial sustainability for private bus owners operating night services by offsetting operating costs through verified permit fee incentive credits (I_night).

• Regulatory Significance for Government: Gives transport authorities (RPTA/NTC) transparent, objective, digital operational data, replacing manual oversight with automated distance-based permit fee collection and automated route compliance verification.

1.7 Scope

In-Scope:

• Development of onboard IoT field device hardware using ESP32 microcontroller, NEO-6M GPS, and MPU6050 IMU communicating over MQTT/HTTPS via TLS.

• Cloud communication layer utilizing Azure IoT Hub and Spring Boot microservices backend.

• Spatial perpendicular map-matching algorithm with a 30-second deviation corridor threshold (θ_route).

• Automated time-slot policy engine for Peak, Normal, and Night service slots, including standby vehicle assignment (< 3s latency).

• Distance-based permit fee (R_permit) and night incentive credit (I_night) computation engine.

• Driver telematics rule engine for overspeeding, aggressive braking, aggressive turning, and abnormal slow movement.

• Client applications: React Native mobile app for drivers/owners and React.js/Ant Design web portal for transport regulators.

Out-of-Scope: Physical passenger ticketing hardware, automated fare collection (AFC) gates, in-cabin video drowsiness cameras, and multi-modal rail integration.

1.8 Overview of the Proposed Solution

The proposed system establishes a four-tier architecture: (1) IoT Field Layer, (2) Cloud Communication Layer, (3) Backend Processing Layer, and (4) Stakeholder Application Layer. Onboard ESP32 devices transmit location coordinates, speed, and 6-axis IMU acceleration/gyro readings to Azure IoT Hub. The Spring Boot backend processes spatial map matching against digitised route polylines in PostgreSQL/PostGIS, calculates operational mileage per time slot, enforces scheduling policies, computes distance-based permit fees and off-peak incentives, and evaluates driver safety telemetry. Client applications display real-time bus locations, compliance alerts, driver safety scores, and financial summaries to regulators, bus owners, and drivers.

1.9 Chapter Summary

This chapter established the operational challenges of private bus transit in Sri Lanka, highlighting off-peak service collapse, flat permit fee limitations, and unmonitored driver behavior. It defined the research gap, primary research question, scope, motivation, and system architecture overview. Chapter 2 outlines the formal research objectives.

Chapter 2 Objectives

2.1 General Objective or Aim

The overall aim of this research is to design, implement, and evaluate an integrated IoT-enabled bus route monitoring, policy-driven dynamic scheduling, driver telematics, and distance-based revenue management system that incentivizes private bus operators to maintain essential off-peak public transport services in Sri Lanka.

2.2 Specific Objectives

To achieve the general research aim, the following specific objectives were executed:

1. Specific Objective 1 (IoT Telematics & Route Verification): To design and deploy an onboard IoT field device (ESP32, NEO-6M GPS, MPU6050 IMU) and implement a perpendicular map-matching algorithm to achieve real-time bus tracking, halt detection accuracy ≥ 95%, and route deviation detection accuracy ≥ 94% along authorized route corridors.

2. Specific Objective 2 (Policy & Dynamic Scheduling Engine): To develop a cloud-based policy engine capable of classifying bus operations into Peak, Normal, and Night time slots with ≥ 95% classification accuracy, calculating schedule delay MAE within 1.0 minute, and automating standby vehicle assignment in < 5 seconds during breakdown disruptions.

3. Specific Objective 3 (Distance-Based Revenue & Off-Peak Incentive Engine): To formulate and implement a distance-based permit fee liability model (R_{permit}) and off-peak night incentive credit mechanism (I_{night}) achieving 100% mathematical correctness across validation cases and ≥ 99% distance logging agreement with reference records.

4. Specific Objective 4 (Driver Safety Monitoring & Telematics): To implement an IMU-based driver behavior monitoring engine that detects overspeeding, aggressive braking, aggressive turning, and abnormal slow movement events with an overall detection accuracy ≥ 90%.

5. Specific Objective 5 (System Integration & Stakeholder Dashboards): To integrate all system components into a secure cloud architecture (Azure IoT Hub, Spring Boot, PostgreSQL/PostGIS) and deliver responsive mobile (React Native) and web (React.js/Ant Design) client interfaces for drivers, bus owners, and transport regulators.

Chapter 3 Literature Review

3.1 Chapter Overview

This chapter provides a detailed review of literature across five core domain areas: (1) IoT-based vehicle tracking and AVL architectures, (2) map-matching algorithms for route compliance, (3) dynamic bus scheduling and real-time operational control, (4) sensor-based driver behavior monitoring, and (5) performance-based transit revenue and subsidy models. Section 3.5 synthesizes the research gap and outlines implications for the proposed system design.

3.2 Domain Concepts and Theories

Intelligent Transportation Systems (ITS) rely on spatial-temporal data streams generated by satellite positioning, inertial sensors, wireless telemetry networks, and geographic information systems (GIS). Automatic Vehicle Location (AVL) systems capture raw latitude, longitude, timestamp, and instantaneous velocity. However, raw positioning signals contain satellite ephemeris errors, atmospheric distortions, and multipath interference, particularly in urban canyons. Interpreting raw GPS points requires map-matching techniques to snap coordinate streams to digitized road network polylines.

From an economic regulatory perspective, public transport service provision involves principal-agent dynamics between government transport authorities (principals) and private bus operators (agents). When operators face low off-peak demand, flat-rate permit fees encourage profit-maximizing operators to cancel trips. Economic theory suggests replacing fixed permit fees with dynamic, distance-verified service contracts that penalize non-compliance while providing targeted financial credits for operating during low-demand off-peak hours.

3.3 Existing Studies, Systems or Frameworks

3.3.1 IoT-Based Bus Monitoring and Real-Time Vehicle Tracking

Early AVL research established satellite-based tracking as a foundation for fleet management and passenger information systems **[1]**, **[2]**. Hounsell et al. **[3]** demonstrated that continuous bus telemetry improves operational oversight while accumulating large spatial-temporal datasets for network planning. Modern IoT architectures expand traditional AVL by connecting low-cost microcontrollers, edge sensors, and cloud message brokers **[1]**. However, existing commercial tracking deployments in developing nations remain strictly passenger-centric—displaying bus locations on mobile maps without evaluating regulatory permit compliance, route adherence, or financial permit accounting.

3.3.2 Map Matching and Route Compliance Verification

Raw GPS trajectories cannot be directly compared against permit routes due to positioning noise. Quddus et al. **[4]** classified map-matching algorithms into geometric, topological, probabilistic, and Kalman filtering approaches. Geometric point-to-segment algorithms offer low computational overhead, making them suitable for real-time edge and server processing. Zhou et al. **[5]** utilized historical bus trajectory fitting to reconstruct route sequences. While map matching successfully snaps coordinates to road links, prior studies treat map matching purely as a visualization tool rather than an automated evidence-generation tool for enforcing permit route compliance.

3.3.3 Dynamic Scheduling and Real-Time Bus Operations

Fixed timetables struggle to handle urban traffic congestion and operational disruptions. Fu and Yang **[6]** investigated bus-holding strategies to maintain headway regularity. Berrebi et al. **[7]** demonstrated that real-time headway predictions improve service stability compared to static schedules. Gkiotsalitis **[8]** reviewed real-time control measures including holding, stop-skipping, and emergency vehicle dispatch. Existing dynamic scheduling literature focuses almost exclusively on peak-period headway stabilization, ignoring off-peak service maintenance and automated policy enforcement.

3.3.4 Sensor-Based Driver Behavior Telematics

Driver monitoring telematics utilize 3-axis accelerometers and gyroscopes to identify unsafe driving events. Ferreira et al. **[9]** and Vlahogianni and Barmpounakis **[10]** established that harsh deceleration, sharp cornering, and rapid acceleration can be accurately classified using inertial sensor thresholds. Sarteshnizi and Khomeini **[11]** and Al-Hussein et al. **[12]** evaluated IMU sampling rates and classifier configurations for driver profiling. However, driver telematics systems are universally deployed as standalone safety products, failing to connect driver behavior scores to operator permit renewals or regulatory evaluations.

3.3.5 Performance-Based Revenue and Incentive Mechanisms

Hensher and Mulley **[13]** pioneered performance-based contracts in public bus transport, demonstrating that linking operator payments to service quality targets improves compliance. Ling et al. **[14]** and Luo et al. **[15]** formulated incentive subsidy models based on route service levels. However, these frameworks depend on self-reported operator logs or periodic manual surveys rather than continuous, automated telemetry validation.

3.4 Technical Approaches

Designing an IoT-enabled transport governance platform requires evaluating three key technical domains: (1) spatial map-matching algorithms, (2) edge computing versus cloud processing architectures, and (3) multi-sensor data fusion techniques.

3.4.1 Comparative Evaluation of Map-Matching Algorithms

Raw satellite positioning coordinates contain inherent spatial errors caused by satellite clock bias, ionospheric delays, and multipath reflections in dense urban corridors. Map matching resolves these positioning errors by snapping raw GPS latitude/longitude points onto digitised road network polylines. Three primary algorithmic paradigms were evaluated for real-time bus tracking:

1. Point-to-Point Geometric Matching: Compares raw GPS points directly to the nearest vertex in the road database. While computationally fast (O(1) complexity per point), it suffers from severe topological mismatches at complex urban intersections and parallel service roads.

2. Hidden Markov Model (HMM) Matching: Models vehicle trajectories using emission probabilities (distance to road segment) and transition probabilities (routing feasibility between segments). HMM achieves high spatial accuracy (>98%) but requires substantial computational memory and matrix multiplication overhead, introducing latencies of 1.5–3.0 seconds per batch.

3. Perpendicular Point-to-Line Corridor Matching: Calculates the perpendicular distance (d_{perp}) from raw GPS coordinates to the candidate road segment polyline within a spatial corridor threshold ($\theta_{route} = 30s$). This geometric-topological approach achieves high accuracy (94.95% deviation detection) while executing in under 15 milliseconds per coordinate batch, making it ideal for continuous backend server execution.

Table 3.2: Technical Comparison of Spatial Map-Matching Algorithmic Paradigms

Algorithm Type	Spatial Accuracy	Computational Complexity	Server Latency (ms)	Suitability for Real-Time Governance
Point-to-Point Geometric	Low (72.4%)	O(N) per point	< 5 ms	Unsuitable due to high false deviation alerts at intersections.

Algorithm Type	Spatial Accuracy	Computational Complexity	Server Latency (ms)	Suitability for Real-Time Governance
Hidden Markov Model (HMM)	Very High (98.2%)	O(N * M^2) Viterbi decoding	1,500 - 3,000 ms	Suitable for offline historical analysis; introduces real-time latency.
Perpendicular Point-to-Line	High (94.95%)	O(N * M) spatial bounding	< 15 ms	Optimal balance of real-time responsiveness and high precision.

3.4.2 Edge Computing vs. Cloud Telemetry Pipeline

The architectural design balances edge microcontroller processing on the ESP32 device with cloud processing in Azure IoT Hub and Spring Boot. Sampling 6-axis IMU acceleration data at 50 Hz generates 300 data points per second. Transmitting raw 50 Hz IMU streams directly over 4G cellular networks would saturate bandwidth and incur excessive cloud data transfer costs. Therefore, the onboard ESP32 microcontroller executes edge window filtering (sliding window = 1.0s, 50 samples) to classify driving events (overspeeding, harsh braking, sharp turning, abnormal slow movement) locally, transmitting lightweight JSON alert summaries over MQTT/TLS only when event thresholds are breached. Concurrently, 1 Hz GPS positioning coordinates are streamed continuously to maintain live cloud GIS map tracking.

Table 3.1: Comparative Analysis of Transport Management Approaches

Dimension	Traditional AVL Systems	Standalone Telematics	Proposed Integrated IoT Framework
Primary Focus	Passenger arrival ETA	Driver safety scoring	Closed-loop regulatory & financial governance
Route Adherence	Visual map display only	Not monitored	Automated perpendicular map matching & alerts

Dimension	Traditional AVL Systems	Standalone Telematics	Proposed Integrated IoT Framework
Scheduling Model	Static timetables	None	Policy-driven time-slot classification & standby dispatch
Permit Revenue	Flat administrative fee	None	Verified distance-based fee (R_permit) & night credit (I_night)
Driver Monitoring	Not integrated	Isolated event alerts	Real-time IMU threshold evaluation linked to authority logs

3.5 Research Gap and Implications for Your Work

While individual ITS building blocks—GPS localization, map matching, dynamic control, IMU telematics, and transit subsidies—are mature, they operate in silos. Existing systems do not feed verified spatial-temporal movement into dynamic policy enforcement and permit fee accounting. The proposed research addresses this exact gap by creating a unified framework where a single stream of verified vehicle telemetry simultaneously powers route compliance verification, dynamic time-slot scheduling, distance-based permit fee calculation, off-peak incentive credits, and driver safety telematics.

3.6 Chapter Summary

This chapter reviewed relevant literature across transport telematics, map matching, dynamic scheduling, driver monitoring, and transit economic incentives. It highlighted the research gap and justified the integrated design. Chapter 4 presents the research methodology.

Chapter 4 Methodology

4.1 Research Design

This research adopts the Design Science Research Methodology (DSRM) framework **[17]**, which is specifically tailored for information systems engineering. The methodology follows six iterative phases: (1) Problem Identification and Motivation, (2) Definition of Solution Objectives, (3) Design and Development of the Artefact, (4) Demonstration, (5) Empirical Evaluation, and (6) Communication. The developed artefact consists of an integrated hardware-software platform comprising an onboard IoT field device, cloud telemetry pipeline, spatial map-matching engine, policy time-slot engine, revenue and incentive calculator, driver telematics module, and stakeholder web/mobile applications.

4.2 Data, Participants or Stakeholders

4.2.1 Stakeholder Identification

The system interacts with four primary stakeholder groups:

• Government Transport Authorities (RPTA / NTC): Require real-time fleet visibility, automated route compliance monitoring, objective distance-based permit fee collection, and off-peak service enforcement.

• Private Bus Owners: Seek transparent, distance-verified permit fee calculations, profit optimization, and incentive credits for maintaining off-peak night services.

• Bus Drivers: Require clear schedule updates, instant route deviation alerts, standby dispatch notifications, and real-time safety feedback.

• Passengers / Commuters: Benefit from reliable 24-hour public transport availability, improved schedule adherence, and safer driving standards.

4.2.2 Data Collection and Validation Strategy

Data was collected from multiple empirical sources:

• Field Sensor Data: Recorded using prototype IoT field devices installed on test vehicles operating along selected Sri Lankan bus routes. Collected data includes raw GPS coordinates, speed, timestamp, 3-axis acceleration, and 3-axis angular velocity.

• Controlled Test Scenarios: Controlled driving maneuvers (overspeeding, harsh braking, aggressive cornering, abnormal slow movement, route deviations) performed to establish ground-truth validation datasets.

• Official Regulatory Data: Bus route geometries, digitized road polylines, timetable intervals, and permit fee structures provided by the System Administrator at the Road Passenger Transport Authority (RPTA) **[16]**.

• Stakeholder Feedback: Structured interviews and questionnaires administered to transport officers, bus owners, and drivers to evaluate operational workflows and usability.

4.3 Requirements and Analysis

4.3.1 Functional Requirements Specification

Table 4.1: Functional Requirements Specification (FR1 - FR8)

Req ID	Requirement Title	Input Data	System Processing	Output Result
FR1	User Authentication	Credentials / Permit No	Validate, encrypt bcrypt, issue JWT token	Login confirmation or error message
FR2	Real-Time Bus Location	GPS telemetry via MQTT	Ingest Azure IoT Hub, update PostGIS database	Live bus markers on GIS map portal
FR3	Perpendicular Map Matching	GPS stream & route polyline	Calculate d_⊥, monitor 30s corridor threshold	Route compliance status & alert log
FR4	Trip Start & End Monitoring	Driver app trigger / geofence	Detect trip initiation/completion, log distance	Trip status updated on dashboard
FR5	Time-Slot Policy Engine	Trip start timestamp t_start	Classify Peak/Normal/Night, standby dispatch	Slot assignment & standby assignment
FR6	Distance Revenue & Incentive	Verified distance D_k & rates	Compute R_permit liability & deduct I_night	Itemized financial billing statements
FR7	Driver Behavior Telematics	6-axis IMU acceleration/gyro	Evaluate overspeed/braking/turning thresholds	Real-time driver app alert & log

Req ID	Requirement Title	Input Data	System Processing	Output Result
FR8	Admin Web Dashboard	Admin credentials & params	Authenticate admin, aggregate GIS analytics	Interactive analytics portal & reports

4.3.2 Non-Functional Requirements Specification

Table 4.2: Non-Functional Requirements Specification

Category	Specification Detail
System Reliability	99.0% server uptime; auto device reconnect on cellular recovery; local ESP32 flash buffer
Data Security	End-to-end TLS encryption; Spring Security with JWT tokens; bcrypt password hashing; data anonymization
System Performance	Telemetry ingestion < 500ms; map matching < 100ms per batch; UI dashboard render < 2s
Usability & Accessibility	Intuitive React Native mobile app with high-contrast UI; Ant Design web portal; target SUS > 68
Scalability	Stateless Spring Boot microservices architecture supporting up to 5,000 active devices

4.4 Proposed Design

4.4.1 High-Level System Architecture

The proposed framework adopts a 4-tier architectural layout: IoT Field Layer, Cloud Communication Layer, Backend Processing Layer, and Application Layer.

Figure 4.1: High-Level 4-Tier System Architecture Diagram




Figure 4.1: High-Level 4-Tier System Architecture Diagram

4.4.2 Revenue & Off-Peak Incentive Computation Workflow




Figure 4.2: Distance-Based Revenue & Off-Peak Incentive Computation Workflow

4.4.3 Hardware and Software Specifications

Table 4.3: Onboard Hardware Component Specifications & Technical Justification

Component	Technical Specification	Engineering Justification
ESP32 Microcontroller	Dual-core 240 MHz, 520 KB SRAM, Wi-Fi/BT	High-speed dual-core processing permits parallel sensor sampling and MQTT cloud transmission.
NEO-6M GPS Module	50-channel receiver, 2.5 m CEP accuracy, 1 Hz	Provides reliable spatial tracking coordinates (latitude, longitude, speed) for map matching.
MPU6050 6-Axis IMU	3-axis accelerometer (±8g) + 3-axis gyro (±2000°/s)	Captures tri-axial linear acceleration and angular velocity for driver behavior classification.

Component	Technical Specification	Engineering Justification
4G LTE / GSM Module	SIM800L / A7670C cellular modem over UART	Ensures continuous telemetry transmission over cellular networks across urban and suburban bus routes.

Table 4.4: Software Frameworks, Cloud Platforms & Database Justification

Software Component	Technology Selected	Technical Justification
Cloud Message Broker	Azure IoT Hub	Handles bi-directional MQTT/HTTPS communication, TLS security, and cloud scalability.
Backend Framework	Java Spring Boot (v3.x)	Provides robust microservices backend, REST API design, dependency injection, and high throughput.
Spatial Database	PostgreSQL with PostGIS	Delivers industrial-grade spatial indexing (R-Tree), spatial distance queries, and transaction safety.
Mobile Application	React Native	Cross-platform framework allowing single codebase deployment for Android/iOS driver and owner apps.
Web Admin Portal	React.js with Ant Design	Delivers interactive dashboards, live GIS map integration (Leaflet/Mapbox), and analytics charts.

Table 4.5: Development & Debugging Tools Justification

Tool Name	Primary Purpose	Technical Justification

Tool Name	Primary Purpose	Technical Justification
Git / GitHub	Version control & collaboration	Tracks code revisions across firmware, backend, and frontend repositories with branch protection.
Postman	API endpoint testing	Verifies REST API request/response payloads, authentication headers, and mock server endpoints.
Arduino IDE / Serial Monitor	Firmware debugging	Used to inspect real-time I2C/UART sensor outputs from ESP32, GPS NMEA sentences, and IMU calibration.
Google Maps Roads / OSRM	Road network snapping	Provides digitized road geometry polylines for validating map-matching algorithm outputs.

4.5 Development or Implementation Procedure

The implementation of the proposed framework followed a rigorous four-stage engineering procedure: (1) Onboard IoT Hardware Firmware Engineering, (2) Spatial Database & PostGIS Polyline Mapping, (3) Cloud Microservices & Policy Rules Implementation, and (4) Client Dashboards Integration.

4.5.1 Detailed Mathematical Model Formulations

The revenue redistribution engine replaces rigid flat-rate permit fees with distance-verified permit liabilities (R_permit) and off-peak night incentive credits (I_night). The mathematical formulations are derived below:

1. Distance-Based Permit Fee Liability (R_permit):

The total permit fee liability levied on a bus operator for a specified billing period (e.g. monthly) is calculated as the sum of distance liabilities across all verified operational trips:

$$R_{permit} = \Sigma \left[D_{actual,k} * C_{base} * \alpha_{slot} * (1 + \mu_{dev} * I_{dev,k}) \right]$$

Where:

• D_actual,k is the PostGIS-verified operational distance (in kilometers) for trip k, calculated by snapping 1 Hz GPS telemetry to the authorized route polyline.

• C_base is the baseline permit tariff rate per kilometer (e.g. LKR 15.00 / km).

• α_slot is the operational time-slot multiplier: Peak Hours (07:00-09:00, 16:30-18:30) α = 1.2; Normal Hours α = 1.0; Night Hours (21:00-05:00) α = 0.5 (representing a 50% permit liability discount).

• μ_dev is the route deviation penalty multiplier (set to 0.25).

• I_dev,k is a binary indicator flag set to 1 if unapproved route deviation distance exceeds the 200m corridor threshold, and 0 otherwise.

2. Off-Peak Night Service Incentive Credit (I_night):

To compensate private bus operators for operating during low-demand night hours, the policy engine computes an off-peak night incentive credit credited directly against the operator's permit liability account:

$I_{night} = \Sigma [D_{night,m} * C_{incentive} * \eta_{compliance,m}]$

Where:

• D_night,m is the verified operational distance (in kilometers) completed during the designated night service window (21:00 to 05:00).

• C_incentive is the statutory night credit rate per kilometer (e.g. LKR 25.00 / km), funded through the high-density peak-hour permit surcharge revenue pool.

• η_compliance,m is the trip route adherence ratio (D_route / D_total). If $\eta_{compliance} < 0.95$ (meaning the bus bypassed > 5% of its authorized route), the incentive credit for that trip is forfeited ($\eta_{compliance} = 0$).

4.5.2 PostGIS Spatial Polyline Map-Matching Implementation

To calculate D_actual,k and detect unauthorized route deviations in real time, the PostgreSQL/PostGIS spatial database executes spatial SQL queries snapping incoming telemetry points (p_lat, p_lon) onto digitized route geometry polylines (geom_polyline). The spatial execution pipeline operates as follows:

```
-- Step 1: Snap raw GPS point to authorized route polyline and measure perpendicular offset distance
SELECT route_id, ST_Distance(geom_polyline::geography,
ST_SetSRID(ST_MakePoint(longitude, latitude), 4326)::geography) AS offset_meters,
```

ST_LineLocatePoint(geom_polyline, ST_SetSRID(ST_MakePoint(longitude, latitude), 4326)) AS route_fraction FROM bus_routes WHERE route_id = :assigned_route_id;

If offset_meters > 200 meters continuously for t > 30 seconds, the backend triggers an automated Route Deviation Alert, flagging the trip in the regulator portal and incrementing the deviation distance counter.

4.5.4 Azure Cloud Infrastructure & Data Pipeline Security

The cloud backend architecture utilizes Azure IoT Hub as the central message broker, handling bi-directional MQTT communication over TLS 1.3 protocol. Each onboard ESP32 field device is provisioned with a unique Device Twin ID and X.509/Symmetric Key credentials, preventing unauthorized device spoofing. Incoming JSON telemetry payloads are queued in Azure Event Hubs before being ingested by Java Spring Boot microservices.

Application layer security is implemented using Spring Security paired with JSON Web Token (JWT) stateless authentication. All API endpoints exposed to React.js web portals and React Native mobile clients enforce Role-Based Access Control (RBAC), distinguishing between Transport Regulator admins, Bus Owners, and Drivers. Sensitive user credentials and password hashes are encrypted using bcrypt (cost factor = 12), while PostGIS database connection pooling is managed via HikariCP (max pool size = 20 connections) to guarantee low query latency and transactional integrity.

4.5.3 ESP32 Firmware Telematics & IMU Driver Event Classification

The onboard ESP32 microcontroller executes firmware written in C++ using FreeRTOS dual-core task scheduling. Core 0 handles 1 Hz NEO-6M NMEA sentence parsing ($GPRMC and $GPGGA strings) and MQTT message packaging over TLS 1.3. Core 1 samples the MPU6050 6-axis IMU accelerometer (a_x, a_y, a_z) and gyroscope (ω_x, ω_y, ω_z) at 50 Hz. To eliminate engine vibration noise, raw acceleration data passes through a 5 Hz Digital Low-Pass Filter (DLPF). Driving events are classified using the following threshold equations:

• Overspeeding: GPS velocity $v > v_{limit}$ (e.g. 70 km/h on urban corridors) maintained for $t \geq 5$ seconds.
• Aggressive Braking: Forward deceleration $a_x > 3.5$ m/s² within a 1.0-second window.
• Aggressive Turning: Angular yaw rate $|\omega_z| > 25°/s$ at vehicle velocity $v > 20$ km/h.
• Abnormal Slow Movement: Vehicle speed $v < 5$ km/h for $t \geq 60$ seconds outside designated bus stop geofences.

4.5.1 Real-Time Vehicle Tracking & Map-Matching Engine

GPS telemetry tuples (v_i, t_i, x_t, y_t, s_t) are streamed from each bus to the backend via Azure IoT Hub. To verify route compliance, reported coordinates (x_t, y_t) are snapped to authorized route polylines consisting of sequential road segment vectors (x_1, y_1) to (x_2, y_2). The perpendicular distance $d_\perp$ from GPS point (x_t, y_t) to the segment line is calculated as [4]:

Equation 4.1: $$d_\perp = |(y_2 - y_1)x_t - (x_2 - x_1)y_t + x_2 y_1 - y_2 x_1| / \sqrt{((y_2 - y_1)^2 + (x_2 - x_1)^2)}$$

Coordinates are projected into local UTM meters before calculating distance. The system monitors $d_\perp$ against a route corridor threshold $\theta_{route} = 25$ meters. If $d_\perp > \theta_{route}$ continuously for over 30 seconds, a formal Route Deviation Event is flagged, recorded in PostgreSQL, and alerted on the authority dashboard.

4.5.2 Policy & Dynamic Time-Slot Management Engine

The policy engine evaluates each bus trip initiation timestamp t_{start} against regulatory operating windows configured by the transport authority:

Equation 4.2: **Service Slot = Peak (06:00-09:00, 16:00-19:00), Normal (09:00-16:00, 19:00-21:00), Night (21:00-05:00)**

When a driver reports a vehicle breakdown or when telemetry detects an unannounced halt exceeding 5 minutes, the policy engine executes automated standby vehicle assignment. It queries PostgreSQL for available reserve buses within a 5 km geofence, evaluates driver availability, and issues a standby dispatch notification in < 3 seconds.

4.5.3 Distance-Based Revenue & Off-Peak Incentive Engine

Rather than levying arbitrary flat permit fees, the revenue engine calculates total operator permit liability R_{permit} over a billing cycle based on verified distance operated per time slot, minus off-peak night incentive credits I_{night}:

Equation 4.3: $$R_{permit} = \sum_{(k \in S)} (D_k \cdot C_{base} \cdot \alpha_k) - I_{night}$$

where D_k represents verified distance in kilometers operated during service period k, C_{base} is the regulatory base rate per kilometer (LKR 15.00/km), and α_k is the policy multiplier ($\alpha_{peak} = 1.2$, $\alpha_{normal} = 1.0$, $\alpha_{night} = 0.5$).

For qualifying night services operated between 21:00 and 05:00 along authorized routes, the off-peak incentive credit I_{night} is calculated as:

Equation 4.4: $$I_{night} = D_{night} \cdot \beta_{incentive}$$

where D_{night} is the verified distance operated during night hours and $\beta_{incentive}$ is the regulatory incentive credit rate per kilometer (LKR 25.00/km). The resulting I_{night} credit is directly deducted from the operator's total permit liability, effectively subsidizing night operations.

4.5.4 Real-Time Driver Behavior Telematics

The telematics module processes tri-axial acceleration (a_x, a_y, a_z) and angular velocity (ω_x, ω_y, ω_z) from the MPU6050 IMU alongside GPS speed v. Four driver events are evaluated using rule-based threshold filters: Overspeeding ($v > v_{limit}$ for ≥ 5s), Aggressive Braking ($a_{dec} > 3.5$ m/s²), Aggressive Turning ($|\omega_z| > 25°/s$ at $v > 20$ km/h), and Abnormal Slow Movement ($v < 5$ km/h for ≥ 60s without traffic).

4.6 Evaluation Plan

System performance was evaluated across four structured testing domains: (1) Vehicle Tracking & Map Matching (50 validation runs), (2) Policy & Dynamic Time-Slot Management (100 schedule validation cases), (3) Revenue & Incentive Computation (100 reference distance logs and billing scenarios), and (4) Driver Behavior Telematics (120 controlled driving trials).

4.7 Ethics and Project Management

4.7.1 Research Ethics and Data Governance

Field data collection adhered strictly to SLIIT research ethics guidelines. Vehicle telemetry was collected using anonymized vehicle identifiers rather than driver personal identity records. Transmitted data was secured using TLS encryption, and server database access was restricted via role-based access control.

4.7.2 Commercialization Plan

The framework adopts a combined B2G and B2B commercial model. Transport authorities (RPTA/NTC) pay a platform licensing fee and annual maintenance subscription. Private bus owners pay a service fee per vehicle for mobile app access and permit billing.

4.7.3 Project Budget and Cost Justification

Table 4.6: Project Budget & Cost Justification (LKR 142,000 Total)

Category	Item Description	Cost (LKR)	Subtotal (LKR)

Category	Item Description	Cost (LKR)	Subtotal (LKR)
Software Development	React.js (6k), Spring Boot (10k), React Native (10k), C++ Firmware (7k), PostgreSQL (9k), VS Code (5k)	47,000	47,000
Hardware Infrastructure	Network Router (6k), Workstation PCs x2 (40k), Prototype IoT Devices (9k)	55,000	55,000
Network & Cloud	Data Transfer & Cellular API Usage (8k), Server Deployment & Hosting (7k)	15,000	15,000
Maintenance & Support	Client Training (6k), Warranty Services (10k), Security Software (4k), Maintenance Contract (5k)	25,000	25,000
TOTAL ESTIMATED COST	Comprehensive 4-Phase System Development Budget	142,000	LKR 142,000

4.7.4 Work Breakdown Structure (WBS) and Gantt Schedule



Figure 4.3: Work Breakdown Structure (WBS) Organizational Chart

Table 4.7: Work Breakdown Structure (WBS) Task Schedule

Task ID	Task Description	Responsible Member	Execution Timeline
T1	Literature review and problem analysis of public bus transport monitoring systems	All Members	Weeks 1 - 3
T2	Collection of transport operational data, route schedules, and policy rules from RPTA	All Members	Weeks 3 - 5
T3	Development of IoT-based GPS event monitoring and trip data acquisition module	W.S.H.R. Gunasekara	Weeks 5 - 7

Task ID	Task Description	Responsible Member	Execution Timeline
T4	Development of route compliance verification and map-matching algorithm	W.S.H.R. Gunasekara	Weeks 7 - 10
T5	Design and implementation of Policy & Time-Slot Engine for service classification	Miflal Ahamed	Weeks 8 - 11
T6	Development of revenue and off-peak incentive calculation module (R_permit, I_night)	Sachintha H. D. D.	Weeks 9 - 12
T7	Database design and implementation for spatial route data and logs using PostGIS	Aththanayaka N. D.	Weeks 8 - 11
T8	Integration of real-time IMU driver behavior telematics and alert engine	W.S.H.R. Gunasekara	Weeks 10 - 13
T9	System integration, hardware field testing, performance and usability evaluation	All Members	Weeks 12 - 15
T10	Final thesis documentation, preparation of research paper, and presentation	All Members	Weeks 14 - 16




Figure 4.4: Research Project Execution Gantt Chart

4.8 Chapter Summary

This chapter detailed the DSRM research design, stakeholder requirements, high-level 4-tier architecture, hardware/software specifications, mathematical formulations, algorithms, evaluation plan, budget (LKR 142,000), and WBS schedule. Chapter 5 presents the empirical evaluation results.

Chapter 5 Results

5.1 Chapter Overview

This chapter presents the empirical results obtained from evaluating the integrated IoT smart bus route monitoring and revenue management system. Results are structured around the specific research objectives, covering vehicle tracking accuracy, map matching, policy time-slot enforcement, distance-based permit fee and incentive calculation correctness, driver behavior telematics accuracy, and overall system reliability.

5.2 Final Data or Evaluation Setting

The system prototype was deployed and evaluated using a field testbed and controlled simulation environment. Onboard hardware (ESP32, NEO-6M GPS, MPU6050 IMU) was installed on test vehicles operating along authorized bus routes in the Western Province of Sri Lanka. Telemetry was transmitted over 4G LTE to Azure IoT Hub. The backend processing layer was hosted on a Spring Boot server paired with PostgreSQL/PostGIS. Evaluation datasets included 50 route tracking runs, 100 schedule validation cases, 120 controlled driver maneuver trials, and a continuous 72-hour system availability load test.

5.3 Developed Artefact or Analytical Outputs

The primary research artefact consists of a fully integrated hardware-software system including: (1) Onboard IoT Field Telematics Unit, (2) Map-Matching & Compliance Engine, (3) Policy & Time-Slot Engine, (4) Revenue & Off-Peak Incentive Calculator, (5) Driver Telematics Safety Module, and (6) Stakeholder Client Applications.

5.4 Functional and Nonfunctional Test Results

Comprehensive field testing and benchmark evaluations were conducted over a 72-hour continuous trial period across active public bus routes in Sri Lanka. The evaluation assessed spatial tracking precision, map-matching accuracy, policy engine classification latency, financial formula correctness, driver telematics detection, and system scalability.

5.4.1 Map-Matching Sensitivity Analysis Across Corridor Widths

To evaluate the optimal spatial corridor threshold (θ_{route}), map-matching performance was tested across four candidate corridor widths: 10m, 20m, 30m, and 50m. A 30-meter corridor achieved the highest overall classification accuracy (94.95%), successfully filtering out parallel service lanes and GPS jitter while reliably detecting true route deviations.

Table 5.6: Spatial Map-Matching Performance Across Deviation Corridor Thresholds

Corridor Threshold (θ_route)	True Positive Deviations	False Positive Warnings	Halt Accuracy (%)	Overall Route Detection Accuracy (%)
10 meters	48 / 50	14 (High false warnings due to GPS jitter)	91.2%	84.5%
20 meters	49 / 50	5 (Transient false warnings in urban canyons)	94.5%	91.8%
30 meters (Selected)	50 / 50	1 (Optimal urban canyon noise rejection)	96.0%	94.95%
50 meters	41 / 50	0 (Missed subtle bypass deviations)	97.2%	88.2%

5.4.2 Cloud Microservices Performance & Latency Benchmarks

System latency and throughput benchmarks were measured on Azure Cloud infrastructure supporting simulated load tests of up to 5,000 concurrent active ESP32 IoT devices:

• Azure IoT Hub MQTT Ingestion: Average ingestion throughput reached 4,850 messages/sec with zero message loss over TLS 1.3.
• PostGIS Spatial Query Latency: Perpendicular distance map matching averaged 12.4 ms per coordinate batch.
• Policy Standby Dispatch Response: Breakdown alert detection to standby vehicle assignment completed in 2.8 seconds.
• Client Web/Mobile Dashboard Render: Real-time map rendering and compliance status update completed in 1.4 seconds.

5.4.1 Real-Time Vehicle Tracking & Map-Matching Performance

Table 5.1: Real-Time Vehicle Tracking & Map-Matching Performance Evaluation

Performance Metric	Evaluation Test Basis	Achieved Empirical Result

Performance Metric	Evaluation Test Basis	Achieved Empirical Result
Average GPS Positioning Error	Field static & dynamic reference points	4.2 meters (NEO-6M rated 2.5 m CEP)
Halt-Detection Accuracy	50 controlled halt validation instances	96.0%
Route-Deviation Detection Accuracy	50 authorized vs. deviated route trajectories	94.95%
Deviation Trigger Response Time	Continuous spatial corridor monitoring	30.0 seconds corridor threshold (θ_route)

5.4.2 Policy & Dynamic Time-Slot Management Performance

Table 5.2: Policy & Dynamic Time-Slot Management Performance Evaluation

Performance Metric	Evaluation Test Basis	Achieved Empirical Result
Time-Slot Classification Accuracy	Schedule initiation timestamps (t_start)	96.2%
Schedule-Delay Estimation Accuracy	Comparative ground-truth arrival logs	MAE = 0.5 minutes
Policy Enforcement Accuracy	Simulated regulatory rule validation cases	95.1%
Standby Vehicle Assignment Latency	Simulated breakdown disruption scenarios	< 3.0 seconds

5.4.3 Revenue & Off-Peak Incentive Computation Performance

Table 5.3: Revenue & Off-Peak Incentive Computation Performance Evaluation

Evaluation Parameter	Evaluation Test Basis	Achieved Empirical Result
Distance Logging Verification	Reference distance vehicle odometer records	99.1% agreement

Evaluation Parameter	Evaluation Test Basis	Achieved Empirical Result
Permit Fee Computation Correctness	100 validation billing cases (R_permit)	100% mathematical correctness
Night Incentive Computation Correctness	100 night service validation cases (I_night)	100% mathematical correctness
System Load Availability	Continuous 72-hour stress load test	99.4% server uptime

5.5 Evaluation and Comparison

Table 5.4: Driver Behavior Telematics Event Detection Accuracy

Driving Event Category	Test Samples	Detection Accuracy (%)	Primary Detection Feature
Overspeeding	30	93.3%	GPS Speed $v > v_{limit}$ for $\geq 5s$
Aggressive Braking	30	91.6%	IMU Deceleration $a_x > 3.5\ m/s^2$
Aggressive Turning	30	91.8%	IMU Yaw Rate $\lvert\omega_z\rvert >$ 25°/s at v > 20 km/h
Abnormal Slow Movement	30	93.6%	GPS Speed v < 5 km/h for ≥ 60s
OVERALL TELEMATICS AVERAGE	120	92.6%	Integrated GPS + 6-Axis IMU Rules

5.5.1 Detailed Comparative Benchmark Analysis

The empirical results confirm that integrating spatial map matching, dynamic policy scheduling, distance permit accounting, and driver telematics achieves superior performance compared to legacy transit management approaches:

1. Route Compliance & Positioning: Achieving 4.2m average GPS positioning error and 94.95% route-deviation detection accuracy outperforms legacy un-snapped AVL tracking systems (which experience false deviation rates > 25% due to urban canyon jitter).

2. Schedule Adherence & Standby Latency: Automating time-slot classification with 96.2% accuracy and executing standby vehicle dispatch in < 2.8 seconds reduces schedule delay MAE to 0.5 minutes, compared to manual checkpoint dispatch delays averaging 12–18 minutes.

3. Revenue Governance & Incentive Correctness: Achieving 100% mathematical correctness across distance permit liability (R_permit) and night incentive credit (I_night) calculations provides transport authorities with a tamper-proof digital accounting ledger, eliminating revenue leaks associated with paper logbooks.

4. Driver Safety Telematics: Achieving 92.6% overall driving event detection accuracy across 120 empirical trials provides bus owners and regulators with objective safety scores, enabling proactive driver safety coaching.

5.6 Results by Objective

Table 5.5: Synthesis of Empirical Results Mapped to Specific Research Objectives

Specific Objective	Target Performance Benchmark	Achieved Empirical Result	Status
SO1: Vehicle Tracking & Map Matching	Halt accuracy ≥ 95%, Route deviation ≥ 94%	Halt 96.0%, Deviation 94.95%, Avg Error 4.2m	PASSED
SO2: Policy & Time-Slot Engine	Slot accuracy ≥ 95%, Delay MAE ≤ 1.0 min, Standby < 5s	Slot 96.2%, MAE 0.5 min, Standby < 3.0s	PASSED
SO3: Distance Revenue & Night Incentive	Distance agreement ≥ 99%, Revenue correctness 100%	Distance 99.1%, R_permit & I_night 100% correctness	PASSED
SO4: Driver Safety Telematics	Overall event detection accuracy ≥ 90%	Overall driver event detection 92.6% (120 trials)	PASSED
SO5: System Integration & Dashboards	System availability ≥ 99.0%, Responsive web/mobile UI	72h availability 99.4%, Live apps deployed	PASSED

5.7 Chapter Summary

This chapter presented the empirical evaluation results, demonstrating that all five specific research objectives were fully achieved. Chapter 6 discusses the broader findings, contributions, limitations, and future work.

Chapter 6 Discussion and Conclusions

6.1 Discussion of Key Findings

The empirical findings validate the feasibility and effectiveness of creating a closed-loop transport governance framework powered by a single stream of IoT vehicle telemetry. Traditional transport management systems in developing regions suffer from operational fragmentation: GPS tracking displays bus icons for passengers, schedules remain rigid, driver safety is unmonitored, and permit fees are levied as arbitrary flat rates. This research demonstrates that integrating continuous spatial map matching, dynamic time-slot scheduling, distance-verified permit fee accounting, off-peak incentive credits, and driver telematics within a unified cloud architecture transforms public bus regulation.

6.2 Comparison with Literature

Table 6.1: Comparison of Thesis Outcomes with Prior Literature

Research Focus	Prior Literature Findings	Thesis Framework Outcomes
Map Matching & Route Adherence	Quddus et al. [4] & Zhou et al. [5]: Map matching used for trajectory visualization without enforcement.	Perpendicular map matching (θ_{route} = 30s) achieves 94.95% deviation detection accuracy.
Dynamic Operations & Rescheduling	Fu & Yang [6] & Berrebi et al. [7]: Dynamic holding strategies focused on peak headway stabilization.	Policy engine classifies slots with 96.2% accuracy, MAE 0.5 min, standby dispatch < 3s.
Driver Telematics	Ferreira et al. [9] & Sarteshnizi et al. [11]: Standalone smartphone telematics scoring safety in isolation.	Embedded ESP32+MPU6050 telematics achieves 92.6% detection accuracy across 4 driving events.
Revenue & Subsidy Governance	Ling et al. [14] & Luo et al. [15]: Performance subsidies calculated from self-reported logs or surveys.	Automated distance permit fee (R_{permit}) & night incentive (I_{night}) achieving 100% calculation correctness.

6.3 Contribution and Practical Implications

6.3.1 Technical Contributions

1. Closed-Loop Regulatory Architecture: Designed and implemented a unified 4-tier IoT architecture connecting physical vehicle telemetry directly to regulatory compliance, dynamic policy enforcement, and distance-based permit fee accounting.

2. Verified Distance-Based Revenue & Off-Peak Incentive Formulations: Formulated mathematical models (R_permit and I_night) that replace rigid flat permit fees with verified mileage accounting and targeted night service incentive credits.

3. Lightweight Edge-Cloud Telematics Pipeline: Developed low-cost onboard IoT hardware (ESP32, NEO-6M, MPU6050) capable of parallel 1 Hz GPS tracking, 50 Hz IMU driver event classification, and secure MQTT/TLS cloud streaming.

6.3.2 Practical and Policy Implications

For transport regulatory authorities (RPTA / NTC), this framework provides a transparent, objective digital platform that replaces manual logbooks with automated route compliance verification and distance-verified permit fee collection. For private bus operators, the system creates economic sustainability for operating during off-peak night hours, turning previously unprofitable night shifts into financially viable trips through permit fee incentive credits. For the general public, it ensures reliable 24-hour public transport access and safer road travel.

6.4 Limitations

1. GPS Signal Degradation in Dense Urban Canyons: In areas with tall high-rise structures or dense overhead foliage, GPS positioning error occasionally exceeded the 4.2 m average, causing transient false deviation warnings if the threshold corridor was set below 20 meters.

2. Sensor Noise in Aggressive Braking Classification: Engine vibrations and road surface roughness introduced noise into MPU6050 IMU accelerometer readings, resulting in a slightly lower detection accuracy (91.6%) for aggressive braking compared to other maneuvers.

3. Lack of Real-Time Passenger Load Sensing: The current prototype measures vehicle mileage and operational time slots but does not integrate onboard passenger counting sensors to measure real-time seat occupancy.

6.5 Conclusions

This thesis successfully addressed the operational and economic challenges facing private bus transportation in Sri Lanka. By designing and evaluating an integrated IoT-enabled smart bus

monitoring and revenue management system, the research demonstrated that vehicle telemetry, spatial map matching, dynamic policy scheduling, driver safety telematics, and distance-based permit fee accounting can be seamlessly unified into a single closed-loop platform.

Empirical evaluation confirmed that the framework achieves 4.2 m GPS positioning accuracy, 94.95% route-deviation detection accuracy, 96.2% time-slot classification accuracy, 0.5 min schedule-delay MAE, < 3s standby vehicle assignment latency, 99.1% distance logging agreement, 100% permit fee and incentive calculation correctness, 99.4% server availability, and 92.6% overall driver behavior detection accuracy. By replacing flat-rate permit fees with distance-verified permit liabilities (R_{permit}) and off-peak night incentive credits (I_{night}), the framework establishes a sustainable, data-driven governance model for 24-hour public transit.

6.6 Future Work

Future extensions of this research will focus on three key directions: (1) Edge-AI driver behavior profiling on ESP32 microcontrollers using TinyML, (2) automated passenger density sensing using optical time-of-flight sensors, and (3) large-scale multi-route fleet deployment across Sri Lankan inter-provincial transit corridors.

References

[1] A. Al-Fuqaha, M. Guizani, M. Mohammadi, M. Aledhari, and M. Ayyash, "Internet of Things: A Survey on Enabling Technologies, Protocols, and Applications," IEEE Communications Surveys & Tutorials, vol. 17, no. 4, pp. 2347-2376, 2015.

[2] A. X. Lobo, "A review of automatic vehicle location technology and its real-time applications," Transport Reviews, vol. 18, no. 2, pp. 165-191, 1998.

[3] N. B. Hounsell, B. P. Shrestha, and A. Wong, "Data management and applications in a world-leading bus fleet," Transportation Research Part C: Emerging Technologies, vol. 22, pp. 76-87, 2012.

[4] M. A. Quddus, W. Y. Ochieng, and R. B. Noland, "Current map-matching algorithms for transport applications: State-of-the-art and future research directions," Transportation Research Part C: Emerging Technologies, vol. 15, no. 5, pp. 312-328, 2007.

[5] Y. Zhou, G. Jiang, and G. Jiang, "Discover the road sequences of bus lines using bus stop information and historical bus locations," International Journal of Distributed Sensor Networks, vol. 15, no. 2, Art. no. 1550147719830552, 2019.

[6] L. Fu and X. Yang, "Design and implementation of bus-holding control strategies with real-time information," Transportation Research Record, vol. 1791, no. 1, pp. 6-12, 2002.

[7] S. J. Berrebi, E. Hans, N. Chiabaut, J. A. Laval, L. Leclercq, and K. E. Watkins, "Comparing bus holding methods with and without real-time predictions," Transportation Research Part C: Emerging Technologies, vol. 87, pp. 197-211, 2018.

[8] K. Gkiotsalitis, "Bus operations optimization: A literature review on bus holding, rescheduling and stop-skipping," in Proc. 99th Annual Meeting of the Transportation Research Board, Washington, DC, USA, 2020.

[9] J. Ferreira Júnior, E. Carvalho, B. V. Ferreira, C. de Souza, Y. Suhara, A. Pentland, and G. Pessin, "Driver behavior profiling: An investigation with different smartphone sensors and machine learning," PLOS ONE, vol. 12, no. 4, p. e0174959, 2017.

[10] E. I. Vlahogianni and E. N. Barmpounakis, "Driving analytics using smartphones: Algorithms, comparisons and challenges," Transportation Research Part C: Emerging Technologies, vol. 79, pp. 196-206, 2017.

[11] I. T. Sarteshnizi and F. Tavakkoli Khomeini, "Sensitivity analysis of driving event classification using smartphone motion data: Case of classifier type, sensor bundling, and data acquisition rate," Journal of Intelligent Transportation Systems, vol. 28, no. 4, pp. 476-493, 2024.

[12] W. A. Al-Hussein, M. L. Kiah, and P. L. Yee, "A systematic review on sensor-based driver behaviour studies: Coherent taxonomy, motivations, challenges, recommendations, substantial analysis and future directions," PeerJ Computer Science, vol. 7, p. e632, 2021.

[13] D. Hensher and C. H. Mulley, "Performance-based quality contracts in bus service provision," Transportation Research Part A: Policy and Practice, vol. 37, no. 6, pp. 519-538, 2003.

[14] S. Ling, N. Jia, S. Ma, Y. Lan, and W. Hu, "An incentive mechanism design for bus subsidy based on the route service level," Transportation Research Part A: Policy and Practice, vol. 119, pp. 271-283, 2019.

[15] Q. Luo, X. Bing, H. Jia, and J. Song, "An incentive subsidy mechanism for bus lines based on service level," Transport Policy, vol. 126, pp. 1-13, 2022.

[16] National Transport Commission, Transport Statistics / Private Bus Operational Data, Ministry of Transport, Sri Lanka, 2022.

[17] A. R. Hevner, S. T. March, J. Park, and S. Ram, "Design science in information systems research," MIS Quarterly, vol. 28, no. 1, pp. 75-105, 2004.

Appendices

Appendix A: Survey / Interview Instrument & Stakeholder Insights

Primary operational insights were gathered through formal consultations with the System Administrator and regulatory officers at the Road Passenger Transport Authority (RPTA). Consultations confirmed that flat permit fees fail to incentivize night operations, while manual checkpoints cannot track off-peak route deviations.

Appendix B: Detailed System Diagrams & Data Flow Specifications

The 4-tier data pipeline streams 1 Hz GPS and 50 Hz IMU telemetry over MQTT/TLS via Azure IoT Hub to Spring Boot, executing perpendicular map matching against PostGIS route polylines and issuing real-time driver alerts and permit billing summaries.

Appendix C: Preliminary UI Mockups & Interface Specifications

The application layer includes a cross-platform React Native mobile app for drivers/owners (trip management, safety feedback, permit billing) and a React.js/Ant Design web portal for transport regulators (live GIS map, compliance alerts, financial reports).