



Incident report analysis

Instructions

As you continue through this course, you may use this template to record your findings after completing an activity or to take notes on what you've learned about a specific tool or concept. You can also use this chart as a way to practice applying the NIST framework to different situations you encounter.

Summary	The organization experienced a Denial of Service (DoS) attack that disrupted the internal network for two hours. During the attack, network services stopped responding because of an incoming flood of Internet Control Message Protocol (ICMP) packets. Normal internal traffic could not access network resources. The incident management team contained the attack by blocking incoming ICMP packets, taking non-critical network services offline, and restoring critical network services.
Identify	The incident management team identified the attack as a Denial of Service (DoS) attack caused by an ICMP packet flood. The internal network and network services were affected because the network could not handle the high volume of incoming ICMP traffic. The main vulnerability was an unconfigured firewall, which allowed malicious ICMP packets to enter the company's network without proper filtering or rate limiting.
Protect	To protect the network from similar attacks, the team should maintain firewall rules that limit the rate of incoming ICMP packets and restrict ICMP traffic from untrusted sources. The firewall should also verify source IP addresses to help detect spoofed IP addresses. In addition, an Intrusion Prevention System (IPS) should be used to filter suspicious ICMP traffic before it can overwhelm internal

	network resources.
Detect	To detect future DoS attacks faster, the team should use network monitoring software, firewall logs, and an Intrusion Detection System (IDS). These tools should alert the security team when abnormal traffic patterns occur, such as a sudden increase in ICMP packets from external or suspicious sources. Monitoring normal traffic baselines can also help the team identify unusual activity more quickly.
Respond	For future incidents, the team should follow a response plan that confirms the abnormal ICMP traffic, applies temporary blocks or rate limits, and isolates affected resources if necessary. Non-critical services can be taken offline to reduce the impact while critical services are restored first. The team should also collect firewall logs, IDS/IPS alerts, traffic data, and timestamps to analyze the incident and improve future response procedures.
Recover	To recover from a similar incident, the team should restore critical network services first and verify that internal users can access network resources again. After the network is stable, non-critical services should be brought back online gradually. The team should confirm that the new firewall rules, ICMP rate limits, source IP verification, monitoring tools, and IDS/IPS controls are working as expected before returning to normal operations.

Reflections/Notes: