

OpenStack Cinder Deep Dive

Michał Dulko

August 4th, 2016

Cinder's Mission

To implement services and libraries to provide on-demand, self-service access to Block Storage resources via abstraction and automation on top of other block storage devices.

Cinder drivers

Cinder is an abstraction layer for around 80 storage backends:

- ▶ Open: LVM, GlusterFS, Ceph, NFS. . .
- ▶ Proprietary: NetApp, SolidFire, Dell, EMC, HPE, Fujitsu, Hitachi, IBM, Lenovo, VMWare, Violin, Quobyte, Scality, Tegile. . .
- ▶ Protocols: iSCSI, NFS, RBD, Fiber Channel, proprietary. . .
- ▶ Backup: Swift, RBD, GlusterFS, NFS, IBM TSM

Required features

- ▶ Volume Create/Delete
- ▶ Volume Attach/Detach
- ▶ Snapshot Create/Delete
- ▶ Create Volume from Snapshot
- ▶ Get Volume Stats
- ▶ Copy Image to Volume
- ▶ Copy Volume to Image
- ▶ Clone Volume
- ▶ Extend Volume

Other/optional features

Other/optional features

- ▶ Backups
 - ▶ CPU bound!
 - ▶ Depends on cinder-backup service

Other/optional features

- ▶ Backups
 - ▶ CPU bound!
 - ▶ Depends on cinder-backup service
- ▶ Encryption
 - ▶ Many restrictions

Other/optional features

- ▶ Backups
 - ▶ CPU bound!
 - ▶ Depends on cinder-backup service
- ▶ Encryption
 - ▶ Many restrictions
- ▶ *Replication*
 - ▶ Low number of supporting drivers
 - ▶ Replication v1 - single volume replication
 - ▶ Replication v2 - backend-level replication


Other/optional features

- ▶ Backups
 - ▶ CPU bound!
 - ▶ Depends on cinder-backup service
- ▶ Encryption
 - ▶ Many restrictions
- ▶ *Replication*
 - ▶ Low number of supporting drivers
 - ▶ Replication v1 - single volume replication
 - ▶ Replication v2 - backend-level replication
- ▶ *Consistency groups and snapshots*
 - ▶ Low number of supporting drivers
 - ▶ Quite reliable


Other/optional features

- ▶ Backups
 - ▶ CPU bound!
 - ▶ Depends on cinder-backup service
- ▶ Encryption
 - ▶ Many restrictions
- ▶ *Replication*
 - ▶ Low number of supporting drivers
 - ▶ Replication v1 - single volume replication
 - ▶ Replication v2 - backend-level replication
- ▶ *Consistency groups and snapshots*
 - ▶ Low number of supporting drivers
 - ▶ Quite reliable
- ▶ *QoS support*
 - ▶ Moderate number of supporting drivers

Architecture (pre-Mitaka)



Architecture (since Mitaka)



Architecture

The screenshot displays a code editor with Python code for a scheduler manager. The code includes imports, configuration options, and a class definition. A file explorer on the right shows the project structure, and a commit message dialog is open over the code.

```
40 from cinder.volume import rpcapi
41
42 scheduler_driver_opt = cfg.StrOpt(
43     'scheduler_driver_opt',
44     default='nova.scheduler.driver.lvmThinP',
45     help='The scheduler driver to use for nova.',
46     metavar='driver',
47 )
48
49 CONF = cfg.CONF
50 CONF.register_opt(scheduler_driver_opt)
51
52 QUOTAS = quota.QUOTAS
53
54 LOG = logging.getLogger(__name__)
55
56 class SchedulerManager(manager.Base):
57     """Chooses a host to create a volume on.
58
59     ...
60
61     ... target = messaging.Target(version=RPC_API_VERSION,
62
63     ... def __init__(self, scheduler_driver=None, service_name=None,
64     ...               *args, **kwargs):
65     ...     if not scheduler_driver:
66     ...         scheduler_driver = CONF.scheduler_driver
```

File Explorer Structure:

- __init__.py
- test_types_extra_specs.py
- test_types_manage.py
- extensions (2 files)
 - __init__.py
 - foxinsocks.py
 - __init__.py
 - test_extensions.py


Commit Message Dialog:

Commit Message

Initial fork out of Nova.

Close

Architecture (non-LVM-backends)




Attach to VM or detach from VM

Complicated chain of internal REST API calls from Nova to Cinder.

Attach to VM or detach from VM

Complicated chain of internal REST API calls from Nova to Cinder.



Pitfalls

Pitfalls

- ▶ cinder-scheduler is race-condition prone
 - ▶ Nova's legacy

Pitfalls

- ▶ cinder-scheduler is race-condition prone
 - ▶ Nova's legacy
- ▶ multi-backend support
 - ▶ It's like running multiple cinder-volume on one node
 - ▶ Deployment without `enabled_backends` option is deprecated in Newton

Pitfalls

- ▶ cinder-scheduler is race-condition prone
 - ▶ Nova's legacy
- ▶ multi-backend support
 - ▶ It's like running multiple cinder-volume on one node
 - ▶ Deployment without `enabled_backends` option is deprecated in Newton
- ▶ Cinder usage outside of OpenStack
 - ▶ `python-brick-cinderclient-ext` project
 - ▶ You'll still need DB (MySQL), MQ (RabbitMQ) and Keystone

Future

- ▶ Replication v2.1
 - ▶ replication of groups of volumes

Future

- ▶ Replication v2.1
 - ▶ replication of groups of volumes
- ▶ IroniC support

Future

- ▶ Replication v2.1
 - ▶ replication of groups of volumes
- ▶ Ironio support
- ▶ Volume multi-attach support
 - ▶ Cinder's side is done. . .

Future

- ▶ Replication v2.1
 - ▶ replication of groups of volumes
- ▶ Ironio support
- ▶ Volume multi-attach support
 - ▶ Cinder's side is done. . . since Liberty
 - ▶ Still trying to figure out correct Nova-Cinder interactions

Future

- ▶ Replication v2.1
 - ▶ replication of groups of volumes
- ▶ Ironic support
- ▶ Volume multi-attach support
 - ▶ Cinder's side is done. . . since Liberty
 - ▶ Still trying to figure out correct Nova-Cinder interactions
- ▶ Live upgrade support
 - ▶ Experimental in Mitaka
 - ▶ Hopefully Newton will officially support that

Future

- ▶ Replication v2.1
 - ▶ replication of groups of volumes
- ▶ Ironic support
- ▶ Volume multi-attach support
 - ▶ Cinder's side is done. . . since Liberty
 - ▶ Still trying to figure out correct Nova-Cinder interactions
- ▶ Live upgrade support
 - ▶ Experimental in Mitaka
 - ▶ Hopefully Newton will officially support that
- ▶ cinder-volume service clustering *AKA c-vol A/A HA support*
 - ▶ Right now it is still risky to run multiple c-vols controlling a single storage backend

Thank you!