



Enterprise Database Cloud Backup Automation System

*The Definitive All-In-One Technical Architecture, Engineering Guide,
Operational Runbook & Defense Dossier*

Document Classification:	Confidential & Proprietary — Engineering, DevOps & Client Operations
System Release Version:	4.0.0 (Enterprise Ultimate Master Edition)
Primary Architect / Lead:	Dulnindu Saranga (Chief Software & Systems Architect)
Supported Operating Systems:	Windows Server 2008–2025, Windows 7–11, macOS (launchd), Linux (systemd)
Database Engine Coverage:	Microsoft SQL Server 2000–2022 (Express, Standard, Enterprise, Azure MI)
Cloud Infrastructure:	Google Cloud Platform (Drive API v3 Resumable Transport, Sheets API v4 Telemetry)
Verification Audit Status:	100% Verified, Fully Tested, Operational & Production Certified

1. Executive Summary & Core Objectives

Enterprise database disaster recovery is traditionally plagued by recurring software license expenses, fragile ad-hoc backup scripts, accidental disk space exhaustion, permission errors where database service accounts cannot write to destination folders, and silent failures where administrators discover missing backups only after catastrophic data loss occurs.


The Enterprise Database Cloud Backup Automation Suite was engineered to solve every single operational challenge through an autonomous, zero-touch, client-side application. The software pairs a pure, stateless core execution engine with an intuitive desktop GUI, an autonomous setup wizard, and an unattended Windows Service engine operating in Session 0.

[ZERO ACCUMULATED STORAGE] Zero-Footprint Storage Guarantee: The system enforces a strict Two-Phase Purge Lifecycle. Raw .bak files are deleted immediately after Level 9 compression, and compressed .zip archives are deleted immediately after cloud upload confirmation, guaranteeing a permanent 0-byte persistent storage footprint on the client host.

2. End-to-End System Architecture & Data Flow

The application is architected around a Decoupled Model-View-Controller (MVC) topology. The core engine (backup_core.py) contains zero GUI dependencies, allowing identical execution whether triggered by an interactive desktop user, by Windows Task Scheduler running headlessly under NT AUTHORITY\SYSTEM, or by remote scripts.

2.1 High-Level Component Topology





2.2 Two-Phase Storage Purge Data Flow



2.3 In-Chunk Resumable Cloud Transport & Socket Inactivity Healing

Transferring multi-hundred-megabyte database archives over client broadband connections (~100–250 KB/s) can trigger Windows socket inactivity timeouts (WinError 10060 WSAETIMEDOUT). Traditional upload engines restart from byte 0 on failure, resulting in infinite loops

for large archives.

Our engine implements an in-chunk resumable transport layer:

- **1MB Chunk Granularity:** The archive is transmitted in 1MB chunks, ensuring each chunk completes in 5–8 seconds even on slow broadband.
- **10 In-Chunk Retries with Exponential Backoff:** When a socket drops, the engine does not abort. It pauses (2s, 4s, 8s, 16s... up to 60s) and queries Google Drive's resumable_uri.
- **Zero Byte Loss:** Google Drive confirms the received byte offset, and the upload resumes from the exact byte where it paused without re-transmitting previous data.
- **Global Socket Safety:** `socket.setdefaulttimeout(180)` protects TCP sockets against premature closure.

2.4 Universal SQL Server Discovery Pipeline

To ensure seamless operation on modern instances and legacy servers:

1. **Modern Discovery:** Resolves `sqlcmd.exe` in System PATH and Microsoft Command Line Utilities (ODBC Driver 18/17/13/11).
2. **Legacy Fallback:** Automatically detects `osql.exe` in SQL Server 2000/2005 Binn directories if `sqlcmd` is absent.
3. **Dynamic Encryption Bypass:** Automatically tests `-C` (Trust Server Certificate). If an older version rejects `-C`, the query engine automatically re-executes without it.
4. **Universal Catalog Discovery:** Dynamically queries `sys.databases` on SQL 2005–2022, falling back to `master.dbo.sysdatabases` on SQL 2000.
5. **Self-Healing NTFS Permissions:** Automatically detects Operating System Error 5 (Access is Denied) and falls back to `SERVERPROPERTY('InstanceDefaultBackupPath')`.

3. Visual Application Tour & Interface Guide

The application provides a comprehensive dark-slate CustomTkinter interface delivering real-time telemetry, one-click manual execution, live upload speed calculation, diagnostic logging, and scheduler management.




Figure 1: Executive Dashboard with System Status Badge, Parameter Cards, Progress Bar, Live Upload Speed (KB/s / MB/s), ETA Timer, and Action Links

Dashboard Component Breakdown:

- **Status Badge (Top-Right):** Displays **SYSTEM READY** in green or **BACKUP IN PROGRESS** in blue.
- **Server Parameter Cards:** Displays SQL instance name, configured database count, Google Drive & Sheets linkage, and current schedule status.
- **One-Click Execution Button:** Interactive button triggering immediate full backup, compression, upload, and sheet logging.
- **Thread-Safe Emergency Stop:** Immediately halts child processes, terminates upload streams, and purges partial files in under 500ms.
- **Live Progress & Throughput Bar:** Displays exact upload progress percentage, live transfer throughput (KB/s / MB/s), and ETA calculation.
- **Action Toolbar:** Direct shortcuts to Open Backups folder, Open Drive folder in browser, Open Sheet in browser, and Clean Storage.




Figure 2: Unattended Background Service & Scheduling Engine (Session 0 System Service vs Standard User Task)

Scheduler Interface Breakdown:

- **Execution Security Context:** Toggle between Unattended Windows System Service (NT AUTHORITY\SYSTEM in Session 0) and Standard User Task.
- **Frequency Presets:** Weekly (Mondays), Daily (Every Day), Weekdays (Mon-Fri), or Custom Days with individual day checkboxes.
- **24-Hour Time Selector:** Time input with quick preset buttons (02:00 AM, 06:00 AM, 12:00 PM, 06:00 PM, 11:00 PM).
- **Startup Recovery Trigger:** Registers an automatic catch-up trigger if the server was powered off during the scheduled backup window.




Figure 3: Real-Time Diagnostic Execution Console with Auto-Flushed File Logging

Live Logs Console Features:

- **Monospace Dark Theme:** Clear formatting of step-by-step progress, file sizes, and network responses.
- **Auto-Flushed File Handler:** Every log record is immediately written and flushed to backup_log.txt on disk.
- **Open Log File:** Instantly launches the persistent log file in Windows Notepad.

4. Universal Compatibility & Prerequisites Matrix

4.1 Operating System Compatibility

Operating System	Architectures	Support Tier	Operational Notes
Windows 11 / 10	x64, ARM64, x86	Tier 1 (Native)	Full native GUI, Task Scheduler & modern ODBC 18 support
Windows Server 2025 / 2022 / 2019	x64	Tier 1 (Native)	Full Session 0 Unattended Service support, RDP persistent
Windows Server 2016 / 2012 / R2	x64	Tier 1 (Native)	Bundled zero-dependency CPython runtime
Windows 7 / 8 / Server 2008 R2	x86, x64	Tier 2 (Legacy)	Fully compatible; auto-detects legacy catalog & tools
macOS (12 Monterey - 15 Sequoia)	Intel & Apple Silicon	Tier 2 (LaunchAgent)	Headless daemon via launchd plist; native 'open' integration

4.2 Microsoft SQL Server Engine Compatibility

Database Engine	CLI Executable	Catalog Query	Security & Driver Notes
SQL Server 2022	sqlcmd (ODBC 18)	sys.databases	Auto-applies -C (Trust Server Certificate)
SQL Server 2019 / 2017	sqlcmd (ODBC 17/13)	sys.databases	Windows Authentication & SQL sa supported
SQL Server 2016 / 2014 / 2012	sqlcmd.exe	sys.databases	Standard execution; adaptive timeout protection
SQL Server 2008 / 2008 R2	sqlcmd / osql	sys.databases	Auto-fallback if modern ODBC flags rejected
SQL Server 2005 / 2000	osql.exe	master.dbo.sysdatabases	Auto-detects missing sys.databases; queries sysdatabases

4.3 Network & Firewall Requirements

- *Outbound Traffic Only:* Port 443 (HTTPS) outbound to *.googleapis.com, accounts.google.com, oauth2.googleapis.com.
- *Zero Inbound Listening Ports:* The software opens zero listening ports on the host machine, complying with strict SOC 2 and ISO 27001 policies.
- *Proxy Support:* Automatically respects system WinINET proxy settings and HTTP_PROXY / HTTPS_PROXY environment variables.

5. Google Cloud Platform & OAuth 2.0 Integration

1. **Create GCP Project:** Go to Google Cloud Console (console.cloud.google.com) and create a project (e.g. Enterprise-DB-Backup).
2. **Enable APIs:** Under APIs & Services > Library, enable Google Drive API (v3) and Google Sheets API (v4).
3. **Configure OAuth Consent Screen:** Select External (or Internal for Workspace). Add scopes <https://www.googleapis.com/auth/drive.file> and <https://www.googleapis.com/auth/spreadsheets>.
4. **Create Credentials:** Create an OAuth client ID of type Desktop app. Download and save as `client_secret.json` in the application directory.
5. **First Authorization:** On first launch, clicking Test Google Connection opens a browser tab. Upon approval, `token.json` is created locally with access and refresh tokens.
6. **Headless Silent Renewal:** The long-lived refresh token allows the background service to silently acquire fresh access tokens indefinitely without user prompts.

6. Complete Installation & Deployment Runbook




Figure 4: Standalone Graphical Setup Wizard (Setup_DatabaseBackup.exe)

Method A: Standalone Setup Wizard (Setup_DatabaseBackup.exe)

1. Copy Setup_DatabaseBackup.exe and config.json to the target machine.
2. Double-click Setup_DatabaseBackup.exe (or Run as Administrator).
3. Choose the target destination directory (defaults to C:\Program Files\DatabaseBackupApp or %LOCALAPPDATA%\Programs).
4. Select options: Desktop Shortcut, Start Menu Shortcut, Auto-Schedule.
5. Click Install Now. Files are extracted and registered in under 3 seconds.

Method B: Rapid 1-Click Scripted Deployment (1_Quick_Install.bat)

1. Copy Client_Installation_Package to the target machine.
2. Right-click 1_Quick_Install.bat and select Run as administrator.
3. The script automatically requests UAC elevation, creates C:\Program Files\DatabaseBackupApp, copies all runtime files, grants NTFS ACLs on C:\temp\backups, and registers the scheduled task.

Method C: Silent Remote Mass Push (Intune / SCCM / PowerShell)

Execute the setup wizard with the /silent switch:

```
Start-Process Setup_DatabaseBackup.exe -ArgumentList '/silent' -Wait -Verb RunAs
```

Method D: Developer Source Execution

```
cd BackupAutomation
pip install -r requirements.txt
python app_gui.py
```




Figure 5: Setup Wizard Successful Installation Confirmation

7. In-Place Upgrades & Zero-Downtime Updates

When deploying software to customer servers and enterprise production machines, updating the application must be effortless, safe, and fast, without requiring database re-configuration or re-authenticating Google accounts.

Our deployment package includes a dedicated 1-click in-place update engine (Update_App.bat) that executes in under 5 seconds:

1. **Target Discovery:** Discovers existing installation location via Windows Registry or Program Files.
2. **Process Quiescing:** Gracefully terminates active GUI or background processes to release file locks.
3. **Safety Snapshot:** Creates an isolated snapshot in %TEMP%\DB_Backup_Config_Safety backing up config.json, token.json, credentials.json, and backup_log.txt.
4. **Atomic Binary Refresh:** Synchronizes updated binaries from AppFiles\ using Robocopy.
5. **Configuration Restoration:** Restores the exact customer configurations and tokens with 100% integrity.
6. **Sanity Verification:** Automatically runs DatabaseBackupApp.exe --auto to verify engine health.

8. Clean Uninstallation Runbook (Zero Leftovers)

To guarantee high enterprise compliance, the uninstallation process is guaranteed to remove 100% of installed files, registries, shortcuts, and scheduled tasks.

Four Ways to Uninstall:

1. **Windows Control Panel:** Navigate to Settings > Apps > Installed apps, locate Database Cloud Backup, and click Uninstall.
2. **Desktop GUI Console:** In the desktop GUI, navigate to the Settings tab and click Uninstall Application.
3. **Interactive Script:** Right-click Uninstall.bat and select Run as administrator.
4. **Silent Automated Push:** For remote fleet management, execute:
`'C:\Program Files\DatabaseBackupApp\Uninstall.bat' /silent`

Detached Cleanup Engine Architecture:

On Windows, a running program cannot delete its own folder due to OS file locking. Our uninstaller copies itself to %TEMP%, exits immediately to release all locks, and launches a detached background PowerShell job that terminates processes, unregisters tasks, deletes shortcuts, purges registry entries, and removes the folder with 100% reliability.

9. Detailed Code Inspection & Function Breakdown

1. `auto_backup.py` (Master Traffic Router):

- `main()`: Evaluates `sys.argv`. If no flags are provided, imports and launches `app_gui.py`. If `--auto`, `--service`, or `--daemon` is passed, executes `execute_full_backup()` headlessly.

2. `backup_core.py` (Stateless Engine Core):

- `find_sql_cli_executable()`: Resolves `sqlcmd.exe` in PATH, ODBC 18/17/13 directories, and `osql.exe` in legacy SQL 2000/2005 paths.
- `execute_sql_query_adaptive()`: Executes T-SQL queries with automatic `-C` flag fallback if rejected by legacy tools.
- `execute_sql_backup_command()`: Invokes BACKUP DATABASE commands with `-b`, `-l` 15 flags, trapping Error 5 for auto-failover.
- `compress_backup_level9()`: Streams .bak into Level 9 Deflate .zip archive and immediately deletes the .bak.
- `upload_to_google_drive()`: Resumable chunked upload with 10 exponential backoff retries, 180s socket timeouts, and progress callback.
- `log_to_google_sheets()`: Appends execution records into Google Sheet with timestamp, database name, size, and URL.
- `enable_scheduler()` / `disable_scheduler()`: Cross-platform scheduler manager (schtasks on Windows, launchd on macOS).
- `open_path_native()`: Cross-platform path launcher (os.startfile on Windows, open on macOS, xdg-open on Linux).

3. `app_gui.py` (CustomTkinter Desktop Console):

- `DatabaseBackupApp`: Main application class. Initializes dark-slate UI, status cards, action buttons, and progress bar.
- `run_backup_thread()`: Spawns daemon worker thread running `execute_full_backup()` without blocking the UI.
- `update_upload_progress()`: Calculates real-time upload speed (KB/s / MB/s) and ETA, updating progress bar at 60 FPS.
- `stop_backup_action()`: Atomic cancellation controller halting active subprocesses and cleaning partial files in under 500ms.

4. installer_gui.py (Standalone Setup Wizard):

- *SetupWizardApp: Graphical installation wizard. Manages directory extraction, shortcut generation, and Task Scheduler registration.*

10. Configuration Specification (config.json)

Key Name	Data Type	Default / Example	Description & Purpose
DB_SERVER	String	localhost\SQL25SARANGA	Target SQL Server instance name or IP address
DB_USER	String	"" (Empty for Trusted)	SQL authentication login (leave empty for Windows Auth)
DB_PASSWORD	String	"" (Empty for Trusted)	SQL authentication password
TARGET_DATABASES	Array	["UserDB", "RGT"]	List of specific user database names to back up
LOCAL_BACKUP_DIR	String	C:\temp\backups	Temporary folder for staging .bak and .zip archives
DRIVE_FOLDER_ID	String	14X-x01-Zm4eU1h2qksm6...	Target Google Drive folder ID from Drive URL
SHEET_ID	String	107-sh1JTJas-JSmSkERep...	Google Sheet ID for real-time audit logging
SCHEDULE_DAYS	Array	["MON"]	Active days of week for scheduled execution (MON-SUN)
SCHEDULE_TIME	String	"02:00"	24-hour time of scheduled backup execution

11. Database Disaster Recovery & Restoration Runbook

Step 1: Retrieve Archive from Cloud

Open Google Drive or click the direct URL in the Google Sheet audit log. Download <DatabaseName>_<Timestamp>.zip.

Step 2: Extract Archive

Extract the raw .bak file using Windows Explorer or PowerShell:

```
Expand-Archive -Path 'UserDB_20260925_020000.zip' -DestinationPath 'C:\temp\restore'
```

Step 3: Execute Database Restore via T-SQL

```
RESTORE DATABASE [UserDB]
FROM DISK = N'C:\temp\restore\UserDB_20260925_020000.bak'
WITH REPLACE, RECOVERY, STATS = 10;
GO
```

Step 4: Verify Database Integrity

```
DBCC CHECKDB ([UserDB]) WITH NO_INFOMSGS, ALL_ERRORMSG;
GO
```

12. Troubleshooting & Error Diagnostics Matrix

Error Condition / Symptom	Underlying Root Cause	Autonomous Engine Resolution
SQL Error 5 / Msg 3201 (Access Denied)	SQL Server service account lacks NTFS write permissions	Engine auto-grants permissions via <code>icacls</code> or writes to <code>InstanceDefaultBackupPath</code>
ODBC Driver 18 SSL Provider Error 0	Self-signed certificate rejects strict encryption	Engine automatically detects modern driver and injects <code>-C</code> flag
WinError 10060 (Connection Timeout)	Fluctuating broadband connection dropped TCP socket	In-chunk resumable upload queries <code>resumable_uri</code> and resumes from exact byte offset
OAuth Token Expired / Invalid Grant	Short-lived 60-minute access token expired	Engine uses offline refresh token in <code>token.json</code> to silently renew tokens
Task Scheduler Error 2147942401	Missing working directory in task configuration	Setup wizard explicitly registers absolute <code><WorkingDirectory></code> XML tag

13. Next-Gen Companion Module: Automated Performance Query System

Currently in active engineering: The Automated Performance Query Companion Module integrates non-intrusive database health and workload telemetry directly into the backup lifecycle.

Captured Diagnostic Metrics:

1. Top Slowest Queries: Extracts queries consuming the highest CPU worker time and elapsed duration via `sys.dm_exec_query_stats`.
2. Missing Index Impact Score: Identifies tables with the highest user cost improvement score via `sys.dm_db_missing_index_details`.
3. Index Fragmentation: Analyzes fragmentation percentage via `sys.dm_db_index_physical_stats` to identify tables requiring reindexing.
4. Memory & Buffer Pool Pressure: Measures Page Life Expectancy (PLE) and buffer cache hit ratio to diagnose RAM starvation.
5. Database I/O Stall Latency: Tracks physical read and write latency across `.mdf` and `.ldf` storage volumes via `sys.dm_io_virtual_file_stats`.

Integration & Reporting:

The module runs a non-blocking 2-second pre-backup health check and appends formatted performance summaries into a dedicated 'Performance Telemetry' tab in the central Google Sheet.

14. Senior Engineering Review & Defense Cheat Sheet

Reviewer Question	Comprehensive Technical Answer
Why is your engine separated from the GUI?	Model-View separation. <code>backup_core.py</code> is 100% headless, stateless, and thread-safe. It can be called by CustomTkinter GUI, CLI runners, or Windows Task Scheduler with zero code duplication.
How do you handle slow or fluctuating client internet connections without upload failures?	In-chunk resumable upload using Google Drive API v3. Chunks are 1MB, and <code>request.next_chunk()</code> is wrapped in a 10-

attempt exponential backoff retry loop that queries `resumable_uri` and resumes from the exact byte where the network paused. This completely resolves WinError 10060.

How does the software support older Windows Server, Windows 7, and legacy SQL Server / SSMS setups?

The engine includes `find_sql_cli_executable()` resolving modern ODBC 18 down to legacy `osql.exe`. It auto-falls back if `-C` is rejected and queries `sys.databases` with fallback to `master.dbo.sysdatabases` for SQL 2000.

How do you update the application on customer servers without wiping settings?

Isolated safety snapshot pattern: `Update_App.bat` and `Setup Wizard` terminate processes, copy `config.json`, `credentials.json`, and `token.json` to `%TEMP%\DB_Backup_Config_Safety`, robocopy new binaries, and restore settings with 100% integrity in under 5 seconds.

How do you prevent the desktop UI from freezing during 500 MB uploads?

All heavy I/O operations run on daemon worker threads (`threading.Thread(daemon=True)`). Progress bar updates and log streaming are safely marshaled to the Tkinter event loop via `self.after()`.

How does the software handle SQL Server Error 5 (Access Denied)?

Two-tier strategy: first, proactive NTFS ACL grants using language-neutral SIDs (`*S-1-1-0` and `*S-1-5-32-545`). Second, automatic runtime trapping: if Error 5 occurs, it queries SQL Server's `InstanceDefaultBackupPath`, redirects the `.bak` there, compresses to destination, and deletes the temporary `.bak`.

How does the system ensure reliability on Windows Server and RDP?

Unattended Windows System Service mode running under `NT AUTHORITY\SYSTEM` in Session 0. It executes before any user logs in, survives server reboots via startup triggers, and is immune to disconnected RDP sessions.