

[Late Collat Rev Part]

Statistics

Statistics is a branch of applied mathematics which is applied to observational data. It deals with data collection, presentation, organization and summarizing data, decision making etc.


Types:

- i) Descriptive, [Everything upto Probability]
- ii) Inferential, [AF Theory of Probability & TOP+T]
 - ↳ Theory of Probability, Sampling, Test of Significance, Test of hypothesis etc → based on sample → if random is involved
 - ↳ Data Presentation, Organization and summarization of data, measure of location, dispersion, shape characteristics (central tendency things)

Population: The entire set of individuals or objects of interest on the measurements obtained from all individuals or object of interest.

Sample: A ^{representative} portion, or part, of the population of interest
 ↳ MUST Represent the population

Data:



Types of Levels of Data:

va

i)

ii) Interval Level Data → 0 ^{does not} means any non-existent

iii) Ratio Level Data → 0 means non-existent and a state

Describing Data:* Frequency Distribution Table:

Construct a FDT / Arrange the data / Make a table...

 $k = \text{smallest number of classes}$ $2^k \geq \text{no. of data}$: For what minimum value of k , 2^k will be greater than number of data

For 180,

~~200~~ $k = 8$

$\therefore 2^8 = 256 > 180$

 $\therefore$ Min class number = 256 $i = \text{class width}$, $H = \text{highest value}$, $L = \text{lowest value}$

$i \geq \frac{H - L}{k}$; always $\lceil i \rceil$

* If gap is high, you can take ~~b~~ adjust data

$$\begin{array}{l}
 H = 3894 \\
 L = 294 \\
 i = 375
 \end{array}
 \left. \vphantom{\begin{array}{l} H = 3894 \\ L = 294 \\ i = 375 \end{array}} \right\} \rightarrow
 \begin{array}{l}
 H = 3900 \\
 L = 200 \\
 i = 400
 \end{array}$$

Hence, the observation number is,
 $n = 180$

[Check Q from Book]

The smallest number of classes (k) is,

$$2^k \geq 180$$

or, $2^8 \geq 180$ // find it in rough

which means, number of class, $k = 8$.

And, the class width (i) is,

$$i \geq \frac{H - L}{k}; \quad \begin{cases} \text{Here,} \\ \text{highest value, } H = 3292 \\ \text{lowest " , } L = 294 \end{cases}$$

$$\text{or, } i \geq \frac{3292 - 294}{8} \\ \geq 374.75$$

* $N \rightarrow$ usually population size
 * but in this case,
 $N =$ ~~size~~ total frequency
 * $n =$ sample size

Hence,

we consider the class width 400
 we consider 200 in lieu of 294 and ~~3400~~ ~~in~~ of 3400 3400 of 3292

Table: Frequency Distribution Table of Profit (\$) on vehicles sold by

Applewood Auto // Name is MUST. Write short but MUST

actual name less than cumulative frequency

used to get a better idea of everything

proportion

class interval (Profit)	Tally	Frequency f_i	Cumulative Frequency F_i	Relative Frequency $\left(\frac{f_i}{N}\right)$
200 - 600		8	8	$\frac{8}{180} = 0.04$
600 - - -		11	19	$\frac{11}{180} = 0.06$
	.	.	.	.
	.	.	.	.
	.	.	.	.
	.	.	.	.
	.	.	.	.
	$N = \sum f_i =$	180		






Fig: Histogram of the Profit -
(Table Name but replace it ~~for~~ with Histogram)



* When classes have names, we use bar diagram or pie chart

Bar Diagram:

X-axis: Name ; scaling not needed
Y-axis: Frequency ; scaling needed

* Mark the bars : 

* Classes without names can also be plotted.
Replace names with class width.


Y-axis remains same

Pie Chart:

At first we calculate the angles

Class	Frequency	Angle
Total	n	

* No need for protractor
or maintaining serial
or showing calculation



use eye to calculate

Measures of Central Tendency

1. Mean $\rightarrow$ Arithmetic mean
 $\rightarrow$ Geometric means (%) $\rightarrow$ rate
 $\rightarrow$ Harmonic (x/y & units)

2. Median

3. Mode

Formula for Ungrouped Data

* Mean :

Arithmetic mean: $\bar{X} = \frac{\sum x_i}{n}$

Geometric mean: $\sqrt[n]{x_0 x_1 x_2 \dots x_n} = \bar{H}(x_i)$
(Lin Marshall - 72)

(S.P Gupta - Q4: 99)

Harmonic mean = $\frac{n}{\sum \frac{1}{x_i}}$



Median :

*Median:
The value which takes the middle most position
in an orderly arranged data set.

→ Mode:

→ **Mode:**
The value with maximum numbers of occurrence/frequency in a data set is known as mode.

Formula For Grouped Data:

* Arithmetic Mean: $\bar{X} = \frac{\sum f_i x_i}{N}$

* Geometric Mean : $\text{Antilog } \frac{1}{N} \sum f_i \log x_i$; $\log_{10}$ (NOT $\ln$)
 $\text{Antilog } x = 10^x$

* Harmonic Mean : $\frac{N}{\sum \frac{f_i}{x_i}}$

* Harmonic Mean : $\frac{1}{\sum \frac{f_i}{x_i}}$

* Median : $M_e = L + \frac{\frac{N}{2} - c.f}{f_m} \times C$

* Mode : $M_o = L + \frac{\Delta_1}{\Delta_1 + \Delta_2} \times C$

$\left\{ \begin{array}{l} L = \text{Lower limit of median class} \\ c.f = \text{Cumulative frequency of prior median class} \\ f_m = \text{Median class frequency} \\ C = \text{Median class width} \\ N = \text{Total observation} \end{array} \right.$

$$\text{Mode } M_o = L + \frac{\Delta_1}{\Delta_1 + \Delta_2} \times C$$

L = Lower limit

L = Lower limit
 Δ_1 = diff. between frequencies of modal and premodal class

$$\Delta_2 = 11$$

c = modal class width

Example of Geo. Mean.

As the data is percentages, we will use geometric mean.

Let,

replace with unit mentioned
in the question.

100 [rate] is invested

return 30%.

mean

130 [rate]

" 20%.

"

120 [rate]

" -40%.

"

80 [rate]

" 200%.

"

300 [rate]

we convert the data in smaller form.

That is: 1.3, 1.2, 0.6, 3.0

Then, the (geometric) mean rate of return is:

$$G.M = \sqrt[n]{(x_1)(x_2) \dots (x_n)} = \sqrt[4]{(1.3)(1.2)(0.6)(3.0)}$$
$$= 1.294$$

i.e. 129.4%

∴ Return is 29.4%.

Example (S.G. Gupta) :

% Rise	Expenses taking 100%	$\log X$
32	132	!
40	140	!
,		
,		

* Do : S.G Gupta! Miscellaneous Examples

(27, 30, 32, 33)
(but do all)

Harmonic Mean:

$$H.M = \frac{1}{\frac{1}{x_1} + \frac{1}{x_2} + \frac{1}{x_3} + \dots}$$

$$= \frac{n}{\sum \frac{1}{x_i}}$$

used whenever there is a per unit (unit) involved
* Any rate (km/hr, take/kg)

X goes 20 km per in 5 hour

$$\frac{20 \text{ km}}{5 \text{ hour}} = 4 \text{ km/hr} ; \text{ [for finding distance in } t \text{ time]}$$

$$\frac{5 \text{ hour}}{20 \text{ km}} = \frac{1}{4} \text{ hr/km} ; \text{ [for finding time required to cross } d \text{ distance]}$$

Example:

$$A \rightarrow 4 \text{ min/work} = 0.25$$

$$B \rightarrow 5 \text{ min/work} = 0.2$$

$$C \rightarrow 6 \text{ min/work} = 0.167$$

$$D \rightarrow 10 \text{ min/work} = 0.1$$

$$E \rightarrow 12 \text{ min/work} = 0.833$$

i) Avg work per min = ?

ii) How much work in 6 hours per day

∴ The work is done per unit, we will use harmonic mean

$$\therefore H.M = \frac{5}{\frac{1}{4} + \frac{1}{5} + \frac{1}{6} + \frac{1}{10} + \frac{1}{12}} = 0.25 \text{ min/work}$$
$$= 0.16 \text{ work/min (Ans.)}$$

$$\therefore \text{Work in 6 hours} = 0.16 \times 60 \times 60$$
$$=$$

Combine d Mean

$$\begin{array}{|c|} \hline n_1 \\ \hline \bar{x}_1 \\ \hline \end{array}$$

$$\begin{array}{|c|} \hline n_2 \\ \hline \bar{x}_2 \\ \hline \end{array}$$

$$\begin{array}{|c|} \hline n_k \\ \hline \bar{x}_k \\ \hline \end{array}$$

k number of groups containing n_i elements with $\bar{x}_i$ mean

~~∴ They will have com~~

∴ Combined Mean, $\bar{X} = \frac{\sum n_i \bar{x}_i}{\sum n_i}$

Example (6a) :

Given that,

$$n_1 = 100$$

$$n_2 = 80$$

$$\bar{x}_1 = 4570\$$$

$$\bar{x}_2 = 750\$$$

$$\therefore \bar{X} = \frac{n_1 \bar{x}_1 + n_2 \bar{x}_2}{n_1 + n_2} =$$

Given: 6(b)

$$\begin{array}{l} \bar{X}_c = 72 \\ n_1 + n_2 = 100 \\ n_1 = 70 \\ n_2 = 30 \end{array} \left| \begin{array}{l} \bar{x}_1 = \text{something} \\ \bar{x}_2 = ? \end{array} \right.$$

$$\bar{X}_c = \frac{n_1 \bar{x}_1 + n_2 \bar{x}_2}{n_1 + n_2}$$

$$\therefore \bar{x}_2 = \dots$$

Weighted Mean:

$$\bar{X}_w = \frac{\sum w_i x_i}{\sum w_i}$$

* Arithmetic mean but *FANCY* ~

@

Grouped Data

Example: Random sample of 25 from 2 brands
Decide which brand performs better
in average

Hours	1-2	2-3	3-4	4-5	5-6
Type - I	2	4	8	7	4
Type - II	3	6	8	6	2

* Anything that has less deviation is more consistent
∴ DO NOT use this method.

Class	Frequency (f_i)	x_i	$f_i x_i$	$f_i \log x_i$	$\frac{f_i}{x_i}$	Cumulative frequency c.f.
				for arith mean ↑ for geo mean ↑ Harmonic mean ↑ Median ↑		
				No approximation is allowed BUT keep upto 3 digits i.e. $1.99999 \approx 1.999$		
Total	$N =$		$\sum f_i x_i$	$\sum f_i \log x_i$	$\sum \frac{f_i}{x_i}$	

* Always,

$$A.M > G.M > H.M$$

* Median class is the class with half of the total frequency

Consumption of fuel (lit/hr.)	Number of observations (f_i)	x_i	$f_i x_i$	$f_i \log x_i$	$\frac{f_i}{x_i}$	Cumulative Frequency $\sum f_i$
1-2	2	1.5	3	0.352	1.33	2
2-3	4	2.5	10	1.592	1.6	6
3-4	8	3.5	28	4.352	2.285	14
4-5	7	4.5	31.5	4.572	1.555	21
5-6	4	5.5	22	2.961	0.727	25
Total	$N = 25$		$\sum f_i x_i = 94.5$	$\sum f_i \log x_i = 13.829$		$\sum \frac{f_i}{x_i} = 7.497$

$\therefore$ Arithmetic mean $\bar{x} = \frac{\sum f_i x_i}{N} = \frac{94.5}{25} = 3.78 \text{ lit/hr}$

$\therefore$ Geo. Mean $= \text{Antilog } \frac{1}{N} \sum f_i \log x_i$
 $= \text{Antilog } \left\{ \frac{1}{25} \times 13.829 \right\}$
 $= 3.574 \text{ lit/hr}$

Harmonic mean, $H.M = \frac{N}{\sum \frac{f_i}{x_i}} = \frac{25}{7.497}$

$$= 3.334 \text{ lit/hr.}$$

Here, we have $N = 25$ observations and $N/2$

$$= 25/2 = 12.5$$

Thus, from the table we may decide median class is 3-4.

Therefore, the median is, $M_e = L + \frac{\frac{N}{2} - C.F}{f_m} \times C$

$$= 3 + \frac{12.5 - 6}{8} \times 1$$

$$= 3.8125 \text{ lit/hr.}$$


Here, the class with the maximum number of frequencies is 3-4, which is 8. Thus, 3-4

is our modal class



The mode is, $M_o = L + \frac{\Delta_1}{\Delta_1 + \Delta_2} \times C$

$$= 3 + \frac{8 - 4}{(8 - 4) + (8 - 7)} \times 1 = 3 + 0.8$$

$$= 3.8 \text{ lit/hr.}$$



Order $\longrightarrow$




Relative Positions of the Mean, Median and Mode


Reason of Skewness

- * Extreme values skew the graph
- * Values that are extremely high or extremely low shifts the value towards it.



✳

- * Arithmetic mean is affected by the extreme value in a data set while the median is free from it (- Explain with example)





Measures of Dispersion:



A is more consistent/reliable/steady etc than B

* Two types of measures:

i) Absolute measures

ii) Relative "

- (a) Range (R)
- (b) Mean deviation about mean ($MD, \bar{x}$)
- (c) Quartile deviation (QD)
- (d) Standard " (S)

- (a) Coefficient of range (C.R.)
 - (b) " " " mean deviation about mean ($CMD, \bar{x}$)
 - (c) Coefficient of Quartile deviation (CQD)
 - (d) Coefficient of Standard deviation
- or, Coefficient of Variation (C.V.)

For Ungrouped:

(i)(a) Range = $R = x_H - x_L$; $x_H = \text{highest value}$
 $x_L = \text{lowest value}$

*** (b) Mean deviation about mean

$$MD(\bar{x}) = \frac{\sum |x_i - \bar{x}|}{n}$$

(c) Quantile deviation, $QD = \frac{Q_3 - Q_1}{2}$; $Q_3 = 3^{\text{rd}} \text{ quantile}$
 $Q_1 = 1^{\text{st}} \text{ quantile}$



*** (d) Standard Deviation, $S = \sqrt{\frac{\sum (x_i - \bar{x})^2}{n-1}}$; $\bar{x} = \frac{\sum x}{n}$

$$= \sqrt{\frac{\sum x_i^2 - \frac{(\sum x_i)^2}{n}}{n-1}}$$

→ preferred

For grouped:

(i)(a) No need

*(b) $MD(\bar{x}) = \frac{\sum f_i |x_i - \bar{x}|}{N}$; $N = \sum f_i$
 $\bar{x} = \frac{\sum f_i x_i}{N}$

(c) No need

*** (d) $S = \sqrt{\frac{\sum f_i (x_i - \bar{x})^2}{N-1}} = \sqrt{\frac{\sum f_i x_i^2 - \frac{(\sum f_i x_i)^2}{N}}{N-1}}$
 → preferred

$$2 (i) (a) C.R. = \frac{x_H - x_L}{x_H + x_L} \times 100$$

$$* (b) C.M.D(\bar{x}) = \frac{MD(\bar{x})}{\bar{x}} \times 100$$

$$(c) C.Q.D = \frac{Q_3 - Q_1}{Q_3 + Q_1} \times 100$$

$$* (d) C.V = \frac{s}{\bar{x}} \times 100; s = \text{sample standard deviation}$$

23.0	8.0
22.0	7.0
21.0	6.0
20.0	5.0
19.0	4.0
18.0	3.0
17.0	2.0
16.0	1.0
15.0	0.0
14.0	0.0
13.0	0.0
12.0	0.0
11.0	0.0
10.0	0.0
9.0	0.0
8.0	0.0
7.0	0.0
6.0	0.0
5.0	0.0
4.0	0.0
3.0	0.0
2.0	0.0
1.0	0.0
0.0	0.0

$$\Sigma x = 200, \Sigma x^2 = 2000, \Sigma x^3 = 20000$$

$$s = \sqrt{\frac{\Sigma x^2}{n} - \left(\frac{\Sigma x}{n}\right)^2}$$

#Example: Suppose, the value from strength test on some samples of yarns from different spinning machines are given (in lbs):

from 1st machine:

8.5, 8.5, 8.8, 7.8, 7.9, 9.15, 9.0

from 2nd machine:

8.8, 9.2, 8.4, 8.4, 9.2, 9.10, 8.25

Decide which machine looks more reliable regarding their performance variations.

Solⁿ: The calculation table for ~~stand~~ standard deviation is given below (for first machine)

x_i	x_i^2
8.5	72.25
8.5	72.25
8.8	77.44
7.8	60.84
7.9	62.41
9.15	83.7225
9.0	81
$\Sigma x_i = 51.5$	$\Sigma x_i^2 = 509.9125$

$$\Sigma x_i = 51.5 \quad \Sigma x_i^2 = 509.9125$$

∴ the standard deviation for the first spinning machine is,

$$s = \sqrt{\frac{\Sigma x_i^2 - \frac{(\Sigma x_i)^2}{n}}{n-1}} = 4.7636$$

That is, the strengths of yarns are varying by ~~1.75~~ 4.763 lbs from the value of the overall outputs.

Now, the coefficient of variation is,

$$C.V = \frac{s}{\bar{x}} \times 100$$

$$= \boxed{20} 65\%$$

$$= \boxed{20} 65\%$$

That is, the percentage rate of variation of strengths of yarns is 12% for the 1st machine

[Do for 2nd machine]

Regression

* It indicates _____ is working well

Simple linear regression:

$$y = \beta_0 + \beta_1 x + \epsilon$$

x = independent variable
 y = dependent variable
 β_1 = coefficient of x
 β_0 = constant term

ϵ = Error term



$$\hat{\beta}_0 = \bar{y} - \hat{\beta}_1 \bar{x} \quad \left| \quad \hat{\beta}_1 = \frac{\sum x_i y_i - \frac{\sum x_i \sum y_i}{n}}{\sum x_i^2 - \frac{(\sum x_i)^2}{n}} \quad \text{If } \epsilon = 0$$

* Error will happen naturally

#Regression:

Let,

$$X = [\text{data}] \text{ (unit)}$$

$$Y = [\text{data}] \text{ (unit)}$$

The simple linear regression equation is, $\rightarrow$ The formula from last page
The calculation table of regression model/parameters is given below:

X_i	Y_i	X_i^2	Y_i^2	$X_i Y_i$
$\Sigma X_i^2 =$	$\Sigma Y_i =$	$\Sigma X_i^2 =$	$\Sigma Y_i^2 =$	$\Sigma X_i Y_i =$


Thus, the estimates of the regression parameters are,

$$\hat{\beta}_1 = \frac{\Sigma X_i Y_i - \frac{\Sigma X_i \Sigma Y_i}{n}}{\Sigma X_i^2 - \frac{(\Sigma X_i)^2}{n}} = [\quad]$$

$$\hat{\beta}_0 = [\quad]$$

∴ The regression model is,

$$y = \dots + \dots x$$



Standard Error of the Estimate:

The measure of the dispersion or scatter of the observed values (sample observations) around the estimated regression line.

$$S_{yx} = \sqrt{\frac{\sum (y_i - \hat{y}_i)^2}{n-2}} = \sqrt{\frac{\sum y_i^2 - \hat{\beta}_0 \sum y_i - \hat{\beta}_1 \sum x_i y_i}{n-2}}$$

* * *

↪ preferred

$$= \sqrt{MSE} = \sqrt{\text{Mean Square Error}}$$

Coefficient of Determination

The amount of variation in the response variable (y) that can be explained by the variation of independent variable (x).

$$R^2 = \frac{RSS}{TSS} = 1 - \frac{ESS}{TSS}; \quad \begin{matrix} RSS = \text{Regression sum square} \\ ESS = \text{Error sum of square} \end{matrix}$$

* * *

↪ preferred

Here, $TSS = RSS + ESS$ $0 \leq R^2 \leq 1$
 where, $TSS = \text{Total sum of square} = \sum (y_i - \bar{y})^2 = \sum y_i^2 - \frac{(\sum y_i)^2}{n}$


Probability

*Ask P

- * Randomness = uncertain outcome
- * Variables used in probability are called Random Variables
- * Sample Space: Set of all possible outcomes. $\rightarrow S$
- * Event: Subset of sample space ~~for from~~ that contains required outcomes.
- * Discrete: Individual
- Continuous: Between
- * Mutually Exclusive: Two or more events with no common event
 $\rightarrow A \cap B = \emptyset$

Probability:

(old) Let, a random experiment has 'n' outcomes
 A be = any specific characteristic
 n_A = number of outcomes having characteristic 'A'
 $\therefore P(A) = \frac{n_A}{n}$



4th Axioms of Probability:

Let,

a random experiment has 'n' outcomes:

$$A_1, A_2, A_3, \dots, A_n$$

$$(i) \sum P(A_i) = 1$$

$$(ii) 0 \leq P(A_i) \leq 1 \text{ for any } A_i$$

$$(iii) \text{For any two events } A_1 \text{ and } A_2, \text{ if } A_1 \cap A_2 \neq \emptyset, \text{ then,}$$
$$P(A_1 \cup A_2) = P(A_1) + P(A_2)$$

Rules of Solving Problems:

$$(i) \text{Complementary Rule: } P(A) = 1 - P(A')$$

$$(ii) \text{Additional Rule: For any two events } A \text{ and } B,$$

$$P(A \cup B) = P(A) + P(B) - P(A \cap B)$$
$$= P(A) + P(B); \text{ [mutually exclusive]}$$

$$(iii) \text{Conditional Rule: If } A \text{ depends on } B \text{ then,}$$

$$P(A|B) = \frac{P(A \cap B)}{P(B)}; [P(B) \neq 0]$$


$A|B \equiv A \text{ given } B$
 $\uparrow$ depends on

$$(iv) \text{Independence Rule: Any two events } A \text{ and } B \text{ are said to be independent of each other if,}$$

$$P(A \cap B) = P(A) \cdot P(B)$$

$$(v) \text{Bayes' Rule: } P(A_i|B) = \frac{P(A_i) \cdot P(B|A_i)}{\sum P(A_i) P(B|A_i)}$$

$\rightarrow$ total sum



Suppose, in a controlled room, 3 operators are giving commands for ^{completing} a mission. Their previous records say that:

The chances of failures of the three operators are 9%, 12% and 7.5%.

The given mission will be considered completed if the 3 ops work together and each operator is independent of the other two ops.

Find the probability that a newly given mission will be completed successfully by them.

Let,
 A = first operator works successfully
 B = second " " "
 C = third " " "

Given that,
 their failure rates in terms of probability are:

$$P(A') = 0.09, P(B') = 0.12, P(C') = 0.075$$

$$\begin{aligned} \therefore \text{Their success rates} &= P(A) \cdot P(B) \cdot P(C) \\ &= \{1 - P(A')\} \cdot \{1 - P(B')\} \cdot \{1 - P(C')\} \quad [] \\ &= 1 - 0.09 \quad = 1 - 0.12 \quad = 1 - 0.075 \\ &= 0.91 \quad = 0.88 \quad = 0.925 \end{aligned}$$

∴ The probability that the given mission will be completed successfully is,

$$P(A \cap B \cap C) = P(A) \cdot P(B) \cdot P(C)$$

$$= (0.91)(0.88)(0.925); []$$

$$= 0.74074$$

$$= 74.074\% \quad (\text{Ans.})$$

C-21 (w-14)

25/09/24

Actual data

(Ch-2, Ex-2.19)

Contamination	Center	Edge	Total
Low	514	68	582
High	112	246	358
Total	626	314	940

Suppose Si wafers are to setup. In total 582 are of low level contamination, 112 wafers are high but center. There are 314 edge ones.

Suppose one wafer is selected at Random.

Find the probability that

i) IF is located in the edge area or it has low level contamination

(ii) IF is located in the edge area and it has low level contamination

(iii) IF is located in the edge area such that it has low level contamination

(iv) IF is located in the edge area but it has low level contamination

The inform

$$(403)9 - (1)9 + (3)9 = (403)9 - \frac{83}{010} - \frac{833}{010} + \frac{018}{010} =$$

Solⁿ: The in Let,

H = high level contamination

L = low "

C = center area

E = edge "

The information table is,

Contamination Table	Location		Total
	Edge (E)	Centre (C)	
High (H)	246	112	358
Low (L)	68	514	582
Total	314	626	940

Now,

the probability that a randomly selected 9:
wafer is

(i) located in the edge area or it has low level contamination

$$= P(E \cup L) = P(E) + P(L) - P(E \cap L)$$

$$= \frac{314}{940} + \frac{582}{940} - \frac{68}{940} =$$

(ii) Located in the edge and it has low level contamination = $P(E \cap L) = \frac{68}{940} =$

(iii) Located in the edge such it has low level contamination = $P(E|L) = \frac{P(E \cap L)}{P(L)}$
$$= \frac{\frac{68}{940}}{\frac{582}{940}}$$
$$= \frac{68}{582}$$

(iv) [same as (ii)]

* Mont something (Red book): 2.20, 2.22, ~~2.9~~

Exercise: 2.78, 2.77, 2.81,
2.90, 2.94

2-7. Bayes Theorem:

A_1	A_2	A_3
35.%. .01%. error	40.%. 0.011%. error	25.%. 0.012%. error

Suppose there is an error.

Which person has the most probability of doing the error

Solⁿ:

Let,

A_1 = The work is done by the first person

A_2 = " " " " " second "

A_3 = " " " " " third "

and E = The work is error

Given that,

the overall probability of work of the three persons are

$$P(A_1) = 0.35$$

$$P(A_2) = 0.4$$

$$P(A_3) = 0.25$$

The error rates of the ~~the~~ three persons are:

$$P(E|A_1) = 0.0001$$

$$P(E|A_2) = 0.00011$$

$$P(E|A_3) = 0.00012$$

Therefore, the probability that a randomly found error in the work of a given day is done by first person is

$$P(A_1|E) = \frac{P(A_1) \times P(E|A_1)}{\sum P(A_i) P(E|A_i)}$$

$$= \frac{P(A_1) \times P(E|A_1)}{P(A_1)P(E|A_1) + P(A_2)P(E|A_2) + P(A_3)P(E|A_3)}$$

$$= \frac{0.35 \times 0.0001}{(0.35)(0.0001) + (0.4)(0.00011) + (0.25)(0.00012)}$$

3rd Person = $\frac{P(A_3) P(E|A_3)}{1}$

Greatest value

SP Gupta: Ch - 11: 400 $\rightarrow$ 14, 15, 27, 30, 29, 30, 31

sp Gupta: Ch-11: 400 → 14, 15, 27, 30, 31

Exercise $\rightarrow 29, 30, 31$

$$(A|B)_9 > (A)_9$$

$$(A|B)q(A)q + (A|B)q(A)q$$

$$(2A/3) \cdot (2A)^4 +$$

1000.0 x 78.0

$$(1000.0)(1.0) + (1000.0)(72.0) + (31000.0)(75.0) +$$

Probability Distribution

Binomial Distribution Binomial Probability:

Summation of Bernoulli trial is Binomial Distribution

$$f(x) \rightarrow P(x) = \binom{n}{x} p^x q^{n-x}, \quad x = 0, 1, 2, \dots, n$$

n = Trial numbers

x = No. of success

p = Probability of success (from past experience)

q = " " failure

$$\text{and, } p + q = 1$$

$$\text{Mean, } E(x) = np$$

$$\text{Variance, } V(x) = npq$$

Bernoulli Trial:

Trial with only two possible outcomes; expected or failure.

Binomial Distribution:

$$P(x) = f(x) = {}^nC_x p^x q^{n-x}; x = 0, 1, 2, \dots, n$$

where,

n = trial number

x = no. of success

p = probability of success (from prev. experiences)

q = " " failure

and, ~~p~~ $p + q = 1$

Mean: $E(x) = np$

Variance, $V(x) = npq$

} $np > npq$

The chance that a bit transmitted through a digital transmission channel is received in error is 0.1. Also assume that the transmission trials are independent.

If 4 bits are transmitted, find the probabilities that

- (i) Exactly 2 bits will be errors
- (ii) At least 2 bits will " "
- (iii) At best 1 bits " "
- (iv) More than 1 but not more than 3 bits will be errors.
- (v) At best 3 bits will be correct

Solⁿ:

Let,

x be the number of bits received in error which follows a Binomial distribution

Given that,

trial number, $n = 4$

Probability of success, $p = 0.1$

" " failure, $q = 1 - p = 0.9$

Thus,

Probability function is,

$$P(x) = \binom{n}{x} p^x q^{n-x} = \binom{4}{x} (0.1)^x (0.9)^{4-x}; [x = 0, \dots, 4]$$

(i)

∴ The probabilities that,

(i) Exactly 2 bits will be in error

$$= P(2) = {}^4C_2 (0.1)^2 (0.9)^{4-2}$$

(ii) At least 2 bits will be in error

$$= P(x \geq 2) = P(2) + P(3) + P(4)$$

=

=

(iii) At best 1 bits in error

$$= P(x \leq 1) = P(0) + P(1)$$

=

$$= (0.9)^4 + (0.1)(0.9)^3 = 0.9^3(0.9 + 0.1) = 0.9^3(1) = 0.729$$

(iv) More than 1 but less than 3.

$$= P(1 < x \leq 3) = P(2) + P(3)$$

-

(v) Hence,

x is the number of bits received correctly

$\therefore$ Probability of success, $p = 0.9$

$\therefore$ " " failure, $q = 0.1$

$$\therefore P(x) = {}^4C_x (0.9)^x (0.1)^{4-x}, [x = 0, 1, 2, 3, 4]$$

Now,

Probability of at best 3 bits will be received correctly = $P(x \leq 3) = P(0) + P(1) + P(2) + P(3)$

$$= 1 - P(4) =$$

Mark $\rightarrow 3.18,$

$E_x \rightarrow 3.84, 3.87, 3.91$

SP Gupta $\rightarrow 421$ (Ch-12) $\rightarrow 4, 5, 35$

Normal Distribution

$$f(x) = \frac{1}{\sigma\sqrt{2\pi}} e^{-\frac{1}{2}\left(\frac{x-\mu}{\sigma}\right)^2}$$

Here,

$$\text{Mean, } E(x) = \mu ; \quad [-\infty < \mu < \infty]$$

$$\text{Variance, } V(x) = \sigma^2 ; \quad 0 < \sigma^2 < \infty$$

$$\text{Standard deviation} = \sigma$$


Standard Normal Distribution:

When $\mu = 0$ and $\sigma^2 = 1$, then

then, it is a special case of Normal Distribution,

which is called standard normal distribution.

The variable is z where, $z = \frac{x-\mu}{\sigma}$



$$\int_{-\infty}^{\infty} f(x) dx = 1$$

$$\int_{\mu-\sigma}^{\mu+\sigma} f(x) dx = 0.6827; \mu \pm \sigma \text{ covers } 68.27\% \text{ of area}$$

$$\int_{\mu-2\sigma}^{\mu+2\sigma} f(x) dx = 0.9545; \mu \pm 2\sigma \text{ covers } 95.45\% \text{ of area}$$

$$\int_{\mu-3\sigma}^{\mu+3\sigma} f(x) dx = 0.9972; \mu \pm 3\sigma \text{ covers } 99.72\% \text{ of area}$$

#4.10, 4.13, 4.14

Assume that the current measurements in a strip of wire follow a normal distribution with a mean of 10 milliamperes and variance 4 (mA)

(i) what is the probability that a measurement exceeds 13 mA?

(ii) what is the probability that a current measurement is between 9 and 11 mA?

(iii) Determine the value for which the probability that a current measurement is below this value is 0.98

[Use the stat table]

Mont — 4.15, 4.16
Ex → 4.58, 4.61, 4.62, 4.64, 4.65

Solⁿ:



Let,

x be the current measurement which follows normal distribution

Given that,

mean, $\mu = 10 \text{ mA}$

variance, $\sigma^2 = 4 \text{ mA}$

$\therefore$ Standard deviation, $\sigma = 2 \text{ mA}$

The probability that the current measurement for given a randomly given strip of wire is


(i) Φ will exceed 13 is,

$$P(x > 13) = P\left(\frac{x - \mu}{\sigma} > \frac{13 - \mu}{\sigma}\right)$$

$$= P(z) = P(z > 1.5) = 1 - P(z < 1.5)$$

$$= 1 - 0.9332$$

$$= 0.0668$$




(ii) between 9 and 11

$$P(9 < x < 11) = P(-0.5 < z < 0.5)$$

$$= P(z < 0.5) - P(z < -0.5)$$

$$= 0.6915 - 0.3085$$

$$= 0.3830$$



(iii) the value for which the probability that a current is below the value is 0.98

$$z = 2.05$$

$$\text{or, } \frac{x - \mu}{\sigma} = 2.05$$

$$\therefore x = 14.1 \text{ mA}$$

$$(z > 2.05) = 1 - 0.98 = 0.02$$

$$0.02 = 0.0233$$

$$0.02 = 0.0233$$

