The first European Web3 Hackathon is Here
Master Z. | IOTA
February-March 2026
APPLY NOW
100% Online

idea≠solve a problem

ideas ➡ problems

Problems ➡ MVPs

YOUR FIRST GOAL

your first goal in this hackathon, in order to move to the evaluation phase, is to build a simple MVP integrating one IOTA service:

- Digital Identity
- Supply Chain
- Notarization
- Tokenization

The MVP must be deployed on IOTA Mainnet.

What Is an MVP

An MVP (Minimum Viable Product) is:

- the smallest version of a product
- that solves one real problem
- for one specific user

An MVP is not the final product.

It is a learning tool.

What an MVP Is NOT

An MVP is NOT:

- a full platform
- a scalable infrastructure
- a complex architecture
- a feature-rich product

If it feels complete, it’s not an MVP.

Start From the Problem, Not the Tech

Good MVPs start with:

- a real problem
- experienced by real people/companies
- happening today

Bad MVPs start with:

- “Let’s use blockchain”
- “Let’s build something cool”
- “Let’s use all features”

How to Find a Problem to Solve

Ask yourself:

- Who is the user?
- What is slow, expensive, or broken?
- Where is trust missing?
- Where are manual checks still used?
- Where do people rely on intermediaries?

If the problem exists without blockchain, it’s a good sign.

One Problem, One User

For your MVP:

- choose one user
- choose one problem
- choose one action

Example:

“Verify a document”

NOT

“Manage all company documents”

One Problem, One User

For your MVP:

- choose one user
- choose one problem
- choose one action

Example:

“Verify a document”

NOT

“Manage all company documents”

Match the Problem to IOTA Services

When to Use Digital Identity

Use IOTA Digital Identity when:

- identity verification is required
- trust between parties is missing
- credentials must be verifiable
- privacy and user control matter

Example:

- diploma verification
- KYC credentials
- access permissions

When to Use Tokenization

Use IOTA Tokenization when:

- you represent ownership
- you manage assets or rights
- you need transferability
- you need programmable value

Example:

- asset certificates
- licenses
- vouchers
- carbon credits

When to Use Notarization-Proof of existance

Use IOTA Notarization when:

- data must be immutable
- timestamps matter
- proof of existence is required
- auditability is needed

Example:

- document hash anchoring
- contract proof
- event logs

Visualizing a Simple MVP

A simple MVP can be:

- 1 user flow
- 2–3 screens
- 1 smart contract or on-chain action
- simple UI + working backend

No dashboards. No admin panels.

MVP Architecture Rule

Your MVP architecture should:

- be understandable in 1 minute
- fit on 1 slide
- use the minimum number of components

If you need a diagram legend, it’s too complex.

Common MVP Mistakes

- adding features “just in case”
- using multiple IOTA services together
- optimizing performance too early
- thinking about scale before validation

The MVP Mindset

Your goal is to answer one question:

- “Does this solution solve a real problem?”

Not:

- Is it scalable?
- Is it perfect?
- Is it production-ready?