

The DFI Engine, a Data Flow Graph Paradigm Implementation with Imperative Encapsulation in Isolated Stateful Nodes.

D. Yashenkin
dmitryy@mailfence.com

Introduction

The Data-flow Graph (DFG) paradigm (discrete time, clocked synchronous, modular, data-centric) is a declarative pure functional paradigm. It is used to model the flow of data through a system. It is useful in fields such as computer science, engineering, and data analysis. For example, neural networks are data-flow graphs. Below is a very simplified illustration of the DFG paradigm, covering its structure.




Figure 1. DFG system visual representation example.

As many other information systems, DFG-based system performs transformation of input data into the output data (computation results). This all is done by using computational nodes connected by data-transferring edges, where nodes represent operations and edges represent the data dependencies between operations (Fig. 1). The visual description in terms of data flow graphs, made up of computational component "boxes" or "cells" (operations) connected by "wires" (variables). It visually depicts how data moves through different processes or operations, making it easier to understand and analyze complex systems. A characteristic feature is that computations intended to act on whole streams are written as if they were to act on one element at a time. This structure allows for parallel execution and optimization of the computational process. For many computation problems a static mapping from input to output values is not sufficient; outputs need to change over time according to corresponding changes in inputs and/or internal state. At the Figure 1, just a minimalistic schema is given to get the idea. In the real working applications, complexity and the size of such schemes could be much larger.

Key Concepts

Nodes and Edges:

Nodes ("boxes", "cells"): represent operations, processes, or data storage elements. Each node performs a specific function or computation.

Edges ("wires"): represent the data flow between nodes. An edge from node A to node B indicates that the output of A is used as input for B.

Each node can have zero or more inputs and exactly one output. A schema in the data flow programming paradigm is a directed graph resembling an inverted tree, where the roots located at the end of the data flow are the decisions, and the branches located at the beginning receive the input data. In this case, each of the trees responsible for a certain sub task can intersect with other trees in terms of data, have nodes looped on themselves and, in the

general case, receive data from arbitrary sources, each of which, however, can only be the output of any of the nodes of the current diagram. Each of the computational components - the nodes of the graph - is depicted as a black box that has only one output and, being connected to the outputs of other computational elements, receives an arbitrary number of input values. In this case, the computational element, knowing the type, source and meaning of each of its arguments, operates in its computational block with the actual values supplied from the outputs of other elements. A characteristic feature of this representation is the implicit assumption that the computation of the entire flow must occur element by element, and the memory of the values of previous elements is stored automatically using short-term memory components (either in the black boxes themselves or in the "wires"), which, unlike other components, do not imply instantaneous data transfer.

Applications

Applications range from reactive systems, embedded in a context with user input devices, sensors or communication channels, to processors and generators of time-series data, such as audio signals or dynamic simulations in numerous branches of science and engineering.

Programming Languages. DFGs are used in compilers to optimize code by analyzing data dependencies and determining the most efficient order of operations.

Digital Signal Processing (DSP). In DSP, DFGs help visualize the flow of signals through various processing stages, aiding in the design and analysis of algorithms.

Software Engineering. DFGs can be used to model the flow of data in software applications, helping developers understand how data is transformed and passed through different components.

Machine Learning. In machine learning frameworks (like TensorFlow), DFGs represent the flow of data through various layers of a neural network, illustrating how inputs are transformed into outputs.

Robotics & Autonomous Systems. High-throughput signal processing, sensor fusion, and driving actuators in real time.

Industrial Automation. Replacing heavy PLC logic with portable C++ integrations.

Edge Computing / IoT. Orchestration of distributed controllers without centralized message brokers.

Simulations & Digital Twins. Logical linking of separately attached hardware or virtual devices.

Advantages

- Clear visual representation of data flow, making it easier to understand complex systems.
- The data flow graph of the model, is more illuminating with respect to concrete algorithmic details.
- By analyzing the flow of data, developers can identify bottlenecks and optimize performance.
- Extending schema to solve more complex problem can be achieved without modifications of the existing schematic
- Integration of some solutions is done by just connecting it proper by "wires".
- Parallel processing by highlighting independent operations that can be executed simultaneously.

Challenges

- Regular, inverse tree-shaped data flow is far more clumsy than in term notations, in particular when non-commutative operators are concerned.
- There is no canonical concept for control issues, such as branching, mode transition, self-configuration, initialization. In terms of data structures, product shape is well-supported, whereas co-product shape is not. It is no coincidence that practical systems often provide a distinct, not fully integrated language layer for this purpose.
- The view is heavily biased towards numeric data and operations; their symbolic counterparts, essential for complex and high-level applications, are treated quite poorly.

The DFI Engine Programming Language – Implementation.

The primary goal was to create a scripting language with a simple, understandable, familiar syntax, based on a declarative data-flow paradigm for concurrency, easily extensible from within host application. The DFI language interpreter is a software library written in C++ that provides the API for embedding into a C++ applications. It was created to be light-weight for embeddability, very easy extensible from within C++, to have zero dependencies from 3-rd party compiler tools and to be complete hardware platform independent. Hardware platform independence is achieved by compiling the script source code into a tree-like execution structure, so neither a virtual machine nor translation into machine code is needed. Declarative Data Flow Graph paradigm is pure functional but presented data flow implementation is partially stateful (which has not impacted the concurrency) providing host application-defined language extensions, side effects and tracking of state. And since the language dictates the global structure of data flows, and the elements are programmed imperatively, there is also control flow at the "micro level", at the level of computation elements bodies contents. Because of possible resulting solution schematic representation complexity, the current implementation's aim is to maximize definition simplicity for the language building blocks. The language building blocks includes: **Cell Template**, **Cell (corresponds DFG Node)** and **Function**. The cell (computation cell) is also called **Computational Element**, **Computational Node**. DFG approach is achieved by the ability to instantiate computation nodes from templates and connect them to each other by passing instances names as the arguments to other instances. Besides this, nothing else needs to be done – after the program is launched, all elements will automatically execute cyclically, receiving updated output values from other elements to which they are connected with each new execution. As the example, we can create possible implementation for the **Figure 1** provided at the very first page of this document:

```
// ----- cells templates -----
duplicate(a) { return a * 2; }
square(a) { return a * a; }
sum(a1, a2) { return a1 + a2; }
mul_add(a1, a2, a3) { return a1 * a2 + a3; }
rnd_gen() { return frand() * 100; } // frand() function provided by C++ host application

// ----- cells instances -----
// input cell instances
'Input_1' Input_1;
'Input_2' Input_2;

// working cell instances
rnd_gen Gen_1();
duplicate Proc_1(Input_1);
square Proc_2(Input_2);

// working cells instances exposed to a host application as outputs
sum Proc_3(Proc_2, Gen_1) 'Output_1';
mul_add Proc_4(Proc_1, Proc_2, Proc_3) 'Output_2';
```

The language has similar to JavaScript case-sensitive syntax so **ID1** and **id1** are different names. Computation cells can deal with built-in integral and floating-point **numeric** types, **strings**, **character** types, **boolean** type, **objects**, **arrays**, **vec4** and **mat4** types. In addition, it is possible to extend language from within C++ code of the host application with **functions** and **user objects** and their bound **methods**. So, in the code above, the **Input_1** and **Input_2** elements are the input elements whose values are available to be set from the C++ code by names **'Input_1'** and **'Input_2'** respectively.

The element named **Proc_1** is an instance of the template **duplicate** which on input accepts value from **Input_1**, the element **Proc_2** is an instance of the template **square** which on input accepts value from **Input_2**, the element **Proc_3** is an instance of the template **sum** accepting on input two values – one from **Proc_2** and another from **Gen_1**, the element **Proc_4** is an instance of the template **mul_add** accepting on input three values – from **Proc_1**, from **Proc_2** and from **Proc_3**, and finally, the element **Gen_1** is an instance of the template **rnd_gen** that does not accept parameters just generating random value in [0..99] range.

The **Proc_2** and **Proc_3** cells are the output cells visible from outside the language runtime (visible from embedding C++ code) by names **'Output_1'** and **'Output_2'**.

Each template for the cells accept the same number of the arguments as the instantiated cell of that template. In programming, this known as formal and actual parameters (formal params are in the template, actual are in the cell instance and they must match). For example, **Proc_3** cell accepts two inputs and corresponding **sum** template also has two parameters. The order of the parameters also matters, so you have to know sequence and meaning of the arguments during instantiation.

Note that every element and element template is forward-declared so we can use element name before the definition of it. Also we are free to move all the template definitions to the end of file, after cells definitions. Or we can instantiate cell by template right after that template definition. In simple words, you can make a complete mess of definitions inside your code if you wish (and it will work correctly being correctly implemented besides the absence of the beauty of code).

Template body, when encloses just one statement, allowed to omit curly braces.

So let's have some fun rewriting the initial program using a new knowledge about the language code structure:

```
'Input_1' Input_1;
'Input_2' Input_2;
rnd_gen Gen_1();
duplicate Proc_1(Input_1);
square Proc_2(Input_2);
sum Proc_3(Proc_2, Gen_1) 'Output_1';
mul_add Proc_4(Proc_1, Proc_2, Proc_3) 'Output_2';
////////////////////////////////////
duplicate(a) return a * 2;
square(a) return a * a;
sum(a1, a2) return a1 + a2;
mul_add(a1, a2, a3) return a1 * a2 + a3;
rnd_gen() return frand() * 100;
```

Now the cells definitions are placed first, and the cell templates are at the end of the file for readability. This might be useful when, opening file in text editor, we first want to see a computational elements interconnections, without necessity of scrolling text of the program skipping the templates – they are just the implementation details and we don't need to deep dive into the templates code.

Another thing to be mentioned is a state of the computational elements. Since DFI language is not pure functional, computational elements may have a *state* and *side effects*. The state of the element is implemented in the form of access to the internal fields of the elements using keyword **this**. Initially, cell has no fields. Assigning values to a names within **this** scope is performed using dot notation. Side effects are possible through the calls to the functions with side-effect (such as I/O functions) from the template bodies. Now, rewrite a program to demonstrate usage of state and side effects:

```

// input cell instances
'Input_1' Input_1;
'Input_2' Input_2;
// cell templates
stateful_transform(a) {
    if(this.stored_val == undefined) this.stored_val = 0;
    this.stored_val = (this.stored_val + a) % 10;
    return this.stored_val * 2;
}
square(a) return a * a;
sum(a1, a2) return a1 + a2;
muladd(a1, a2, a3) return a1 * a2 + a3;
rnd_gen() return rand() % 10;
// cell instances
stateful_transform Proc_1(Input_1);
square Proc_2(Input_2);
rnd_gen Gen_1();
sum Proc_3(Proc_2, Gen_1) 'Output_1'; // output 1
muladd Proc_4(Proc_1, Proc_2, Proc_3) 'Output_2'; // output 2
// cell template
print_val(label, val) println(label, val); // side effect in form of console output
// cell instances
print_val Prn_3("Proc_3: ", Proc_3);
print_val Prn_4("Proc_4: ", Proc_4);

```

Possible output:

```

Proc_3: 3
Proc_4: 15
Proc_3: 3
Proc_4: 15
Proc_3: 8
Proc_4: 24
Proc_3: 14
Proc_4: 28
Proc_3: 3
Proc_4: 13
Proc_4: 13
Proc_3: 10
Proc_4: 310
Proc_3: 3
Proc_4: 15
Proc_3: 29
Proc_4: 79

```

```
Proc_3: 17
```

```
Proc_4: 35
```

```
Proc_3: 36
```

```
...
```

In this example, we can see both the state usage and the side effects. **Proc_1** is now an instance of the **stateful_transform** template. Inside the body of that template definition, **stored_value** field is used to keep value between computation cycles. Value stored in that field is used together with an argument to form returned value. Each computational cycle that field value is updated in addition. A **print_val** template instantiated by **Prn_3** and **Prn_4** cells prints their respective input values to the console calling build-in function **println**.

C++ Integration

To integrate the DFI Engine interpreter capabilities into your C++ application, you need to include header file defining DFI Engine language runtime, create an instance (stack or heap) of the `dfi::runtime` class, load one or more files/strings containing the source code for your DFI Engine program and call method `run_mt()` of the runtime object.

File first_example.dfi

```
duplicate(a) return a * 2;
square(a) return a * a;
sum(a1, a2) return a1 + a2;
mul_add(a1, a2, a3) return a1 * a2 + a3;
rnd_gen() return frand() * 100;
'Input_1' Input_1;
'Input_2' Input_2;
rnd_gen Gen_1();
duplicate Proc_1(Input_1);
square Proc_2(Input_2);
sum Proc_3(Proc_2, Gen_1) 'Output_1';
mul_add Proc_4(Proc_1, Proc_2, Proc_3) 'Output_2';
```

File first_example.cpp

```
#include <iostream>
#include <thread>
#include <chrono>
#include <dfi_runtime.hpp>

int main(int argc, char **argv) {
    dfi::runtime rt{};

    // load the eample file
    rt.load_file("first_example.dfi");
    // signal runtime that loading of files is finished
    rt.loading_complete();

    // start execution of the runtime asynchronously in multi-threaded
    // mode with threads number equal to host's CPU cores
    rt.run_mt(std::thread::hardware_concurrency());

    // update inputs for runtime and read outputs from it displaying in console
    while(!rt.termination_requested()) {
        rt.set_input("Input_1", rand() % 1000);
        rt.set_input("Input_2", rand() % 1000);

        std::this_thread::sleep_for(std::chrono::milliseconds{500});
    }
}
```

```

        std::cout << "Output_1 = " << rt.get_output("Output_1") << std::endl;
        std::cout << "Output_2 = " << rt.get_output("Output_2") << std::endl;
    }

    return 0;
}

```

In this small but complete example, C++ (host) application creates instance of the DFI Engine runtime, feed it the "first_example.dfi" file containing DFI Engine code and executes it in multi-threaded mode (synchronous single-threaded mode applicable in some cases is available also).

Extending from C++ Host Code

Adding Functions

File func_injection.cpp

```

#include <iostream>
#include <thread>
#include <chrono>
#include <unistd.h>
#include <dfi_runtime.hpp>

int main(int argc, char **argv) {
    dfi::runtime rt{};

    // function being injected into the runtime to be available in scripts
    rt.add_function("hostname", DFIFUN(fname, args) {
        std::vector<char> hostname{};
        hostname.resize(2048);
        if(gethostname(&hostname[0], hostname.size() - 1) != 0) {
            return std::string{};
        }
        return std::string{hostname.data()};
    });

    // injecting a function with an argument
    rt.add_function("square", DFIFUN(fname, args) {
        return args[0] * args[0];
    });

    rt.load_file("func_injection.dfi");
    rt.loading_complete();

    rt.run_cycle();

    return 0;
}

```

File func_injection.dfi

```

function_injection_test() {
    println("host name: ", hostname());
    println("34.51 squared = ", square(34.51));
}

function_injection_test test();

```

Output:

```

host name: carbon
34.51 squared = 1190.94

```

Adding Object

File object_injection.cpp

```
#include <iostream>
#include <thread>
#include <chrono>
#include <unistd.h>
#include <dfi_runtime.hpp>

class my_obj {
public:
    std::string name() const { return name_; }
    void set_name(std::string const &n) { name_ = n; }

private:
    std::string name_{"default name"};
};

int main(int argc, char **argv) {
    dfi::runtime rt{};

    // object factory function
    rt.add_function("my_obj", DFIFUN(fname, args) { return dfi::valbox{my_obj{}}, "my_obj"; });
    // getter
    rt.add_method("my_obj", "name", DFIFUN(fname, args) {
        return args[0].as_class<my_obj>().name();
    });
    // setter
    rt.add_method("my_obj", "set_name", DFIFUN(fname, args) {
        args[0].as_class<my_obj>().set_name(args[1].cast_to_string());
        return args[1].cast_to_string() == args[0].as_class<my_obj>().name();
    });
    rt.load_file("func_injection.dfi");
    rt.loading_complete();

    rt.run_cycle();

    return 0;
}
```

File object_injection.dfi

```
object_injection_test() {
    o = my_obj();
    println("default object name: \", o.name(), "\");
    o.set_name("new name");
    println("new object name: \", o.name(), "\");
    o.set_name(29);
    println("numeric object name: \", o.name(), "\");
}

object_injection_test test();
```

Output:

```
default object name: "default name"
new object name: "new name"
numeric object name: "29"
```

This examples shows how easy it is to extend the capabilities of a scripting language using C++ code.

Examples

Example 1.

Consider an extremely simplistic example of a data flow for calculating a mathematical expression like:

$$z = (x + y) \times (a - b)$$

Computation nodes:

Node 1: Addition ($x + y$)

Node 2: Subtraction ($a - b$)

Node 3: Multiplication ($(x + y) * (a - b)$)

Edges:

An edge from Node 1 to Node 3 (output of addition to multiplication).

An edge from Node 2 to Node 3 (output of subtraction to multiplication).

In proposed language, this might be implemented as following:

Listing 1. The Example 1 implementation.

```
plus(arg1, arg2) return arg1 + arg2;
minus(arg1, arg2) return arg1 - arg2;
multiply(arg1, arg2) return arg1 * arg2;
'x' x;
'y' y;
'a' a;
'b' b;
plus node1(x, y);
minus node2(a, b);
multiply node3(node1, node2) 'z';
```

Here the “plus”, “minus” and “multiply” are implemented only for demonstration purposes cause everything could be done in a single template.

Example 2.

Another example is a quadratic equation:

$$ax^2 + bx + c = 0$$

the roots of equation are:

$$x = \frac{-b \pm \sqrt{D}}{2a}$$

where

$$D = b^2 - 4ac$$

We can write the following code to solve that equation in DFI Engine:

Listing 2. The Example 2 implementation.

```
// cell templates
discriminant(a, b, c) return pow(b, 2) - 4.0 * a * c;
x1_tmpl(a, b, d) return d >= 0 ? (-b + sqrt(d)) / (2.0 * a) : undefined;
x2_tmpl(a, b, d) return d > 0 ? (-b - sqrt(d)) / (2.0 * a) : undefined;
num_of_roots(d) return d > 0 ? 2 : d == 0 ? 1 : 0;
// input cells
'a' a;
'b' b;
'c' c;
// worker cells
discriminant d(a, b, c);
x1_tmpl x1(a, b, d) 'x1'; // \
x2_tmpl x2(a, b, d) 'x2'; // ) workers exposed as outputs
num_of_roots nr(d) 'num_roots'; // /
```

Example 3.

Here is more complex example, communication channel controlling script. This will show logical links between different type of values – numeric and boolean. Communicational channel includes two or more participants. In order to correctly use system resources (sockets, CPU time, memory) channel should be managed properly (closed when needed to release resources being consumed for it's work).

Listing in language:

Listing 3. The Example 3 implementation.

```
// templates
abandoned(num_connected, initiator_was_connected) {
    return num_connected == 0 && initiator_was_connected;
}
nobody_invited_long_time(
    num_invited_not_declined,
    users_disposition_changed_timeout,
    max_timeout_to_invite
) {
    return num_invited_not_declined < 2 &&
        users_disposition_changed_timeout > max_timeout_to_invite;
}
initial_waiting_for_answer(
    answered,
    num_connected,
    initiator_connected_now,
    call_duration,
    max_initial_answer_awaiting_seconds
) {
    return num_connected == 1 && initiator_connected_now &&
        call_duration <= max_initial_answer_awaiting_seconds &&
        !answered;
}
initial_waiting_for_answer_too_much(
    num_connected,
    initiator_connected_now,
    answered,
    call_duration,
    max_initial_answer_awaiting_seconds
) {
    return num_connected == 1 &&
        initiator_connected_now &&
        !answered &&
        call_duration > max_initial_answer_awaiting_seconds;
}
one_is_waiting_for_answer_in_group_normally(
    num_connected,
    answered,
    is_group_channel,
    users_disposition_changed_timeout,
    max_initial_answer_awaiting_seconds
) {
    return num_connected == 1 && answered &&
        is_group_channel &&
```

```

        users_disposition_changed_timeout <= max_initial_answer_awaiting_seconds;
    }
    one_is_waiting_for_answer_in_group_too_much(
        num_connected,
        answered,
        is_group_channel,
        users_disposition_changed_timeout,
        max_initial_answer_awaiting_seconds
    )
    return num_connected == 1 && answered && is_group_channel &&
        users_disposition_changed_timeout > max_initial_answer_awaiting_seconds;
    alone_caller_left_in_nongroup(
        num_connected,
        answered,
        is_group_channel,
        users_disposition_changed_timeout,
        max_single_call_disconnect_gap_seconds
    ) {
        return num_connected == 1 && answered &&
            !is_group_channel &&
            users_disposition_changed_timeout > max_single_call_disconnect_gap_seconds;
    }
    regular_conversation(num_connected) {
        return num_connected > 1;
    }
    can_channel_continue_working(
        regular_conversation,
        initial_waiting_for_answer,
        one_is_waiting_for_answer_in_group_normally,
        alone_caller_left_in_nongroup,
        abandoned,
        one_is_waiting_for_answer_in_group_too_much,
        initial_waiting_for_answer_too_much,
        nobody_invited_long_time
    ) {
        return (regular_conversation || initial_waiting_for_answer || one_is_waiting_for_answer_in_group_normally) &&
            !alone_caller_left_in_nongroup && !abandoned && !one_is_waiting_for_answer_in_group_too_much &&
            !initial_waiting_for_answer_too_much && !nobody_invited_long_time;
    }
    should_channel_shutdown(
        abandoned, one_is_waiting_for_answer_in_group_too_much, alone_caller_left_in_nongroup,
        initial_waiting_for_answer_too_much, nobody_invited_long_time
    ) {
        return abandoned || one_is_waiting_for_answer_in_group_too_much ||
            alone_caller_left_in_nongroup ||
            initial_waiting_for_answer_too_much ||
            nobody_invited_long_time;
    }

    // input cells
    'connected_users_count' num_connected;
    'invited_not_declined_count' num_non_decliners;
    'call_duration' call_duration;
    'users_disposition_changed_timeout' usrs_changes_timeout;

```

```

'initiator_was_connected' init_was_conn;
'initiator_connected_now' init_is_conn;
'answered' answered;
'is_group_channel' is_grp;
'max_initial_answer_awaiting_seconds' max_1st_ans_wait_sec;
'max_timeout_to_invite' invite_timeout;
'max_single_call_disconnect_gap_seconds' disconn_gap_sec;

// worker cells
abandoned abandoned(num_connected, init_was_conn);
nobody_invited_long_time nobody_inv_lt(num_non_decliners, usrs_changes_timeout, invite_timeout);
initial_waiting_for_answer init_wait_answr(answered, num_connected, init_is_conn,
                                           call_duration, max_1st_ans_wait_sec) 'initial_waiting_for_answer';
initial_waiting_for_answer_too_much init_wait_answr_toomuch(num_connected, init_is_conn, answered,
                                                           call_duration, max_1st_ans_wait_sec);
one_is_waiting_for_answer_in_group_normally one_waiting_norm(num_connected, answered, is_grp,
                                                             usrs_changes_timeout, max_1st_ans_wait_sec);
one_is_waiting_for_answer_in_group_too_much one_waiting_too_much(num_connected, answered, is_grp,
                                                                usrs_changes_timeout, max_1st_ans_wait_sec);
alone_caller_left_in_nongroup alone_nongroup(num_connected, answered, is_grp,
                                              usrs_changes_timeout, disconn_gap_sec);
regular_conversation is_regular(num_connected);
can_channel_continue_working can_channel_continue_working(is_regular, init_wait_answr, one_waiting_norm, alone_nongroup,
                                                         abandoned, one_waiting_too_much, init_wait_answr_toomuch, nobody_inv_lt);
should_channel_shutdown should_shutdown(abandoned, one_waiting_too_much, alone_nongroup,
                                         init_wait_answr_toomuch, nobody_inv_lt ) 'should_channel_shutdown';

```

Example 4.

Now let's try to implement logic of the 74181, a 4-bit slice arithmetic logic unit (ALU), implemented as a 7400 series TTL integrated circuit to ensure this is possible case of use for language. The logic for this integrated circuit is as following:




Figure 2. ALU 74181 logic.

In this code, cells templates representing logic gates operating on boolean values.
Listing:

Listing 4. The Example 4 implementation.

```
not(a) return !a;
buf(a) return a && a;
and2(a, b) return a && b;
and3(a, b, c) return a && b && c;
and4(a, b, c, d) return a && b && c && d;
and5(a, b, c, d, e) return a && b && c && d && e;
nand2(a, b) return !(a && b);
```

```

nand3(a, b, c) return !(a && b && c);
nand4(a, b, c, d) return !(a && b && c && d);
nand5(a, b, c, d, e) return !(a && b && c && d && e);
or2(a, b) return a || b;
or3(a, b, c) return a || b || c;
or4(a, b, c, d) return a || b || c || d;
nor2(a, b) return !(a || b);
nor3(a, b, c) return !(a || b || c);
nor4(a, b, c, d) return !(a || b || c || d);
xor2(a, b) return a ^ b;
xor3(a, b, c) return a ^ b ^ c;
xor4(a, b, c, d) return a ^ b ^ c ^ d;
xnor2(a, b) return !(a ^ b);
xnor3(a, b, c) return !(a ^ b ^ c);
xnor4(a, b, c, d) return !(a ^ b ^ c ^ d);
i2or2(a, b) return !a || !b;

scale_factor(v) return v;
ray_window() {
    if(!this.win_created) {
        ray_init_window(1422, 800, "ALU 74181");
        ray_set_target_fps(30);
        ray_begin_drawing();
        ray_clear_background(Color(0, 0, 0, 255));
        this.win_created = true;
    }
    if(ray_window_should_close()) {
        ray_end_drawing(); ray_close_window();
        return 0;
    }
    if(ray_get_key_pressed() == 300) {
        ray_toggle_full_screen();
    }
    ray_end_drawing();
    ray_begin_drawing();
    ray_clear_background(Color(0, 0, 0, 255));
    return this.win_created;
}

color_select() return Color(0x29, 0xae, 0x9cc, 255);
color_in() return Color(0x64, 0xff, 0x9f, 255);
color_out() return Color(0x1e, 0xed, 0x00, 255);
color_carry() return Color(0xfe, 0x24, 0x02, 255);
color_pgeq() return Color(0x9e, 0xdb, 0x00, 255);
draw_bool(v, x, y, f, lbl, crclr) {
    rctclr = Color(64, 64, 64, 255);
    rcdclr = Color(32, 32, 32, 255);
    ray_draw_circle(x * f, y * f, 7 * f, v ? crclr : Color(0, 0, 0, 255));
    ray_draw_text(lbl, (x - 9) * f, (y + 11) * f, 15 * f, Color(80, 200, 100, 255));
    ray_draw_line((x - 10.5) * f, (y - 10) * f, (x + 10) * f, (y - 10) * f, rctclr);
    ray_draw_line((x - 10) * f, (y - 10) * f, (x - 10) * f, (y + 10) * f, rctclr);
    ray_draw_line((x + 10.5) * f, (y + 10) * f, (x + 10) * f, (y - 10) * f, rcdclr);
    ray_draw_line((x + 10) * f, (y + 10) * f, (x - 10) * f, (y + 10) * f, rcdclr);
    return v;
}

//////////////////////////////// cells instances //////////////////////////////////
// inputs -----

```

```

'S0' s0;
'S1' s1;
'S2' s2;
'S3' s3;
'A0' a0;
'A1' a1;
'A2' a2;
'A3' a3;
'B0' b0;
'B1' b1;
'B2' b2;
'B3' b3;
'C_in' c_in;
'M' m;

// workers -----
not    alu_0(b3);
not    alu_1(b2);
not    alu_2(b1);
not    alu_3(b0);
not    alu_4(m);
and3   alu_5(b3, s3, a3);
and3   alu_6(a3, s2, alu_0);
and2   alu_7(alu_0, s1);
and2   alu_8(s0, b3);
buf    alu_9(a3);
and3   alu_10(b2, s3, a2);
and3   alu_11(a2, s2, alu_1);
and2   alu_12(alu_1, s1);
and2   alu_13(s0, b2);
buf    alu_14(a2);
and3   alu_15(b1, s3, a1);
and3   alu_16(a1, s2, alu_2);
and2   alu_17(alu_2, s1);
and2   alu_18(s0, b1);
buf    alu_19(a1);
and3   alu_20(b0, s3, a0);
and3   alu_21(a0, s2, alu_3);
and2   alu_22(alu_3, s1);
and2   alu_23(s0, b0);
buf    alu_24(a0);
nor2   alu_25(alu_5, alu_6);
nor3   alu_26(alu_7, alu_8, alu_9);
nor2   alu_27(alu_10, alu_11);
nor3   alu_28(alu_12, alu_13, alu_14);
nor2   alu_29(alu_15, alu_16);
nor3   alu_30(alu_17, alu_18, alu_19);
nor2   alu_31(alu_20, alu_21);
nor3   alu_32(alu_22, alu_23, alu_24);
xor2   alu_33(alu_25, alu_26);
xor2   alu_34(alu_27, alu_28);
xor2   alu_35(alu_29, alu_30);
xor2   alu_36(alu_31, alu_32);
buf    alu_37(alu_26);
and2   alu_38(alu_25, alu_28);
and3   alu_39(alu_25, alu_27, alu_30);

```

```

and4 alu_40(alu_25, alu_27, alu_29, alu_32);
nand5 alu_41(alu_25, alu_27, alu_32, alu_31, c_in);
nand4 alu_42(alu_25, alu_27, alu_32, alu_31)      'P';
and5 alu_43(c_in, alu_31, alu_32, alu_27, alu_4);
and4 alu_44(alu_32, alu_27, alu_32, alu_4);
and3 alu_45(alu_27, alu_30, alu_4);
and2 alu_46(alu_28, alu_4);
and4 alu_47(c_in, alu_31, alu_29, alu_4);
and3 alu_48(alu_29, alu_32, alu_4);
and2 alu_49(alu_30, alu_4);
and3 alu_50(c_in, alu_31, alu_4);
and2 alu_51(alu_32, alu_4);
nand2 alu_52(c_in, alu_4);
nor4 alu_53(alu_37, alu_38, alu_39, alu_40)      'G';
nor4 alu_54(alu_43, alu_44, alu_45, alu_46);
nor3 alu_55(alu_47, alu_48, alu_49);
nor2 alu_56(alu_50, alu_51);
i2or2 alu_57(alu_53, alu_41)                    'C_out';
xor2 alu_58(alu_33, alu_54)                     'f3';
xor2 alu_59(alu_34, alu_55)                     'f2';
xor2 alu_60(alu_35, alu_56)                     'f1';
xor2 alu_61(alu_36, alu_52)                     'f0';
and4 alu_62(alu_58, alu_59, alu_60, alu_61)      'EQ';

```

```

// servicing cells -----
ray_window rwnd();
scale_factor fctr(3.0);
color_select clr_s();
color_in clr_in();
color_out clr_out();
color_carry clr_c();
color_pgeq clr_pgeq();
draw_bool dr_c_in(c_in, 200, 20, fctr, "inC", clr_c);
draw_bool dr_m(m, 240, 20, fctr, " M", clr_in);
draw_bool dr_s0(s3, 20, 20, fctr, "s3", clr_s);
draw_bool dr_s1(s2, 60, 20, fctr, "s2", clr_s);
draw_bool dr_s2(s1, 100, 20, fctr, "s1", clr_s);
draw_bool dr_s3(s0, 140, 20, fctr, "s0", clr_s);
draw_bool dr_a0(a3, 20, 60, fctr, "a3", clr_in);
draw_bool dr_a1(a2, 60, 60, fctr, "a2", clr_in);
draw_bool dr_a2(a1, 100, 60, fctr, "a1", clr_in);
draw_bool dr_a3(a0, 140, 60, fctr, "a0", clr_in);
draw_bool dr_b0(b3, 20, 100, fctr, "b3", clr_in);
draw_bool dr_b1(b2, 60, 100, fctr, "b2", clr_in);
draw_bool dr_b2(b1, 100, 100, fctr, "b1", clr_in);
draw_bool dr_b3(b0, 140, 100, fctr, "b0", clr_in);
draw_bool dr_f3(alu_61, 20, 160, fctr, "f3", clr_out);
draw_bool dr_f2(alu_60, 60, 160, fctr, "f2", clr_out);
draw_bool dr_f1(alu_59, 100, 160, fctr, "f1", clr_out);
draw_bool dr_f0(alu_58, 140, 160, fctr, "f0", clr_out);
draw_bool dr_c_out(alu_57, 200, 160, fctr, "outC", clr_c);
draw_bool dr_p(alu_42, 20, 200, fctr, " P", clr_pgeq);
draw_bool dr_g(alu_53, 60, 200, fctr, " G", clr_pgeq);
draw_bool dr_AeB(alu_62, 120, 200, fctr, "EQ", clr_pgeq);

```

Below is the image displaying script work result. As you can see, only a few lines of code is used for debug drawing that picture (again, which is side-effect). During the execution process, this script randomly changes the input values

and provides calculated output values set depending on input. The main circuit schema logic is directly reflected to the scripting code: each circuit element (from Fig. 2) corresponds to a single element of the script. And each run cycle they do the work of calculating the resulting set of values. This example also shows extendability of the system: in this case RayLib has been used as the extension for the purposes of visualization.




Figure 3. Displaying input/output values of working data flow system emulating ALU74181 logical circuit.

Example 5.

Despite that the proposed implementation language program overall structure is DFG paradigm-based, the individual computing elements templates are programmed with the imperative code. Now is time to see the imperative aspect of the language. Consider such a problem in order to get acquainted with the imperative possibilities of programming computing elements:

Sheldon, Leonard, Penny, Rajesh, and Howard are standing in line at a Double Cola vending machine; there are no other people in line. The first person in line (Sheldon) buys a can, drinks it, and becomes two! The resulting two Sheldons join the back of the line. Then the next person in line (Leonard) buys a can, drinks it, and joins the back of the line as a double, and so on. This process continues ad infinitum.

Write a program that, by a given arbitrary serial step number N, finds which character's copy it is to take a drink at the given step.

Below is the solution for this problem:

Listing 4. The Example 5 implementation.

```
function serialize_tbbt_array(a) {
    res = "[";
    sep = "";
    for(i = 0; i < a.size(); ++i) {
        for(n = 0; n < a[i].num; ++n) {
            res += sep + a[i].name;
            sep = ", ";
        }
    }
    res += "]";
    return res;
}

tbbt(n) {
    if(n > 0) {
        println("Target step number: ", n);
        a = array();
        a[0].name = "Sheldon"; a[0].num = 1;
        a[1].name = "Leonard"; a[1].num = 1;
        a[2].name = "Penny"; a[2].num = 1;
        a[3].name = "Rajesh"; a[3].num = 1;
        a[4].name = "Howard"; a[4].num = 1;
        for(i = 1; i < n; ++i) {
            --a[0].num;
            pf = a[0];
            if(pf.num <= 0) {
                a.pop_front();
            }
            last = a.size() - 1;
            if(a[last].name == pf.name) {
                a[last].num += 2;
            } else {
                t = object();
                t.num = 2;
                t.name = pf.name;
                a.push_back(t);
            }
        }
    }
}
```

```

    }
    println("The character to take a drink at step ", n, " is \"", a[0].name, "\"");
    println("Current queue state: ", serialize_tbbt_array(a));
    println();
} else {
    println("wrong argument: ", n);
}
}
return 0;
}
seq_gen() {
    if(this.curr == undefined) { this.curr = 0; }
    if(this.curr >= 10) { exit(0); }
    return ++this.curr;
}
seq_gen sqg();
tbbt duplicating_beverage(sqg);

```

And the outputs is as follows:

```

Target step number: 1
The character to take a drink at step 1 is "Sheldon"
Current queue state: [Sheldon, Leonard, Penny, Rajesh, Howard]

Target step number: 2
The character to take a drink at step 2 is "Leonard"
Current queue state: [Leonard, Penny, Rajesh, Howard, Sheldon, Sheldon]

Target step number: 3
The character to take a drink at step 3 is "Penny"
Current queue state: [Penny, Rajesh, Howard, Sheldon, Sheldon, Leonard, Leonard]

Target step number: 4
The character to take a drink at step 4 is "Rajesh"
Current queue state: [Rajesh, Howard, Sheldon, Sheldon, Leonard, Leonard, Penny, Penny]

Target step number: 5
The character to take a drink at step 5 is "Howard"
Current queue state: [Howard, Sheldon, Sheldon, Leonard, Leonard, Penny, Penny, Rajesh, Rajesh]

Target step number: 6
The character to take a drink at step 6 is "Sheldon"
Current queue state: [Sheldon, Sheldon, Leonard, Leonard, Penny, Penny, Rajesh, Rajesh, Howard, Howard]

Target step number: 7
The character to take a drink at step 7 is "Sheldon"
Current queue state: [Sheldon, Leonard, Leonard, Penny, Penny, Rajesh, Rajesh, Howard, Howard, Sheldon, Sheldon]

Target step number: 8
The character to take a drink at step 8 is "Leonard"
Current queue state: [Leonard, Leonard, Penny, Penny, Rajesh, Rajesh, Howard, Howard, Sheldon, Sheldon, Sheldon, Sheldon]

Target step number: 9
The character to take a drink at step 9 is "Leonard"
Current queue state: [Leonard, Penny, Penny, Rajesh, Rajesh, Howard, Howard, Sheldon, Sheldon, Sheldon, Sheldon, Leonard, Leonard]

Target step number: 10
The character to take a drink at step 10 is "Penny"
Current queue state: [Penny, Penny, Rajesh, Rajesh, Howard, Howard, Sheldon, Sheldon, Sheldon, Sheldon, Leonard, Leonard, Leonard]

```

Actually, single computation element like **duplicating_beverage** in the above program could be used as the imperative program resembling main() function of the C language. But interaction between the cells forms a computation network which is declarative data flow, functional.

Example 6.

Another example of general purpose computations on a single cell, a Fractal Demo in DFI Engine (adapted from a Wren version by Robert Nystrom):

Listing 5. The Example 6 implementation.

```
fractal_temptate() {
    yMin = -0.2;
    yMax = 0.1;
    xMin = -1.5;
    xMax = -1.1;
    for (yPixel = 0; yPixel < 40; yPixel++) {
        y0 = (yPixel / 40.0) * (yMax - yMin) + yMin;
        for (xPixel = 0; xPixel < 79; xPixel++) {
            x0 = (xPixel / 78.0) * (xMax - xMin) + xMin;
            x = x0; y = y0;
            pixel = ' ';
            for (iter = 0; iter < 80; iter++) {
                xx = x * x - y * y + x0;
                yy = 2.0 * x * y + y0;
                x = xx; y = yy;
                if (x * x + y * y > 4.0) {
                    pixel = " .;+=xX$&"[iter / 8];
                    break;
                }
            }
            print(pixel);
        }
        println();
    }
    exit(); // terminate system execution
    return 0;
}
fractal_temptate fractal_inst();
```

And, of course, the output:



The output is a fractal image rendered using characters. It features a complex, self-similar pattern of characters (dots, plus signs, Xs, and dollar signs) arranged in a roughly triangular shape. The pattern is composed of many small, repeating units that form a larger, intricate structure. The characters are used to represent different parts of the fractal, with some areas being more dense than others. The overall effect is a detailed and visually striking representation of a fractal.

The ability to perform general-purpose computations is the foundation of the operation of computational cells in a data flow processing graph. As is known, any functional programming language hides low-level imperative capabilities under the hood, thanks to which it is possible to describe the solution scheme of a computational problem in a

declarative style. The DFI Engine is a hybrid, partially stateful implementation combining declarative and imperative possibilities in well balanced ratio to allow developer to program a complex schemes keeping program in tight inter-operation with host system.

Example 7.

The following example relates to network synchronization of computing elements located on different nodes of a computer network:

Listing 6. The Example 7 implementation.

```
value_generator() {
    if(steady_clock() > this.last_time + 0.1) {
        this.last_time = steady_clock();
        choice = rand() % 8;
        if(choice == 0) this.res = rnd_str(rand() % 32 + 1);
        if(choice == 1) this.res = rand() % 100 + 1;
        if(choice == 2) this.res = vec4(randf(), randf(), randf(), randf());
        if(choice == 3) this.res = mat4(
            randf(), randf(), randf(), randf(),
            randf(), randf(), randf(), randf(),
            randf(), randf(), randf(), randf(),
            randf(), randf(), randf(), randf()
        );
        if(choice == 4) this.res = [200.0 * (randf() - 0.5), rnd_str(12)];
        if(choice == 5) { o = object(); o["key"] = 200.0 * (randf() - 0.5); this.res = o; }
        if(choice == 6) this.res = sin;
        if(choice == 7) this.res = timestamp();
        if(choice == 8) this.res = matrix(2, 2, [1,2, 3,4]);
        console.print("original value changed to: ", this.res);
    }
    return this.res;
}

// just a regular cell, no fancy stuff, no effort to expose it
// all the cells are already exposed by the embedded local network server
// inside the Engine Runtime
// and this cell's value is accessed below over the network (TCP/IP)
value_generator just_a_regular_cell();
// value obtained over the network by URL with name "value_from_net".
// in real scenario, localhost will be changed to real host name or IP addr.
// and the name of the value above is mentioned in path part of this URL
//
// in other words, locally-accessible cell "just_a_regular_cell" accessed
// over the network for testing and demo purposes
extern 'dfi://127.0.0.1:43987/just_a_regular_cell' value_from_net;

// the following extern value is an example of network access to the other
// external value resided on other host in the network which is also could
// be an extern value and so on. this way you can create a chain of values
// network alues. this may be used to create network values hubs.
extern 'dfi://127.0.0.1:43987/value_from_net' value_from_net_copy;

ext_print_name_and_value(vname, exv) {
    if(exv != this.exv) {
        this.exv = exv;
        console.print("remote ", typeof(exv), " \'", vname, "\': ", this.exv);
    }
    return 0;
}

ext_print_name_and_value use1("value_from_net", value_from_net);
ext_print_name_and_value use2("value_from_net_copy", value_from_net_copy);
```

The possible output:

```

2026-05-12T22:35:20.566826643+03:00 print: original value changed to: 2026-05-12T22:35:20.566811983+03:00
2026-05-12T22:35:20.567414930+03:00 print: remote timestamp "value_from_net": 2026-05-12T22:35:20.566811983+03:00
2026-05-12T22:35:20.666966303+03:00 print: original value changed to: 76
2026-05-12T22:35:20.667552326+03:00 print: remote timestamp "value_from_net_copy": 2026-05-12T22:35:20.566811983+03:00
2026-05-12T22:35:20.667607399+03:00 print: remote u64 "value_from_net": 76
2026-05-12T22:35:20.668604801+03:00 print: remote u64 "value_from_net_copy": 76
2026-05-12T22:35:20.767354594+03:00 print: original value changed to: {key:94.957056195377657098,}
2026-05-12T22:35:20.768046085+03:00 print: remote object "value_from_net": {key:94.957056195377660401,}
2026-05-12T22:35:20.769069980+03:00 print: remote object "value_from_net_copy": {key:94.957056195377660401,}
2026-05-12T22:35:20.867537815+03:00 print: original value changed to: <function>
2026-05-12T22:35:20.868764452+03:00 print: remote func "value_from_net": <function>
2026-05-12T22:35:20.869910191+03:00 print: remote func "value_from_net_copy": <function>
2026-05-12T22:35:20.967798920+03:00 print: original value changed to: 2026-05-12T22:35:20.967785194+03:00
2026-05-12T22:35:20.968598370+03:00 print: remote timestamp "value_from_net": 2026-05-12T22:35:20.967785194+03:00
2026-05-12T22:35:20.969733494+03:00 print: remote timestamp "value_from_net_copy": 2026-05-12T22:35:20.967785194+03:00
2026-05-12T22:35:21.067911671+03:00 print: original value changed to: mat4{{78.668949, 7.181736, -1.123789, -66.400874},{-44.384543, -85.976441, -34.503501, 22.735861},{73.163806, 38.855588, 87.172866, 11.024429},{75.893685, -42.665274, -4.131100, -25.600740}}
2026-05-12T22:35:21.068565229+03:00 print: remote mat4 "value_from_net": mat4{{78.668949, 7.181736, -1.123789, -66.400874},{-44.384543, -85.976441, -34.503501, 22.735861},{73.163806, 38.855588, 87.172866, 11.024429},{75.893685, -42.665274, -4.131100, -25.600740}}
2026-05-12T22:35:21.069842050+03:00 print: remote mat4 "value_from_net_copy": mat4{{78.668949, 7.181736, -1.123789, -66.400874},{-44.384543, -85.976441, -34.503501, 22.735861},{73.163806, 38.855588, 87.172866, 11.024429},{75.893685, -42.665274, -4.131100, -25.600740}}
2026-05-12T22:35:21.167950819+03:00 print: original value changed to: <function>
2026-05-12T22:35:21.169183350+03:00 print: remote func "value_from_net": <function>
2026-05-12T22:35:21.170368006+03:00 print: remote func "value_from_net_copy": <function>
2026-05-12T22:35:21.268063080+03:00 print: original value changed to: 27
2026-05-12T22:35:21.268835987+03:00 print: remote u64 "value_from_net": 27
2026-05-12T22:35:21.269975298+03:00 print: remote u64 "value_from_net_copy": 27
2026-05-12T22:35:21.368405910+03:00 print: original value changed to: <function>
2026-05-12T22:35:21.369056730+03:00 print: remote func "value_from_net": <function>
2026-05-12T22:35:21.369663920+03:00 print: remote func "value_from_net_copy": <function>
2026-05-12T22:35:21.468558058+03:00 print: original value changed to: 68
2026-05-12T22:35:21.469241928+03:00 print: remote u64 "value_from_net": 68
2026-05-12T22:35:21.470498226+03:00 print: remote u64 "value_from_net_copy": 68
2026-05-12T22:35:21.568625044+03:00 print: original value changed to: <function>
2026-05-12T22:35:21.570088455+03:00 print: remote func "value_from_net": <function>
2026-05-12T22:35:21.571212075+03:00 print: remote func "value_from_net_copy": <function>
2026-05-12T22:35:21.668913466+03:00 print: original value changed to: mat4{{-83.045647, 31.071398, 21.583882, 23.963227},{26.040414, 43.130236, -32.710817, 15.827982},{29.288805, 80.896623, -54.159027, -62.938327},{78.718327, 79.869299, 71.122538, -27.567846}}
2026-05-12T22:35:21.670483727+03:00 print: remote mat4 "value_from_net": mat4{{-83.045647, 31.071398, 21.583882, 23.963227},{26.040414, 43.130236, -32.710817, 15.827982},{29.288805, 80.896623, -54.159027, -62.938327},{78.718327, 79.869299, 71.122538, -27.567846}}
2026-05-12T22:35:21.671616103+03:00 print: remote mat4 "value_from_net_copy": mat4{{-83.045647, 31.071398, 21.583882, 23.963227},{26.040414, 43.130236, -32.710817, 15.827982},{29.288805, 80.896623, -54.159027, -62.938327},{78.718327, 79.869299, 71.122538, -27.567846}}
2026-05-12T22:35:21.768955852+03:00 print: original value changed to: vec4{96.781632, -64.228156, -92.518026, 33.643579}
2026-05-12T22:35:21.770040460+03:00 print: remote vec4 "value_from_net": vec4{96.781632, -64.228156, -92.518026, 33.643579}
2026-05-12T22:35:21.771140282+03:00 print: remote vec4 "value_from_net_copy": vec4{96.781632, -64.228156, -92.518026, 33.643579}
2026-05-12T22:35:21.869009063+03:00 print: original value changed to: <function>
2026-05-12T22:35:21.869952312+03:00 print: remote func "value_from_net": <function>
2026-05-12T22:35:21.871276977+03:00 print: remote func "value_from_net_copy": <function>
2026-05-12T22:35:21.969035956+03:00 print: original value changed to: 91
2026-05-12T22:35:21.969745811+03:00 print: remote u64 "value_from_net": 91
2026-05-12T22:35:21.971271929+03:00 print: remote u64 "value_from_net_copy": 91

```

Here you can see an extern declarations that point to network URL:

```
extern 'dfi://127.0.0.1:43987/just_a_regular_cell' value_from_net;
```

This feature binds a local script variable (`value_from_net`) to a remote cell/node on another DFI Engine engine instance over the network. The syntax cleverly mimics standard C/C++ extern but uses a custom URI scheme instead of a library/object path. This is core concept identified as a transparent network communication / remote variable access mapped onto a data-flow topology introducing **Distributed Data Flow**.

Conclusion

Data Flow Graph Paradigm is a powerful tool for visualizing and analyzing the flow of data in various systems. It helps in understanding dependencies, optimizing performance, and facilitating parallel processing. Whether in programming, digital signal processing, or machine learning, Declarative Data Flow Graph parallel Paradigm play a crucial role in the design and analysis of complex systems. This approach allows us to obtain powerful capabilities based on the scheme in a compact and quite readable form. If the analysis of all input data was performed in an imperative style inside the flow, branched garlands of if-expressions nested inside each other would end up in the place of the scheme recalculation call. As already mentioned, the weak point of the scheme is the coupling of imperative code with the data flow. You can see what awkward and cumbersome expressions are obtained during inter-module data exchange and, as a result, inside the function body. It is worth noting that as the scheme grows, the complexity of processing increases linearly at most, which could not be said when processing multiple input values with imperative code. The combining of the two paradigms is not syntactically seamless, indicating that we are trying to merge two worlds. However, the benefits of such a merger outweigh the effort of fusion. And the showed implementation allows simple embedding into C++ code. Interacting between C++ and Data Flow Language runtime is also very simple and straightforward. Essentially, DFG is a way computing elements are communicating with each other during computational process. Every system is built on top of some rules of interaction between building blocks.

In the DFG such rule set are:

- Programmable computing elements templates.
- Template is a stateful object definition represented by function consuming arguments and returning a value.
- Each input element is associated with the name visible from the outside the language runtime.
- Each computing element is an instance of the mentioned earlier template. Arguments of the template and the instance of that template corresponds.
- Each computing element has zero or more inputs.
- Each computing element has exactly one output.
- Each computing element's output may be used as the input by this or any number of any other elements.
- Discrete time, clocked synchronous.

These rules are powerful enough to allow build systems solving many of the tasks much more effectively than the other programming paradigms.

Proposed implementation of the language has small footprint with meaning to be used in small or embedded computing systems.