

Fundamentals of deep learning

Crash course in using PyTorch to train models

Terence Parr


MSDS program

University of San Francisco

Deep learning regressors

What's a neural network?

- Ignore the neural network metaphor, but know the terminology
- A combination of linear and nonlinear transformations
 - Linear: $z^{[layer]} = W^{[layer]} \mathbf{x}^T + \mathbf{b}^{[layer]}$
 - Nonlinear: $\mathbf{a}^{[layer]} = \sigma(z^{[layer]})$; called *activation function*
- Networks have multiple *layers*; layer is a stack of *neurons*



- Transform raw \mathbf{x} vector into better and better features, final linear layer can then make excellent prediction

DL Building blocks

$$\mathbf{w}\mathbf{x} + b$$

linear




sigmoid




ReLU (rectified linear unit)

- $\hat{y} = w_1x_1 + w_2x_2 + \dots + w_mx_m + b = \mathbf{w}\mathbf{x}^T + b$ for $n \times m$ dim X
- Linear/logistic regression equivalents (one x instance):



Assume we magically know \mathbf{w} and b

(For simplicity, I'm using proper $\mathbf{w}\mathbf{x}^T$ in math but omitting transpose in diagrams)




Underfitting a bit here
(need more of a quadratic)

Try adding layers to get more power

- But, sequence of linear models is just a linear model


$$\hat{y} = w'(\mathbf{w}\mathbf{x}^T + b) + b' = w'\mathbf{w}\mathbf{x}^T + w'b + b' = \mathbf{w}''\mathbf{x}^T + b''$$

(w' is scalar since $\mathbf{w}\mathbf{x}^T + b$ is scalar)



- PyTorch code





```
model = nn.Sequential(  
    nn.Linear(m, 1), # m features  
    nn.Linear(1, 1)  
)
```



Still just a line

Must introduce nonlinearity


```
model = nn.Sequential(  
    nn.Linear(m, 1),  
    nn.ReLU(),  
    nn.Linear(1, 1)  
)
```



ReLU idea here: Draw two lines
then clip at intersection


Stack linear models (neurons) for more power

- Stack gives layer: W matrix and b
- $\mathbf{a}^{[1]} = \text{relu}(W^{[1]}\mathbf{x}^T + \mathbf{b}^{[1]})$
- $\hat{y} = \mathbf{a}^{[2]} = W^{[2]}\mathbf{a}^{[1]} + \mathbf{b}^{[2]}$




All those w and b are different


$W^{[1]}$ means W for layer 1



Math for dataset 1D: weight→MPG



```
model = nn.Sequential(
    nn.Linear(1, 5),
    nn.ReLU(),
    nn.Linear(5, 2),
    nn.ReLU(),
    nn.Linear(2, 1)
)
```



(leaving out b 's)

$$a1 = F.relu(W1 @ x)$$

$$a2 = F.relu(W2 @ a1)$$

$$a3 = W3 @ a2$$


The diagram shows the matrix operations for the first three layers. For the first layer, $W1$ is a 5x1 matrix and x is a 1x1 matrix, resulting in $a1$ which is a 5x1 matrix. For the second layer, $W2$ is a 2x5 matrix and $a1$ is a 5x1 matrix, resulting in $a2$ which is a 2x1 matrix. For the third layer, $W3$ is a 1x2 matrix and $a2$ is a 2x1 matrix, resulting in $a3$ which is a 1x1 matrix.

(courtesy of TensorSensor)
<https://explained.ai/tensor-sensor/index.html>

Too much strength can lead to overfitting

- Models with too many parameters will overfit easily, if we train a long time
- We'll look at regularization later

```
model = nn.Sequential(  
    nn.Linear(1, 1000),  
    nn.ReLU(),  
    nn.Linear(1000, 1)  
)
```





Classifiers

Binary classifiers


- Add sigmoid to regressor and we get a two-class classifier
- Prediction \hat{y} is probability of class 1
- One-layer (hidden) network with sigmoid activation function is just a logistic regression model
- Provides hyper-plane decision surfaces

```
# 2 input vars: proline, alcohol  
model = nn.Sequential(  
    nn.Linear(2, 1),  
    nn.Sigmoid(),  
)
```




Stack neurons, add layer

- We get a nonlinear decision surface





```
model = nn.Sequential(  
    nn.Linear(2, 3),  
    nn.Sigmoid(),  
    nn.Linear(3, 1),  
    nn.Sigmoid()  
)
```

All those w and b are different



More neurons: more complex decision surface




Likely overfit

Not only more complex than hyperplane but non-contiguous regions!

Even ReLUs can get "curvy" surfaces


```
model = nn.Sequential(  
    nn.Linear(2, 10),  
    nn.ReLU(),  
    nn.Linear(10, 10),  
    nn.ReLU(),  
    nn.Linear(10, 1),  
    nn.Sigmoid()  
)
```

(Last activation function still must be sigmoid)




k -class classifiers

- **2-class problems:** final 1 neuron linear layer + sigmoid layer



- **k -class problems:** final k -neuron linear layer + softmax



k -class classifiers

- Instead of one neuron in last layer, we use k for k classes
- Last layer has vector output: $\mathbf{z}^{[layer]} = W^{[layer]} \mathbf{x}^T + \mathbf{b}^{[layer]}$
- Instead of sigmoid, we use softmax function
- Vector of k probabilities as activation: $\hat{\mathbf{y}} = \text{softmax}(\mathbf{z}^{[layer]})$
- Normalized probabilities of k classes

$$\text{softmax}(\mathbf{z})_i = \frac{e^{z_i}}{\sum_{j=1}^k e^{z_j}}$$

Sample softmax computation

- For layer output vector \mathbf{z} :
$$\text{softmax}(\mathbf{z})_i = \frac{e^{z_i}}{\sum_{j=1}^k e^{z_j}}$$

```
z = np.array([0.1, 1, 5])  
np.exp(z)
```

```
array([ 1.10517092,  2.71828183, 148.4131591 ])
```

```
np.exp(z) / np.sum(np.exp(z))
```

```
array([0.00725956, 0.01785564, 0.9748848 ])
```

Training deep learning networks

Refresher: What does training mean?


- Making a prediction means running a feature vector through the network
 - i.e., computing a value using the model parameters; e.g., $\hat{y} = 3x + 2$ is a different model than $\hat{y} = .5x + 10$
- Training: find optimal (or good enough) model parameters as measured by a *loss* (cost) function
- Loss function measures the difference between model predictions and known targets
- We have huge search space (of parameters) and it is challenging to find parameters giving low loss

Refresher: Loss functions

- **Regression:** typically mean squared error (MSE); should have smooth derivative, though mean absolute error works despite discontinuity (it's derivative is a V shape)
- **Classification:** log loss (also called cross entropy)
 - Penalizes very confident misclassifications strongly
 - Function of actual y and estimated probabilities, not predicted class
 - Perfect score is 0 log loss, imperfection gives unbounded scores
 - PyTorch log loss: `loss = cross_entropy(y_softmax, y_true)`
 - Predictions: `y_pred = argmax(y_softmax)`

Log loss

- Let p be predicted probability that $y=1$
- $\text{loss} = \text{penalty}(p)$ if $y=1$ else $\text{penalty}(1-p)$
- Let $\text{penalty}(p) = -\log(p)$



- Two-class log loss:


$$\text{loss} = -\frac{1}{n} \sum_{i=1}^n y_i \log(p) + (1 - y_i) \log(1 - p_i)$$

So log loss is average penalty where penalty is very high for confidence in wrong answer

Minimize loss with Gradient descent


- We use information about the loss function in the neighborhood of current parameters (here called β_i) to decide which direction shifts towards smaller loss
- Tweak parameters in that direction, amplified by a learning rate
- Go in opposite dir of slope

```
while not_converged:  
     $\beta = \beta - \text{rate} * \text{gradient}(\beta)$ 
```



If learning rate is too high?

- We oscillate across valleys
- It can even diverge, exploding
- If too small, we don't make progress to min



Training process


1. Prepare data
 - normalize numeric variables
 - dummy vars for categoricals
 - conjure up values for missing values
2. Split out at least a validation set from training set
3. Choose network architecture, appropriate loss function
4. Choose hyper-parameters, such as dropout rate
5. Choose a learning rate, number of epochs (passes through data)
6. Run training loop (until validation error goes up or num iterations)
7. Goto 3, 4, or 5 to tweak; iterate until good enough

Training loop

Regression

```
for epoch in range(nepochs):  
    y_train_pred = model(X_train)  
    loss = MSE(y_train_pred, y_train)  
    update model parameters in direction of lower loss
```

Vectorized forward network pass
(send in all instances at once)




Classification

```
for epoch in range(nepochs):  
    y_train_pred = model(X_train) # assume softmax final layer  
    loss = cross_entropy(y_train_pred, y_train)  
    update model parameters in direction of lower loss
```

Common train vs validation loss behavior

- DL networks have so many parameters, we can often get training error down to zero!
- But, we care about generalization
- Unfortunately, validation error often tracks away from training error as the number of epochs increases
- This model is clearly overfitting
- Need to use regularization to improve validation loss



Regularization techniques

- Get more training data; can try augmentation techniques (more data is likely to represent population distribution better)
- Reduce number of model parameters (i.e., simplify it) (reduce power/ability to fit the noise)
- Add drop out layers (randomly kill some neurons)
- Weight decay (L2 regularization on model parameters, restrict model parameter search space)
- Early stopping, when validation error starts to go up (generally we choose model that yields the best validation error)
- Batch normalization has some small regularization effect (Force layer activation distributions to be 0-mean, variance 1)
- Stochastic gradient descent tends to land on better generalizations

Aside: What is vectorization?

- Use vectors not loops
- For torch/numpy arrays, we can use vector math instead of a loop:

$$\mathbf{c} = \mathbf{a} + \mathbf{b}$$

- Gives an opportunity to execute vector addition in parallel

```
for i in range(len(a)):  
    c[i] = a[i] + b[i]
```

| | | | | | |
|-------|---|---|---|---|---|
| | 3 | 2 | 5 | 1 | a |
| + | 1 | 7 | 4 | 2 | b |
| <hr/> | | | | | |
| | 4 | 9 | 9 | 3 | c |



Vectorization in training loop

- Running one instance through network is how we think about it
- In practice, we send a subset or all X instances through the network in one go and compare all \hat{y} predictions to all y
- Instead of looping through instances, we pass X through to use matrix-matrix multiplies instead of matrix-vector multiplies

```
for epoch in range(nepochs):
    for i in range(n):
        x = X[i]
        y[i] = model(x)
    ...
```

$$\begin{array}{c} \frac{x}{3} \\ \leftarrow \end{array} = \frac{X}{3} [i] \quad \begin{array}{c} y[i] \\ \leftarrow \end{array} = \frac{W}{3} @ \frac{x.T}{3}$$

Assume $n=100$, $m=3$, $n_neurons=1$ in 1×3 weight matrix W

```
for epoch in range(nepochs):
    Y = model(X)
    ...
```

$$\begin{array}{c} Y \\ \leftarrow \end{array} = \begin{array}{c} W \\ \leftarrow \end{array} @ \begin{array}{c} X.T \\ \leftarrow \end{array}$$

Get 100 answers

Summary

- Vanilla deep learning models are layers of linear regression models glued together with nonlinear functions such as sigmoid/ReLUs
- Regressor: final layer transforms previous layer to single output
- Classifier: add sigmoid to last regressor layer (2-class) or add softmax to last layer of k neurons (k -class)
- Training a model means finding optimal (or good enough) model parameters as measured by a *loss* (cost or error) function; hyper parameters describe architecture and learning rate, amount of regularization, etc.
- We train using (stochastic) gradient descent; tuning model and hyper parameters is more or less trial and error ☹️ but experience helps a lot