Project SOne Serial Decoding Documentation

Hotte Shen | October 15, 2021

Direction: Panel to Box
Protocol: Standard UART
Baudrate: 4800bps
Logic Level: 5V TTL
Note: for each button touch, the same bytearray is repeated 3 times with 200ms interval, thus, it takes 400ms and a little more for one transmission.

Actions

M
Heater on +1
LightAC on +2
Light2 on +4
N
Power on 1
Power off 9

(1) 0xMN

Set Temperature

(5) celcius value
(6) fahrenheit value

Heater Levels

0x00 for 0%, 0x1E for 30%, 0x32 for 50%
0x46 for 70%, 0x64 for 100%

(10) Heater 1 level in %
(11) Heater 2 levle in %
(12) Heater 3 level in %

System Status

WARNING!
*Unclear yet
Maybe related to the status coming from the box*

0x42 for off
0xC2 for heating
0x82/0x02 unclear

(14) heater and system status

| 0 | CC | 1 | 09 | 2 | 00 | 3 | 00 | 4 | 00 | 5 | 2d | 6 | 71 | 7 | 00 | 8 | 00 | 9 | 00 | 10 | 00 | 11 | 42 | 12 | 00 | 13 | 08 | 14 | 42 | 15 | 67 |

Start Byte

(0) always 0xCC

Set Time

(2) set time in minutes
(3) automode set time in hours
(4) automode set time in minutes

Other Actions

*setting temperature
(7) 0x01*

*setting time
(7) 0x02
(9) 0x01*

*setting time in automode
(7) 0x03
(9) 0x00 for entering automode, 0x02 for hours chage, 0x04 for minutes change*

Light 1

(13) lighting mode between 0x00 - 0x08

Checksum

(15) custom checksum

[Sum[(1)..(14)] - 138] mod 256