
ALIGNED, NOT ADAPTED: WHAT A STUDENT INHERITS FROM ITS TEACHER’S GEOMETRY

Anonymous authors

Paper under double-blind review

ABSTRACT

1 INTRODUCTION

2 RELATED WORK

3 METHOD

Let $f_T : \mathcal{X} \rightarrow \mathbb{R}^{d_T}$ be a frozen teacher and f_S a student with L Transformer layers and width $d_S < d_T$. Writing $\text{norm}(\mathbf{x}) = \mathbf{x}/(\|\mathbf{x}\|_2 + \epsilon)$, we run the teacher once over an unlabeled corpus $\{x_i\}_{i=1}^N$ and cache only its final sentence embeddings, $\tilde{\tau}_i = \text{norm}(f_T(x_i))$. Pooling and normalising the student’s final token states gives $\mathbf{z}_i \in \mathbb{S}^{d_S-1}$. The two vectors have different widths, so nothing can be compared until a map bridges them; we fix that map before training and never touch it again.

3.1 TEACHER TARGETS

We fit the leading d_S -dimensional principal subspace $P_{\text{PCA}} \in \mathbb{R}^{d_T \times d_S}$ on the centred cache. Its orientation inside that subspace is arbitrary — invisible to every cosine-metric evaluation, but not to a point-wise loss — so we remove it once by orthogonal Procrustes against the *untrained* student. With $\mathbf{T}_{\text{PCA}}$ the normalised principal coordinates of a fitting subset and $\mathbf{Z}_0$ the student’s normalised outputs on the same sentences (Schönemann, 1966),

$$R^* = \arg \min_{R \in O(d_S)} \|\mathbf{T}_{\text{PCA}} R - \mathbf{Z}_0\|_F = UV^\top, \quad U\Sigma V^\top = \text{svd}(\mathbf{T}_{\text{PCA}}^\top \mathbf{Z}_0), \quad (1)$$

and the target of sentence x_i is

$$\tau_i = \text{norm}(f_T(x_i) P_{\text{PCA}} R^*) \in \mathbb{S}^{d_S-1}. \quad (2)$$

Both factors are fitted before the first gradient step and frozen for the whole run. Because R^* is orthogonal it leaves the targets’ pairwise cosines and retained variance exactly unchanged, so the two factors are independent: the projection decides *what* of the teacher survives, the rotation only *where* it is placed relative to the student’s starting point.

3.2 OBJECTIVE

Only the final layer is supervised:

$$\mathcal{L} = \mathbb{E}_i[1 - \langle \mathbf{z}_i, \tau_i \rangle] + \lambda_{\text{ctr}} \mathcal{L}_{\text{InfoNCE}}(\mathbf{z}, \mathbf{z}'), \quad (3)$$

where $\mathbf{z}'$ is a second dropout view of the same batch and $\mathcal{L}_{\text{InfoNCE}}$ is the usual in-batch contrastive loss at temperature τ_c . The first term is the whole of the teacher signal. The second is not a second teacher signal but an anti-collapse regulariser: point-wise matching pins the student along the target directions and leaves the rest of its spectrum unconstrained (Jing et al., 2022; Gao et al., 2021). λ_{ctr} is the only weight in the method.

What the method does not contain. No projector is trained, no relational or Gram term is added, no intermediate layer is supervised, and nothing is attached to the student at inference: the deployed model is the unmodified encoder. Training costs one teacher pass over the corpus, one truncated SVD of the cache, one $d_S \times d_S$ SVD for R^* , and then ordinary student training against a fixed lookup table of targets — no teacher hidden state, attention map or online teacher forward pass is used.

4 EXPERIMENTS

4.1 SETUP

Teacher–student pairs. We evaluate three teacher–student configurations that differ in teacher family, teacher width, and student capacity: (a) Qwen3-Embedding-4B ($d_T = 2560$, last-token pooling) $\rightarrow$ BERT-base (109M, $d_S = 768$, 12 layers), the capacity-gap setting; (b) BGE-M3 ($d_T = 1024$, an XLM-R encoder with CLS pooling) $\rightarrow$ MiniLMv2-L6-H768 (66M, $d_S = 768$, 6 layers), a different teacher family; (c) Qwen3-Embedding-0.6B ($d_T = 1024$, last-token pooling) $\rightarrow$ MiniLMv2-L6-H384 (22M, $d_S = 384$, 6 layers), the compact-student setting.

Training corpus. All methods are distilled on the same corpus of **102,361 unlabeled sentences**, sampled once from the training splits of the nine evaluation benchmarks (SciTail; Tweet; Emotion; STS-B; Banking77; MRPC; WiC; SICK; STS12) and fixed across every run in Table 1. Only raw text is read: no label, pair annotation, or similarity score enters any objective, so the training signal is unsupervised apart from the teacher.

Evaluation. We score frozen student embeddings on nine benchmarks in three families. For classification (Banking77, Emotion, Tweet) a logistic-regression probe is fitted on that benchmark’s own training split and scored with macro-F1. For pair classification (MRPC, SciTail, WiC) the cosine similarity is mapped to $[0, 1]$ and scored with average precision. For STS (SICK, STS12, STS-B) we report Spearman correlation against gold scores. The Avg. column is the unweighted mean of the nine primary scores. Appendix ?? gives the split sizes and the threshold protocol.

5 ANALYSIS

6 CONCLUSION

REFERENCES

- Tianyu Gao, Xingcheng Yao, and Danqi Chen. SimCSE: Simple contrastive learning of sentence embeddings. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, 2021.
- Li Jing, Pascal Vincent, Yann LeCun, and Yuandong Tian. Understanding dimensional collapse in contrastive self-supervised learning. In *International Conference on Learning Representations*, 2022.
- Peter H. Schönemann. A generalized solution of the orthogonal Procrustes problem. *Psychometrika*, 31(1):1–10, 1966.

Table 1: Experimental results on nine datasets. Avg. is the unweighted mean of the nine benchmark scores.

Method	Classification (F1)			Pair Classification (AP)			STS (Spearman)			Avg.
	Banking77	Tweet	Emotion	MRPC	SciTail	WiC	SICK	STS12	STS-B	
<i>(a) Qwen3-Embedding-4B → BERT-base (109M)</i>										
Teacher	93.63	72.22	68.94	84.79	91.77	66.80	83.43	82.55	86.87	81.22
Student base	84.86	47.79	68.02	77.36	67.74	59.22	42.43	21.54	20.30	54.36
Stella	91.08	73.40	64.40	86.23	83.22	68.98	78.38	71.31	79.16	77.35
CDM	89.71	70.76	52.67	84.03	71.47	69.83	71.36	68.87	74.68	72.60
DSKD	88.89	69.31	53.39	86.35	67.73	68.89	70.58	67.99	74.29	71.94
EMO	85.92	69.39	55.41	85.79	64.34	67.73	63.79	64.41	70.14	69.60
TALAS	93.34	74.45	72.70	86.16	87.78	68.11	80.70	77.34	83.57	80.46
GeoODE-KD	93.22	74.53	72.39	85.92	86.13	67.01	81.17	75.58	81.27	79.69
<i>(b) BGE-M3 → MiniLMv2-H768 (66M)</i>										
Teacher	93.52	73.85	68.56	85.81	91.87	61.47	79.18	78.73	84.87	79.76
Student base	81.84	47.70	71.67	79.67	65.06	60.89	49.46	26.76	24.12	56.35
Stella	86.62	71.08	58.57	83.63	75.85	69.38	70.87	63.08	67.88	71.89
CDM	87.96	71.31	58.31	83.83	75.43	69.58	67.37	62.12	67.09	71.44
DSKD	88.45	70.93	58.96	83.25	75.96	69.53	66.19	61.50	65.53	71.14
EMO	87.61	71.19	59.27	82.90	75.03	69.69	65.93	57.46	62.75	70.20
TALAS	90.14	74.91	63.50	86.76	81.27	66.53	76.31	67.66	78.18	76.14
GeoODE-KD	92.37	76.70	66.93	86.96	86.40	63.53	78.84	72.56	80.32	78.29
<i>(c) Qwen3-Embedding-0.6B → MiniLMv2-H384 (22M)</i>										
Teacher	93.21	71.33	66.53	83.37	90.00	66.85	80.64	77.11	84.60	79.29
Student base	68.29	41.07	69.90	78.39	64.56	59.58	47.60	21.95	22.08	52.60
Stella	84.36	68.81	54.01	81.61	72.69	68.53	65.30	61.02	64.70	69.00
CDM	85.21	69.36	52.31	81.65	73.12	68.52	65.20	61.91	65.23	69.17
DSKD	85.28	69.34	53.41	81.40	72.77	68.56	64.88	61.42	64.85	69.10
EMO	84.40	69.20	56.13	81.68	72.21	68.22	63.82	57.88	63.34	68.54
TALAS	86.67	72.41	59.93	84.75	80.47	66.72	71.59	69.80	74.94	74.14
GeoODE-KD	91.44	74.24	66.59	85.28	82.47	67.03	77.19	72.33	77.71	77.14