



APPLICATIONS

- Commercial Areas
- Hospitality Installations
- Residential Lightings
- Retail shops
- Social Areas



GENERAL INFORMATION

Model Number	LG7108.8dru
Product Code	LG7108.8dru+E27+927+V0240
Cap Base	E27
Dimmable	100-5%
Warm Up Time 60% of Full Light	Instant
Starting Time	< 0.5 s
Working Temperature	-30°C to +45°C
Housing Colour	White
Cover Design	Opal
Flammability of Plastic Component	≥ V2
Series	A60 (Classic Bulbs)

LIFE PERFORMANCE

Lifetime (L70 B50)	25000
Number of Switching Cycles	> 100000

ELECTRICAL DATA

Input Voltage	220-240 VAC
Frequency	50 Hz
Power Factor	≥ 0.70
Displacement Factor	0.70
Equivalent Wattage	60 W
Input Current	54 mA
Surge Protection	500


PHOTOMETRICAL INFORMATION

Luminous Flux	810 lm
Luminous Efficacy	92 lm/W
Colour Temperature	2700 K
Colour Consistency	6
CRI	Ra97
SVM	0.4
P _{ST} LM	1.0
Chromaticity Coordinates (x and y)	0.458, 0.410

CERTIFICATES & STANDARDS

Weighted Energy Consumption	9
Energy Class	F
Photobiological Safety Group	RG0
Lamp Cap Twist Safe	3
Approvals	CE, RoHS
Standards Compliance	IEC/EN 62560, IEC/EN 62493, IEC/EN 62471, ErP 2019/2020, IEC 62612, IEC CISPR15, EN 55015, IEC/EN 61547, IEC/EN 61000-3-2, IEC/EN 61000-3-3

DIMENSIONS & WEIGHT



Width (W)	60 mm
Height (H)	109 mm
Diameter (D)	60 mm
Weight	43 g