

Veritas NetBackup™ Copilot™ for Oracle Configuration Guide

Veritas NetBackup™ Copilot™ for Oracle Configuration Guide

Release: 3.0

Legal Notice

Copyright © 2016 Veritas Technologies LLC. All rights reserved.

Veritas, the Veritas Logo, NetBackup, and Copilot are trademarks or registered trademarks of Veritas Technologies LLC or its affiliates in the U.S. and other countries. Other names may be trademarks of their respective owners.

This product may contain third party software for which Veritas is required to provide attribution to the third party ("Third Party Programs"). Some of the Third Party Programs are available under open source or free software licenses. The License Agreement accompanying the Software does not alter any rights or obligations you may have under those open source or free software licenses. Refer to the third party legal notices document accompanying this Veritas product or available at:

<https://www.veritas.com/about/legal/license-agreements>

The product described in this document is distributed under licenses restricting its use, copying, distribution, and decompilation/reverse engineering. No part of this document may be reproduced in any form by any means without prior written authorization of Veritas Technologies LLC and its licensors, if any.

THE DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID. VERITAS TECHNOLOGIES LLC SHALL NOT BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH THE FURNISHING, PERFORMANCE, OR USE OF THIS DOCUMENTATION. THE INFORMATION CONTAINED IN THIS DOCUMENTATION IS SUBJECT TO CHANGE WITHOUT NOTICE.

The Licensed Software and Documentation are deemed to be commercial computer software as defined in FAR 12.212 and subject to restricted rights as defined in FAR Section 52.227-19 "Commercial Computer Software - Restricted Rights" and DFARS 227.7202, et seq. "Commercial Computer Software and Commercial Computer Software Documentation," as applicable, and any successor regulations, whether delivered by Veritas as on premises or hosted services. Any use, modification, reproduction release, performance, display or disclosure of the Licensed Software and Documentation by the U.S. Government shall be solely in accordance with the terms of this Agreement.

Veritas Technologies LLC
500 E Middlefield Road
Mountain View, CA 94043

<http://www.veritas.com>

Technical Support

Technical Support maintains support centers globally. All support services will be delivered in accordance with your support agreement and the then-current enterprise technical support policies. For information about our support offerings and how to contact Technical Support, visit our website:

<https://www.veritas.com/support>

You can manage your Veritas account information at the following URL:

<https://my.veritas.com>

If you have questions regarding an existing support agreement, please email the support agreement administration team for your region as follows:

Worldwide (except Japan)

CustomerCare@veritas.com

Japan

CustomerCare_Japan@veritas.com

Documentation

The latest documentation is available on the Veritas website:

<https://sort.veritas.com/documents>

Documentation feedback

Your feedback is important to us. Suggest improvements or report errors or omissions to the documentation. Include the document title, document version, chapter title, and section title of the text on which you are reporting. Send feedback to:

APPL.docs@veritas.com

You can also see documentation information or ask a question on the Veritas community site:

<http://www.veritas.com/community/>

Veritas Services and Operations Readiness Tools (SORT)

Veritas Services and Operations Readiness Tools (SORT) is a website that provides information and tools to automate and simplify certain time-consuming administrative tasks. Depending on the product, SORT helps you prepare for installations and upgrades, identify risks in your datacenters, and improve operational efficiency. To see what services and tools SORT provides for your product, see the data sheet:

https://sort.veritas.com/data/support/SORT_Data_Sheet.pdf

Contents

Chapter 1	Overview	5
	About Copilot	5
	Database dump backup details	6
	Oracle Accelerator backup details	6
	Restore details	7
	Copilot configuration overview	7
Chapter 2	Creating an appliance share	8
	Creating a share from the NetBackup Appliance Shell Menu	8
	NFS export options	9
Chapter 3	Mounting an appliance share	11
	Mounting an appliance share	11
Chapter 4	Storage Lifecycle Policy (SLP) configuration	13
	Create a snapshot-based storage lifecycle policy for Copilot	13
	Configure a second storage lifecycle policy for Copilot	21
	Register the Oracle database credentials with NetBackup for Copilot	28
Chapter 5	Oracle Intelligent Policy (OIP) configuration	32
	Oracle Intelligent Policy configuration options for Copilot	32
	Create the Oracle Intelligent Policy for Oracle accelerator backups	33
	Create the Oracle Intelligent Policy for database dump backups	41

Overview

This chapter includes the following topics:

- [About Copilot](#)
- [Copilot configuration overview](#)

About Copilot

Copilot is a NetBackup appliance exclusive feature that integrates with native Oracle tools and processes to give database backup administrators (DBA) more control, visibility, and the ability to recover their database backups. Backup administrators can then manage policies, move the data to different storage types, and create off-site backup copies of the database backups.

Additionally, Copilot features NetBackup Accelerator technology to boost Oracle backup and restore performance. NetBackup Accelerator integrates with Oracle's incremental merge capabilities to eliminate the need for full backups and allow new full database images to be synthesized on backup storage post-process.

Copilot lets you create shares on the appliance for Oracle backup and recovery and create further protection policies in NetBackup for advanced data protection features like long-term retention, replication, and NetBackup Oracle Accelerator technology. Copilot is exclusive to the appliance but requires additional configuration steps within NetBackup software.

You can choose to create a standard share or optimized share. Both share types support all workload sizes, but optimized shares employ storage enhancements to reduce protection windows for larger databases. Standard shares are supported on the 5230 and 5330 appliances and do not have disk layout requirements, while optimized shares are only supported on the 5330 appliance and require reservation of an Expansion Storage Shelf for optimized shares.

See [“Database dump backup details”](#) on page 6.

See [“Oracle Accelerator backup details”](#) on page 6.

See [“Restore details”](#) on page 7.

Database dump backup details


In a database dump configuration, RMAN is configured to put backup data on the appliance share, which a scheduled NetBackup policy protects. Backup metadata is synced with the RMAN catalog and the restore can be initiated either through RMAN or NetBackup.

See [“Oracle Intelligent Policy configuration options for Copilot”](#) on page 32.

See [“Create the Oracle Intelligent Policy for database dump backups”](#) on page 41.

Oracle Accelerator backup details

In an Oracle accelerator backup configuration, an initial full backup is required and subsequent backups consist of only changed blocks. The changed blocks are merged with the full image to protect a new full backup. Once the merge process is completed, a snapshot is created to produce a NetBackup backup image for restore. Storage Lifecycle Policies (SLPs) are used for replication for data protection. All images on the share and in NetBackup are available in RMAN or NetBackup for restore. The following graphic illustrates how an Oracle accelerator backup works:



See [“Oracle Intelligent Policy configuration options for Copilot”](#) on page 32.

See [“Create the Oracle Intelligent Policy for Oracle accelerator backups”](#) on page 33.

Restore details

Copilot restores can be initiated from RMAN and NetBackup. In either case, RMAN needs to be functional to complete the restore, as is the case with traditional restores. The process to restore data is the same regardless if the data resides on a share or in a NetBackup storage unit.

Copilot configuration overview

The following is a high level overview of what is needed to configure Copilot from start to finish. The configuration covered in this guide uses two NetBackup appliances. Your configuration may vary if using a different number of appliances in your configuration.

- Create a share on the appliance using the NetBackup Appliance Shell Menu.
See [“Creating a share from the NetBackup Appliance Shell Menu”](#) on page 8.
- Mount the appliance share on the Oracle client using OS tools.
See [“Mounting an appliance share”](#) on page 11.
- Configure a Storage Lifecycle Policy (SLP) using NetBackup.
See [“Create a snapshot-based storage lifecycle policy for Copilot”](#) on page 13.
See [“Configure a second storage lifecycle policy for Copilot”](#) on page 21.
See [“Register the Oracle database credentials with NetBackup for Copilot”](#) on page 28.
- Configure an Oracle Intelligent Policy (OIP) using NetBackup. There are two OIP options available:
See [“Create the Oracle Intelligent Policy for Oracle accelerator backups”](#) on page 33.
See [“Create the Oracle Intelligent Policy for database dump backups”](#) on page 41.

Creating an appliance share

This chapter includes the following topics:

- [Creating a share from the NetBackup Appliance Shell Menu](#)
- [NFS export options](#)

Creating a share from the NetBackup Appliance Shell Menu

The following procedure explains how to create a standard share or optimized share from the shell menu.

Before starting this procedure, determine what type of share you want to create. You can choose between the following:

- Standard Share
- Optimized Share

Note: If you want to create an optimized share and have not yet created the optimized share reserve, you are prompted to create it within the command.

To create a new share from the shell menu:

- 1 Open an SSH session to log on to the appliance as an administrator.
- 2 Enter the create command specific to share you want to create:
 - `Main_Menu > Manage > Storage > Create Share Standard` creates a standard share.

- Main_Menu > Manage > Storage > Create Share Optimized creates an optimized share.

The command guides you through the process of configuring a new share.

- 3 Enter the share name, for example `share_1`.
- 4 Enter a short description for the share, for example `Test for share_1`.
- 5 Enter the allocated capacity for the share, for example `5GB`.
- 6 Enter a comma-separated list of Oracle server clients that can access the share, for example `10.100.0.2, 10.100.0.3`.

Note: Client names can be entered using the short name, the FQDN, or the IP format. These are translated to the FQDN format after entry.

- 7 Enter the NFS export options for each of the Oracle clients. You are prompted to enter options for each client you added in the previous step.
See [“NFS export options”](#) on page 9.
- 8 Once you have entered the NFS export options, a summary is displayed.
- 9 Enter `yes` to create the share. A series of messages are displayed as the share is created.

See [“Copilot configuration overview”](#) on page 7.

Refer to the *NetBackup™ Copilot™ for Oracle Configuration Guide* for more information on configuring Oracle database backups.

Refer to the *NetBackup™ for Oracle Administrator's Guide* for more information on Copilot in NetBackup software.

NFS export options

The following table describes the export options available for share creation or modification.

Option	Description
<code>ro</code>	Allows only read requests on the Share.
<code>rw</code>	Allows both read requests and write requests on the Share.

Option	Description
<code>no_root_squash</code>	<p>Disables all root squashing.</p> <p>Allows root account on client to access export share on server as the root account.</p>
<code>root_squash</code>	<p>Maps requests from UID and GID 0 to the anonymous UID and GID.</p>
<code>all_squash</code>	<p>Maps all UIDs and GIDs to the anonymous user account.</p> <p>By default, the NFS server chooses a UID and GID of 65534 for squashed access. These values can be overridden by using the <code>anonuid</code> and <code>anongid</code> options.</p>
<code>anonuid</code>	<p>Sets the <code>uid</code> of the anonymous user account.</p> <p>This option forces all anonymous connections to a predefined UID on a server.</p>
<code>anongid</code>	<p>Sets the <code>gid</code> of the anonymous account.</p> <p>This option forces all anonymous connections to a predefined GID on a server.</p>
<code>secure</code>	<p>Requires that requests originate from an Internet port less than <code>IPPORT_RESERVED</code> (1024).</p>
<code>insecure</code>	<p>Disables the requirement that requests originate from an Internet port less than <code>IPPORT_RESERVED</code> (1024).</p>

Mounting an appliance share

This chapter includes the following topics:

- [Mounting an appliance share](#)

Mounting an appliance share

This procedure covers how to mount the share on Linux or Solaris Oracle server. For more information about mounting the share on a Windows Oracle server, please refer to documentation for configuring Direct NFS (dNFS) at <http://docs.oracle.com/>.

Note: Oracle Direct NFS (dNFS) is recommended for optimal NFS client performance with Copilot.

Use the following procedure to mount the appliance share.

Mount an appliance share

- 1 Log on to the Oracle server as root.
- 2 Create a directory for the mount point using the following command:

```
- #mkdir /mntpoint
```
- 3 Mount the appliance share using the following command. Replace *<appliance_name>* with the name of the appliance and *<share_name>* with the name of the share to be mounted.
 - For a Linux-based server, use:

```
- #mount -t nfs <appliancename>:<share_name> -o  
rw,bg,hard,nointr,rsize=1048576,wsiz=1048576,tcp,actimeo=0,vers=3,timeo=600  
/mntpoint
```

■ For a Solaris-based server, use:

```
- #mount -F nfs <appliancename>:<share_name> -o  
rw,bg,hard,rsiz=1048576,wsiz=1048576,vers=3,forcedirectio,nointr,proto=tcp  
/mntpoint
```

4 Grant the Oracle user permission to access the mount point using the following command:

```
- #chmod 700 /mntpoint  
- #chown <oracle_user>:<oracle_group> /mntpoint
```

Note: To change share permissions, the `no_root_squash` option must be enabled when on the share. This option can be disabled when the permissions have been changed. Use the Edit Share command to change the NFS options of the share. See the *NetBackup Appliance Administrator's Guide* for more information on editing a share.

Note: Before restarting, make sure to unmount shares on all clients. If you cannot perform this action, unmount the shares on the clients, then remount the shares once the appliance has restarted fully.

See [“Copilot configuration overview”](#) on page 7.

Storage Lifecycle Policy (SLP) configuration

This chapter includes the following topics:


- [Create a snapshot-based storage lifecycle policy for Copilot](#)
- [Configure a second storage lifecycle policy for Copilot](#)
- [Register the Oracle database credentials with NetBackup for Copilot](#)

Create a snapshot-based storage lifecycle policy for Copilot

Use the following procedure to create a snapshot-based storage lifecycle policy (SLP) for Copilot using the NetBackup Admin console.

Create a snapshot-based SLP

- 1 Log on to the NetBackup Admin Console.
- 2 Right click, then select **New Storage Lifecycle Policy**.



- 3 Enter a policy name, then click **Add**.

New Storage Lifecycle Policy

Storage Lifecycle Policy | Validation Report

Storage lifecycle policy name: snapSLP

Data classification: <No data classificati... Priority for secondary operations: 0 (higher number is greater priority)

Operation	Window	Target Master	Storage	Volume Pool	Media Owner	Retention Ty...	Retention P...	Alternate Re...	Preserve m...
-----------	--------	---------------	---------	-------------	-------------	-----------------	----------------	-----------------	---------------

↑ ↓ ← →

Add... Change Remove

State of secondary operation processing

☒ Active ☐ Postponed

☐ Until 8/24/15 12:45 PM

To find impact on Policies associated with this SLP due to change in configuration click here.

Validate Across Backup Policies

OK Cancel Help

- 4 Select **Snapshot** in the **Operation** drop-down menu.

- 5 Select **No Storage Unit** in the **Destination storage** drop-down menu, then click **OK**.

The screenshot shows a 'New Operation' dialog box with a 'Properties' tab. The 'Source storage' field is empty. The 'Operation' dropdown menu is set to 'Snapshot'. Below this, there are two sections: 'Destination Storage Attributes' and 'Retention'. In the 'Destination Storage Attributes' section, the 'Destination storage' dropdown menu is set to 'No Storage Unit'. In the 'Retention' section, the 'Retention type' dropdown menu is set to 'Maximum snapshot limit'. At the bottom of the dialog box are three buttons: 'OK', 'Cancel', and 'Help'.

Properties	
Source storage: ---	
Operation: Snapshot	
Destination Storage Attributes	Retention
Destination storage:	Retention type:
No Storage Unit	Maximum snapshot limit

6 Click **Add...**

New Storage Lifecycle Policy

Storage Lifecycle Policy

Validation Report

Storage lifecycle policy name:

snapSLP

Data classification:

<No data classificati...

Priority for secondary operations:

0

(higher number is greater priority)

Operation	Window	Target Master	Storage	Volume Pool	Media Owner	Retention Ty...	Retention P...	Alternate Re...	Preserve m...
Snapshot	--	--	No Storage...	--	--	Maximum s...	--	--	--

↑

↓

←

→

Add...

Change

Remove

State of secondary operation processing

☒ Active

☐ Postponed

☐ Until

8/24/15 12:46 PM

To find impact on Policies associated with this SLP due to change in configuration click here.

Validate Across Backup Policies

OK

Cancel

Help

7 Select **Backup From Snapshot** in the **Operation** drop-down menu.

- 8 Select the storage unit from the **Destination storage** drop-down menu, then click **OK**.

New Operation

Properties Window

Source storage: No Storage Unit (Snapshot)

Operation: Backup From Snapshot

Destination Storage Attributes

Destination storage: chamavam2_stu1

Volume pool: NetBackup

Media owner: Any

Retention

Retention type: Fixed

Retention period: infinity (Retention Level 9)

Duplication

Alternate read server:

☐ Preserve multiplexing

☐ Postpone creation of this copy until the source copy is about to expire

Advanced

OK Cancel Help

9 Click Add...

Change Storage Lifecycle Policy

Storage Lifecycle Policy

Validation Report

Storage lifecycle policy name:

snapSLP

Data classification:

<No data classificati...

Priority for secondary operations:

0

(higher number is greater priority)

Operation	Window	Target Master	Storage	Volume Pool	Media Owner	Retention Ty...	Retention P...	Alternate Re...
Snapshot	--	--	No Storage ...	--	--	Maximum s...	--	--
Backup From Snapshot	Default_24x...	--	chamay...	--	--	Fixed	Infinity	--

↑

↓

←

→

Add...

Change

Remove

State of secondary operation processing

Active

Postponed

Until

8/24/15 12:57 PM

To find impact on Policies associated with this SLP due to change in configuration click here.

Validate Across Backup Policies

OK

Cancel

Help

10 Select Duplication from the Operation drop-down menu.

- 11 Select the storage unit from the **Destination** storage drop-down menu, then click **OK**.

New Operation

Properties Window

Source storage: chamavn2_stu1 (Backup From Snapshot)

Operation: Duplication

Destination Storage Attributes

Destination storage: mrrh-1_stu1

Volume pool: NetBackup

Media owner: Any

Retention

Retention type: Fixed

Retention period: infinity (Retention Level 9)

Duplication

Alternate read server:


☐ Preserve multiplexing

☐ Postpone creation of this copy until the source copy is about to expire

Advanced

OK Cancel Help

- 12
- Review the configuration and verify that you have the snapshot backup and duplication portion of the SLP setup correctly, then click **OK**.



See [“Configure a second storage lifecycle policy for Copilot”](#) on page 21.


See [“Copilot configuration overview”](#) on page 7.

Configure a second storage lifecycle policy for Copilot

Use the following procedure to configure a second backup storage lifecycle policy (SLP) for Copilot using the NetBackup Admin console.

Configure a second SLP

- 1 Log on to the NetBackup Admin Console.
- 2 Right click, then select **New Storage Lifecycle Policy**.



- 3 Enter a storage lifecycle policy name, then click **Add**.

New Storage Lifecycle Policy

Storage Lifecycle Policy | Validation Report

Storage lifecycle policy name:

Data classification:

Priority for secondary operations: (higher number is greater priority)

Operation	Window	Target Master	Storage	Volume Pool	Media Owner	Retention Ty...	Retention P...	Alternate Re...	Preserve m...

↑ ↓ ← →

Add... Change Remove

State of secondary operation processing

☒ Active

☐ Postponed

☐ Until

To find impact on Policies associated with this SLP due to change in configuration click here.

Validate Across Backup Policies

OK Cancel Help

- 4 Select **Backup** from the **Operation** drop-down menu.

- 5 Select the storage unit from the **Destination storage** drop-down menu, then click **OK**.

The screenshot shows a 'New Operation' dialog box with the following fields and options:

- Source storage:** ---
- Operation:** Backup
- Destination Storage Attributes:**
 - Destination storage:** chamavn2_stu1
 - Volume pool:** NetBackup
 - Media owner:** Any
- Retention:**
 - Retention type:** Fixed
 - Retention period:** infinity (Retention Level 9)

At the bottom of the dialog are three buttons: OK, Cancel, and Help.

6 Click Add...

New Storage Lifecycle Policy

Storage Lifecycle Policy | Validation Report

Storage lifecycle policy name:

Data classification:

Priority for secondary operations: (higher number is greater priority)

Operation	Window	Target Master	Storage	Volume Pool	Media Owner	Retention Ty.	Retention P...	Alternate Re...	Preserve m.
Backup	--	--	chamav...	--	--	Fixed	Infinity	--	No

State of secondary operation processing

☒ Active
☐ Postponed

☐ Until

To find impact on Policies associated with this SLP due to change in configuration click here.

7 Select Duplication from the Operation drop-down menu.

- 8 Select the storage unit from the **Destination storage** drop-down menu, then click **OK**.

New Operation

Properties Window

Source storage: chamavm2_stu1 (Backup)

Operation: Duplication

Destination Storage Attributes

Destination storage: mrrh-1_stu1

Volume pool: NetBackup

Media owner: Any

Retention

Retention type: Fixed

Retention period: Infinity (Retention Level 9)

Duplication

Alternate read server:

☐ Preserve multiplexing

☐ Postpone creation of this copy until the source copy is about to expire

Advanced

OK Cancel Help

- 9 Review the configuration to verify that you have setup the stream portion of the SLP setup correctly, then click **OK**.

New Storage Lifecycle Policy

Storage Lifecycle Policy | **Validation Report**

Storage lifecycle policy name: streamSLP

Data classification: <No data classificati... | **Priority for secondary operations:** 0 (higher number is greater priority)

Operation	Window	Target Master	Storage	Volume Pool	Media Owner	Retention Ty...	Retention P...	Alternate Re...	Preserve m...
Backup	--	--	chamav...	--	--	Fixed	Infinity	--	No
Duplication Default_24x...	--	--	mrrh-1...	--	--	Fixed	Infinity	--	No

Buttons: Add..., Change, Remove

State of secondary operation processing

☒ Active
☐ Postponed
☐ Until 8/24/15 12:52 PM

To find impact on Policies associated with this SLP due to change in configuration click here.
[Validate Across Backup Policies](#)

Buttons: OK, Cancel, Help

- 10 Review the SLPs window to verify that both SLPs are active.

chamavm1 (Master Server)

2 Storage Lifecycle Policies (0 selected)

Name	Data Classification	Job Priority	Secondary Operation
snapSLP	--	0	Active
streamSLP	--	0	Active

See [“Register the Oracle database credentials with NetBackup for Copilot”](#) on page 28.

See [“Copilot configuration overview”](#) on page 7.


Register the Oracle database credentials with NetBackup for Copilot


Use the following procedure to register the Oracle database credentials with NetBackup.

Register the Oracle database credentials

- 1** Right click on the instance, then select **Register**.

- 2 Enter the proper credentials for the instance, then click **OK**.





Register Instance

☐ Add to group and register using group credentials

Instance Group: <No instance groups available>

☒ Use Instance Credentials

Using Instance OS Credentials

Username:

Password:

Domain:

Authentication

☒ OS Authentication

☐ Oracle Authentication

Username:

Password:

Net Service Name:

(TNS Alias)

Oracle RMAN Recovery Catalog Credentials

☐ Use Oracle RMAN Recovery Catalog

Username:


Password:

Net Service Name:

(TNS Alias)

OK Cancel Help

3 Review the instance window to verify the instance is registered correctly.



chamavm1 (Master Server)

1 instances (0 selected)

Instance Name (OR...)	State	Host	OS Type	Oracle Home	Registered
orac112	Active	chamavm3	Unix	/db/orac112/app/ora...	08/24/2015 13:11:54

Left sidebar menu:

- chamavm1 (Master Server)
 - Backup, Archive, and Restore
 - Activity Monitor
 - NetBackup Management
 - Reports
 - Policies
 - Storage
 - Storage Units
 - Storage Unit Groups
 - Storage Lifecycle Policies
 - SLP Windows
 - Catalog
 - Host Properties
 - Master Servers
 - Media Servers
 - Clients
 - Applications
 - Oracle
 - All Instances
 - Instance Groups
 - Microsoft SQL Server
 - Media and Device Management
 - Device Monitor
 - Media
 - Devices
 - Credentials
 - Access Management
 - Vault Management
 - Bare Metal Restore Management
 - Logging Assistant

See [“Oracle Intelligent Policy configuration options for Copilot”](#) on page 32.

See [“Copilot configuration overview”](#) on page 7.

Oracle Intelligent Policy (OIP) configuration

This chapter includes the following topics:

- [Oracle Intelligent Policy configuration options for Copilot](#)
- [Create the Oracle Intelligent Policy for Oracle accelerator backups](#)
- [Create the Oracle Intelligent Policy for database dump backups](#)

Oracle Intelligent Policy configuration options for Copilot

There are two options available during the OIP configuration for Copilot. You can choose between the following two options:

- **Database Backup Shares**
Select this option to perform database dump backups.
See [“Database dump backup details”](#) on page 6.
See [“Create the Oracle Intelligent Policy for database dump backups”](#) on page 41.
- **Whole Database - Datafile Copy Share**
Select this option to perform Oracle accelerator backups.
See [“Oracle Accelerator backup details”](#) on page 6.
See [“Create the Oracle Intelligent Policy for Oracle accelerator backups”](#) on page 33.

Create the Oracle Intelligent Policy for Oracle accelerator backups

Use the following procedure to create the Oracle Intelligent Policy (OIP) for Oracle accelerator backups.

Create the OIP for Oracle accelerator backups

- 1 In the left pane of the NetBackup Admin Console, expand **NetBackup Management > Policies**.
- 2 Select **Actions > New > Policy** or right-click on **All Policies** in the center pane, then click **New Policy** on the shortcut menu.
- 3 Select **Oracle** in the **Policy type** drop-down menu.
- 4 Select the stream policy you created earlier in the **Policy storage** drop-down menu.

Change Policy - demo

Server: chamavm1

Attributes Schedules Instances and Databases Backup Selections **Oracle**

Policy type: Oracle

Destination:

Data classification: <No data classification>

Policy storage: streamSLP

Policy volume pool: NetBackup

☐ Take checkpoints every: 0 minutes

☒ Limit jobs per policy: 1

Job priority: 0 (higher number is greater priority)

Media Owner: Any

Snapshot Client and Replication Director

☐ Perform block level incremental backups

☐ Use Replication Director

☒ Perform snapshot backups Options...

☐ Retain snapshot for Instant Recovery or SLP management

☐ Hyper-V server:

☐ Perform off-host backup

Use:

Machine:

☒ Go into effect at: 08/24/2015 13:12:21

☐ Follow NFS

☐ Cross mount points

☐ Compress

☐ Encrypt

Collect disaster recovery information for:

☐ Bare Metal Restore

☐ Collect true image restore information

☐ with move detection (Required for synthetic backups and Bare Metal Restore)

☐ Allow multiple data streams

☐ Disable client-side deduplication

☐ Enable granular recovery

☐ Use Accelerator

☐ Enable optimized backup of Windows deduplicated volumes

Keyword phrase (optional):

Microsoft Exchange Server Attributes


Exchange DAG or Exchange 2007 replication (LCR/CCR)

Database backup source:


Preferred server list... (Exchange DAG only)

OK Cancel Help

- 5 Click the **Instances and Databases** tab, then select **Protect Instances and Databases**.




- 6 Click the **Backup Selections** tab, then select **Whole Database - Datafile Copy Share**.




- 7 Click **Browse** to open the **browse backup selections** window.

- 8 Select the instance name and location you want to include in the backup, then click **OK**.



- 9 Review the **Backup Selection List** and verify that the proper instance location is selected.

The selected instance is the share mount point on the Oracle server.



- 10 Click the **Schedules** tab to create a full schedule.
- 11 Select **Full Backup** in the **Type of backup** drop-down menu and enter a name for the schedule.
- 12 Select **Override policy storage selection** and choose the storage lifecycle policy you created earlier for the snapshot.

13 Click **Add**.

The screenshot shows the 'Add Schedule - Policy demo' window. The 'Server' is 'chamavm1'. The 'Attributes' tab is active. The 'Name' field contains 'Full'. The 'Type of backup' dropdown is set to 'Full Backup'. Under 'Schedule type', the 'Frequency' radio button is selected, with a value of '1' and unit of 'weeks'. The 'Destination' section has 'Override policy storage selection' checked, with 'snapSLP' selected in the dropdown. 'Override policy volume pool' is set to 'NetBackup'. 'Override media owner' is empty. 'Retention' is set to 'Determined by SLP'. 'Media multiplexing' is set to '1'. Under 'Instant Recovery', the 'Snapshots and copy snapshots to a storage unit' radio button is selected. The 'Add' button is highlighted.

14 Select **Archived Redo Log Backup** from the **Type of backup** drop-down menu and enter a name for the schedule.

15 Click **OK** to confirm.

Add Schedule - Policy demo

Server: chamavm1

Attributes | Start Window | Exclude Dates

Name:
Archive

Type of backup:
Archived Redo Log Backup

☐ Synthetic backup
☐ Accelerator forced rescan

Schedule type:
☐ Calendar
☐ Retries allowed after runday
☒ **Frequency:**
 1 weeks


Destination:
☐ Multiple copies Configure...
☐ **Override policy storage selection:**
☐ **Override policy volume pool:**
 NetBackup
☐ **Override media owner:**
 Retention:
 Determined by SLP

Media multiplexing:
 1

Instant Recovery:
☒ Snapshots and copy snapshots to a storage unit
☐ Snapshots only


Add **OK** **Cancel** **Help**

16 Review the created schedule to verify that all selections are correct.



17 Click the **Oracle** tab to adjust any selections as needed.

18 Click **OK** to complete the setup.



See [“Copilot configuration overview”](#) on page 7.

Create the Oracle Intelligent Policy for database dump backups

Use the following procedure to create the Oracle Intelligent Policy (OIP) for database dump backups.

Create the OIP for database dump backups

- 1 In the left pane of the NetBackup Admin Console, expand **NetBackup Management > Policies**.
- 2 Select **Actions > New > Policy** or right-click on **All Policies** in the center pane, then click **New Policy** on the shortcut menu.

- 3 Select **Oracle** in the **Policy type** drop-down menu.
- 4 Select the stream policy you created earlier in the **Policy storage** drop-down menu.

Change Policy - demo

Server: mrrh

Attributes Schedules Instances and Databases Backup Selections **Oracle**

Policy type: Oracle

Destination:

Data classification: <No data classification>

Policy storage: streamSLP

Policy volume pool: NetBackup

☐ Take checkpoints every: 0 minutes

☐ Limit jobs per policy: 0 (higher number is greater priority)

Job priority: 0 (higher number is greater priority)

Media Owner: Any

Snapshot Client and Replication Director

☐ Perform block level incremental backups

☐ Use Replication Director

☒ Perform snapshot backups Options...

☐ Retain snapshot for Instant Recovery or SLP management

☐ Hyper-V server:

☐ Perform off-host backup

Use:

Machine:

☒ Go into effect at: 01/07/2016 09:04:46

☐ Follow NFS

☐ Cross mount points

☐ Compress

☐ Encrypt

Collect disaster recovery information for:

☐ Bare Metal Restore

☐ Collect true image restore information

☐ with move detection (Required for synthetic backups and Bare Metal Restore)

☐ Allow multiple data streams

☐ Disable client-side deduplication

☐ Enable granular recovery

☐ Use Accelerator

☐ Enable optimized backup of Windows deduplicated volumes

Keyword phrase (optional):

Microsoft Exchange Server Attributes


Exchange DAG or Exchange 2007 replication (LCR/CCR)

Database backup source:


Preferred server list... (Exchange DAG only)

OK Cancel Help

- 5 Click the **Instances and Databases** tab, then select **Protect Instances and Databases**.



6 Click the **Backup Selections** tab, then select **Database Backup Shares**.



- 7 Click the **Attributes** tab, then select **Perform snapshot backups** and **Retain snapshot for Instant Recovery or SLP management**.

The screenshot shows the 'Change Policy - demo' window with the 'Attributes' tab selected. The configuration is as follows:

- Policy type:** Oracle
- Destination:**
 - Data classification: <No data classification>
 - Policy storage: streamSLP
 - Policy volume pool: NetBackup
- ☐ Take checkpoints every: 0 minutes
- ☐ Limit jobs per policy: 1
- Job priority:** 0 (higher number is greater priority)
- Media Owner:** Any
- Snapshot Client and Replication Director**
 - ☐ Perform block level incremental backups
 - ☐ Use Replication Director
 - ☒ **Perform snapshot backups** (Options... button)
 - ☒ **Retain snapshot for Instant Recovery or SLP management**
 - ☐ Hyper-V server:
 - ☐ Perform off-host backup
 - Use:
 - Machine:
- Go into effect at:** 01/07/2016 09:04:46
- ☐ Follow NFS
- ☐ Cross mount points
- ☐ Compress
- ☐ Encrypt
- Collect disaster recovery information for:**
 - ☐ Bare Metal Restore
 - ☐ Collect true image restore information
 - ☐ with move detection (Required for synthetic backups and Bare Metal Restore)
 - ☐ Allow multiple data streams
 - ☐ Disable client-side deduplication
 - ☐ Enable granular recovery
 - ☐ Use Accelerator
 - ☐ Enable optimized backup of Windows deduplicated volumes
- Keyword phrase (optional):**
- Microsoft Exchange Server Attributes**
 - Exchange DAG or Exchange 2007 replication (LCR/CCR)
 - Database backup source:**
 - Preferred server list... (Exchange DAG only)

Buttons at the bottom: OK, Cancel, Help

- 8 Click the **Options...** button, then select **remote_vxfs** from the **Snapshot method for this policy** drop-down menu.

- 9 Click **OK** to confirm.

The following selections are optional. If no snapshot method is selected, NetBackup will select a snapshot method at the time of backup.

Snapshot method for this policy:
remote_vxfs

The following parameters can be set for backups performed in this policy that use this snapshot method:

Configuration Parameters

Parameter	Value
Maximum Snapshots (Instant Recovery only)	2

Snapshot Resources

Array SN	Source	Snapshot Devices

Add Change Remove Remove All

OK Cancel Help

- 10 Click the **Schedules** tab to create a full schedule.
- 11 Select **Full Backup** in the **Type of backup** dropdown menu and enter a name for the schedule.
- 12 Select **Override policy storage selection** and choose the storage lifecycle policy you created earlier for the snapshot.

13 Click **Add**.

The screenshot shows the 'Add Schedule - Policy demo' window. The 'Server' is 'mrrh1'. The 'Attributes' tab is selected. The 'Name' field contains 'Full'. The 'Type of backup' dropdown is set to 'Full Backup'. Under 'Schedule type', 'Frequency' is selected with a value of '1' and unit 'weeks'. The 'Destination' section has 'Override policy storage selection' checked, with 'snapSLP' selected. 'Override policy volume pool' is set to 'NetBackup'. 'Override media owner' is empty. 'Retention' is 'Determined by SLP'. 'Media multiplexing' is set to '1'. Under 'Instant Recovery', 'Snapshots and copy snapshots to a storage unit' is selected. At the bottom are 'Add', 'OK', 'Cancel', and 'Help' buttons.

14 Select **Archived Redo Log Backup** from the **Type of backup** drop-down menu and enter a name for the schedule.

15 Click **OK** to confirm.

Add Schedule - Policy demo

Server: mrrh1

Attributes | Start Window | Exclude Dates

Name:
Archive

Type of backup:
Archived Redo Log Backup

☐ Synthetic backup
☐ Accelerator forced rescan

Schedule type:
☐ Calendar
☐ Retries allowed after runday
☒ **Frequency:**
 1 weeks

Destination:
☐ Multiple copies Configure...
☐ **Override policy storage selection:**
☐ **Override policy volume pool:**
☐ **Override media owner:**

Retention:
Determined by SLP

Media multiplexing:
1

Instant Recovery:
☒ Snapshots and copy snapshots to a storage unit
☐ Snapshots only

Add **OK** **Cancel** **Help**

16 Review the created schedule to verify that all selections are correct.

Change Policy - demo

Server: mrrh1

Attributes Schedules Instances and Databases Backup Selections Oracle

2 4 6 8 10 12 14 16 18 20 22 24

Sun
Mon
Tue
Wed
Thu
Fri
Sat

Name	Type	Synthetic B...	Disk-Only B...	Retention P...	Retention L...	Frequency	Media Multi...	Storage	Volume Pool	P...
Full	Full Backup	--	No	Determine...	0 1 week	1	1 snapSLP			demo
Archive	Archived R...	--	No	Determine...	0 1 week	1				demo

New... Delete Change...

OK Cancel Help

17 Click the **Oracle** tab to adjust any selections as needed.

18 Click **OK** to complete the setup.

The screenshot shows the 'Change Policy - demo' dialog box with the 'Oracle' tab selected. The dialog is divided into several sections:

- Tbsp/Datfile Options:**
 - Number of parallel streams: 1
 - ☐ Specify read-only tablespace options: SKIP
 - ☐ Offline (cold) database backup
 - ☐ Skip offline datafiles
 - ☐ Specify maximum limits
 - Maximum I/O Limits:**
 - Read rate (KB/sec): 0
 - Size of backup piece (KB): 0
 - Number of open files: 0
 - Maximum backup set limits:**
 - Number of files per backup set: 0
 - Size of backup set (KB): 0
 - Backup Identifier Options:**
 - Backup set identifier:
 - Datfile copy tag: demo
- Archived Redo Log Options:**
 - ☐ Include archived redo logs in full and incremental schedules
 - ☒ Delete after making copies: 1
 - Number of parallel streams: 1
 - ☐ Specify maximum limits
 - Number of files per backup set:** 0
 - Size of backup set (KB):** 0
- User Specified Backup File Name Formats:**
 - ☐ Specify backup file name formats
 - For Datafiles:** bk_d%d_u%u_s%s_p%p_1%t
 - For Archived redo logs:** arch_d%d_u%u_s%s_p%p_1%t
 - For Control file:** ctrl_d%d_u%u_s%s_p%p_1%t
 - For FRA:** fra_d%d_u%u_s%s_p%p_1%t
- Database Backup Share Options:**
 - ☐ Delete protected backup sets from share after: 1 weeks
 - ☐ Delete protected backup copies from share after: 1 weeks

At the bottom of the dialog are three buttons: **OK**, **Cancel**, and **Help**.

See “Copilot configuration overview” on page 7.