

.NET 10 App Dev Hands-On Lab

Razor Pages Lab 5 – View Components, Tag Helpers

This lab walks you through creating a View Component and custom Tag Helpers. Prior to starting this lab, you must have completed Razor Pages Lab 4.

Part 1: Adding the Menu View Component

Step 1: Update the Global Using Statements

- Add the following global using statements to the `GlobalUsings.cs` file in the `AutoLot.Web` project:

```
global using AutoLot.Models.Entities;  
global using Microsoft.AspNetCore.Mvc.ViewComponents;
```

Step 2: Create the View Component Server-Side Code

- Create a new folder named `ViewComponents` in the `AutoLot.Web` project and add a new class named `MenuViewComponent.cs`. Update the class to the following:

Note: Only implement the `Invoke` or the `InvokeAsync` method, not both

```
namespace AutoLot.Web.ViewComponents;  
public class MenuViewComponent(IMakeRepo makeRepo) : ViewComponent  
{  
    public async Task<IViewComponentResult> InvokeAsync()  
    {  
        return await Task.Run<IViewComponentResult>(() =>  
        {  
            var makes = makeRepo.GetAll().ToList();  
            if (!makes.Any())  
            {  
                return new ContentViewComponentResult("Unable to get the makes");  
            }  
            return View("MenuView", makes);  
        });  
    }  
}
```

Step 3: Update the `ViewImports.cshtml` File

- To use the `ViewComponent` as a Tag Helper, the assembly must be registered in the `_ViewImports.cshtml` file in the `Pages` folder. Add the following to the end of the file:

```
@addTagHelper *, AutoLot.Web
```

Step 4: Create the ViewComponent Partial View

- Add a new folder named Components under the Pages\Shared folder. Add a new folder named Menu under the Components folder. Add a new partial view named MenuView.cshtml in the new folder. Update the code to match the following:

```
@model IEnumerable<Make>
<div class="dropdown-menu">
  <a class="dropdown-item text-dark" asp-area="" asp-page="/Cars/Index" asp-route-makeId="" asp-
route-makeName="">All</a>

  @foreach (var item in Model)
  {
    <a class="dropdown-item text-dark" asp-page="/Cars/Index" asp-route-makeId="@item.Id"
    asp-route-makeName="@item.Name">@item.Name</a>
  }
</div>
```

Step 5: Update the _Menu.cshtml Partial View

- Open the _Menu.cshtml file in Pages\Shared\Partials folder and add the view component as a tag helper before each of the Privacy menu items:

```
<ul class="navbar-nav flex-grow-1">
  <li class="nav-item dropdown">
    <a class="nav-link dropdown-toggle text-dark" data-toggle="dropdown">
      Inventory <i class="fa fa-car"></i>
    </a>
    <vc:menu/>
  </li>
  ...
</ul>
```

Step 6: Stub out the Cars Index Page

- Add a new directory named Cars in the Pages directory. Add a new Razor Page – Empty named Index.cshtml to the Cars directory. Update the code behind to the following:

```
namespace AutoLot.Web.Pages.Cars;

public class IndexModel : PageModel
{
  public string MakeName { get; set; }
  public int? MakeId { get; set; }
  public void OnGet(int? makeId, string makeName)
  {
    MakeId = makeId;
    MakeName = makeName;
  }
}
```

- Update the Index view to the following:

```
@page
@model AutoLot.Web.Pages.Cars.IndexModel
@{
    if (Model.MakeId.HasValue)
    {
        <h1>@Model.MakeName</h1>
    }
    else
    {
        <h1>All Makes</h1>
    }
}
```

- **Note:** This page will be completed in the next lab. If you run the app now, the Inventory menu will show all the Makes in the drop-down, but none of the links will be functional.

Part 2: Adding the Custom Tag Helpers

Step 1: Update the GlobalUsings.cs file

- Add the following to the GlobalUsings.cs file:

```
global using Microsoft.AspNetCore.Mvc.Routing;
global using Microsoft.AspNetCore.Razor.TagHelpers;
global using Microsoft.AspNetCore.Mvc.Abstractions;
global using Microsoft.AspNetCore.Mvc.Controllers;
```

Step 2: Create the ItemLinkTagHelperBase

- Create a new folder in the AutoLot.Web project named TagHelpers and add another folder named Base under the TagHelpers folder. In the Base folder, add a new class named ItemLinkTagHelperBase.cs. Update the class to the following:

```
namespace AutoLot.Web.TagHelpers.Base;

public abstract class ItemLinkTagHelperBase : TagHelper
{
    protected readonly IUrlHelper UrlHelper;
    public int? ItemId { get; set; }
    private readonly string _pageName;
    protected string ActionName { get; set; }

    protected ItemLinkTagHelperBase(IHttpContextAccessor contextAccessor,
        IUrlHelperFactory urlHelperFactory)
    {
        //UrlHelper =
        urlHelperFactory.GetUrlHelper(contextAccessor.HttpContext.GetEndpoint()?.Metadata.GetMetadata<ActionDescriptor>());
        var httpContext = contextAccessor.HttpContext;
        var endpoint = httpContext?.GetEndpoint();
        var actionDescriptor = endpoint?.Metadata.GetMetadata<ActionDescriptor>() as
        ControllerActionDescriptor;
        UrlHelper = urlHelperFactory.GetUrlHelper(new ActionContext
        {
            HttpContext = httpContext,
            RouteData = httpContext.GetRouteData(),
            ActionDescriptor = actionDescriptor
        });
        var pageRouteValue = httpContext?.GetRouteData()?.Values["page"] as string;
        _pageName = pageRouteValue?.Split('/',
        StringSplitOptions.RemoveEmptyEntries).FirstOrDefault();
    }

    protected void BuildContent(TagHelperOutput output,
        string cssClassName, string displayText, string fontAwesomeName)
    {
        output.TagName = "a";
        var target = ItemId.HasValue
            ? UrlHelper.Page($"{_pageName}/{ActionName}", new { id = ItemId })
            : UrlHelper.Page($"{_pageName}/{ActionName}");
        output.Attributes.SetAttribute("href", target);
        output.Attributes.Add("class", cssClassName);
        output.Content.AppendHtml($"@{{displayText}} <i class=""fa-solid fa-{fontAwesomeName}""></i>");
    }
}
```

- Add the following to the GlobalUsings.cs file:

```
global using AutoLot.Web.TagHelpers;
global using AutoLot.Web.TagHelpers.Base;
```

Step 3: Create the ItemCreateTagHelper

- In the TagHelpers folder, add a new class named ItemCreateTagHelper.cs and update the code to the following:

```
namespace AutoLot.Web.TagHelpers;
public class ItemCreateTagHelper : ItemLinkTagHelperBase
{
    public ItemCreateTagHelper(IHttpContextAccessor contextAccessor,
        IUrlHelperFactory urlHelperFactory) : base(contextAccessor, urlHelperFactory)
    {
        ActionName = "Create";
    }
    public override void Process(TagHelperContext context, TagHelperOutput output)
    {
        BuildContent(output, "text-success", "Create New", "plus");
    }
}
```

Step 4: Create the ItemDeleteTagHelper

- In the TagHelpers folder, add a new class named ItemDeleteTagHelper.cs and update the code to the following:

```
namespace AutoLot.Web.TagHelpers;
public class ItemDeleteTagHelper : ItemLinkTagHelperBase
{
    public ItemDeleteTagHelper(IHttpContextAccessor contextAccessor,
        IUrlHelperFactory urlHelperFactory)
        : base(contextAccessor, urlHelperFactory)
    {
        ActionName = "Delete";
    }
    public override void Process(TagHelperContext context, TagHelperOutput output)
    {
        BuildContent(output, "text-danger", "Delete", "trash");
    }
}
```

Step 5: Create the ItemDetailsTagHelper

- In the TagHelpers folder, add a new class named ItemDetailsTagHelper.cs and update the code to the following:

```
namespace AutoLot.Web.TagHelpers;

public class ItemDetailsTagHelper : ItemLinkTagHelperBase
{
    public ItemDetailsTagHelper(IHttpContextAccessor contextAccessor,
                               IUrlHelperFactory urlHelperFactory)
        : base(contextAccessor, urlHelperFactory)
    {
        ActionName = "Details";
    }
    public override void Process(TagHelperContext context, TagHelperOutput output)
    {
        BuildContent(output, "text-info", "Details", "info-circle");
    }
}
```

Step 6: Create the ItemEditTagHelper

- In the TagHelpers folder, add a new class named ItemEditTagHelper.cs and update the code to the following:

```
namespace AutoLot.Web.TagHelpers;

public class ItemEditTagHelper : ItemLinkTagHelperBase
{
    public ItemEditTagHelper(IHttpContextAccessor contextAccessor,
                             IUrlHelperFactory urlHelperFactory)
        : base(contextAccessor, urlHelperFactory)
    {
        ActionName = "Edit";
    }
    public override void Process(TagHelperContext context, TagHelperOutput output)
    {
        BuildContent(output, "text-warning", "Edit", "edit");
    }
}
```

Step 7: Create the ItemListTagHelper

- In the TagHelpers folder, add a new class named `ItemListTagHelper.cs` and update the code to the following:

```
namespace AutoLot.Web.TagHelpers;

public class ItemListTagHelper : ItemLinkTagHelperBase
{
    public ItemListTagHelper(IHttpContextAccessor contextAccessor,
                           IUrlHelperFactory urlHelperFactory)
        : base(contextAccessor, urlHelperFactory)
    {
        ActionName = "Index";
    }
    public override void Process(TagHelperContext context, TagHelperOutput output)
    {
        BuildContent(output, "text-default", "Back to List", "list");
    }
}
```

Summary

The lab created the Menu view component and the custom tag helpers.

Next steps

In the next part of this tutorial series, you will build the `BasePageModel` and complete the Cars pages, which will use the custom tag helpers.