

```
1  # (Re)introducing strings
2
3  name = "Neal"
4  # A string is a sequence of characters of some length.
5  # A "sequence" is a bunch of individual things in a row,
6  # ordered from left to right. Each of the "things" in a string
7  # is a character.
8
9  # Draw name's layout in memory.
10
11
12
13
14 # len(): returns the length of a given string value.
15 print(len(name))
16
17
18 # Brackets can be used to read an individual character from a
19 # particular *index*. An index is a position within a string, with
20 # the first character being index 0.
21
22 print(name[0]) # access an individual character of the string
23 # Python is unusual: it allows negative indexes, which count from
24 # the right end instead of the left.
25 print(name[-1])
26 # Same as:
27 print(name[len(name) - 1])
28
29
30 # Although we can access at an index, we can't modify at an index.
31 # name[0] = 'D' -- not allowed
32
33
34 # Strings can be compared with == and !=.
35 if name == "Neal":
36     print("Hi, Neal!")
37 else:
38     print("I don't know who you are!")
39
40
41 # Individual characters can be compared, too.
42 other_name = "Neil"
43 if other_name[2] == "i":
44     print("You spell your name wrong,", other_name, "!")
45
46
47 # We can use a loop to iterate over each individual
48 # character of a string.
49 for i in range(len(name)): # what does this do?
50     print(name[i])
51
52
```

```
53 # CHALLENGE: write a loop that prints the string backwards.
54
55
56
57
58
59 # CHALLENGE: write a loop that prints every other letter of the string.
60
61
62
63
64
65
66
67 # CHALLENGE: write a loop that prints out all the consonants in
68 # the string.
69
70
71
72
73
```

```
1 # Simple functions on strings
2
3 # count_x: return the number of times the letter 'x' can be found in a string.
4 def count_x(st):
5
6
7
8
9
10
11 # double_letter: returns True if the given string has the same letter
12 #   twice in a row.
13 def double_letter(st):
14
15
16
17
18
19
20 # reverse_string: returns the reverse of the given string, without using
21 #   the built-in Python function.
22 def reverse_string(st):
23
24
25
26
27 # is_palindrome: given a string that only contains lowercase letters,
28 #   determine if the string is a palindrome.
29
30 def is_palindrome(st):
31
32
33
34
35
36
37 print(is_palindrome("lonelytylenol"))
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
```

53
54
55
56

```
1 # String slices
2
3 # A "slice" is a portion of an existing string, designated with a start index
4 # and an end index. The slice creates a copy of the string starting at the given
5 # index, and copying all characters in the string up to but not including the
6 # end index.
7
8 st = "CECS 174 is so much fun"
9 department = st[0:4]
10 # First number is the start index; second is the end index (remember, not
    inclusive).
11 # Another way:
12 department = st[:4]
13 # With no start index, we start at 0.
14 print(department)
15
16 course_num = st[5:8]
17 print(course_num)
18 feeling = st[12:] # with no end index, we go to the last character
19 print(feeling)
20
21
22
23 # Remember: a slice does NOT MODIFY the original string. It just copies some
    indexes
24 # into a new string.
25
```

```
1 # "Parse" a phone number into three integer variables: the
2 # area_code, the prefix, and the suffix.
3
4 # The phone number can be in one of three formats:
5 # (AAA) BBB-CCCC
6 # AAA BBB CCCC
7 # AAABBBCCCC
8
9 phone_number = input("Enter a phone number")
10
11 if phone_number[0] == '(':
12     area_code = phone_number[1:4]
13     prefix = phone_number[6:9]
14     suffix = phone_number[10:]
15 elif phone_number[3] == ' ':
16     sp = phone_number.split(" ")
17     area_code = sp[0]
18     prefix = sp[1]
19     suffix = sp[2]
20 else:
21     parsed = int(phone_number)
22     suffix = parsed % 10000
23     prefix = (parsed // 10000) % 1000
24     area_code = parsed // 10000000
25
26 print("Area code {0}, prefix {1}, suffix {2}".format(area_code, prefix, suffix))
27
```

```
1 # Simple functions on strings
2
3 # count_x: return the number of times the letter 'x' can be found in a string.
4 def count_x(st):
5     any_variable = 0
6     for i in range(len(st)):
7         if st[i] == 'x':
8             any_variable += 1
9
10    return any_variable
11
12 print(count_x("abxcdefxxg"))
13
14
15 # double_letter: returns True if the given string has the same letter
16 #   twice in a row.
17 def double_letter(st):
18     for i in range(len(st) - 1):
19         if st[i] == st[i + 1]:
20             return True
21
22    return False
23
24 print(double_letter("terrell"))
25
26
27 # reverse_string: returns the reverse of the given string, without using
28 #   the built-in Python function.
29 def reverse_string(st):
30     rev = ""
31
32     for i in range(len(st) - 1, -1, -1):
33         rev += st[i] + " "
34
35    return rev
36 print(reverse_string("terrell"))
37
38
39 # is_palindrome: given a string that only contains lowercase letters,
40 #   determine if the string is a palindrome.
41
42 # hannah
43 # otto
44 # racecar
45
46 def is_palindrome(st):
47     i = 0
48     j = len(st) - 1
49
50     while i < len(st) // 2:
51         j = len(st) - i - 1
52
```

```
53     if st[i] != st[j]:
54         return False
55     i += 1
56     j -= 1
57
58     return True
59
60 print(is_palindrome("hannah"))
61 print(is_palindrome("A dog, a panic in a pagoda!"))
62 print(is_palindrome("lonelytylenol"))
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
```