

Document Title	Specification of Standard Types
Document Owner	AUTOSAR
Document Responsibility	AUTOSAR
Document Identification No	49

Document Status	published
Part of AUTOSAR Standard	Classic Platform
Part of Standard Release	R23-11

Document Change History			
Date	Release	Changed by	Description
2023-11-23	R23-11	AUTOSAR Release Management	 Added Safety Transformer Error Codes in [SWS_Std_00028] Editorial Changes
2022-11-24	R22-11	AUTOSAR Release Management	 Added Std_TransformerForwardCode and removed [SWS_Std_00027] Introduced Not applicable requirement [SWS_Std_NA_00999] Removed use of deprecate "compiler abstraction" from [SWS_Std_00031] Editorial Changes
2021-11-25	R21-11	AUTOSAR Release Management	Added SWS_Std_00031 (NULL_PTR) Editorial Changes
2020-11-30	R20-11	AUTOSAR Release Management	 Fixed Design issues with E2E communication protection for methods Added TransformerError and TransformerForward Fixed missing Type definitions Editorial Changes
2019-11-28	R19-11	AUTOSAR Release Management	 Added chapter Std_TransformerError Editorial changes Changed Document Status from Final to published





 \triangle

2018-10-31	4.4.0	AUTOSAR Release Management	Header File Cleanup (no impact on behavior)	
2017-12-08	4.3.1	AUTOSAR Release Management	TOSAR lease • Updated OSEK reference (editorial)	
2016-11-30	4.3.0	AUTOSAR Release Management	Corrected editorial traceability issues	
2015-07-31	4.2.2	AUTOSAR Release Management	Harmonized traceability	
2014-10-31	4.2.1	AUTOSAR Release Management	Editorial changes	
2013-10-31	4.1.2	AUTOSAR Release Management	 Editorial changes Removed chapter(s) on change documentation 	
2013-03-15	4.1.1	AUTOSAR Administration	Harmonized requirements according to SWS_General	
2011-12-22	4.0.3	AUTOSAR Administration	Update of SWS documents for new traceability mechanism	
2010-02-02	3.1.4	AUTOSAR Administration	 Removed instanceID from StdVersionType Concretized the published parameters to have the prefix STD_TYPES Legal disclaimer revised 	
2008-08-13	3.1.1	AUTOSAR Administration	Legal disclaimer revised	
2007-12-21	3.0.1	AUTOSAR Administration	 Add Module ID for Complex Drivers Document meta information extended Small layout adaptations made 	
2007-01-24	2.1.15	AUTOSAR Administration	 "Advice for users" revised "Revision Information" added	



 \triangle

<u>—</u>			
2006-11-28- 01	2.1.1	AUTOSAR Administration	 Changed definition of Standard_ReturnType to match the RTE definition. A complete overview of definitions and values has been performed to match the requirements in the SRS General.
2006-05-16	2.0	AUTOSAR Administration	Initial Release



Disclaimer

This work (specification and/or software implementation) and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the work.

The material contained in this work is protected by copyright and other types of intellectual property rights. The commercial exploitation of the material contained in this work requires a license to such intellectual property rights.

This work may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only. For any other purpose, no part of the work may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The work has been developed for automotive applications only. It has neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.



Contents

1	Introduction and functional overview			
2	Acronyms and abbreviations 8			
3	Related documentation 9			
	3.1 Input documents & related standards and norms			
4	Constraints and assumptions 10			
	4.1 Limitations			
5	Software Architecture 11			
	5.1 Dependencies to other modules			
6	Requirements Tracing 12			
7	Functional specification 13			
	7.1 General issues 13 7.2 Error Classification 13 7.2.1 Development Errors 13 7.2.2 Runtime Errors 13 7.2.3 Transient Faults 14 7.2.4 Production Errors 14 7.2.5 Extended Production Errors 14			
8	API specification 15			
	8.1 Type definitions 15 8.1.1 Std_ReturnType 15 8.1.2 Std_VersionInfoType 16 8.1.3 Std_TransformerError 16 8.1.4 Std_TransformerForwardCode 18 8.1.5 Std_MessageTypeType 19 8.1.6 Std_MessageResultType 19 8.1.7 Std_ExtractProtocolHeaderFieldsType 20 8.2 Symbol definitions 20 8.2.1 E_OK, E_NOT_OK 20 8.2.2 STD_HIGH, STD_LOW 21 8.2.3 STD_ACTIVE, STD_IDLE 21 8.2.4 STD_ON, STD_OFF 21 8.2.5 NULL_PTR 22			
	8.3 Function definitions			

Specification of Standard Types AUTOSAR CP R23-11



9	Sequence diagrams	23
10	Configuration specification	24
Α	Not applicable requirements	25
В	History of Requirements	26
	 B.1 Requirement History of this Document According to AUTOSAR Release R22-11 B.1.1 Added Specification Items in R22-11 B.1.2 Changed Specification Items in R22-11 B.1.3 Deleted Specification Items in R22-11 B.2 Requirement History of this Document According to AUTOSAR Re- 	26 26
	lease R23-11	26 26



1 Introduction and functional overview

This document specifies the AUTOSAR standard types header file. It contains all types that are used across several modules of the basic software and that are platform and compiler independent.

It is strongly recommended that those standard types files are unique within the AUTOSAR community to guarantee unique types and to avoid types changes when changing from supplier A to B.



2 Acronyms and abbreviations

Acronyms and abbreviations that have a local scope are not contained in the AUTOSAR glossary. These must appear in a local glossary.

Acronym:	Description:
API	Application Programming Interface
OSEK/VDX	Offene Systeme und deren Schnittstellen fuer die Elektronik im Kraftfahrzeug

Abreviation:	Description:
STD	Standard



3 Related documentation

3.1 Input documents & related standards and norms

- [1] General Requirements on Basic Software Modules AUTOSAR_CP_SRS_BSWGeneral
- [2] General Requirements on SPAL AUTOSAR_CP_SRS_SPALGeneral
- [3] Specification of RTE Software AUTOSAR CP SWS RTE
- [4] Requirements on Basic Software Module Description Template AUTOSAR_CP_RS_BSWModuleDescriptionTemplate
- [5] List of Basic Software Modules
 AUTOSAR CP TR BSWModuleList
- [6] ISO 17356-3:Road vehicles Open interface for embedded automotive applications – Part 3:OSEK/VDX Operating System (OS)

3.2 Related specification

AUTOSAR provides a General Specification on Basic Software modules [1, SWS BSW General], which is also valid for Standard Types.

Thus, the specification SWS BSW General shall be considered as additional and required specification for Standard Types.

Further specification:

[2, SRS SPALGeneral] [3, SWS RTE] [4, RS BSW General] [5, TR BSW General] [6, OSEK/VDX Operating System] [ISO/IEC 9899:1990]



4 Constraints and assumptions

4.1 Limitations

No limitations.

4.2 Applicability to car domains

Many symbols defined in this specification (like OK, NOT_OK, ON, OFF) are already defined and used within legacy software. These conflicts ('redefinition of existing symbol') are expected, but neglected, because of the following reasons:

 AUTOSAR has to maintain network compatibility with legacy ECUs, but no software architecture compatibility with legacy software Many types are defined and used exactly in the same way that legacy software does. Legacy software can keep on using the symbols, only the definitions have to be removed and taken from this file instead.



5 Software Architecture

5.1 Dependencies to other modules

5.2 File structure

The include structures differ between BSW modules which are part of the COM-stack and other modules. BSW modules which is considered part of the COM stack shall include the ComStackTypes.h other modules shall include StandardTypes.h

5.2.1 Communication related BSW modules

[SWS_Std_00030] [The include file structure shall be as follows:

- ComStackTypes.h shall include StandardTypes.h
- Communication related basic software modules shall include ComStackTypes.h

]()



6 Requirements Tracing

The following tables reference the requirements specified in SRS BSW General [1] and links to the fulfillment of these. Please note that if column "Satisfied by" is empty for a specific requirement this means that this requirement is not fulfilled by this document.

Requirement	Description	Satisfied by
[SRS_BSW_00004]	All Basic SW Modules shall perform a pre-processor check of the versions of all imported include files	[SWS_Std_00015] [SWS_Std_91003]
[SRS_BSW_00161] The AUTOSAR Basic Software shall provide a microcontroller abstraction layer which provides a standardized interface to higher software layers		[SWS_Std_00004]
[SRS_BSW_00305]	Data types naming convention	[SWS_Std_00017] [SWS_Std_00019] [SWS_Std_91001] [SWS_Std_91002]
[SRS_BSW_00348]	All AUTOSAR standard types and constants shall be placed and organized in a standard type header file	[SWS_Std_00007] [SWS_Std_00010] [SWS_Std_00013]
[SRS_BSW_00357]	For success/failure of an API call a standard return type shall be defined	[SWS_Std_00005] [SWS_Std_00006] [SWS_Std_00011]
[SRS_BSW_00441]	Naming convention for type, macro and function	[SWS_Std_00011]
[SRS_BSW_00480]	Null pointer errors shall follow a naming rule	[SWS_Std_00031]
[SRS_Xfrm_00002]	A transformer shall provide fixed interfaces	[SWS_Std_00028] [SWS_Std_00029]
[SRS_Xfrm_00004]	A transformer shall support error handling	[SWS_Std_00021] [SWS_Std_00022] [SWS_Std_00024] [SWS_Std_00025]
[SRS_Xfrm_00008]	A transformer shall specify its output format	[SWS_Std_00022] [SWS_Std_00023]
[SRS_Xfrm_00009]	A fixed set of transformer classes shall exist	[SWS_Std_00023]
[SRS_Xfrm_00010]	Each transformer class shall provide a fixed set of abstract errors	[SWS_Std_00024]
[SRS_Xfrm_00011]	A transformer shall belong to a specific transformer class	[SWS_Std_00026]

Table 6.1: RequirementsTracing



7 Functional specification

7.1 General issues

[SWS_Std_00004] [It is not allowed to add any project or supplier specific extension to this file. Any extension invalidates the AUTOSAR conformity. | (SRS_BSW_00161)

[SWS_Std_00014] The standard types header file shall be protected against multiple inclusion:

```
1 #ifndef STD_TYPES_H
2
3 #define STD_TYPES_H
4
5 ...
6
7 /*
8
9 * Contents of file
10
11 */
12
13 ..
14
15 #endif /* STD_TYPES_H */
|()
```

7.2 Error Classification

The section "Error Handling" of the document "General Specification of Basic Software Modules" describes the error handling of the Basic Software in detail. Above all, it constitutes a classification scheme consisting of five error types which may occur in BSW modules.

Based on this foundation, the following section specifies particular errors arranged in the respective subsections below.

7.2.1 Development Errors

There are no development errors.

7.2.2 Runtime Errors

There are no runtime errors.



7.2.3 Transient Faults

There are no transient faults.

7.2.4 Production Errors

There are no production errors.

7.2.5 Extended Production Errors

There are no extended production errors.



8 API specification

8.1 Type definitions

8.1.1 Std_ReturnType

[SWS_Std_00005] Definition of datatype Std_ReturnType [

Name	Std_ReturnType		
Kind	Туре		
Derived from	uint8		
Range	E_OK	0	see 8.2.1, SWS_Std_00006
	E_NOT_OK	1	see 8.2.1, SWS_Std_00006
	0x02-0x3F	2	Available to user specific errors
Description	This type can be used as standard API return type which is shared between the RTE and the BSW modules. It shall be defined as follows: typedef uint8 Std_ReturnType;		
Available via	Std_Types.h		

(SRS_BSW_00357)

[SWS_Std_00011] [The Std_ReturnType shall normally be used with value E_OK or E_NOT_OK. If those return values are not sufficient user specific values can be defined by using the 6 least specific bits.

For the naming of the user defined values the module prefix shall be used as requested in SRS_BSW_00441

Layout of the Std_ReturnType shall be as stated in the RTE specification. Bit 7 and Bit 8 are reserved and defined by the RTE specification.

|(SRS_BSW_00357, SRS_BSW_00441)




Figure 8.1: Layout of Std_Return_Type



8.1.2 Std_VersionInfoType

[SWS_Std_00015] Definition of datatype Std_VersionInfoType [

Name	Std_VersionInfoType	
Kind	Structure	
vendorID		
Elements	Туре	uint16
	Comment	_
	moduleID	
	Туре	uint16
	Comment	_
	sw_major_version	
	Type uint8	
	Comment – sw_minor_version	
	Type uint8	
	Comment	-
	sw_patch_version	
	Type uint8	
	Comment	-
Description	This type shall be used to request the version of a BSW module using the <module name="">_Get VersionInfo() function.</module>	
Available via	Std_Types.h	

(SRS_BSW_00004)

8.1.3 Std_TransformerError

The data type Std_TransformerError is a struct which contains the error code and the transformer class to which the error belongs.

The data type Std_TransformerError shall be defined as follows:

[SWS_Std_00021] Definition of datatype Std_TransformerError [

Name	Std_TransformerError	
Kind	Structure	
Elements	errorCode	
	Туре	Std_TransformerErrorCode
	Comment	The specific meaning of the values of Std_TransformerErrorCode is to be seen for the specific transformer chain for which the data type represents the transformer error.
	transformerClass	
	Туре	Std_TransformerClass
	Comment	_
Description	Std_TransformerError represents a transformer error in the context of a certain transformer chain.	
Available via	Std_Types.h	

(SRS Xfrm 00004)



The values are specified for each transformer class in [26, ASWS Transformer General].

[SWS_Std_00022] Definition of datatype Std_TransformerErrorCode [

Name	Std_TransformerErrorCode		
Kind	Туре		
Derived from	uint8		
Range	-	-	The values are specified for each transformer class in ASWS_ TransformerGeneral.
Description	The type of the Std_TransformerError.		
Available via	Std_Types.h		

(SRS Xfrm 00004, SRS Xfrm 00008)

The Std_TransformerClass represents the transformer class in which the error occurred.

[SWS_Std_00023] [The underlying data type of the type Std_TransformerClass shall be uint8. | (SRS_Xfrm_00009, SRS_Xfrm_00008)

The type Std_TransformerClass shall be an enumeration with the following elements where each element represents a transformer class:

[SWS_Std_00024] Definition of datatype Std_TransformerClass [

Name	Std_TransformerClass		
Kind	Туре		
Derived from	uint8		
Range	STD_TRANSFORMER_ UNSPECIFIED	0x00	Transformer of a unspecified transformer class.
	STD_TRANSFORMER_ SERIALIZER	0x01	Transformer of a serializer class.
	STD_TRANSFORMER_ SAFETY	0x02	Transformer of a safety class.
	STD_TRANSFORMER_ SECURITY	0x03	Transformer of a security class.
	STD_TRANSFORMER_ CUSTOM	0xFF	Transformer of a custom class not standardized by AUTOSAR.
Description	Std_TransformerClass is an enumeration where each element represents a transformer class.		
Available via	Std_Types.h		

(SRS Xfrm 00004, SRS Xfrm 00010)

[SWS_Std_00025] [The transformer class STD_TRANSFORMER_UNSPECIFIED shall be used if no transformer error occured. | (SRS_Xfrm_00004)

[SWS_Std_00026] The mapping from transformerClass of TransformationTechnology to value of data type Std TransformerClass shall be:

- transformerClass serializer STD TRANSFORMER SERIALIZER
- transformerClass safety STD TRANSFORMER SAFETY



- transformerClass security STD_TRANSFORMER_SECURITY
- transformerClass custom STD TRANSFORMER CUSTOM

(SRS_Xfrm_00011)

8.1.4 Std TransformerForwardCode

The data type Std_TransformerForwardCode represents a forwarded transformer code in the context of a certain transformer chain (see [5]).

The specific meaning of the values of Std_TransformerForwardCode is always to be seen for the specific transformer chain for which the data type represents the transformer status.

[SWS_Std_00028]{DRAFT} Safety Transformer Error Codes

Error Name	Error Code	Description
E_OK	0x00	No specific error to be injected
E_SAFETY_INVALID_REP	0x01	Repeat the last used sequence number.
E_SAFETY_INVALID_CRC	0x03	Generate a deliberately wrong CRC.
E_SAFETY_INVALID_SEQ	0x02	Use a wrong sequence number.

Table 8.1: Safety Transformer Error Codes

(SRS_Xfrm_00002)

The underlying data type of the type Std TransformerForwardCode shall be uint8:

[SWS_Std_00029]{DRAFT} Definition of datatype Std_TransformerForwardCode

Name	Std_TransformerForwardCode (draft)			
Kind	Туре	Туре		
Derived from	uint8			
Range	E_OK	0x00	_	
	E_SAFETY_INVALID_REP	E_SAFETY_INVALID_REP 0x01 -		
	E_SAFETY_INVALID_SEQ 0x02 -			
	E_SAFETY_INVALID_CRC	0x03	_	
Description	-			
	Tags: atp.Status=draft			
Available via	Std_Types.h			

(SRS_Xfrm_00002)



8.1.5 Std_MessageTypeType

[SWS_Std_91001] Definition of datatype Std_MessageTypeType [

Name	Std_MessageTypeType		
Kind	Туре		
Derived from	uint8		
Range	STD_MESSAGETYPE_ 0x00 Message type for a request message		
	STD_MESSAGETYPE_ RESPONSE	0x01	Message type for a response message
	0x02-0x3F	0x02	reserverd for future message type
Description	This type is used to encode the different type of messages Currently this encoding is limited to the distinction between requests and responses in C/S communication.		
Available via	Std_Types.h		

(SRS BSW 00305)

[SWS_Std_00017] [The Std_MessageTypeType shall be used ot encode the different types of messages exchanged in AUTOSAR. - Currently this encoding is limited to the distinction between requests and responses in C/S communication.] (SRS_BSW_-00305)

Note: In future AUTOSAR release, the literals for this type may be extended with additional message types.

8.1.6 Std_MessageResultType

[SWS Std 91002] Definition of datatype Std MessageResultType [

Name	Std_MessageResultType		
Kind	Type		
Derived from	uint8		
Range	STD_MESSAGERESULT_ 0x00 STD_MESSAGERESULT_OK OK		
	STD_MESSAGERESULT_ 0x01 Messageresult fresponse		Messageresult for an ERROR response
	0x02-0x3F	0x02	reserverd for future message results
Description	This type is used to encode different types of results for response messages Currently this encoding is limited to the distinction between OK and ERROR responses.		
Available via	Std_Types.h		

(SRS BSW 00305)

[SWS_Std_00019] [The Std_MessageResultType shall be used ot encode the different types of results for response messages. - Currently this encoding is limited to the distinction between OK and ERROR responses. | (SRS_BSW_00305)

Note: In future AUTOSAR release, the literals for this type may be extended with additional result types.



8.1.7 Std_ExtractProtocolHeaderFieldsType

[SWS_Std_91003] Definition of datatype Std_ExtractProtocolHeaderFieldsType [

Name	Std_ExtractProtocolHeaderFieldsType		
Kind	Function Pointer		
Syntax	<pre>Std_ReturnType (*Std_ExtractProtocolHeaderFieldsType) (const uint8* buffer, uint32 bufferLength, Std_MessageType* messageType, Std_MessageResultType* messageResult)</pre>		
Parameters (in)	buffer Buffer allocated by the RTE, where the transformed data has to be stored by the transformer		
	bufferLength Length of the buffer		
Parameters (inout)	None		
Parameters (out)	messageType Canonical representation of the message type (extracted from the transformers protocol header).		
	messageResult Canonical representation of the message result type (extracted from the transformers protocol header).		
Return value	Std_ReturnType -		
Description	Type for the function pointer to extract the relevant protocol header fields of the message and the type of the message result of a transformer At the time being, this is limited to the types used for C/S communication (i.e., REQUEST and RESPONSE and OK and ERROR).		
Available via	Std_Types.h		

∫(SRS_BSW_00004)

8.2 Symbol definitions

8.2.1 E_OK, E_NOT_OK

[SWS_Std_00006] Definition of datatype E_OK, E_NOT_OK [

Name	E_OK, E_NOT_OK		
Kind	Enumeration		
Range	E_OK	0x00u	_
	E_NOT_OK	0x01u	_
Description	Because E_OK is already defined within OSEK, the symbol E_OK has to be shared. To avoid name clashes and redefinition problems, the symbols have to be defined in the following way (approved within implementation): #ifndef STATUSTYPEDEFINED		
	#define STATUSTYPEDEFINED #define E_OK 0x00u		
	typedef unsigned char StatusType; /* OSEK compliance */ #endif		
	#define E_NOT_OK 0x01u		
Available via	Std_Types.h		

](SRS_BSW_00357)



8.2.2 STD_HIGH, STD_LOW

[SWS_Std_00007] Definition of datatype STD_HIGH, STD_LOW [

Name	STD_HIGH, STD_LOW		
Kind	Enumeration		
Range	STD_LOW	0x00u	_
	STD_HIGH	0x01u	-
Description	The symbols STD_HIGH and STD_LOW shall be defined as follows:		
	#define STD_HIGH 0x01u /* Physical state 5V or 3.3V */ #define STD_LOW 0x00u /* Physical state 0V */		
Available via	Std_Types.h		

(SRS_BSW_00348)

8.2.3 STD_ACTIVE, STD_IDLE

[SWS_Std_00013] Definition of datatype STD_ACTIVE, STD_IDLE [

Name	STD_ACTIVE, STD_IDLE			
Kind	Enumeration			
Range	STD_IDLE	STD_IDLE 0x00u -		
	STD_ACTIVE	0x01u	_	
Description	The symbols STD_ACTIVE and STD_IDLE shall be defined as follows:			
	#define STD_ACTIVE 0x01u /* Logical state active */ #define STD_IDLE 0x00u /* Logical state idle */			
Available via	Std_Types.h			

(SRS_BSW_00348)

8.2.4 STD_ON, STD_OFF

[SWS_Std_00010] Definition of datatype STD_ON, STD_OFF [

Name	STD_ON, STD_OFF			
Kind	Enumeration	Enumeration		
Range	STD_OFF	STD_OFF 0x00u -		
	STD_ON	0x01u	-	
Description	The symbols STD_ON and STD_OFF shall be defined as follows:			
	#define STD_ON 0x01u #define STD_OFF 0x00u			
Available via	Std_Types.h			

(SRS_BSW_00348)



8.2.5 NULL_PTR

[SWS_Std_00031] [

Define	NULL_PTR	
Range	void pointer	((void *)0)
Description	The implementation shall provide the NULL_PTR define with a void pointer to zero definition.	

(SRS_BSW_00480)

8.3 Function definitions

Not applicable.



9 Sequence diagrams

Not applicable.



10 Configuration specification

Not applicable.



A Not applicable requirements

[SWS Std NA 00999] [These requirements are not applicable to this specification. | (SRS BSW 00300, SRS BSW 00301, SRS BSW 00302, SRS BSW 00304, SRS BSW 00305, SRS BSW 00306, SRS BSW 00307, SRS BSW 00308, SRS -BSW 00309. SRS BSW 00310. SRS BSW 00312. SRS BSW 00314. SRS -BSW 00321, SRS BSW 00325, SRS BSW 00327, SRS BSW 00330, SRS -SRS BSW 00334, BSW 00331, SRS BSW 00333, SRS BSW 00335, SRS -BSW 00342. SRS BSW 00343. SRS BSW 00341. SRS -SRS BSW 00346. BSW 00347. SRS BSW 00350, SRS BSW 00353. SRS BSW 00358. SRS -BSW 00359, SRS BSW 00360, SRS BSW 00373, SRS BSW 00374, SRS -BSW 00377, SRS BSW 00378, SRS BSW 00379, SRS BSW 00401, SRS -BSW 00408. SRS BSW 00410, SRS BSW 00411, SRS BSW 00413. SRS -BSW 00414, SRS BSW 00415, SRS BSW 00005. SRS BSW 00006, SRS -BSW 00007, SRS BSW 00009, SRS BSW 00010, SRS BSW 00160, SRS -BSW 00161. SRS BSW 00162. SRS BSW 00164. SRS BSW 00172. SRS -BSW 00344, SRS BSW 00404, SRS BSW 00405, SRS BSW 00345, SRS -BSW 00159. SRS BSW 00167. SRS BSW 00171. SRS BSW 00170. SRS -BSW_00380, SRS BSW 00419, SRS BSW 00383, SRS BSW 00388, SRS -BSW 00389. SRS BSW 00390, SRS BSW 00392, SRS BSW 00393, SRS -BSW 00394. SRS BSW 00395. SRS BSW 00396. SRS -SRS BSW 00397. BSW 00398, SRS BSW 00399, SRS BSW 00400. SRS BSW 00375, SRS -BSW 00101, SRS BSW 00416, SRS BSW 00406, SRS BSW 00168, SRS -BSW 00407. SRS BSW 00423. SRS BSW 00424. SRS BSW 00425. SRS -SRS_BSW 00427. BSW 00426. SRS BSW 00428, SRS BSW 00429. SRS -SRS BSW 00433, BSW 00432, SRS BSW 00336, SRS BSW 00337, SRS -BSW 00369. SRS BSW 00339. SRS BSW 00422. SRS BSW 00417. SRS -SRS BSW 00409. SRS BSW 00385. BSW 00323. SRS BSW 00386. SRS -BSW 00452, SRS BSW 00473, SRS BSW 00458, SRS BSW 00466)



B History of Requirements

Please note that the lists in this chapter also include requirements that have been removed from the specification in a later version. These requirements do not appear as hyperlinks in the document.

B.1 Requirement History of this Document According to AUTOSAR Release R22-11

B.1.1 Added Specification Items in R22-11

[SWS Std NA 00999]

B.1.2 Changed Specification Items in R22-11

[SWS_Std_00005] [SWS_Std_00006] [SWS_Std_00007] [SWS_Std_00010] [SWS_Std_00013] [SWS_Std_00015] [SWS_Std_00021] [SWS_Std_00022] [SWS_Std_00024] [SWS_Std_00029] [SWS_Std_00031] [SWS_Std_91001] [SWS_Std_91002] [SWS_Std_91003]

B.1.3 Deleted Specification Items in R22-11

[SWS Std 00027] [SWS Std 00999]

B.2 Requirement History of this Document According to AUTOSAR Release R23-11

B.2.1 Added Specification Items in R23-11

none

B.2.2 Changed Specification Items in R23-11

[SWS Std 00028]

B.2.3 Deleted Specification Items in R23-11

none