

Last chance! 4 days left! [Get 20% off membership now](#)

A Comprehensive Guide to Convolutional Neural Networks — the ELI5 way



Sumit Saha · [Follow](#)


Published in Towards Data Science · 7 min read · Dec 16, 2018



14.7K



66




Artificial Intelligence has been witnessing monumental growth in bridging the gap between the capabilities of humans and machines. Researchers and enthusiasts alike, work on numerous aspects of the field to make amazing things happen. One of many such areas is the domain of Computer Vision.

The agenda for this field is to enable machines to view the world as humans do, perceive it in a similar manner, and even use the knowledge for a multitude of tasks such as Image & Video recognition, Image Analysis & Classification, Media Recreation, Recommendation Systems, Natural Language Processing, etc. The advancements in Computer Vision with Deep Learning have been constructed and perfected with time, primarily over one particular algorithm — a **Convolutional Neural Network**.

Ready to try out your own convolutional neural nets? Check out [Saturn Cloud](#) for free compute (including free GPUs).

Introduction



A CNN sequence to classify handwritten digits

A **Convolutional Neural Network (ConvNet/CNN)** is a Deep Learning algorithm that can take in an input image, assign importance (learnable weights and biases) to various aspects/objects in the image, and be able to

differentiate one from the other. The pre-processing required in a ConvNet is much lower as compared to other classification algorithms. While in primitive methods filters are hand-engineered, with enough training, ConvNets have the ability to learn these filters/characteristics.

The architecture of a ConvNet is analogous to that of the connectivity pattern of Neurons in the Human Brain and was inspired by the organization of the Visual Cortex. Individual neurons respond to stimuli only in a restricted region of the visual field known as the Receptive Field. A collection of such fields overlap to cover the entire visual area.

Why ConvNets over Feed-Forward Neural Nets?

Flattening of a 3×3 image matrix into a 9×1 vector

An image is nothing but a matrix of pixel values, right? So why not just flatten the image (e.g. 3×3 image matrix into a 9×1 vector) and feed it to a Multi-Level Perceptron for classification purposes? Uh.. not really.

In cases of extremely basic binary images, the method might show an average precision score while performing prediction of classes but would have little to no accuracy when it comes to complex images having pixel dependencies throughout.

A ConvNet is able to **successfully capture the Spatial and Temporal dependencies** in an image through the application of relevant filters. The architecture performs a better fitting to the image dataset due to the reduction in the number of parameters involved and the reusability of weights. In other words, the network can be trained to understand the sophistication of the image better.

Input Image

4×4×3 RGB Image

In the figure, we have an RGB image that has been separated by its three

color planes — Red, Green, and Blue. There are a number of such color spaces in which images exist — Grayscale, RGB, HSV, CMYK, etc.

You can imagine how computationally intensive things would get once the images reach dimensions, say 8K (7680×4320). The role of ConvNet is to reduce the images into a form that is easier to process, without losing features that are critical for getting a good prediction. This is important when we are to design an architecture that is not only good at learning features but also scalable to massive datasets.

Convolution Layer — The Kernel

Convoluting a 5×5×1 image with a 3×3×1 kernel to get a 3×3×1 convolved feature

Image Dimensions = 5 (Height) x 5 (Breadth) x 1 (Number of channels, eg. RGB)

In the above demonstration, the green section resembles our 5x5x1 input

image, I. The element involved in the convolution operation in the first part of a Convolutional Layer is called the **Kernel/Filter, K**, represented in color yellow. We have selected **K** as a **3x3x1 matrix**.

Kernel/Filter, K =

1	0	1
0	1	0
1	0	1

The Kernel shifts 9 times because of **Stride Length = 1 (Non-Strided)**, every time performing an **elementwise multiplication operation (Hadamard Product)** between **K** and the portion **P** of the image over which the kernel is hovering.

Movement of the Kernel

The filter moves to the right with a certain Stride Value till it parses the complete width. Moving on, it hops down to the beginning (left) of the image with the same Stride Value and repeats the process until the entire image is traversed.

Convolution operation on a $M \times N \times 3$ image matrix with a $3 \times 3 \times 3$ Kernel

In the case of images with multiple channels (e.g. RGB), the Kernel has the same depth as that of the input image. Matrix Multiplication is performed between K_n and I_n stack ($[K_1, I_1]; [K_2, I_2]; [K_3, I_3]$) and all the results are summed with the bias to give us a squashed one-depth channel Convolved Feature Output.

Convolution Operation with Stride Length = 2

The objective of the Convolution Operation is to **extract the high-level features** such as edges, from the input image. ConvNets need not be limited to only one Convolutional Layer. Conventionally, the first ConvLayer is responsible for capturing the Low-Level features such as edges, color, gradient orientation, etc. With added layers, the architecture adapts to the High-Level features as well, giving us a network that has a wholesome understanding of images in the dataset, similar to how we would.

There are two types of results to the operation — one in which the convolved feature is reduced in dimensionality as compared to the input, and the other in which the dimensionality is either increased or remains the same. This is done by applying **Valid Padding** in the case of the former, or **Same Padding** in the case of the latter.

SAME padding: $5 \times 5 \times 1$ image is padded with 0s to create a $6 \times 6 \times 1$ image

When we augment the $5 \times 5 \times 1$ image into a $6 \times 6 \times 1$ image and then apply the $3 \times 3 \times 1$ kernel over it, we find that the convolved matrix turns out to be of dimensions $5 \times 5 \times 1$. Hence the name — **Same Padding**.

On the other hand, if we perform the same operation without padding, we are presented with a matrix that has dimensions of the Kernel ($3 \times 3 \times 1$) itself — **Valid Padding**.

The following repository houses many such GIFs which would help you get a better understanding of how Padding and Stride Length work together to achieve results relevant to our needs.

vdumoulin/conv_arithmetic

A technical report on convolution arithmetic in the context of deep learning - vdumoulin/conv_arithmetic

github.com

Pooling Layer

3×3 pooling over 5×5 convolved feature

Similar to the Convolutional Layer, the Pooling layer is responsible for reducing the spatial size of the Convolved Feature. This is to **decrease the computational power required to process the data** through dimensionality reduction. Furthermore, it is useful for **extracting dominant features** which are rotational and positional invariant, thus maintaining the process of effectively training the model.

There are two types of Pooling: Max Pooling and Average Pooling. **Max Pooling** returns the **maximum value** from the portion of the image covered by the Kernel. On the other hand, **Average Pooling** returns the **average of all the values** from the portion of the image covered by the

Kernel.

Max Pooling also performs as a **Noise Suppressant**. It discards the noisy activations altogether and also performs de-noising along with dimensionality reduction. On the other hand, Average Pooling simply performs dimensionality reduction as a noise-suppressing mechanism. Hence, we can say that **Max Pooling performs a lot better than Average Pooling**.

Types of Pooling

The Convolutional Layer and the Pooling Layer, together form the i -th layer of a Convolutional Neural Network. Depending on the complexities in the images, the number of such layers may be increased for capturing low-level details even further, but at the cost of more computational power.

After going through the above process, we have successfully enabled the model to understand the features. Moving on, we are going to flatten the final output and feed it to a regular Neural Network for classification purposes.

Classification — Fully Connected Layer (FC Layer)

Adding a Fully-Connected layer is a (usually) cheap way of learning non-linear combinations of the high-level features as represented by the output of the convolutional layer. The Fully-Connected layer is learning a possibly non-linear function in that space.

Now that we have converted our input image into a suitable form for our Multi-Level Perceptron, we shall flatten the image into a column vector. The flattened output is fed to a feed-forward neural network and backpropagation is applied to every iteration of training. Over a series of epochs, the model is able to distinguish between dominating and certain

low-level features in images and classify them using the **Softmax Classification** technique.

There are various architectures of CNNs available which have been key in building algorithms which power and shall power AI as a whole in the foreseeable future. Some of them have been listed below:

1. LeNet
2. AlexNet
3. VGGNet
4. GoogLeNet
5. ResNet
6. ZFNet

GitHub Notebook — Recognising Hand Written Digits using MNIST Dataset with TensorFlow

ss-is-master-chief/MNIST-Digit.Recognizer-CNNs

Implementation of CNN to recognize hand written digits (MNIST) running for 10 epochs. Accuracy: 98.99% ...

github.com

Ready to try out your own convolutional neural nets? Check out [Saturn Cloud](#) for free compute (including free GPUs).

Convolution Neural Net

TensorFlow

Computer Vision

Machine Learning

Deep Learning



Written by Sumit Saha

2.1K Followers · Writer for Towards Data Science

Data Scientist | Software Engineer | Writer

Follow



More from Sumit Saha and Towards Data Science

 Sumit Saha in Towards Data Science

What is the C4.5 algorithm and how does it work?

The C4.5 algorithm is used in Data Mining as a Decision Tree Classifier which can be...


Aug 21, 2018  478  3  

 Dominik Polzer in Towards Data Science

17 (Advanced) RAG Techniques to Turn Your LLM App Prototype...

A collection of RAG techniques to help you develop your RAG app into something...


 Jun 26  2.3K  22  

 Zoumana Keita in Towards Data Science

Document Parsing Using Large Language Models—With Code

You will not think about using Regular Expressions anymore.

 Jul 25  717  5  

 Sumit Saha

Principles of Good ML System Design

Machine learning systems are designed to generate maximum business value from...

Jul 20, 2021  276  2  

See all from Sumit Saha

See all from Towards Data Science


Recommended from Medium

 Jorgecardete in The Deep Hub

Convolutional Neural Networks: A Comprehensive Guide

Exploring the power of CNNs in image analysis

Feb 7  2.2K  36  

 Alexander Nguyen in Level Up Coding

The resume that got a software engineer a \$300,000 job at...

1-page. Well-formatted.

 Jun 1  17.3K  274  

Lists

Practical Guides to Machine Learning

10 stories · 1744 saves

Natural Language Processing

1640 stories · 1199 saves

Predictive Modeling w/ Python

20 stories · 1435 saves

data science and AI

40 stories · 211 saves

 Cristian Leo in Towards Data Science

The Math Behind Convolutional Neural Networks

Dive into CNN, the backbone of Computer Vision, understand its mathematics,...

★ Apr 10 🖱 856 💬 2  ⋮

 Ransaka Ravihara

CNN Basics Explained: Beginner's Guide

A simple introduction to convolution neural network

★ Feb 13 🖱 1  ⋮

 Daniel García

The Next Generation of Object Detection is Here: YOLOv10 🚀

Discover How YOLOv10 Redefines Real-Time Object Detection with Unmatched...

★ May 27 🖱 56 💬 1  ⋮

 Luqman Zaceria in Lumos

Understanding Convolutional Neural Networks (CNNs)

Hey everyone! We're going to explore one of the most influential and powerful tools i...

★ Aug 5 🖱 1  ⋮

See more recommendations

