Quarto + Typst + R + TinyTable

Table of contents

1 Tiny Table Examples 1
- 1.1 TT Eg1 3
- 1.2 TT Eg2 3
- 1.3 TT Eg3 4
- 1.4 TT Eg4 4
- 1.5 TT Eg5 5
- 1.6 TT Eg6 6
- 1.7 TT Eg7 6
- 1.8 TT Eg8 7
- 1.9 TT Eg9 8
- 1.10 TT Eg10 10
- 1.11 TT Eg11 10
- 1.12 TT Eg12 11
- 1.13 TT Eg13 12
- 1.14 TT Eg14 13

2 Grouped Table Summaries 14
- 2.1 TT Eg15 14
- 2.2 TT Eg16 15
- 2.3 TT Eg17 16
- 2.4 Caption Change 18
- 2.5 TT Eg18 : Most Popular 18
- 2.6 TT Eg20 : Splitting Tables in 3 cols 20
- 2.7 TT Eg21 : Splitting Tables in 3 cols : Typst 21
- 2.8 TT Eg22 : Splitting Tables in x cols : Typst : B 23

3 Extra Tables 25
- 3.1 TE- 1 : Highlight entire rows where mpg > 21 25
- 3.2 TE2. Different colours for high, medium and low mpg 26
- 3.3 T3. Colour cells in two different columns based on their own values 26
- 3.4 TE4. Highlight maximum and minimum values 27
- 3.5 T#5. Highlight values above and below the average 28
- 3.6 TE6. Apply a continuous colour gradient to cells 29

4 TT Eg- Blank 30

5 TOC- Repeat 31

1 Tiny Table Examples

List of Figures

List of Tables

Table 1 TT-Eg1 3
Table 2 TT-Eg2 3
Table 3 TT-Eg3 4
Table 4 TT-Eg4 5
Table 5 TT-Eg5 5
Table 6 TT-Eg6 6

Table 6a TT-Eg6A 6
Table 6b TT-Eg6B 6
Table 7 TT-Eg7 7
Table 7a TT-Eg7A 7
Table 7b TT-Eg7B 7
Table 8 TT-Eg8 8
Table 8a TT-Eg8A 8
Table 8b TT-Eg8B 8
Table 9 TT-Eg9 9
Table 9a TT-Eg9A 9
Table 9b TT-Eg9B 9
Table 10 TT-Eg10 10
Table 10a TT-Eg10A 10
Table 10b TT-Eg10B 10
Table 11 TT-Eg11 11
Table 11a TT-Eg11A 11
Table 11b TT-Eg11B 11
Table 12 TT-Eg12 12
Table 12a TT-Eg12A 12
Table 12b TT-Eg12B 12
Table 13 TT-Eg13 13
Table 13a TT-Eg13A 13
Table 13b TT-Eg13B 13
Table 14 TT-Eg14 14
Table 14a TT-Eg14A 14
Table 14b TT-Eg14B 14
Table 15 TT-Eg15 15
Table 15a TT-Eg15A 15
Table 15b TT-Eg15B 15
Table 16 TT-Eg16 16
Table 17 TT-Eg17 16
Table 17a TT-Eg17A 16
Table 17b TT-Eg17B 16
Table 18 TT-Eg18 19
Table 19 TT-Eg20 21
Table 20 TT-Eg21 21
Table 21 TT-Eg22 23
Table 22 TE-1 25
Table 23 TE-2 26
Table 24 TE-3 26
Table 25 TE-4 27
Table 26 TE-5 28
Table 27 TE-6 29
Table 28 Conditional Formatting of Fuel Efficiency 30
Table 29 TT-EgBlank 30

1.1 TT Eg1

```
pacman::p_load(tinytable, dplyr)
mtcars %>% head() %>% tt(align = 'left')
print("First Few Rows of mtcars")
```

```
[1] "First Few Rows of mtcars"
```

Table 1: TT-Eg1

mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
22.8	4	108	93	3.85	2.320	18.61	1	1	4	1
21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
18.1	6	225	105	2.76	3.460	20.22	1	0	3	1

Table Table 1 for examples of TinyTable outputs with different styles and captions.

1.2 TT Eg2

```
pacman::p_load(tinytable, dplyr)
mtcars %>%  head() %>%  tt(    .,    caption = "First 6 Rows of mtcars",
    notes = 'This is a note for the table.',    align = 'center'  )
```

Table 2: TT-Eg2

mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
22.8	4	108	93	3.85	2.320	18.61	1	1	4	1
21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
18.1	6	225	105	2.76	3.460	20.22	1	0	3	1

This is a note for the table.

Table 2 for examples of TinyTable outputs with different styles and captions.

1.3 TT Eg3

```
pacman::p_load(tinytable, dplyr)
mtcars %>%  head() %>%  tt(.) %>%  style_tt(    justify = "center",
    font_size = 10,    font_family = "Arial",    caption_font_size = 12,
    caption_font_family = "Arial",    notes_font_size = 10,    notes_font_family = "Arial"  )
```

Table 3: TT-Eg3

mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
22.8	4	108	93	3.85	2.320	18.61	1	1	4	1
21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
18.1	6	225	105	2.76	3.460	20.22	1	0	3	1

Table Table 3 for examples of TinyTable outputs with different styles and captions.

1.4 TT Eg4

```
pacman::p_load(tinytable, dplyr)

mtcars %>%  head() %>%  tt(.) %>%
  style_tt(i = 1:3, j = 1:6, background = 'cyan', color = 'red') %>%
  style_tt(i = 3:6, j = 6:10, background = 'yellow', bold = TRUE) %>%
  group_tt(j = list('Metrics1' = 1:5, 'Metrics2' = 6:11))
```

Table 4: TT-Eg4

Metrics1					Metrics2					
mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
22.8	4	108	93	3.85	2.320	**18.61**	**1**	**1**	**4**	1
21.4	6	258	110	3.08	**3.215**	**19.44**	**1**	**0**	**3**	1
18.7	8	360	175	3.15	**3.440**	**17.02**	**0**	**0**	**3**	2
18.1	6	225	105	2.76	**3.460**	**20.22**	**1**	**0**	**3**	1

Table 4 for examples of TinyTable outputs with different styles and captions.

1.5 TT Eg5

```
pacman::p_load(tinytable, dplyr)
notes2 <- list(
  a = list(i = 1:2, j = 1, text = 'These are special values'),
  b = list(i = 3, j = 2:4, text = 'These are other special values')
)
mtcars %>% head() %>% tt(., width = .8, height = 2, notes = notes2)
```

Table 5: TT-Eg5

mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
21.0[a]	6	160	110	3.90	2.620	16.46	0	1	4	4
21.0[a]	6	160	110	3.90	2.875	17.02	0	1	4	4
22.8	4[b]	108[b]	93[b]	3.85	2.320	18.61	1	1	4	1
21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
18.1	6	225	105	2.76	3.460	20.22	1	0	3	1

[a] These are special values

[b] These are other special values

Table 5 - shows how to set the width of the table using the `width` argument and the height of the table using the `height` argument in the `tt()` function.

1.6 TT Eg6

```
pacman::p_load(tinytable, dplyr)

mtcars %>%  head() %>%  tt(.) %>%
  style_tt(cyl == 6, background = 'green', color = 'black') %>%
  style_tt(cyl == 4, background = 'yellow', bold = TRUE) #%>% style_tt(mpg>20, bold=TRUE)
mtcars %>%  head() %>%  tt(.) %>%  style_tt(    i = 2:3,    j = c(1, 3, 4),
    italic = TRUE,    bold = TRUE,    color = "orange",    font_size = 15  )
```

(a) TT-Eg6A

mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
22.8	**4**	**108**	**93**	**3.85**	**2.320**	**18.61**	**1**	**1**	**4**	**1**
21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
18.1	6	225	105	2.76	3.460	20.22	1	0	3	1

(b) TT-Eg6B

mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
21.0	6	*160*	*110*	3.90	2.875	17.02	0	1	4	4
22.8	4	*108*	*93*	3.85	2.320	18.61	1	1	4	1
21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
18.1	6	225	105	2.76	3.460	20.22	1	0	3	1

Table 6: TT-Eg6

Table 6 - how cells can be formatted based on conditions using the `style_tt()` function. The first table shows how to style rows based on the value of the `cyl` column, while the second table shows how to style specific cells based on their row and column indices.

1.7 TT Eg7

```
pacman::p_load(tinytable, dplyr)

mtcars %>%  head() %>%  tt(.) %>%
  style_tt(i = which(mtcars$mpg > 21), background = "lightblue", bold = TRUE)
mtcars %>%  head() %>%  tt() %>%  style_tt(    i = which(mtcars$mpg > 21),    j = "mpg",
    background = "lightblue",    bold = TRUE  )
#mtcars %>% head() %>% tt(.) %>% style_tt( i = 2:3, j = c(1, 3, 4), italic = TRUE, bold=TRUE, color = "orange", font_size = 15)
```

(a) TT-Eg7A

mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
22.8	**4**	**108**	**93**	**3.85**	**2.320**	**18.61**	**1**	**1**	**4**	**1**
21.4	**6**	**258**	**110**	**3.08**	**3.215**	**19.44**	**1**	**0**	**3**	**1**
18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
18.1	6	225	105	2.76	3.460	20.22	1	0	3	1

(b) TT-Eg7B

mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
22.8	4	108	93	3.85	2.320	18.61	1	1	4	1
21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
18.1	6	225	105	2.76	3.460	20.22	1	0	3	1

Table 7: TT-Eg7

Table 7 - how cells can be formatted based on conditions using the `style_tt()` function.

1.8 TT Eg8

```
pacman::p_load(tinytable, dplyr)

mtcars %>%
  head() %>%
  tt(theme = "empty") |>
  style_tt(i = 0, line = "t", line_color = "orange", line_width = 0.4) |>
  style_tt(i = 1, line = "t", line_color = "purple", line_width = 0.2) |>
  style_tt(i = 4, line = "b", line_color = "orange", line_width = 0.4)
mtcars %>%  head() %>%  tt(theme = "empty") |>  style_tt(
    line = "tblr",    line_color = "white",    line_width = 0.5,
    background = "lightblue",    color = "black"  )
#mtcars %>% head() %>% tt(.) %>% style_tt( i = 2:3, j = c(1, 3, 4), italic = TRUE, bold=TRUE, color = "orange", font_size = 15)
```

(a) TT-Eg8A

mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
22.8	4	108	93	3.85	2.320	18.61	1	1	4	1
21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
18.1	6	225	105	2.76	3.460	20.22	1	0	3	1

(b) TT-Eg8B

mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
22.8	4	108	93	3.85	2.320	18.61	1	1	4	1
21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
18.1	6	225	105	2.76	3.460	20.22	1	0	3	1

Table 8: TT-Eg8

Table Table 8 shows how to style the top and bottom lines of the table and how to style the entire table with a light blue background and black text color.

1.9 TT Eg9

```
pacman::p_load(tinytable, dplyr)

mtcars %>%  head() %>%  mutate(ser = row_number()) %>%  select(ser, everything()) %>%
  tt() |>  group_tt(i = list("Group-A" = 3, "Group-B" = 4, "Group-C" = 7))
mtcars %>%  head() %>%  mutate(ser = row_number()) %>%  select(ser, everything()) %>%
  tt() %>%  group_tt(    i = list("Before 1" = 0, "Before 3" = 3, "After 3" = 4, "After 5" = 6)  )
```

(a) TT-Eg9A

ser	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
1	21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
2	21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
Group-A											
3	22.8	4	108	93	3.85	2.320	18.61	1	1	4	1
Group-B											
4	21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
5	18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
6	18.1	6	225	105	2.76	3.460	20.22	1	0	3	1
Group-C											

(b) TT-Eg9B

ser	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Before 1											
1	21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
2	21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
Before 3											
3	22.8	4	108	93	3.85	2.320	18.61	1	1	4	1
After 3											
4	21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
5	18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
After 5											
6	18.1	6	225	105	2.76	3.460	20.22	1	0	3	1

Table 9: TT-Eg9

Above Table Table 9 shows how to display groups of rows in the table, while the second table Table 9 shows how to display groups of rows with custom labels.

1.10 TT Eg10

```
pacman::p_load(tinytable, dplyr, gt)

tmp <- do.call(  rbind,  by(mtcars %>% select(gear, everything()), ~gear, head, n = 3))
tmp %>%   tt(    caption = "Grouped by Gear",    notes = "This table shows the first 3 rows of mtcars grouped by the number of gears."  )
tmp %>%  arrange(gear, mpg) %>%  tt() |>  group_tt(i = gear) |>  style_tt(align = "l") |>
  style_tt(i = "groupi", align = "l", color = "teal", line = "b") |>  theme_typst()
```

(a) TT-Eg10A

gear	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	carb
3	21.4	6	258.0	110	3.08	3.215	19.44	1	0	1
3	18.7	8	360.0	175	3.15	3.440	17.02	0	0	2
3	18.1	6	225.0	105	2.76	3.460	20.22	1	0	1
4	21.0	6	160.0	110	3.90	2.620	16.46	0	1	4
4	21.0	6	160.0	110	3.90	2.875	17.02	0	1	4
4	22.8	4	108.0	93	3.85	2.320	18.61	1	1	1
5	26.0	4	120.3	91	4.43	2.140	16.70	0	1	2
5	30.4	4	95.1	113	3.77	1.513	16.90	1	1	2
5	15.8	8	351.0	264	4.22	3.170	14.50	0	1	4

This table shows the first 3 rows of mtcars grouped by the number of gears.

(b) TT-Eg10B

gear	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	carb
3										
3	18.1	6	225.0	105	2.76	3.460	20.22	1	0	1
3	18.7	8	360.0	175	3.15	3.440	17.02	0	0	2
3	21.4	6	258.0	110	3.08	3.215	19.44	1	0	1
4										
4	21.0	6	160.0	110	3.90	2.620	16.46	0	1	4
4	21.0	6	160.0	110	3.90	2.875	17.02	0	1	4
4	22.8	4	108.0	93	3.85	2.320	18.61	1	1	1
5										
5	15.8	8	351.0	264	4.22	3.170	14.50	0	1	4
5	26.0	4	120.3	91	4.43	2.140	16.70	0	1	2
5	30.4	4	95.1	113	3.77	1.513	16.90	1	1	2

Table 10: TT-Eg10

Display rows in groups

1.11 TT Eg11

```
pacman::p_load(tinytable, dplyr, gt)

tmp <- do.call(  rbind,  by(mtcars %>% select(gear, everything()), ~gear, head, n = 3))
tmp %>%  arrange(gear, mpg) %>%
  tt() |>  group_tt(i = gear) |>  style_tt(align = "l") |>
  style_tt(i = "groupi", align = "l", color = "teal", line = "b") |>
```

```
  style_tt("~groupi", j = 1, indent = 2) |>  theme_typst()
df <- mtcars |> head() |> sort_by(~am)
#df %>% gt()
df |>  tt() |>  group_tt(i = df$am) |>  style_tt(align = "l") |>  style_tt(i = "groupi", align = "l", color = "teal", line = "b") |
>  theme_typst()
```

(a) TT-Eg11A

gear	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	carb
3										
3	18.1	6	225.0	105	2.76	3.460	20.22	1	0	1
3	18.7	8	360.0	175	3.15	3.440	17.02	0	0	2
3	21.4	6	258.0	110	3.08	3.215	19.44	1	0	1
4										
4	21.0	6	160.0	110	3.90	2.620	16.46	0	1	4
4	21.0	6	160.0	110	3.90	2.875	17.02	0	1	4
4	22.8	4	108.0	93	3.85	2.320	18.61	1	1	1
5										
5	15.8	8	351.0	264	4.22	3.170	14.50	0	1	4
5	26.0	4	120.3	91	4.43	2.140	16.70	0	1	2
5	30.4	4	95.1	113	3.77	1.513	16.90	1	1	2

(b) TT-Eg11B

mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
0										
21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
18.1	6	225	105	2.76	3.460	20.22	1	0	3	1
1										
21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
22.8	4	108	93	3.85	2.320	18.61	1	1	4	1

Table 11: TT-Eg11

1.12 TT Eg12

```
pacman::p_load(tinytable, dplyr, gt)

rowmat <- matrix(colnames(mtcars))
mtcars %>%  head(7) %>%  tt() |>  group_tt(i = c(3, 5), j = rowmat) |>
  style_tt(    i = c(0, 3, 6),    background = "lightblue",    bold = TRUE  )
rowmat <- matrix(c(rep("-", length(mtcars))))
mtcars %>% head(7) %>% tt(theme = 'grid') |> group_tt(i = 3, j = rowmat)
```

(a) TT-Eg12A

mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
mpg	**cyl**	**disp**	**hp**	**drat**	**wt**	**qsec**	**vs**	**am**	**gear**	**carb**
22.8	4	108	93	3.85	2.320	18.61	1	1	4	1
21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
mpg	**cyl**	**disp**	**hp**	**drat**	**wt**	**qsec**	**vs**	**am**	**gear**	**carb**
18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
18.1	6	225	105	2.76	3.460	20.22	1	0	3	1
14.3	8	360	245	3.21	3.570	15.84	0	0	3	4

(b) TT-Eg12B

mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
-	-	-	-	-	-	-	-	-	-	-
22.8	4	108	93	3.85	2.320	18.61	1	1	4	1
21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
18.1	6	225	105	2.76	3.460	20.22	1	0	3	1
14.3	8	360	245	3.21	3.570	15.84	0	0	3	4

Table 12: TT-Eg12

table Table 12 we show how to insert row headings again at new positions or insert new characters in the row headings at new positions. The first table Table 12a shows how to insert row headings again at new positions, while the second table Table 12b shows how to insert new characters in the row headings at new positions.

1.13 TT Eg13

```
pacman::p_load(tinytable, dplyr, gt)

mtcars %>%  head() %>%  tt(theme = 'striped') %>%  group_tt(j = list("GA-1" = 2:3, "GA-2" = 5:7)) |>  group_tt(j = list("GB-1" = c(1, 2,
4), "GB-2" = 6:9)) |>  theme_rotate(i = 0, angle = 30) |>  theme_rotate(i = 1:4, j = 1, angle = 180)
mtcars %>%  head(10) %>%  tt() %>%  theme_striped() %>%  theme_rotate(i = c(1, 3, 7), j = 3:5, angle = 45)
#mtcars %>% head(10) %>% tt()
```

(a) TT-Eg13A

GB-1										
	GA-1			GA-2						
mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
22.8	4	108	93	3.85	2.320	18.61	1	1	4	1
21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
18.1	6	225	105	2.76	3.460	20.22	1	0	3	1

(b) TT-Eg13B

mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
21.0	6	160.0	110	3.90	2.620	16.46	0	1	4	4
21.0	6	160.0	110	3.90	2.875	17.02	0	1	4	4
22.8	4	108.0	93	3.85	2.320	18.61	1	1	4	1
21.4	6	258.0	110	3.08	3.215	19.44	1	0	3	1
18.7	8	360.0	175	3.15	3.440	17.02	0	0	3	2
18.1	6	225.0	105	2.76	3.460	20.22	1	0	3	1
14.3	8	360.0	245	3.21	3.570	15.84	0	0	3	4
24.4	4	146.7	62	3.69	3.190	20.00	1	0	4	2
22.8	4	140.8	95	3.92	3.150	22.90	1	0	4	2
19.2	6	167.6	123	3.92	3.440	18.30	1	0	4	4

Table 13: TT-Eg13

table Table 13 Main . First Table 13b shows how to insert new characters in the row headings at new positions and also rotate text at different angles.

1.14 TT Eg14

```
pacman::p_load(tinytable, dplyr, gt)
dat <- data.frame(
  Metric = c("Sales", "Conversion", "Growth", "Efficiency"),
  Value = c(75, 45, 92, 38),
  Percentage = c(0.75, 0.45, 0.92, 0.38)
)

tt(dat) |>  plot_tt(    j = 2,    fun = "bar",    data = as.list(dat$Value),    color = "darkorange"  ) |>  plot_tt(    j = 3,    fun =
"bar",    data = as.list(dat$Percentage),    color = c("steelblue", "lightgrey"),    xlim = c(0, 1)  )
carAvg <- mtcars %>%  group_by(gear) %>%  summarise(across(c(mpg, disp, hp), mean, .names = "avg_{col}"))

#carAvg %>% gt()

carAvg %>%  tt() |>  plot_tt(    j = 2,    fun = "bar",    data = as.list(carAvg$avg_mpg),    color = "darkorange"  ) |>  plot_tt(    j
```

```
= 3,    fun = "bar",    data = as.list(carAvg$avg_disp),    color = c("steelblue", "lightgrey"),    xlim = c(0, 1)  ) |>  plot_tt(    j
= 4,    fun = "bar",    data = as.list(carAvg$avg_hp),    color = c("steelblue", "lightgrey"),    xlim = c(0, 1)  )
```

(a) TT-Eg14A

Metric	Value	Percentage
Sales		
Conversion		
Growth		
Efficiency		

(b) TT-Eg14B

gear	avg_mpg	avg_disp	avg_hp
3			
4			
5			

Table 14: TT-Eg14

table Table 14 show data in graphical representation using the `plot_tt()` function. The first table Table 14a shows how to plot bar charts for the `Value` and `Percentage` columns, while the second table Table 14b shows how to plot bar charts for the average `mpg`, `disp`, and `hp` values grouped by the number of gears.

2 Grouped Table Summaries

2.1 TT Eg15

```
pacman::p_load(tinytable, dplyr, gt)

tmp <- mtcars %>%  select(mpg, cyl, gear, am) %>%  tibble::rownames_to_column("Car") %>%  arrange(gear, mpg) %>%  group_by(gear) %>%
mutate(gearGroup = paste0("Gear: ", gear, " | No. of Cars: ", n())) %>%  ungroup()

tmp %>%  group_by(gearGroup) %>%  sample_n(2) %>%  tt(    width = c(1, 0.5, 0.5, 0.5, 0.5, 1),    height = 2,    caption = "Grouped by
Gear",    notes = "This table shows the first 3 rows of mtcars grouped by the number of gears."  ) %>%  theme_striped()
# Group labels and last row position of each group

grp <- tmp %>% count(gearGroup, name = "n") %>% mutate(end = cumsum(n))
grp %>% tt()
##group_labels <- as.list(setNames(grp$end, grp$gearGroup))

# Create table
#tt(tmp) %>%  group_tt(i = group_labels) %>%  subset(select = -gearGroup) %>%  style_tt(align = "c") %>%  style_tt(i = "groupi", align =
"l",  color = "teal", line = "b") %>%  theme_typst()
```

(a) TT-Eg15A

Car	mpg	cyl	gear	am	gearGroup
Merc 450SL	17.3	8	3	0	Gear: 3 | No. of Cars: 15
Valiant	18.1	6	3	0	Gear: 3 | No. of Cars: 15
Mazda RX4	21.0	6	4	1	Gear: 4 | No. of Cars: 12
Fiat 128	32.4	4	4	1	Gear: 4 | No. of Cars: 12
Ferrari Dino	19.7	6	5	1	Gear: 5 | No. of Cars: 5
Ford Pantera L	15.8	8	5	1	Gear: 5 | No. of Cars: 5

This table shows the first 3 rows of mtcars grouped by the number of gears.

(b) TT-Eg15B

gearGroup	n	end
Gear: 3 | No. of Cars: 15	15	15
Gear: 4 | No. of Cars: 12	12	27
Gear: 5 | No. of Cars: 5	5	32

Table 15: TT-Eg15

2.2 TT Eg16

```
pacman::p_load(tinytable, dplyr, gt)

tmp <- mtcars %>%  select(mpg, cyl, gear, am) %>%
  tibble::rownames_to_column("Car") %>%  arrange(gear, mpg) %>%  group_by(gear) %>%
  mutate(gearGroup = paste0("Gear: ", gear, " | No. of Cars: ", n())) %>%
  ungroup()

#tmp %>% group_by(gearGroup) %>% sample_n(2) %>% tt(width = c(1, 0.5, 0.5, 0.5, 0.5, 1), height = 2, caption = "Grouped by Gear", notes
= "This table shows the first 3 rows of mtcars grouped by the number of gears.") %>% theme_striped()

# Group labels and last row position of each group

grp <- tmp %>% count(gearGroup, name = "n") %>% mutate(end = cumsum(n))

print(grp)
group_labels <- as.list(setNames(grp$end, grp$gearGroup))

cat(grp$gearGroup, sep = "\n")
# Create table
#tmp %>% tt() %>%  group_tt(i = group_labels) %>%  subset(select = -gearGroup) %>%  style_tt(align = "c") %>%  style_tt(i = "groupi",
align = "l",  color = "teal", line = "b") %>%  theme_typst()
```

```
# A tibble: 3 × 3
  gearGroup                    n   end
  <chr>                    <int> <int>
1 Gear: 3 | No. of Cars: 15    15    15
2 Gear: 4 | No. of Cars: 12    12    27
3 Gear: 5 | No. of Cars: 5      5    32
```

```
Gear: 3 | No. of Cars: 15
Gear: 4 | No. of Cars: 12
Gear: 5 | No. of Cars: 5
```

Table 16: TT-Eg16

2.3 TT Eg17

```
pacman::p_load(tinytable, dplyr, gt)

tmp <- mtcars %>%  select(mpg, cyl, gear, am) %>%  tibble::rownames_to_column("Car") %>%  arrange(gear, mpg) %>%  group_by(gear) %>%
mutate(gearGroup = paste0("Gear: ", gear, " | No. of Cars: ", n())) %>%  ungroup()

#tmp %>% group_by(gearGroup)  %>% tt(width = c(1, 0.2, 0.2, 0.2, 0.2, 1), height = 2, caption = "Grouped by Gear", notes = "This table
shows the first 3 rows of mtcars grouped by the number of gears.") %>% theme_striped()

# Group labels and last row position of each group

grp <- tmp %>%
  count(gearGroup, name = "n") %>%
  mutate(start = cumsum(n) - n + 1, position = start - 1, end = cumsum(n) + 1)

#grp
group_labels1 <- as.list(setNames(grp$end, grp$gearGroup))
group_labels2 <- as.list(setNames(grp$start, grp$gearGroup))

# Create table
tmp %>%  tt() %>%  group_tt(i = group_labels1) %>%  subset(select = -gearGroup) %>%  style_tt(align = "c") %>%  style_tt(i = "groupi",
align = "l", color = "red", line = "b") %>%  theme_striped()
tmp %>%  tt() %>%  group_tt(i = group_labels2) %>%  subset(select = -gearGroup) %>%  style_tt(align = "c") %>%  style_tt(i = "groupi",
align = "l", color = "teal", line = "b") %>%  theme_typst()
```

(a) TT-Eg17A

Car	mpg	cyl	gear	am
Cadillac Fleetwood	10.4	8	3	0
Lincoln Continental	10.4	8	3	0

(b) TT-Eg17B

Car	mpg	cyl	gear	am
Gear: 3 | No. of Cars: 15				
Cadillac Fleetwood	10.4	8	3	0

Car	mpg	cyl	gear	am
Camaro Z28	13.3	8	3	0
Duster 360	14.3	8	3	0
Chrysler Imperial	14.7	8	3	0
Merc 450SLC	15.2	8	3	0
AMC Javelin	15.2	8	3	0
Dodge Challenger	15.5	8	3	0
Merc 450SE	16.4	8	3	0
Merc 450SL	17.3	8	3	0
Valiant	18.1	6	3	0
Hornet Sportabout	18.7	8	3	0
Pontiac Firebird	19.2	8	3	0
Hornet 4 Drive	21.4	6	3	0
Toyota Corona	21.5	4	3	0
Gear: 3 | No. of Cars: 15				
Merc 280C	17.8	6	4	0
Merc 280	19.2	6	4	0
Mazda RX4	21.0	6	4	1
Mazda RX4 Wag	21.0	6	4	1
Volvo 142E	21.4	4	4	1
Datsun 710	22.8	4	4	1
Merc 230	22.8	4	4	0
Merc 240D	24.4	4	4	0
Fiat X1-9	27.3	4	4	1
Honda Civic	30.4	4	4	1
Fiat 128	32.4	4	4	1
Toyota Corolla	33.9	4	4	1
Gear: 4 | No. of Cars: 12				

Car	mpg	cyl	gear	am
Lincoln Continental	10.4	8	3	0
Camaro Z28	13.3	8	3	0
Duster 360	14.3	8	3	0
Chrysler Imperial	14.7	8	3	0
Merc 450SLC	15.2	8	3	0
AMC Javelin	15.2	8	3	0
Dodge Challenger	15.5	8	3	0
Merc 450SE	16.4	8	3	0
Merc 450SL	17.3	8	3	0
Valiant	18.1	6	3	0
Hornet Sportabout	18.7	8	3	0
Pontiac Firebird	19.2	8	3	0
Hornet 4 Drive	21.4	6	3	0
Toyota Corona	21.5	4	3	0
Gear: 4 | No. of Cars: 12				
Merc 280C	17.8	6	4	0
Merc 280	19.2	6	4	0
Mazda RX4	21.0	6	4	1
Mazda RX4 Wag	21.0	6	4	1
Volvo 142E	21.4	4	4	1
Datsun 710	22.8	4	4	1
Merc 230	22.8	4	4	0
Merc 240D	24.4	4	4	0
Fiat X1-9	27.3	4	4	1
Honda Civic	30.4	4	4	1
Fiat 128	32.4	4	4	1
Toyota Corolla	33.9	4	4	1

Car	mpg	cyl	gear	am
Maserati Bora	15.0	8	5	1
Ford Pantera L	15.8	8	5	1
Ferrari Dino	19.7	6	5	1
Porsche 914-2	26.0	4	5	1
Lotus Europa	30.4	4	5	1
Gear: 5 | No. of Cars: 5				

Car	mpg	cyl	gear	am
Gear: 5 | No. of Cars: 5				
Maserati Bora	15.0	8	5	1
Ford Pantera L	15.8	8	5	1
Ferrari Dino	19.7	6	5	1
Porsche 914-2	26.0	4	5	1
Lotus Europa	30.4	4	5	1

Table 17: TT-Eg17

The tables shows how to display groups of rows in the table, while the second table shows how to display groups of rows with custom labels. with typst unbreakable block, the table can be broken across pages if it is too long to fit on a single page. The `set block(breakable: true)` command allows the table to be broken across pages. The first tables shows group labels at the end of each group, while the second table shows group labels at the start of each group.

2.4 Caption Change

2.5 TT Eg18 : Most Popular

```
pacman::p_load(tinytable, dplyr, gt)

tmp <- mtcars %>%  tibble::rownames_to_column("Car") %>%  arrange(gear, mpg)

# Group summary
grp <- tmp %>%  group_by(gear) %>%  summarise( n = n(), avgMPG = round(mean(mpg), 2),  avgWT = round(mean(wt), 2),  .groups = "drop"  ) %>%  mutate(  label = paste0( "Gear: ", gear,  " | Cars: ", n,  " | Avg MPG: ", avgMPG,  " | Avg WT: ", avgWT  ),  end = cumsum(n), start = cumsum(n) - n +1  )

grp %>% tt() %>% style_tt(align = "c") %>% style_tt(i = 0, bold = TRUE, color = "teal", line = "b") %>%style_tt(background = "#EAF4F4") %>% theme_typst()
group_labels <- as.list(setNames(grp$end - grp$n + 1, grp$label))

# Generate tinytable
tmp %>% mutate(ser= row_number()) %>%  select(ser, Car, gear, mpg, wt, everything()) %>% tt(width = c(0.4, 2.5, rep(0.7,11)), caption='Group Heading with more details', notes='Grouped by Gear')  %>% style_tt(font_size = 8) %>%  group_tt(i = group_labels) %>%  style_tt(align = "c") %>%  style_tt(    i = "groupi",    align = "l",    color = "teal",    line = "b"  ) %>% style_tt(j = 1:2, align = "l") %>% style_tt(j = 3:5, align = "r") %>%  style_tt(j = 6:11, align = "c") %>%  theme_grid() %>% style_tt(i = 0, background = "#006D77", color = "brown", bold = TRUE)%>%  style_tt(j = 1, background = "#D9EAF7")  %>% theme_typst()
```

gear	n	avgMPG	avgWT	label	end	start
3	15	16.11	3.89	Gear: 3 | Cars: 15 | Avg MPG: 16.11 | Avg WT: 3.89	15	1
4	12	24.53	2.62	Gear: 4 | Cars: 12 | Avg MPG: 24.53 | Avg WT: 2.62	27	16
5	5	21.38	2.63	Gear: 5 | Cars: 5 | Avg MPG: 21.38 | Avg WT: 2.63	32	28

ser	Car	gear	mpg	wt	cyl	disp	hp	drat	qsec	vs	am	carb
Gear: 3 | Cars: 15 | Avg MPG: 16.11 | Avg WT: 3.89												
1	Cadillac Fleetwood	3	10.4	5.250	8	472.0	205	2.93	17.98	0	0	4
2	Lincoln Continental	3	10.4	5.424	8	460.0	215	3.00	17.82	0	0	4
3	Camaro Z28	3	13.3	3.840	8	350.0	245	3.73	15.41	0	0	4
4	Duster 360	3	14.3	3.570	8	360.0	245	3.21	15.84	0	0	4
5	Chrysler Imperial	3	14.7	5.345	8	440.0	230	3.23	17.42	0	0	4
6	Merc 450SLC	3	15.2	3.780	8	275.8	180	3.07	18.00	0	0	3
7	AMC Javelin	3	15.2	3.435	8	304.0	150	3.15	17.30	0	0	2
8	Dodge Challenger	3	15.5	3.520	8	318.0	150	2.76	16.87	0	0	2
9	Merc 450SE	3	16.4	4.070	8	275.8	180	3.07	17.40	0	0	3
10	Merc 450SL	3	17.3	3.730	8	275.8	180	3.07	17.60	0	0	3
11	Valiant	3	18.1	3.460	6	225.0	105	2.76	20.22	1	0	1
12	Hornet Sportabout	3	18.7	3.440	8	360.0	175	3.15	17.02	0	0	2
13	Pontiac Firebird	3	19.2	3.845	8	400.0	175	3.08	17.05	0	0	2
14	Hornet 4 Drive	3	21.4	3.215	6	258.0	110	3.08	19.44	1	0	1
15	Toyota Corona	3	21.5	2.465	4	120.1	97	3.70	20.01	1	0	1
Gear: 4 | Cars: 12 | Avg MPG: 24.53 | Avg WT: 2.62												
16	Merc 280C	4	17.8	3.440	6	167.6	123	3.92	18.90	1	0	4
17	Merc 280	4	19.2	3.440	6	167.6	123	3.92	18.30	1	0	4
18	Mazda RX4	4	21.0	2.620	6	160.0	110	3.90	16.46	0	1	4
19	Mazda RX4 Wag	4	21.0	2.875	6	160.0	110	3.90	17.02	0	1	4
20	Volvo 142E	4	21.4	2.780	4	121.0	109	4.11	18.60	1	1	2

ser	Car	gear	mpg	wt	cyl	disp	hp	drat	qsec	vs	am	carb
21	Datsun 710	4	22.8	2.320	4	108.0	93	3.85	18.61	1	1	1
22	Merc 230	4	22.8	3.150	4	140.8	95	3.92	22.90	1	0	2
23	Merc 240D	4	24.4	3.190	4	146.7	62	3.69	20.00	1	0	2
24	Fiat X1-9	4	27.3	1.935	4	79.0	66	4.08	18.90	1	1	1
25	Honda Civic	4	30.4	1.615	4	75.7	52	4.93	18.52	1	1	2
26	Fiat 128	4	32.4	2.200	4	78.7	66	4.08	19.47	1	1	1
27	Toyota Corolla	4	33.9	1.835	4	71.1	65	4.22	19.90	1	1	1
Gear: 5 | Cars: 5 | Avg MPG: 21.38 | Avg WT: 2.63												
28	Maserati Bora	5	15.0	3.570	8	301.0	335	3.54	14.60	0	1	8
29	Ford Pantera L	5	15.8	3.170	8	351.0	264	4.22	14.50	0	1	4
30	Ferrari Dino	5	19.7	2.770	6	145.0	175	3.62	15.50	0	1	6
31	Porsche 914-2	5	26.0	2.140	4	120.3	91	4.43	16.70	0	1	2
32	Lotus Europa	5	30.4	1.513	4	95.1	113	3.77	16.90	1	1	2
Grouped by Gear												

Table 18: TT-Eg18

Width can be defined in different ways in tt

- Width can be defined as a single value, which will be applied to all columns.
  - width = 1
- Width can be defined as a vector of values, which will be applied to each column in the order they are specified.
  - width = c(120, 45, 50, 50, rep(45, ncol(tmp) - 4)), width = c(3, 1, 1, 1, rep(.8, ncol(tmp) - 4)),
- Width can be defined as a vector of values with names, which will be applied to each column based on the column name.

2.6 TT Eg20 : Splitting Tables in 3 cols

```
pacman::p_load(tinytable, dplyr, gt, tidyr)

df <- mtcars %>% tibble::rownames_to_column("Car") %>% select(Car, mpg, wt)

nblock <- 3
nrows <- ceiling(nrow(df) / nblock)

df_wide <- df %>%  mutate(    block = ceiling(row_number() / nrows),    row = (row_number() - 1) %% nrows + 1  ) %>%  pivot_wider(    id_cols
```

```
= row,    names_from = block,    values_from = c(Car, mpg, wt),    names_glue = "{.value}_{block}"  ) %>%  select(row, Car_1, mpg_1, wt_1,
Car_2, mpg_2, wt_2, Car_3, mpg_3, wt_3) %>%  select(-row)

tt(  df_wide,  caption = "Motor Cars: Three Side-by-Side Blocks",  width = rep(c(2, 1, 1), 3)) %>%  style_tt(align = "c") %>%  group_tt(j
= list("GA-1" = 1:3, "GA-2" = 4:6, "GA-3" = 7:9)) %>%  theme_typst()
```

GA-1			GA-2			GA-3		
Car_1	mpg_1	wt_1	Car_2	mpg_2	wt_2	Car_3	mpg_3	wt_3
Mazda RX4	21.0	2.620	Merc 450SE	16.4	4.070	AMC Javelin	15.2	3.435
Mazda RX4 Wag	21.0	2.875	Merc 450SL	17.3	3.730	Camaro Z28	13.3	3.840
Datsun 710	22.8	2.320	Merc 450SLC	15.2	3.780	Pontiac Firebird	19.2	3.845
Hornet 4 Drive	21.4	3.215	Cadillac Fleetwood	10.4	5.250	Fiat X1-9	27.3	1.935
Hornet Sportabout	18.7	3.440	Lincoln Continental	10.4	5.424	Porsche 914-2	26.0	2.140
Valiant	18.1	3.460	Chrysler Imperial	14.7	5.345	Lotus Europa	30.4	1.513
Duster 360	14.3	3.570	Fiat 128	32.4	2.200	Ford Pantera L	15.8	3.170
Merc 240D	24.4	3.190	Honda Civic	30.4	1.615	Ferrari Dino	19.7	2.770
Merc 230	22.8	3.150	Toyota Corolla	33.9	1.835	Maserati Bora	15.0	3.570
Merc 280	19.2	3.440	Toyota Corona	21.5	2.465	Volvo 142E	21.4	2.780
Merc 280C	17.8	3.440	Dodge Challenger	15.5	3.520	NA	NA	NA

Table 19: TT-Eg20

2.7 TT Eg21 : Splitting Tables in 3 cols : Typst

```
pacman::p_load(tinytable, dplyr, gt, tidyr)

tmp2 <- mtcars %>%  mutate(ser = row_number()) %>%  tibble::rownames_to_column("Car") %>%  select(ser, Car, mpg, hp, wt, am)

# Convert each row into Typst table cells
  cells <- apply(tmp2, 1, function(x) {
    paste0("[", x, "]", collapse = ", ")
                  })

    typst_code <- paste0(
  "#columns(3, gutter: 10pt)[\n",
```

```
    "#set text(size: 8pt)\n",
    "#table(\n",
  "columns: (0.6fr, 1.5fr, 1fr, 1fr, 1fr, 1fr),\n",
      "inset: 3pt,\n",
  "stroke: 0.3pt + gray.lighten(60%),\n",
"table.header([*Ser*], [*Car*], [*mpg*], [*hp*], [*wt*], [*am*]),\n",
    paste(cells, collapse = ",\n"),
    "\n)\n",
      "]"
      )

cat("```{=typst}\n", typst_code, "\n```\n", sep = "")
```

Ser	Car	mpg	hp	wt	am
1	Mazda RX4	21.0	110	2.620	1
2	Mazda RX4 Wag	21.0	110	2.875	1
3	Datsun 710	22.8	93	2.320	1
4	Hornet 4 Drive	21.4	110	3.215	0
5	Hornet Sportabout	18.7	175	3.440	0
6	Valiant	18.1	105	3.460	0
7	Duster 360	14.3	245	3.570	0
8	Merc 240D	24.4	62	3.190	0
9	Merc 230	22.8	95	3.150	0
10	Merc 280	19.2	123	3.440	0
11	Merc 280C	17.8	123	3.440	0
12	Merc 450SE	16.4	180	4.070	0
13	Merc 450SL	17.3	180	3.730	0
14	Merc 450SLC	15.2	180	3.780	0
15	Cadillac Fleetwood	10.4	205	5.250	0
16	Lincoln Continental	10.4	215	5.424	0
17	Chrysler Imperial	14.7	230	5.345	0
18	Fiat 128	32.4	66	2.200	1
19	Honda Civic	30.4	52	1.615	1
20	Toyota Corolla	33.9	65	1.835	1
21	Toyota Corona	21.5	97	2.465	0
22	Dodge Challenger	15.5	150	3.520	0
23	AMC Javelin	15.2	150	3.435	0
24	Camaro Z28	13.3	245	3.840	0
25	Pontiac Firebird	19.2	175	3.845	0
26	Fiat X1-9	27.3	66	1.935	1
27	Porsche 914-2	26.0	91	2.140	1
28	Lotus Europa	30.4	113	1.513	1
29	Ford Pantera L	15.8	264	3.170	1
30	Ferrari Dino	19.7	175	2.770	1
31	Maserati Bora	15.0	335	3.570	1
32	Volvo 142E	21.4	109	2.780	1

Table 20: TT-Eg21

Note to include results: asis in the chunk options to ensure that the Typst code is rendered correctly in the output document.

2.8 TT Eg22 : Splitting Tables in x cols : Typst : B

```
pacman::p_load(tinytable, dplyr, gt, tidyr)

# User settings
ncols <- 2
font_size <- 7
gutter <- 8

# Prepare data
tmp2 <- mtcars %>%  mutate(ser = row_number()) %>%  tibble::rownames_to_column("Car") %>%  select(ser, Car, mpg, hp, wt)

# Split into consecutive groups of rows
ncols <- max(1L, min(as.integer(ncols), nrow(tmp2)))
rows_per_col <- ceiling(nrow(tmp2) / ncols)

parts <- split(tmp2, ceiling(seq_len(nrow(tmp2)) / rows_per_col))

# Convert text safely to Typst cells
typst_cell <- function(x) {
x <- ifelse(is.na(x), "", as.character(x))
x <- gsub("\\", "\\\\", x)
x <- gsub("([\\[\\]#*])", "\\\\1", x)
paste0("[", x, "]")
}

# Create a Typst table for each part
make_table <- function(df) {
headers <- paste(typst_cell(names(df)), collapse = ", ")

rows <- apply(as.matrix(df), 1, function(x) {
paste(typst_cell(x), collapse = ", ")
})

paste0(
"table(\n",
"columns: (0.5fr, 2fr, 0.7fr, 0.7fr, 0.7fr),\n",
```

```
    "inset: 2pt,\n",
  "stroke: 0.3pt + gray.lighten(60%),\n",
    "table.header(",
        headers,
      "),\n",
  paste(rows, collapse = ",\n"),
      "\n)"
       )
      }

  # Generate grid dynamically
     typst_code <- paste0(
      "#{\n",
    "set text(size: ",
        font_size,
      "pt)\n",
     "grid(\n",
    "columns: (",
paste(rep("1fr", length(parts)), collapse = ", "),
      "),\n",
    "gutter: ",
      gutter,
     "pt,\n",
paste(vapply(parts, make_table, character(1)), collapse = ",\n"),
     "\n)\n",
       "}"
       )

cat("```{=typst}\n", typst_code, "\n```\n", sep = "")
```

ser	Car	mpg	hp	wt
1	Mazda RX4	21.0	110	2.620
2	Mazda RX4 Wag	21.0	110	2.875
3	Datsun 710	22.8	93	2.320
4	Hornet 4 Drive	21.4	110	3.215
5	Hornet Sportabout	18.7	175	3.440
6	Valiant	18.1	105	3.460
7	Duster 360	14.3	245	3.570
8	Merc 240D	24.4	62	3.190
9	Merc 230	22.8	95	3.150
10	Merc 280	19.2	123	3.440
11	Merc 280C	17.8	123	3.440
12	Merc 450SE	16.4	180	4.070
13	Merc 450SL	17.3	180	3.730
14	Merc 450SLC	15.2	180	3.780

ser	Car	mpg	hp	wt
17	Chrysler Imperial	14.7	230	5.345
18	Fiat 128	32.4	66	2.200
19	Honda Civic	30.4	52	1.615
20	Toyota Corolla	33.9	65	1.835
21	Toyota Corona	21.5	97	2.465
22	Dodge Challenger	15.5	150	3.520
23	AMC Javelin	15.2	150	3.435
24	Camaro Z28	13.3	245	3.840
25	Pontiac Firebird	19.2	175	3.845
26	Fiat X1-9	27.3	66	1.935
27	Porsche 914-2	26.0	91	2.140
28	Lotus Europa	30.4	113	1.513
29	Ford Pantera L	15.8	264	3.170
30	Ferrari Dino	19.7	175	2.770

ser	Car	mpg	hp	wt
15	Cadillac Fleetwood	10.4	205	5.250
16	Lincoln Continental	10.4	215	5.424

ser	Car	mpg	hp	wt
31	Maserati Bora	15.0	335	3.570
32	Volvo 142E	21.4	109	2.780

Table 21: TT-Eg22

3 Extra Tables

3.1 TE- 1 : Highlight entire rows where mpg > 21

```
library(tinytable)
library(dplyr)

df <- mtcars %>%
  tibble::rownames_to_column("Car") %>%
  select(Car, mpg, cyl, hp, wt, gear) %>%
  head(12)

df %>%  tt() %>%  style_tt(    i = which(df$mpg > 21),    background = "lightblue",    color = "darkblue",    bold = TRUE  )
```

Car	mpg	cyl	hp	wt	gear
Mazda RX4	21.0	6	110	2.620	4
Mazda RX4 Wag	21.0	6	110	2.875	4
Datsun 710	**22.8**	**4**	**93**	**2.320**	**4**
Hornet 4 Drive	**21.4**	**6**	**110**	**3.215**	**3**
Hornet Sportabout	18.7	8	175	3.440	3
Valiant	18.1	6	105	3.460	3
Duster 360	14.3	8	245	3.570	3
Merc 240D	**24.4**	**4**	**62**	**3.190**	**4**
Merc 230	**22.8**	**4**	**95**	**3.150**	**4**
Merc 280	19.2	6	123	3.440	4
Merc 280C	17.8	6	123	3.440	4
Merc 450SE	16.4	8	180	4.070	3

Table 22: TE-1

3.2 TE2. Different colours for high, medium and low mpg

```
library(tinytable)
library(dplyr)
df %>%  tt() %>%  style_tt(    i = which(df$mpg >= 25),    j = "mpg",    background = "lightgreen",    color = "darkgreen",    bold =
TRUE  ) %>%  style_tt(    i = which(df$mpg >= 18 & df$mpg < 25),    j = "mpg",    background = "lightyellow",    color = "darkorange"  )
%>%  style_tt(    i = which(df$mpg < 18),    j = "mpg",    background = "mistyrose",    color = "darkred",    bold = TRUE  )
```

Car	mpg	cyl	hp	wt	gear
Mazda RX4	21.0	6	110	2.620	4
Mazda RX4 Wag	21.0	6	110	2.875	4
Datsun 710	22.8	4	93	2.320	4
Hornet 4 Drive	21.4	6	110	3.215	3
Hornet Sportabout	18.7	8	175	3.440	3
Valiant	18.1	6	105	3.460	3
Duster 360	**14.3**	8	245	3.570	3
Merc 240D	24.4	4	62	3.190	4
Merc 230	22.8	4	95	3.150	4
Merc 280	19.2	6	123	3.440	4
Merc 280C	**17.8**	6	123	3.440	4
Merc 450SE	**16.4**	8	180	4.070	3

Table 23: TE-2

3.3 T3. Colour cells in two different columns based on their own values

Here, mpg is coloured according to fuel efficiency, while hp is coloured according to horsepower.

```
library(tinytable)
library(dplyr)

df %>%  tt() %>%  style_tt(    i = which(df$mpg > 21),    j = "mpg",    background = "lightgreen",    color = "darkgreen"  ) %>%
style_tt(    i = which(df$hp > 150),    j = "hp",    background = "lightpink",    color = "darkred",    bold = TRUE  )
```

Car	mpg	cyl	hp	wt	gear
Mazda RX4	21.0	6	110	2.620	4

Car	mpg	cyl	hp	wt	gear
Mazda RX4 Wag	21.0	6	110	2.875	4
Datsun 710	22.8	4	93	2.320	4
Hornet 4 Drive	21.4	6	110	3.215	3
Hornet Sportabout	18.7	8	**175**	3.440	3
Valiant	18.1	6	105	3.460	3
Duster 360	14.3	8	**245**	3.570	3
Merc 240D	24.4	4	62	3.190	4
Merc 230	22.8	4	95	3.150	4
Merc 280	19.2	6	123	3.440	4
Merc 280C	17.8	6	123	3.440	4
Merc 450SE	16.4	8	**180**	4.070	3

Table 24: TE-3

3.4 TE4. Highlight maximum and minimum values

```
library(tinytable)
library(dplyr)

df %>%  tt() %>%  style_tt(     i = which(df$mpg == max(df$mpg)),     j = "mpg",     background = "lightgreen",     bold = TRUE   ) %>%
style_tt(    i = which(df$mpg == min(df$mpg)),    j = "mpg",    background = "salmon",    color = "white",    bold = TRUE   )
```

Car	mpg	cyl	hp	wt	gear
Mazda RX4	21.0	6	110	2.620	4
Mazda RX4 Wag	21.0	6	110	2.875	4
Datsun 710	22.8	4	93	2.320	4
Hornet 4 Drive	21.4	6	110	3.215	3
Hornet Sportabout	18.7	8	175	3.440	3
Valiant	18.1	6	105	3.460	3
Duster 360	**14.3**	8	245	3.570	3
Merc 240D	**24.4**	4	62	3.190	4

Car	mpg	cyl	hp	wt	gear
Merc 230	22.8	4	95	3.150	4
Merc 280	19.2	6	123	3.440	4
Merc 280C	17.8	6	123	3.440	4
Merc 450SE	16.4	8	180	4.070	3

Table 25: TE-4

3.5 T#5. Highlight values above and below the average

```
library(tinytable)
library(dplyr)

avg_mpg <- mean(df$mpg)

df %>%  tt() %>%  style_tt(     i = which(df$mpg >= avg_mpg),     j = "mpg",     background = "#D1FAE5",     color = "#065F46"   ) %>%
style_tt(    i = which(df$mpg < avg_mpg),    j = "mpg",    background = "#FEE2E2",    color = "#991B1B"   )
```

Car	mpg	cyl	hp	wt	gear
Mazda RX4	21.0	6	110	2.620	4
Mazda RX4 Wag	21.0	6	110	2.875	4
Datsun 710	22.8	4	93	2.320	4
Hornet 4 Drive	21.4	6	110	3.215	3
Hornet Sportabout	18.7	8	175	3.440	3
Valiant	18.1	6	105	3.460	3
Duster 360	14.3	8	245	3.570	3
Merc 240D	24.4	4	62	3.190	4
Merc 230	22.8	4	95	3.150	4
Merc 280	19.2	6	123	3.440	4
Merc 280C	17.8	6	123	3.440	4
Merc 450SE	16.4	8	180	4.070	3

Table 26: TE-5

3.6 TE6. Apply a continuous colour gradient to cells

Instead of only three categories, create a different background colour for each mpg value.

```
library(tinytable)
library(dplyr)


df2 <- mtcars %>%  tibble::rownames_to_column("Car") %>%  select(Car, mpg, hp, wt) %>%  head(12)

pal <- scales::col_numeric(  palette = c("#FEE2E2", "#FEF08A", "#86EFAC"), domain = range(df2$mpg))

bg_colors <- pal(df2$mpg)

tab <- tt(df2)

for (k in seq_len(nrow(df2))) {
  tab <- style_tt(    tab,    i = k,    j = "mpg",    background = bg_colors[k],    color = "#111827"  )}

tab
```

Car	mpg	hp	wt
Mazda RX4	21.0	110	2.620
Mazda RX4 Wag	21.0	110	2.875
Datsun 710	22.8	93	2.320
Hornet 4 Drive	21.4	110	3.215
Hornet Sportabout	18.7	175	3.440
Valiant	18.1	105	3.460
Duster 360	14.3	245	3.570
Merc 240D	24.4	62	3.190
Merc 230	22.8	95	3.150
Merc 280	19.2	123	3.440
Merc 280C	17.8	123	3.440
Merc 450SE	16.4	180	4.070

Table 27: TE-6

Table 28: Conditional Formatting of Fuel Efficiency

Car	mpg	cyl	hp	wt	gear
Mazda RX4	21.0	6	110	2.620	4
Mazda RX4 Wag	21.0	6	110	2.875	4
Datsun 710	**22.8**	4	93	2.320	4
Hornet 4 Drive	**21.4**	6	110	3.215	3
Hornet Sportabout	18.7	8	175	3.440	3
Valiant	18.1	6	105	3.460	3
Duster 360	14.3	8	245	3.570	3
Merc 240D	**24.4**	4	62	3.190	4
Merc 230	**22.8**	4	95	3.150	4
Merc 280	19.2	6	123	3.440	4
Merc 280C	17.8	6	123	3.440	4
Merc 450SE	16.4	8	180	4.070	3

See Table 28 for the fuel-efficiency comparison.

4 TT Eg- Blank

```
pacman::p_load(tinytable, dplyr, gt)

#mtcars %>% head() %>% select(1:5) %>% tt()
```

Table 29: TT-EgBlank

Table Table 29 is a blank template section for adding a new tinytable example.

5 TOC- Repeat

Sections

1 Tiny Table Examples 1
2 Grouped Table Summaries 14
3 Extra Tables 25
4 TT Eg- Blank 30
5 TOC- Repeat 31

Figures

Tables

Table 1 TT-Eg1 3
Table 2 TT-Eg2 3
Table 3 TT-Eg3 4
Table 4 TT-Eg4 5
Table 5 TT-Eg5 5
Table 6 TT-Eg6 6
Table 6a TT-Eg6A 6
Table 6b TT-Eg6B 6
Table 7 TT-Eg7 7
Table 7a TT-Eg7A 7
Table 7b TT-Eg7B 7
Table 8 TT-Eg8 8
Table 8a TT-Eg8A 8
Table 8b TT-Eg8B 8
Table 9 TT-Eg9 9
Table 9a TT-Eg9A 9
Table 9b TT-Eg9B 9
Table 10 TT-Eg10 10
Table 10a TT-Eg10A 10
Table 10b TT-Eg10B 10
Table 11 TT-Eg11 11
Table 11a TT-Eg11A 11
Table 11b TT-Eg11B 11
Table 12 TT-Eg12 12
Table 12a TT-Eg12A 12
Table 12b TT-Eg12B 12

Table 13 TT-Eg13 13
Table 13a TT-Eg13A 13
Table 13b TT-Eg13B 13
Table 14 TT-Eg14 14
Table 14a TT-Eg14A 14
Table 14b TT-Eg14B 14
Table 15 TT-Eg15 15
Table 15a TT-Eg15A 15
Table 15b TT-Eg15B 15
Table 16 TT-Eg16 16
Table 17 TT-Eg17 16
Table 17a TT-Eg17A 16
Table 17b TT-Eg17B 16
Table 18 TT-Eg18 19
Table 19 TT-Eg20 21
Table 20 TT-Eg21 21
Table 21 TT-Eg22 23
Table 22 TE-1 25
Table 23 TE-2 26
Table 24 TE-3 26
Table 25 TE-4 27
Table 26 TE-5 28
Table 27 TE-6 29
Table 28 Conditional Formatting of Fuel Efficiency 30
Table 29 TT-EgBlank 30