#### X17 (Brown) 6-pin (24-pin Connector Slot) X17 Connector - Rear of A2w instrument cluster, Next to X16

Pin	Туре	Description	Connection	Signal Type	Pin (High)	Use-case	Wire Color
Pin 1	М	Ground	Ground Connection	GND			Orange-Gray
Pin 2	Е	Diagnosis RxD	Diagnostic socket - Pin 15	Square-wave			White-Yellow
Pin 3	Е	Fuse, Terminal R, Accessories Wire (ACC), +12V	+12V via Power Supply	+12V (B+)		Positive Terminal	Orange-Purple
Pin 4	М	Terminal 31, Ground	Ground Connection	GND			Orange
Pin 5	Α	Diagnosis TxD	Diagnostic socket - Pin 20	Square-wave			White
Pin 6	Е	Terminal R, Accessories Wire (ACC), +12V	+12V via Power Supply	+12V (B+)		Positive Terminal	Orange-Purple

# Pin Types TYPE DESCRIPTION E Input A Output M Ground

#### Symbo

Symbol	Description
ABS	Assisted Breaking System
SIA	Service Lights Indicator
TI	Injection Signal
TD	Engine Speed Signal
СС	Check-Control
ССМ	Check-Control Module
LKM	Lamp Control Module
АНМ	Trailer Module
ASC	Automatic Stability Control
EGS	Electronic Transmission Control
К	Instrument Cluster
KVA	Fuel Consumption Indicator
TO	Injection Quantity Diesel

Abbreviation

## Author / Creator

Nickname	0xduraki
Blog	https://duraki.github.io
Notes	https://notes.durakiconsulting.com
Email	hello[at] <u>durakiconsulting.com</u>
Instagram	<u>@e34.brt</u>

#### Thanks to:

http://www.bimmerboard.com/forums/posts/822204

## X16 (Biege) 26-pin X16 Connector - Rear of A2w instrument cluster

Pin	Туре	Description	Connection	Signal Type	Pin (High)	Use-case
Pin 1	Е	Control Light Airbag	Airbag diagnostic module	B-		Airbag indicator lamp
Pin 2	E/A	Data link to CCM, CLK CCM (Data)	CCM X18, Pin 13	Square-wave 0-5V		Serial Clock Output
Pin 3	E/A	Data link to CCM, BC and LKM/LAC	CCM X18, Pin 25 and BC, LKM	Square-wave 0-5V		Load data to parallel register
Pin 4	E/A	Data link to CCM	CCM X18, Pin 9	Square-wave 0-5V		Enable voltage reference
Pin 5	Е	Warning Light - Battery Charge Indicator, Terminal 61	Alternator	B+		
Pin 6	Е	Warning Light - Oil Pressure Switch	Pressure Switch	B-		
Pin 7	Е	Fuse, Terminal 15, Accessories Wire (ACC), +12V	+12V via Power Supply	+12V		Positive Terminal, Run-Start Mode, Control Terminal 15
Pin 8	Е	ASC Indicator Light	ASC Control Unit	B-		
Pin 9	Е	Oil Temperature (M5)	Temperature Sensor	0-12V		Temperature Ranges (Only E34/M5)
Pin 10	Α	Warning Light - Foot Brake, Rear	Connection 1, Rear Brake Sensor	Ground		Break Pad warning, Front and rear sensors are interconnected
Pin 11	Е	Trailer Turn Signal Indicator Light	Relay	B+		
Pin 12	Е	Fuse, Terminal 30, Accessories Wire (ACC), +12V	+12V via Power Supply	+12V		Positive Terminal, Terminal 30
Pin 13	Е	Fuse, Terminal 30, Accessories Wire (ACC), +12V	+12V via Power Supply	+12V		Positive Terminal, Terminal 30
Pin 14	Е	Brake Pressure	Pressure Switch	B-		(Only E34 w/ H31 Brake System)
Pin 15	Е	Warning Light - Brake Fluid Level	Level Switch	B-		
Pin 16	Е	SIA Reset	Diagnostic socket - Pin 7	B-		at B-SIA Reset
Pin 17	Е	TI Injection Signal from DME	DME Control Unit	Square-wave		
Pin 18	Е	TD Signal from DME, Speed Signal	DME Control Unit	Square-wave		Engine speed value
Pin 19	Е	TI Signal 2 from DME II	DME II Control Unit	Square-wave		Line connected as of model year 1990
Pin 20	Е	Warning Light - ABS Indicator	ABS Control Unit	B-		
Pin 21	Е	Terminal R for Airbag Indicator Lamp	Ignition Switch, +12V via Power Supply	+12V		Positive Terminal, Accessory Mode, Airbag, Terminal R
Pin 22	Е	Main Headlights/Beam Indicator	Light Switch	+12V (B+)		
Pin 23	E/A	Data link DAC to CCM and BC, DAC CCM DATA / BC	CCM X18, Pin 7	Square-wave 0-5V		Send UART data here to display it in LCD
Pin 24	Α	Coolant Temperature Sensor Ground	Temperature Sensor	B-		Temperature Range
Pin 25	Е	Warning Light - Foot Brake, Front	Connection 2, Front Brake Sensor	appx. 12V		Break Pad warning, Front and rear sensors are interconnected
Pin 26	Е	Coolant Temperature Input	Temperature Sensor	0-12V		Temperature Range

### X271 (Gray) 12-pin

# X271 Connector - Rear of A2w instrument cluster, next to X502

Pin	Туре	Description	Connection	Signal Type	Pin (High)	Use-case
Pin 1	N/A	NOT_USED	NOT_USED	NOT_USED	NOT_USED	NOT_USED
Pin 2	Е	Fuel Tank Indicator (Reserve/Running Low)	Tank Sensor	B-		Fuel Level Warning Signal
Pin 3	N/A	NOT_USED	NOT_USED	NOT_USED	NOT_USED	NOT_USED
Pin 4	Е	Fuel Tank Contents	Tank Sensor	0-12V		Fuel Level
Pin 5	N/A	NOT_USED	NOT_USED	NOT_USED	NOT_USED	NOT_USED
Pin 6	N/A	NOT_USED	NOT_USED	NOT_USED	NOT_USED	NOT_USED
Pin 7	Е	Warning Light - Handbrake	Handbrake Switch	B-		Park Brake Indicator Control
Pin 8	Е	Vehicle Speed Input (+), Tachometer, Terminal 31	Tachogenerator	Square-wave 0-12V		Tachogenerator Input, Vehicle Speed, To Signal Generator PWM Pin
Pin 9	А	Position Pulse DWA		Square-wave 0-12V		
Pin 10	А	Vehicle Speed Input (-), Tachometer, Terminal 31	Tachogenerator	B-		Tachogenerator Ground, Vehicle Speed, To Signal Generator GND Pin
Pin 11	N/A	NOT_USED	NOT_USED	NOT_USED	NOT_USED	NOT_USED
Pin 12	N/A	NOT_USED	NOT_USED	NOT_USED	NOT_USED	NOT_USED

#### X502 (White) 26-pin

# X502 Connector - Rear of A2w instrument cluster, next to X271

Pin	Туре	Description	Connection	Signal Type	Pin (High)	Use-case
Pin 1	Е	Fog Lights Indicator Lamp	Fog Light Switch	B+		Front Fog Lights
Pin 2	Α	Output for gong signal, Sound Tone Signal (Gong)	Acoustic Generator	B-		Gong
Pin 3	Е	Check Engine Lamp	DME Control Unit	B-		DME
Pin 4	Е	Gear Display (Automatic Only)	Selector Lever	B+		
Pin 5	Е	Gear Display (Automatic Only)	Selector Lever	B+		
Pin 6	Е	Gear Display (Automatic Only)	Selector Lever	B+		
Pin 7	N/A	NOT_USED	NOT_USED	NOT_USED	NOT_USED	NOT_USED
Pin 8	Е	EGS Program Indicator	EGS Control Unit	B-		
Pin 9	Е	EGS Program Indicator	EGS Control Unit	B-		
Pin 10	N/A	NOT_USED	NOT_USED	NOT_USED	NOT_USED	NOT_USED
Pin 11	Е	Gear Display (Automatic Only)	Selector Lever	B+		
Pin 12	N/A	NOT_USED	NOT_USED	NOT_USED	NOT_USED	NOT_USED
Pin 13	N/A	NOT_USED	NOT_USED	NOT_USED	NOT_USED	NOT_USED
Pin 14	Е	Instrument Light, Terminal 58G	+12V Positive Terminal, or Dimmer	Pulses		Instrument Illumination Power
Pin 15	Е	Rear Fog Lights Indicator Lamp	Fog Light Switch	B+		Rear Fog Lights
Pin 16	Е	EML Indicator Lamp	EML Control Unit	B-		
Pin 17	Е	EML Indicator Lamp	EML Control Unit	B-		
Pin 18	Α	Output Speed, Vehicle Speed Signal Output, Tacho A Signal	Various Control Units	Square-wave		
Pin 19	N/A	NOT_USED	NOT_USED	NOT_USED	NOT_USED	NOT_USED
Pin 20		Terminal 61, Auxiliary Alternator	Auxiliary Altenrator	B+		Software v0.90 only
Pin 21	N/A	NOT_USED	NOT_USED	NOT_USED	NOT_USED	NOT_USED
Pin 22	N/A	NOT_USED	NOT_USED	NOT_USED	NOT_USED	NOT_USED
Pin 23	Α	CC Button for BC Displays	BC, Pin 14	B-		B- clears BC display in instrument cluster display
Pin 24	N/A	NOT_USED	NOT_USED	NOT_USED	NOT_USED	NOT_USED
Pin 25	Е	Indicator Light - Left Turn Indicator	Relay	B+		
Pin 26	Е	Indicator Light - Right Turn Indicator	Relay	B+		