

List Append



● Solved

Helpful

For this problem, the prefilled code will contain a list. Write a program to add the given word at the end of the list.

Input

The input will be a single line containing a string.

Output

The output should be a single line containing the list by adding the word at the end of the list.

Explanation

For example, if the given word is "Golf", your code should add the word at the end of the list. So the output should be

```
['Cricket', 'Hockey', 'Football', 'Badminton', 'Golf']
```

Sample Input 1

```
Golf
```

Sample Output 1

```
['Cricket', 'Hockey', 'Football', 'Badminton', 'Golf']
```

Sample Input 2

```
Tennis
```

Sample Output 2

```
['Cricket', 'Hockey', 'Football', 'Badminton', 'Tennis']
```

Extend the List



Easy

● Solved

Helpful

A list `L` is given in the prefilled code.

Write a program that reads space-separated strings and prints a list obtained by adding given space-separated strings to the end of the list `L`.

```
L = ["5", "7", "Rohit", "Virat", "Dhoni"]
```

Input

The input will be a single line containing space-separated strings.

Output

The output should be a single line containing a list obtained by adding given space-separated strings to the end of the given list `L` .

Explanation

For example, if the given space-separated strings are **Surya Rahul Ishan Gill**,

- The given prefilled list is `L = ["5", "7", "Rohit", "Virat", "Dhoni"]` .
- The given strings are **"Surya", "Rahul", "Ishan", and "Gill"**.
- The strings when added to the end of the list `L` are **"5", "7", "Rohit", "Virat", "Dhoni", "Surya", "Rahul", "Ishan", and "Gill"**.

The output should be,

```
["5", "7", "Rohit", "Virat", "Dhoni", "Surya", "Rahul", "Ishan", "Gill"]
```

Sample Input 1

```
Surya Rahul Ishan Gill
```

Sample Output 1

```
['5', '7', 'Rohit', 'Virat', 'Dhoni', 'Surya', 'Rahul', 'Ishan', 'Gill']
```

Sample Input 2

```
apple carrot b12
```

Sample Output 2

```
['5', '7', 'Rohit', 'Virat', 'Dhoni', 'apple', 'carrot', 'b12']
```

Insert an Element

● Solved

Helpful 

For this problem, the prefilled code will contain a list. Write a program to insert a number (N) at the given index (I) location in the list.

Input

The first line of input will contain an integer (N).

The second line of input will contain a positive integer (I).

Output

The output should be a single line containing the list with the number at the given index location.

Explanation

For example, if the given N is 30 and I is 2, your code should insert 30 in the list at index 2. So the output should be

```
[10, 20, 30, 40, 50, 60]
```

Sample Input 1

```
30
2
```

Sample Output 1

```
[10, 20, 30, 40, 50, 60]
```

Sample Input 2

```
70
6
```

Sample Output 2

```
[10, 20, 40, 50, 60, 70]
```

Sample Input 1

```
3
```

Sample Output 1

```
['Python', 'C', 'Java', 'Ruby', 'C++', 'CSS', 'HTML', 'Bash', 'Perl', 'R', 'Swift']
```

Sample Input 2

```
4
```

Sample Output 2

```
['Python', 'C', 'Java', 'Ruby', 'C++', 'CSS', 'HTML', 'Bash', 'Perl', 'R']
```

Remove the Last Items

● Solved [Helpful](#) 

For this problem, the prefilled code will contain a list. Write a program to remove the last N items in the list.

Input

The input will be a single line containing an integer (N).

Output

The output should be a single line containing the list without the last N items.

Explanation

For example, if the given N is 3, your code should remove the last three elements in the list. So the output should be

```
['Python', 'C', 'Java', 'Ruby', 'C++', 'CSS', 'HTML', 'Bash', 'Perl', 'R', 'Swift']
```

Sample Input 1

Sample Input 1

```
3
```

Sample Output 1

```
['Python', 'C', 'Java', 'Ruby', 'C++', 'CSS', 'HTML', 'Bash', 'Perl', 'R', 'Swift']
```

Sample Input 2

```
4
```

Sample Output 2

```
['Python', 'C', 'Java', 'Ruby', 'C++', 'CSS', 'HTML', 'Bash', 'Perl', 'R']
```

Count the Occurrences



● Solved

Helpful

For this problem, the prefilled code will contain a list. Write a program to count all the occurrences of the given number (N) in the list.

Input

The input will be a single line containing an integer (N).

Output

The output should be a single line containing the count of all the occurrences of the given number (N) in the list.

Explanation

For example, if the given N is 5, the output should be 2, as 5 has two occurrences in the list.

Sample Input 1

```
5
```

Sample Output 1

```
2
```

Sample Input 2

```
100
```

Sample Output 2

```
3
```

Find the Indices of Element



Easy ● Solved Helpful

A list `L` is given in the prefilled code.

Write a program that reads a number `N` and prints the index of the given number `N` in the list `L`. If there are multiple occurrences of `N`, print all indices separated by a space.

```
L = [5, 4, 10, 2, 3, 2, 5, 15, 4, 4]
```

Input

The input will be a single line containing an integer representing `N`.

Output

The output should be a single line containing space-separated integers representing the indices of the given number `N` in the list `L`.

Explanation

For example, if the given number is `N = 10`,

- Integers in the list `L` and their respective indices are,

Numbers	5	4	10	2	3	2	5	15	4	4
Indices	0	1	2	3	4	5	6	7	8	9

- The index value of `10` is `2`.

The output should be `2`

For example, if the given number is `N = 2`,

- Integers in the list `L` and their respective indices are,

Numbers	5	4	10	2	3	2	5	15	4	4
Indices	0	1	2	3	4	5	6	7	8	9

- Value `2` is present at two different indices `3` and `5`.

The output should be `3 5`

Sample Input 1

```
10
```

Sample Output 1

```
2
```

Sample Input 2

```
2
```

Sample Output 2

```
3 5
```

Remove All the Occurrences



● Solved

Helpful

For this problem, the prefilled code will contain a list. Write a program to remove all the occurrences of the given number (N) in a list.

Input

The input will be a single line containing an integer (N).

Output

The output should be a single line containing the list without the number (N).

Note: The order of numbers in the output list should be same as in the input list.

Explanation

For example, if the given N is 5, your code should print the list by removing 5 at all the occurrences. So the output should be

```
[10, 20, 35, 50, 20, 100, 200, 10, 150, 100, 100]
```

Sample Input 1

```
5
```

Sample Output 1

```
[10, 20, 35, 50, 20, 100, 200, 10, 150, 100, 100]
```

Sample Input 2

```
10
```

Sample Output 2

```
[5, 20, 35, 5, 50, 20, 100, 200, 150, 100, 100]
```

List Methods



● Solved

Helpful

Consider a list (nums_list = []). Write a program to perform the following commands on the list

1. insert I E - insert the integer E at index I
2. append E - insert integer E at the end of the list
3. pop - remove the last element
4. remove E - remove the first occurrence of integer E
5. sort - sort the list in ascending order
6. print - print the list

Input

The first line of input will contain an integer (N).

The next N lines will contain the commands described above to be performed on the list each in a line.

Output

For each command of type print, print the list on a new line.

Explanation

Initialize your list and read in the value of N followed by N lines of commands where each command will be of the types listed above. Iterate through each command in order and perform the corresponding operation on your list.

For example, if the given N is 5, read the commands in the next five lines. If the given five commands are

- `append 5` - append 5 to the list, `nums_list = [5]`
- `insert 0 2` - insert 2 at index 0, `nums_list = [2, 5]`
- `append 1` - append 1 to the list, `nums_list = [2, 5, 1]`
- `sort` - sort the list, `nums_list = [1, 2, 5]`
- `print` - print the list

So the output should be

```
[1, 2, 5]
```

Sample Input 1

```
5
append 5
insert 0 2
append 1
sort
print
```

Sample Output 1

```
[1, 2, 5]
```

Sample Input 2

```
7
print
append 8
append 7
insert 2 1
remove 8
pop
print
```

Sample Output 2

```
[]
[7]
```