

Liquibase Rollback Guide

Overview

Liquibase rollbacks operate on changesets regardless of whether the changeset is defined in XML or executes an external SQL file via `<sqlFile>`.

1. Rollback by Tag

Purpose: Roll back everything after a release tag.

Example:

v1.0 -> Customer, Orders

v1.1 -> Procedure, Product

v1.2 -> Email column

Commands:

```
liquibase tag v1.2
```

```
liquibase rollback v1.0
```

Use for production release rollback.

2. Rollback Count

Purpose: Undo the last N changesets.

Example: `rollbackCount 2` removes the last two deployed changesets only.

3. Rollback to Date

Purpose: Restore the database to a specific point in time.

Example:

```
liquibase rollbackToDate "2026-07-30T09:06:00"
```

4. Rollback One Changeset

Purpose: Roll back one specific changeset using its ID, author, and changelog file. Useful when a single object change must be reverted.

5. Rollback One Update

Purpose: Undo only the most recent Liquibase update operation (deployment batch).

6. Rollback SQL

Purpose: Generate the SQL that would be executed during rollback without actually running it.

Example:

```
liquibase rollbackSQL v1.0
```

How It Works with the Proposed Architecture

master.xml -> schema.xml -> customer.xml + procedure.xml. Liquibase tracks each changeset independently. A `rollbackCount 2` operation can roll back procedure-001 and customer-002 even though one is XML and the other executes an external SQL file.

Recommended Enterprise Rollback Strategy

1. Rollback by Tag (production releases)
2. Rollback Count (development/testing)

3. Rollback One Changeset (targeted fixes)
4. Rollback SQL (DBA review)
5. Rollback to Date (point-in-time recovery)
6. Rollback One Update (undo latest deployment)