
Z80-Decoder

CUPL(WM) 5.0a Serial# 60008009

Device g16v8as Library DLIB-h-40-2 Created Sat Feb 08 11:47:14 2020

Name Z80-Decoder

Partno 00 Revision 01

Date 2/7/2020

Designer Norberto Collado

Company Koyado.com

Assembly None

Location Hillsboro, OR

Expanded Product Terms

ROM_CS1 =>

A12 & A13 & A14 & A15 & !MEM1 & !MREQ & !ROMDIS # !A11 & !A12 & A13 & A14 & A15 & !MEM1 & !MREQ & !ROMDIS

ROM_CS2 =>

A15 & MEM1 & !MREQ & !ROMDIS

memadr =>

A15 , A14 , A13 , A12 , A11

______ Symbol Table

Pin Pol	Variable Name	Ext	Pin	Туре	Pterms Used	Max Pterms	Min Level
ļ.	A11		5	V	-	-	-
!	A12		4	V	-	-	-
!	A13		3	V	-	-	-
Į.	A14		2	V	-	-	-
!	A15		1	V	-	-	-
!	MEM1		7	V	-	-	-
!	MREQ		8	V	-	-	-
!	ROMDIS		6	V	-	-	-
!	ROM_CS1		19	V	2	8	1
!	ROM_CS2		18	V	6	8	1
	memadr		0	F	-	-	-

LEGEND D : default variable F : field G : group
I : intermediate variable N : node M : extended node
U : undefined V : variable X : extended variable

T : function

Fuse Plot

Svn 02192 - Ac0 02193 x

Pin #19 02048 Pol x 02120 Ac1 x 00000 -x-x-x---x---x---x---x 00032 -x-x-x--x--x--x--x---x 00064 xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx 00224 xxxxxxxxxxxxxxxxxxxxxxxxxxxxx Pin #18 02049 Pol x 02121 Ac1 x 00256 -x-x-x---x---x---x 00288 -x-x---x---x---x---x 00320 x--xx---x---x---x----00352 ---xx---x--x--x--x--x--x---00384 x--x-x-----x---x----00416 ---xx----x----x----x 00480 xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx Pin #17 02050 Pol x 02122 Ac1 -00512 XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX 00576 XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX 00672 XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX 00704 xxxxxxxxxxxxxxxxxxxxxxxxxxxxxx 00736 xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx Pin #16 02051 Pol x 02123 Ac1 -00800 xxxxxxxxxxxxxxxxxxxxxxxxxxxxx 00832 xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx 00864 xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx

```
00896 xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
00928 xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
00960 xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
Pin #15 02052 Pol x 02124 Ac1 -
01120 xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
Pin #14 02053 Pol x 02125 Ac1 -
01408 xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
Pin #13 02054 Pol x 02126 Ac1 -
01536 XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
01600 xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
01632 XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
Pin #12 02055 Pol x 02127 Ac1 -
01792 XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
01824 XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
```


LEGEND X : fuse not blown

- : fuse blown

Chip Diagram

	_				
	- 1	Z80-Decoder			
! A15	x 2	1	20	X	Vcc
! A14	x 2	2	19	X	!ROM_CS1
! A13	x 3	3	18	X	!ROM_CS2
! A12	X	4	17	X	
! A11	X	5	16	X	
!ROMDIS	x 6	6	15	X	
!MEM1	x	7	14	X	
! MREQ	x 8	3	13	X	
	x 9	9	12	X	
GND	x 2	10	11	X	
	-				