

WANG MODEL 701 OUTPUT WRITER

DESCRIPTION

A modified IBM Selectric® Typewriter is used as a printing mechanism to write numeric output data, alphabetic headings, and messages.

A Wang solenoid undercarriage and interfacing electronic circuitry are added to the typewriter for automatic operation. When not being used as part of the system, the Output Writer can be used as a conventional typewriter.

All typewriter functions can be actuated by the calculator's *special function keys* to provide complete control over the alpha-numeric output format. (A *special function key* label is included.)

Numeric Output can be generated by the **WRITE** command under program control or manual control. Decimal point location may be positioned as desired.

Alphabetic Output — Titles and messages are controlled by the **WRITE ALPHA** command. Each code number following this command produces a letter printout. A string of code numbers is terminated by the **END ALPHA** command. (see sample output)

Program Listing — The program in the core memory of the 700/720, consisting of step and program code number, may be listed by depressing the **LIST PROGRAM** key followed by **GO**. Or, the program may be listed as it is being keyed into core by placing the machine in the **LEARN** and **PRINT** mode.

WARRANTY

The typewriter mechanism of the 701 is covered by IBM warranty. The Wang solenoids and interfacing electronics of the 701 carry the same warranty as the Wang 700 Series Calculator.

OPTION

Pin-Feed Platen 13 1/8 in. width. (Specify on initial order.) Vertical distance between pins is 1/2 in. center to center. Minimum horizontal distance from pin to typing margins is one character width.



SPECIFICATIONS

Paper Capacity	15½ inches
Writing Line	13 inches
Characters per Inch	12
Characters per Line	156
No. of Lines per Inch	6
Type Face	Prestige Elite 72 (IBM Code 012)
Max. Printing Speed	15 Char/Sec: (approx.)
Return (CR + LF) Time	.15 Sec + 60 ms/inch
Shift Time	150 ms (approx.)
Space/Back Space Time	70 ms (approx.)
INDEX (LF) Time	150 ms (approx.)
Tabulation Time (5 in. max.)	.5 seconds
Set/Clear Tab Time	.5 seconds
Size: Height	8½ inches
Width	21 inches
Depth	15½ inches
Weight:	Net 48 pounds Gross 68 pounds
Power Requirements:	115 vac ± 10%, 60 Hz, 150W, 2 Amp. (230 vac, 50 Hz, 150W, 1 Amp. on special order, no charge)
Connection Cable:	12 ft. each to 700 Series power cord.

SAMPLE PRINTOUT

Starting co-ords:
 174 32 10.0 432.100 430.136 -41.143 10000.000 10000.000
 -1 82 50 40.0 352.250 -10.398 352.096 10430.136 9958.856
 -2 3 4 3.0 395.400 9.497 395.285 10419.737 10310.952
 2 102 32 45.0 410.000 -402.234 -79.421 10429.235 10706.238
 -1 95 43 20.0 310.000 29.427 -308.600 10027.001 10626.816
 1 164 30 15.0 323.100 -56.375 -318.143 10056.429 10318.216
 10000.073

Error of closure is -.0538 North and -.0732 East or 1 part in 24462.
 Enter 0 to weight and balance, or 1 to just balance.

Course # 1 Hold
 Course # 2 wt. 3
 Course # 3 wt. 3
 Course # 4 wt. 3
 Course # 5 wt. 1
 Course # 6 Hold

Balanced back traverse:

QUAD	DEG	MIN	SEC	DISTANCE	LATITUDE	DEPARTURE	NORTH	EAST
4	5	27	50.0	432.100	430.136	-41.143	10000.000	10000.000
2	88	18	22.4	352.233	-10.411	352.079	10430.136	9958.856
1	88	37	36.7	395.367	9.474	395.254	10419.725	10310.935
3	11	10	18.3	410.018	-402.248	-79.441	10429.199	10706.189
4	84	33	12.7	310.004	29.424	-308.605	10056.375	10626.748
3	79	57	5.0	323.100	-56.375	-318.143	10000.000	10000.000

Enclosed area is -268587.552 square feet or -6.1659 acres.

ORIG IN YOUR COORD SYS
 N 10430.136 E 9958.856

STD SYS
 N 416504.320 E 671254.050

ROT ANGLE DEG 3 MIN 14 SEC 16.00

Transformed traverse:

QUAD	DEG	MIN	SEC	DISTANCE	LATITUDE	DEPARTURE	NORTH	EAST
4	2	13	34.0	432.099	431.773	-16.784	416072.546	671270.834
2	85	4	6.4	352.233	-30.279	350.929	416504.320	671254.050
2	88	8	7.2	395.367	-12.864	395.158	416474.040	671604.979
3	14	24	34.3	410.018	-397.119	-102.033	416461.176	672000.138
4	81	18	56.7	310.004	46.807	-306.450	416064.056	671898.104
3	83	11	21.0	323.099	-38.316	-320.819	416110.863	671591.654
							416072.546	671270.834