

WANG 600 SERIES ELECTRONIC CALCULATORS

exponential form, or paper feed. **AUTOMATIC PRINT:** This feature enables a user to generate a complete hard copy record of all manual operations.

Trace Mode: Alpha Log_{10} or Alpha Log_e turns the TRACE mode on. The printer will print the contents of the window as well as the operation while executing a program. This feature is programmable.

Alpha 10^x , Alpha e^x or PRIME will turn the TRACE mode off.

Identifying Letter: A programmed print command designating one of 16 separate identifying letters is provided.

List Program — Learn Print: Generates a hard-copy output of the program operation, printing the program step number, program instruction code and the operation symbol.

Paper Feed: A key is provided for manual paper feed as well as a two-step program command. Paper feed rate is 400 lines per minute.

SOFTWARE CAPABILITY

An extensive library of programs is available to further enhance the user's programming capabilities.

FIELD RETROFITTING UPDATING A USER'S SYSTEM

Wang's modularity concept allows users to update their systems easily, efficiently and inexpensively on location.

GENERAL

Dimensions: 9 inches high, 20 inches wide, 20½ inches deep.

Weight: Net 39 lbs.

Power: 115 volts ac $\pm 10\%$, 60 Hz, 50 watts (standard); 230 volts ac $\pm 10\%$, 50 Hz, 50 watts (optional, no charge).

WARRANTY

Full warranty of 90 days. Maintenance contracts available.

Input/Output Capabilities: The 600 Series calculators have a number of different peripheral options. The following pages describe briefly what the many different peripherals can do. In most cases a two-keystroke command is all that is needed to address these devices.

ORDERING SPECIFICATIONS

All Models: Self-contained, desktop electronic programmable calculators. They all include; ten-key keyboard, decimal scientific notation, change sign, clear display, set exponent. Also with sixteen separate calculators that will perform addition, subtraction, division, and multiplication, along with STORE, RECALL, and TOTAL. Display has ten-digit accuracy with a sign and a two-digit exponent with a sign. Scientific and engineering keys include; $\sqrt{X}$, X^2 , $|X|$, INT X, e^x , 10^x , $1/X$, $\text{Log}_e X$, $\text{Log}_{10} X$, and trig functions. 32 user-defined subroutine keys. Logic decisions, branching, looping and subroutine capabilities.

MODEL	REGISTER	STEP/STORAGE CAPACITY	TOTAL REGISTERS
600	16	312/39	55
600	16	824/103	119
600	16	1848/231	247

Models that have indirect addressing capabilities allowing for +, -, $\times$, $\div$, STORE, RECALL, and TOTAL in all registers.

OPTIONS:

All models:

Magnetic tape cassette — Automatic program loading.

Rotary drum printer — Alpha character labeling, decimal point formatting.

PERIPHERALS

601	Output Writer
602	Plotting Output Writer
603	Paper Tape Editor
604	Card Reader
605-1	Micro Interface
611	Input/Output Typewriter
612	Flat-Bed Plotter
614	Mark Sense Card Reader