

WANG SERIES 706/707 (cont.)

Wang Series 706/707 is comprised of nine items. These items are described briefly in the following paragraphs. Any user desiring the advantages provided by this equipment may either purchase the complete series or individual components, depending on his specific needs.

MODEL 707 INTERFACE CONTROL UNIT

The Model 707 converts the input/output codes of the 700 Series calculator to or from, respectively, the ASCII codes of the Model 706 Teletype.

Any number of teletypes can be interfaced to the calculator through the Model 707 by using T-connectors (see Model 707-4). If remote teletype operations are desired, the Model 707 can be connected to a data set (see Model 707-1 explanation) which uses telephone lines as the communications link.

Connections are made to both the calculator and teletype(s) through plug-in cables. Two cables link the interface to the rear panel of the calculator; another cable is used between the interface and teletype or T-connector. The connection to the I/O calculator connector is used for Group I and Group II, and input function. The connection to the typewriter connector on the calculator is used for calculator output and converts parallel Selectric Bail code to serial ASCII code for driving the teletype.

MODEL 707-4 FOUR-TERMINAL TELETYPE CONNECTOR

A Model 707-4 is used when connecting more than one Model 706 Teletype to a Model 707 Interface Control Unit. Current Cable 707-5 is used to couple the connector to the teletypes and interface unit.

Four or less teletypes can be connected to each Model 707-4. If more than four teletypes are required, a second Model 707-4 can be connected to one of the channels of the first level Model 707-4 using a current cable. With a 2-level arrangement, seven teletypes can be used. Connectors can be chained in this fashion to accommodate any number of teletypes. If desired, the current cable can be extended to a length of 1,000 feet.

Busy-line lockout is not provided in the Model 707-4. Any teletype that is connected and turned on will act as a repeater or interrupt communication.

MODEL 707-1 DATA SET

The Model 707-1 is available for users who desire calculator access from remote teletype locations. Either of two methods can be used to link the remote station to the calculator configuration. One method uses telephone lines for transmission of data; if this arrangement is used, an acoustic adaptor and coupler are required (see Model 707-2&3 explanations). This configuration causes the remote station to act as the control center with the calculator center becoming the slave station. Conventional telephone service is necessary for this configuration. Transmissions are made by dialing the telephone number of the remote station and placing the telephone headset into the Model 707-2 Acoustic Adaptor.

The second method uses a direct access arrangement whereby 4-conductor cabling is wired from the telephone at the remote station to the Model 707-1 Data Set at the calculator location.

A Model 707-6 Data Set Cable, supplied with the Model 707-1, is used to connect the data set to the Model 707 Interface Control Unit. An integral cable on the acoustic adaptor connects to the other end of the data set. A Western Electric Data Set 103A together with the 804B Data Auxiliary Set may be substituted for the Model 707-1 and 707-2.

MODEL 707-6 DATA SET CABLE

This 6-foot cable is used to connect the Model 707-1 Data Set to the Model 707 Interface Control Unit (see Data Set explanation).

MODEL 707-2 ACOUSTIC ADAPTER

The Model 707-2 is required whenever conventional telephone lines are used as the link between a remote teletype site and the calculator site. It is connected directly to the Model 707-1 Data Set and functions as the coupling device between the telephone headset and the data set. A Western Electric Data Auxiliary Set, 804B may be substituted for this adapter.

MODEL 707-3 ACOUSTIC COUPLER (REMOTE STATION)

The Model 707-3 is used at remote teletype locations to interface the teletype to the telephone. Connection to the remote telephone is made by placing the telephone's headset on the acoustic coupler. The Model 707-7 Voltage Cable, supplied with the Model 707-3, connects the acoustic coupler to the teletype.

MODEL 707-7 VOLTAGE CABLE

Refer to the Model 707-3 explanation.