

BATHMATE



Ver No. 01

Date: 10. 01.2022

Bathmate acrylic sealant is a high quality, permanently flexible, acrylic based sealant which contains a powerful anti-fungal compound to prevent mould growth, providing good adhesion to plastic, ceramic tiles, wood and porcelain. It can be painted over and is easy to use.

APPLICATIONS

- Can be used to seal around ceramic baths, sinks and kitchen worktops
- Good adhesion with wood , porcelain , ceramic and most plastics.

ADVANTAGE

- Anti – fungal
- Flexible
- Eco – friendly
- Bonds most of the building material
- Paintable

HOW TO USE

- Surfaces must be clean, dry & free from grease and detergents
- Mask adjacent surfaces for neat application with masking tape
- Cut tip of cartridge, cut nozzle to desired size at 45° angle, attach to cartridge, and place in caulking gun.
- Apply sealant in continuous, steady flow. Push sealant ahead of nozzle contacting both sides of joint so it is completely filled.
- Smooth sealant surface immediately after application before skin forms.
- Remove masking tape
- Let is dry for minimum 24 hrs. prior to paint and other water usage.

BATHMATE



Ver No. 01

Date: 10. 01.2022

TECHNICAL DETAILS

NAME OF PRODUCT	TESTING STANDARD	RESULTS
PHYSICAL STATE		Viscous paste
COLOR		White
DRYING TIME @ 60 MICRON ON GLASSPLATE AT 25°C		3 – 4 minutes
Sp. GRAVITY @25°C	ASTM D 1475	1.4 – 1.5 gm/cc
Shore A Hardness	ASTM D 2240	22 – 24
% Elongation	ASTM D 412	Min. 400 %

SHELF LIFE

18 months from the date of mfg. and strictly store in cool, away from heat.

STORAGE & HANDLING PRECAUTIONS

Product should be stored in a dry place in their original, properly closed Cartridge at temperature between 2-40°C. Partially emptied cartridge should be closed immediately.

PACKING

300 ml



IMPORTANT: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE