



TRUBUILD PRIMESURE PREMIUM is Excellent water-based primer with good penetration and outstanding bond strength, which can be used on multiple surfaces like concrete, screed, cement sheet, glossed surface like china mosaic, Tiles, etc before application of protective water based top coats.

APPLICATION AREAS

Trubuild Primesure Premium is used as primer can be used for different substrates like concrete, screed, cement sheet, glossed surface like china mosaic, ceramic Tiles and vitrified Tiles etc.

FEATURE & ADVANTAGE

- Economical
- Can be used in both horizontal & vertical surface
- Excellent adhesion on various substrates
- Good penetration
- Reduces the chance of blister formation
- Enhance the bonding and overall durability of the system

TECHNICAL DETAILS

PROPERTIES	STANDARD	RESULTS
Physical State	In House	Low Viscous liquid
Appearance	Visual	opaque
Colour	Visual	Yellow/White
pH	ASTM E70	7-8
Specific Gravity	ASTM D 1475	1.01-1.03
% Solid	IS:4835	25%
Bond strength, on concrete MPA	ASTM D 7234	≥1.5
Bond strength, on vitrified tiles MPA	ASTM D 7234	≥2
Bond strength, on ceramic mat surface, MPA	ASTM D 7234	≥2
Bond strength, on ceramic glaze surface, MPA	ASTM D 7234	≥2

HOW TO USE

SURFACE PREPARATION

The surface should be clean and dried before application of Trubuild Primesure Premium. It should be free from dust, unsound material, loose plaster, oil, paint, grease, algae and corrosion deposits. Fill all the cracks up to 5mm by Trubuild CFP 425 and for more than 5mm and above, by making PMM using Trubuild WPL 333/Trubuild BWP 222.

APPLICATION METHODOLOGY

Mix well after opening the container of Trubuild Primesure Premium before application. Then apply the Trubuild Primesure Premium by brush ensuring covering of all the waterproofing area where subsequent water based top coats will come further. Leave it for 3-5 hours for air curing, then apply water based Top coat.

COVERAGE

*120-150 sqft/ltr/coat.

*Depending upon level and porosity of the substrate.



HANDLING PRECAUTION AND LIMITATION

- Trubuild Primesure Premium should not be diluted with water.
- Trubuild Primesure Premium shall be applied to the substrate temp above 10°C to below 40°C.
- Surface should be clean before application of water based Top coats.
- Ensure to provide a protective water based top coat over the final coat to ensure overall workability.
- Avoid coating in intermittent of rain.
- Apply Trubuild Primesure Premium after cleaning of all type of dust and other contaminants like oil, grease, and other debris if present.
- Mandatory and recommended industrial hygiene procedures should be followed whenever our products are being handled and processed. For additional information please refer Material safety data sheet.

STORAGE

Product should be stored in a dry place in their original, properly closed containers at temperature between 2-40°C. Partially emptied container should be closed immediately.

SHELF LIFE

12 Months, in closed container condition, from the date of manufacturing.

PACKING

1 Ltr & 5 Ltr

IMPORTANT: This technical data sheet replaces all previous versions of it from the immediate effect. The information, and, in particular, the recommendations relating to the application and end-use of Astral Limited construction chemical products, are given in good faith based on our knowledge and experience of the products when properly stored, handled and applied under suitable favourable conditions in accordance with Application instructions recommended in Product Technical Data sheet. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. For the products on which company is offering warranty, please refer to warranty document to know entire terms and conditions. The same can be availed on request or from company website. The values mentioned in the above tables in technical data sheet are obtained in controlled lab conditions when tested properly by competent laboratory. Tolerance up to five to ten percentage on the lower side from the above values are allowable as per standard. Astral Limited, reserves the right to change the properties of its products. The end user of the product must test the product's suitability for the intended application and purpose. Astral Limited will not bear any responsibilities on the product failure if it is wrongly positioned or if improper application methodology adopted by the user or the applicator. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace, and disposal practices are in compliance with applicable laws and other governmental enactments.



ASTRAL LIMITED

Registered Office: 207/1, 'Astral House', B/h Rajpath Club, Off S.G. Highway, Ahmedabad-380059, Gujarat, India.
P: +91 79 6621 2000 | F: +91 79 6621 2121 CIN: U24295GJ2009PLC058120
E-mail: customercare@astraladhesives.com **Website:** www.astraladhesives.com



Experience A Better Connect With The Company

**Exclusively for our
Channel Partners & Customers**

Visit us at:

wecare.astraladhesives.com