

Figure 3

Contents

1	Packages, data and functions	1
1.1	Packages	1
1.2	Data	1
2	Figure 3	2
2.1	Models	2
2.2	Figure	6
3	Versions of R and of the R-packages used	6

1 Packages, data and functions

1.1 Packages

```
library(tidyverse)
library(here)
library(survey)
library(lavaan)
library(lavaan.survey)

# lavaan.survey is an extension of lavaan that can deal with data independency.
# It is no longer on cran, but it is a trustworthy package (there is also a
# publication for it). The source code is
# here https://github.com/daob/lavaan.survey. To get the package you need to
# clone the repository linked above and then build the package locally.
```

1.2 Data

```
load(here("Data/3_ForecastsResults/3_MergedResults/complete.forecasts.RData"))

semDD.simplex <- complete.forecasts %>%
  dplyr::filter(forecast.method == "Simplex EDM",
    Target != "Total_biomass",
    Target != "Mean_oxygen") %>%
```

```
ungroup()
```

2 Figure 3

2.1 Models

```
model <-  
"  
RMSE ~ median_richness + cv.res + pe5 + acf_lag5  
cv.res ~ median_richness  
pe5 ~ median_richness  
acf_lag5 ~ median_richness  
cv.res ~~ pe5  
"  
  
## create random effect variable  
semDD.simplex$group <- paste0(semDD.simplex$Target, "_",  
                              semDD.simplex$bottle, "_",  
                              semDD.simplex$incubator)  
  
# semDD.simplex, semDD.rf, semDD.mv, semDD.rnn, semDD.ar  
out <- sem(model, data=semDD.simplex, group="light_treatment")  
  
### Survey Design Object  
des.card <- svydesign(ids = ~ group, nest=T, data = semDD.simplex)  
  
### Post-Processing  
fit.out.survey <- lavaan.survey(out, des.card, estimator = "MLM")  
  
summary(fit.out.survey, standardized=T, rsquare=T)  
  
## lavaan 0.6.17 ended normally after 105 iterations  
##  
##      Estimator                      ML  
##      Optimization method           NLMINB  
##      Number of model parameters    32
```

```

##
## Number of observations per group:
##   Group 1                126
##   Group 2                127
##
## Model Test User Model:
##                               Standard      Scaled
## Test Statistic              3.219        3.270
## Degrees of freedom           4           4
## P-value (Chi-square)         0.522        0.514
## Scaling correction factor    0.984
##   Satorra-Bentler correction
## Test statistic for each group:
##   Group 1                2.977        3.024
##   Group 2                0.242        0.246
##
## Parameter Estimates:
##
## Standard errors              Robust.sem
## Information                  Expected
## Information saturated (h1) model  Structured
##
##
## Group 1 [Group 1]:
##
## Regressions:
##           Estimate Std.Err z-value P(>|z|) Std.lv Std.all
## RMSE ~
##   median_richnss    0.015  0.031  0.469  0.639  0.015  0.035
##   cv.res           -0.602  0.177 -3.412  0.001 -0.602 -0.416
##   pe5              0.085  0.659  0.128  0.898  0.085  0.017
##   acf_lag5         -0.695  0.112 -6.230  0.000 -0.695 -0.368
## cv.res ~
##   median_richnss    0.005  0.022  0.243  0.808  0.005  0.018
##   pe5 ~
##   median_richnss    0.010  0.007  1.459  0.145  0.010  0.117

```

```

##   acf_lag5 ~
##   median_richnss   -0.018    0.019   -0.948    0.343   -0.018   -0.081
##
## Covariances:
##           Estimate Std.Err z-value P(>|z|) Std.lv Std.all
##   .cv.res ~~
##   .pe5       -0.032    0.008   -4.110    0.000   -0.032   -0.784
##
## Intercepts:
##           Estimate Std.Err z-value P(>|z|) Std.lv Std.all
##   .RMSE       1.177    0.474    2.485    0.013    1.177    2.151
##   .cv.res      0.416    0.119    3.486    0.000    0.416    1.101
##   .pe5         0.595    0.036   16.347    0.000    0.595    5.471
##   .acf_lag5    0.517    0.103    5.012    0.000    0.517    1.782
##
## Variances:
##           Estimate Std.Err z-value P(>|z|) Std.lv Std.all
##   .RMSE       0.203    0.041    5.006    0.000    0.203    0.678
##   .cv.res      0.143    0.034    4.151    0.000    0.143    1.000
##   .pe5         0.012    0.002    5.389    0.000    0.012    0.986
##   .acf_lag5    0.084    0.006   13.688    0.000    0.084    0.993
##
## R-Square:
##           Estimate
##   RMSE       0.322
##   cv.res     0.000
##   pe5        0.014
##   acf_lag5   0.007
##
##
## Group 2 [Group 2]:
##
## Regressions:
##           Estimate Std.Err z-value P(>|z|) Std.lv Std.all
##   RMSE ~
##   median_richnss -0.077    0.035   -2.224    0.026   -0.077   -0.220

```

```

##      cv.res          -0.095    0.173   -0.548    0.583   -0.095   -0.072
##      pe5             0.430    0.569    0.756    0.449    0.430    0.092
##      acf_lag5        -0.350    0.143   -2.455    0.014   -0.350   -0.185
##      cv.res ~
##      median_richnss  -0.030    0.026   -1.150    0.250   -0.030   -0.111
##      pe5 ~
##      median_richnss   0.014    0.007    2.186    0.029    0.014    0.191
##      acf_lag5 ~
##      median_richnss   0.010    0.017    0.592    0.554    0.010    0.053
##
## Covariances:
##              Estimate Std.Err z-value P(>|z|) Std.lv Std.all
##      .cv.res ~~
##      .pe5          -0.022   0.006  -3.968   0.000  -0.022  -0.628
##
## Intercepts:
##              Estimate Std.Err z-value P(>|z|) Std.lv Std.all
##      .RMSE          1.055   0.394   2.681   0.007   1.055   2.235
##      .cv.res         0.713   0.143   4.978   0.000   0.713   1.982
##      .pe5            0.540   0.037  14.714   0.000   0.540   5.319
##      .acf_lag5       0.506   0.093   5.454   0.000   0.506   2.026
##
## Variances:
##              Estimate Std.Err z-value P(>|z|) Std.lv Std.all
##      .RMSE          0.201   0.041   4.898   0.000   0.201   0.903
##      .cv.res         0.128   0.037   3.444   0.001   0.128   0.988
##      .pe5            0.010   0.001   8.040   0.000   0.010   0.963
##      .acf_lag5       0.062   0.007   9.524   0.000   0.062   0.997
##
## R-Square:
##              Estimate
##      RMSE          0.097
##      cv.res         0.012
##      pe5            0.037
##      acf_lag5       0.003

```

2.2 Figure

Figure 3 was done with MS PowerPoint and the above model.

3 Versions of R and of the R-packages used

R version: R version 4.3.2 (2023-10-31).

Base packages: grid, stats, graphics, grDevices, utils, datasets, methods, base.

Other packages: lavaan.survey 1.1.3, lavaan 0.6-17, survey 4.2-1, survival 3.5-7, Matrix 1.6-5, here 1.0.1, lubridate 1.9.3, forcats 1.0.0, stringr 1.5.1, dplyr 1.1.4, purrr 1.0.2, readr 2.1.5, tidyr 1.3.1, tibble 3.2.1, ggplot2 3.5.0, tidyverse 2.0.0, knitr 1.45.

This document was generated on April 18, 2024 at 18:52.